

Brennan Duff
Assignment 2

1. Find the average price of pastries for each category from the pastries table.

a. `SELECT category, AVG(price) AS average_price`

`FROM pastries`

`GROUP BY category;`

	category	average_price
▶	Pastry	4.666666666666667
	Muffin	3.625
	Bakery	4.25
	Scone	3.85
	Breakfast	8
	Cake	3.875

b.

2. Find the total number of baristas at each experience level from the baristas table.

a. `SELECT experience_level, COUNT(*) AS total_baristas`

`FROM baristas`

`GROUP BY experience_level;`

	experience_level	total_baristas
▶	Junior	2
	Senior	2
	Mid-Level	2

b.

3. Count the total number of shops located in each city from the shops table.

a. `SELECT city, COUNT(*) AS total_shops`

`FROM shops`

`GROUP BY city;`

	city	total_shops
▶	Seattle	1
	Portland	1
	Austin	1
	Chicago	1
	Denver	1
	Boston	1

b.

4. Find the maximum price among pastries for each category from the pastries table.

a. SELECT category, MAX(price) AS maximum_price

FROM pastries

GROUP BY category;

	category	maximum_price
▶	Pastry	5.5
	Muffin	3.75
	Bakery	4.25
	Scone	3.85
	Breakfast	8.5
	Cake	4

b.

5. Count how many pastries have been added by each shop using the shopID column from the offers table.

a. SELECT shopID, COUNT(*) AS pastry_count

FROM offers

GROUP BY shopID;

	shopID	pastry_count
▶	1	2
	2	2
	3	2
	4	2
	5	2
	6	2

b.

6. Find the name, category, and price of any pastry whose price matches the maximum price within its category.

a. `SELECT name, category, price`
`FROM pastries p`
`WHERE price = (`
`SELECT MAX(price)`
`FROM pastries`
`WHERE category = p.category`
`);`

	name	category	price
▶	Almond Croissant	Pastry	5.5
	Blueberry Muffin	Muffin	3.75
	Cinnamon Roll	Bakery	4.25
	Chocolate Scone	Scone	3.85
	Blueberry Scone	Scone	3.85
	Breakfast Burrito	Breakfast	8.5
	Lemon Loaf	Cake	4

b.

7. Find the unique shop IDs from the offers table that have offered at least one pastry whose price is strictly greater than the overall average price of all pastries.

a. `SELECT DISTINCT o.shopID`
`FROM offers o`
`JOIN pastries p`
`ON o.pastryID = p.pastryID`
`WHERE p.price > (`
`SELECT AVG(price)`
`FROM pastries`

);

	shopID
▶	1
	5

b.

8. Find the shop ID and pastry ID for the records in the offers table that have the earliest **date_added** (minimum date).

- a. `SELECT shopID, pastryID`
`FROM offers`
`WHERE date_added = (`
`SELECT MIN(date_added)`
`FROM offers`
`);`

b.

	shopID	pastryID
▶	1	1

9. Find the shop ID(s) that offer the highest number of pastries, utilizing a subquery to evaluate the maximum count per shop.

- a. `SELECT shopID`
`FROM offers`
`GROUP BY shopID`
`HAVING COUNT(*) = (`
`SELECT MAX(pastry_count)`
`FROM (`
`SELECT shopID, COUNT(*) AS pastry_count`
`FROM offers`

GROUP BY shopID

) AS shop_counts

);

shopID
1
2
3
4
5
6

b.

10. Find the names of baristas who work at shops located in 'Seattle' using nested subqueries.

a. SELECT name

FROM baristas

WHERE baristaID IN (

SELECT baristaID

FROM employs

WHERE shopID IN (

SELECT shopID

FROM shops

WHERE city = 'Seattle'

)

);

name
Emma Watson
Liam Chen

b.

✓	52	17:49:09	SELECT category, AVG(price) AS average_price FROM pastries GROUP BY category LIMIT 0, 1000	6 row(s) returned	0.016 sec / 0.000 sec
✓	53	17:49:09	SELECT experience_level, COUNT(*) AS total_baristas FROM baristas GROUP BY experience_level LIMIT 0, ...	3 row(s) returned	0.015 sec / 0.000 sec
✓	54	17:49:09	SELECT city, COUNT(*) AS total_shops FROM shops GROUP BY city LIMIT 0, 1000	6 row(s) returned	0.000 sec / 0.000 sec
✓	55	17:49:09	SELECT category, MAX(price) AS maximum_price FROM pastries GROUP BY category LIMIT 0, 1000	6 row(s) returned	0.000 sec / 0.000 sec
✓	56	17:49:09	SELECT shopID, COUNT(*) AS pastry_count FROM offers GROUP BY shopID LIMIT 0, 1000	6 row(s) returned	0.000 sec / 0.000 sec
✓	57	17:49:09	SELECT name, category, price FROM pastries p WHERE price = (SELECT MAX(price) FROM pastries ...	7 row(s) returned	0.000 sec / 0.000 sec
✓	58	17:49:09	SELECT DISTINCT o.shopID FROM offers o JOIN pastries p ON o.pastryID = p.pastryID WHERE p.price > ...	2 row(s) returned	0.000 sec / 0.000 sec
✓	59	17:49:09	SELECT shopID, pastryID FROM offers WHERE date_added = (SELECT MIN(date_added) FROM offers...	1 row(s) returned	0.000 sec / 0.000 sec
✓	60	17:49:10	SELECT shopID FROM offers GROUP BY shopID HAVING COUNT(*) = (SELECT MAX(pastry_count) F...	6 row(s) returned	0.000 sec / 0.000 sec
✓	61	17:49:10	SELECT name FROM baristas WHERE baristaID IN (SELECT baristaID FROM employs WHERE shop...	2 row(s) returned	0.000 sec / 0.000 sec

