



51Folds.AI

API Documentation

Revision 2603.06

Contents

Document Purpose.....	3
Disclaimer.....	3
Conventions.....	4
How to create an API Token	4
Retrieve a Model	5
Update model drivers	8
List Models.....	10
Create a model	12
Retry a failed model	15
Get credit balance	16

Document Purpose

This document defines the standards, conventions, and reference guidance for the 51Folds External API. Its purpose is to ensure that every endpoint behaves consistently and predictably for internal engineers and external integrators, reducing integration time and support overhead while improving reliability and developer experience.

Specifically, this document:

- Establishes canonical behaviors and formats across the API, including authentication headers, media types, and request/response structure.
- Codifies timestamp and timezone practices using ISO 8601/RFC 3339 date-time strings for all temporal fields.
- Clarifies idempotency requirements (e.g., X-Idempotency-Key) for safe execution and consistent write semantics.

Disclaimer

The 51Folds API is currently available as a private preview/beta and is not yet generally available. Access is by invitation and must be explicitly enabled for designated user accounts. While we endeavor to maintain backwards compatibility, the API is still evolving.

Future releases may introduce additional fields, resources, or endpoints to improve existing behavior. Should a breaking change be required, we will communicate the change and provide migration guidance to minimize disruption.

Conventions

- **Authentication:** All operations require a bearer auth token.
- **Media types:** Endpoints commonly use application/json.

Headers to send (typical)

```
Authorization: Bearer {token}
Accept: application/json;
Content-Type: application/json;
```

How to create an API Token

1. Login to your 51folds.ai account
2. Go to <https://app.51folds.ai/account/security-information>
3. In the personal access token section, click the Generate Token button

Personal Access Token

Access Token Status

No token generated

Generate a new token to access the API

Generate Token

4. Copy and keep the token generated. This token is shown in the portal once and cannot be shown again.

Token Generated Successfully!

Important: This is the only time you'll see this token. Copy it now and store it securely. Once you navigate away or refresh this page, you won't be able to see this token again.



at_sk_

Copy

If you do not see the personal access token section on the security information page, you will need request access by sending an email to support@51folds.ai

Retrieve a Model

Retrieve details for a single model by its identifier.

Request: GET /api/v1/models/{id}

Auth: Bearer required.

Path parameters

Field	Type	Required	Description
id	string	Yes	The model id of the model.

Example Request

```
curl -s \  
-H "Authorization: Bearer $TOKEN" \  
-H "Accept: application/json;" \  
-H "Content-Type: application/json;" \  
https://api.51folds.ai/api/v1/models/a1
```

Example Response – 200 OK

```
{  
  "data": {  
    "modelId": "",  
    "ownership": "",  
    "status": "",  
    "createdAt": "",  
    "updatedAt": "",  
    "question": "",  
    "context": "",  
    "shortSummary",  
    "drivers": [  
      {  
        "code": "",  
        "name": ""  
      }  
    ],  
    "current": {  
      "outcomes": [  
        {  
          "id": 1,  
          "label": "",  
          "probability": 0.0  
        }  
      ],  
      "drivers": [  
        {  
          "code": "",  
          "state": ""  
        }  
      ]  
    }  
  }  
}
```

```

    }
  }
}

```

Response Fields

Field	Type	Description
data.modelId	string	The unique identifier for the model.
data.ownership	string	Either the value "Shared" or "Owner".
data.status	string	Represents the status of the model. • pending – model is still in draft • running – model is being generated or updated • succeeded – the model is ready • failed – there was an error during the model creation process
data.createdAt	string	An ISO 8601 string representation of the date the model was created.
data.updatedAt	string	An ISO 8601 string representation of the date the model was last updated.
data.question	string	The question or hypothesis being modelled.
data.context	string	The additional contextual information related to the model. This can be a combination of user generated content and system generated content.
Data.shortSummary	String	A short narrative summarizing the model output.
data.drivers	object[]	An object array representing all drivers that are in the model.
data.drivers[].code	string	An acronym that represents the driver and is used as a key to identify the driver in other areas of the model.
data.drivers[].name	string	The full name of the Driver.
data.current	object	An object that represents the current state of the outcomes and drivers.
data.current.outcomes	object[]	An object array representing all the possible outcomes defined in the model.
data.current.outcomes[].id	int	An identifier for the outcome for the current model. This is only unique within the scope of the current model.

data.current.outcomes[].label	string	The outcome to the question or thesis.
data.current.outcomes[].probability	number	The probability of the outcome, represented as a value between 0 and 1.

Update model drivers

Update the model driver states and re-calculate the probabilities

Request: PUT /api/v1/models/{id}/drivers

Auth: Bearer required.

Path parameters

Field	Type	Required	Description
id	string	Yes	The model id of the model.

Request body

```
{
  "drivers": [
    {
      "code": "ABC",
      "state": "Low"
    }
  ]
}
```

Request Fields

Field	Type	Required	Description
drivers	object[]	Yes	An array of driver state objects. You must supply all the drivers and their states.
drivers[].code	string	Yes	The driver acronym
state	string	Yes	The state of the driver. Valid values are - Negligible (Min in the 51Folds UI) - Low - Medium - High - Extreme (Max in the 51Folds UI)

Example Request

```
curl -s -G \
-H "Authorization: Bearer $TOKEN" \
-H "Accept: application/json;" \
--data '{
  "drivers": [
    {
      "code": "D1",
      "state": "Low"
    },
  ],
}
```



```
{
  "code": "D2",
  "state": "Medium"
},
{
  "code": "D3",
  "state": "Medium"
},
{
  "code": "D4",
  "state": "Negligible"
},
{
  "code": "D5",
  "state": "High"
}
]
}' \
https://api.51folds.ai/api/v1/models/a1/drivers
```

Example Response – 202 Accepted

```
{
  "data": {
    "modelId": "a1",
    "status": "running"
  }
}
```

Response Fields

Field	Type	Description
data.modelId	string	The unique identifier for the model.
data.status	string	Represents the status of the model

Example response – 400 Bad request

```
{
  "reason": [
    "One or more drivers were not supplied"
  ]
}
```

Response Fields

Field	Type	Description
reason	string[]	An array of messages identifying why the request was invalid

List Models

List/search models with optional filters and paging.

Request: GET /api/v1/models

Auth: Bearer required.

Query parameters

Field	Type	Required	Description
SearchText	string	No	Keywords to match against the model question / title.
CreatedFrom	string	No	The lower bound range to filter models based on their created date. (ISO 8601 string representation).
CreatedTo	string	No	The upper bound range to filter models based on their created date. (ISO 8601 string representation).
UpdatedFrom	string	No	The lower bound range to filter models based on their last updated date. (ISO 8601 string representation).
UpdatedTo	string	No	The upper bound range to filter models based on their last updated date. (ISO 8601 string representation).
Page	int	No	Page index starting from 1.
PageSize	int	No	Items returned per page between 1 and 100.

Example Request

```
curl -s -G \  
  -H "Authorization: Bearer $TOKEN" \  
  -H "Accept: application/json;" \  
  --data-urlencode "SearchText=Gold" \  
  --data-urlencode "CreatedFrom=2025-01-01T00:00:00Z" \  
  --data-urlencode "CreatedTo=2025-12-31T23:59:59Z" \  
  --data-urlencode "Page=1" \  
  --data-urlencode "PageSize=50" \  
  https://api.51folds.ai/api/v1/models
```

Example Response – 200 OK

```
{  
  "data": {  
    "models": [  
      {  
        "id": "",  
        "title": "",  
        "createdAt": "",  
        "updatedAt": "",  
        "ownerShip": "",  
        "batchId": ""  
      }  
    ]  
  }  
}
```

```

    }
  ],
  "page": 1,
  "pageSize": 25,
  "total": 1
}
}

```

Response Fields

Field	Type	Description
data.models	object[]	An object array of search results that match the search criteria.
data.models[].id	string	The unique identifier for the model.
data.models[].title	string	The question or hypothesis being modelled.
data.models[].createdAt	string	An ISO 8601 string representation of the date the model was created.
data.models[].updatedAt	string	An ISO 8601 string representation of the date the model was last updated.
data.models[].ownership	string	Either the value "Shared" or "Owner".
data.models[].batchId	string	A Unique identifier that represents the batch the model was created in.
data.page	int	The current page of the results.
data.pageSize	int	The maximum number of models returned for the current page.
data.total	int	The total number of models that match the search criteria.

Example response – 400 Bad request

```

{
  "reason": [
    "The value '23-02-2025' is not valid for CreatedFrom."
  ]
}

```

Response Fields

Field	Type	Description
reason	string[]	An array of messages identifying why the request was invalid

Create a model

Submit a request to generate one or more models (a batch).

Request: POST /api/v1/models

Auth: Bearer required.

Request header

Field	Type	Required	Description
X-Idempotency-Key	string	Yes	A stable UUID to prevent duplicate processing on retries.

Request body

```
{
  "question": "",
  "outcomes": [
    ""
  ],
  "additionalContext": "",
  "type": "",
  "generateDriverContent": true,
  "generateTakeAwayContent": true
}
```

Request Fields

Field	Type	Required	Description
question	string	Yes	The question or hypothesis being tested.
outcomes	string[]	Yes	A set of mutually exclusive outcomes for the hypothesis. Must be between 2-5 outcomes in order to build a model.
type	string	Yes	The type of model. Either "Overview", "Insight" or "Advanced"
additionalContext	string	No	Additional context such as assumptions, clarification or proprietary information related to the hypothesis.
generateDriverContent	boolean	No	Default true. Generates additional content about the drivers of the model. Can be omitted to improve the time to generate a model if not required.
generateTakeAwayContent	boolean	No	Default true. Generates the key takeaway summary of the model. Can be omitted to improve the time to generate a model if not required.

Example request

```
curl -s -X POST \
-H "Authorization: Bearer $TOKEN" \
-H "Accept: application/json; x-api-version=1.0" \
-H "Content-Type: application/json; x-api-version=1.0" \
-H "X-Idempotency-Key: 4d0f6b3a-2a8e-4a8e-9c6c-0b1f7a6e1f01" \
-d '{ "question": "The likelihood of a globally impacted data breach in 2026", "outcomes":
["Very Likely", "Likely", "Unlikely", "Highly Unlikely"], "type": "Insight" }' \
https://api.51folds.ai/api/v1/models
```

Example response – 202 Accepted

```
{
  "data": {
    "modelId": [
      "c3"
    ],
    "question": "The likelihood of a globally impacted data breach in 2026",
    "outcomes": [
      "Very Likely",
      "Likely",
      "Unlikely",
      "Highly Unlikely"
    ],
    "additionalContext": "",
    "type": "insight",
  }
}
```

Response Fields

Field	Type	Description
data.modelId	string[]	An array of model ids. For a default single model creation, the first item in the array is the id of the model.
data.question	string	The hypothesis or question for the model.
data.outcomes	string[]	The set of mutually exclusive outcomes for the model.
data.additionalContext	string	Additional context such as assumptions, clarification or proprietary information related to the hypothesis.
data.type	string	The type of model. Either "Overview", "Insight" or "Advanced".

Example response – 400 Bad request

```
{
  "reason": [
    "The idempotencyKey field is required."
  ]
}
```

Response Fields

Field	Type	Description
reason	string[]	An array of messages identifying why the request was invalid

Retry a failed model

Retry (re-enqueue) processing for the specified model/job that previously failed.

Request: POST /api/v1/models/{id}/retry

Auth: Bearer required.

Path parameters

Field	Type	Required	Description
id	string	Yes	The model id of the model.

Example request

```
curl -s -X POST \  
  -H "Authorization: Bearer $TOKEN" \  
  -H "Accept: application/json;" \  
  https://api.51folds.ai/api/v1/models/c3/retry
```

Example response – 202 Accepted

```
{  
  "data": {  
    "modelId": "c3"  
  }  
}
```

Response Fields

Field	Type	Description
modelId	string	The identifier of the model being re-run

Example response – 400 Bad request

```
{  
  "reason": [  
    "Model is not in a failed state."  
  ]  
}
```

Response Fields

Field	Type	Description
reason	string[]	An array of messages identifying why the request was invalid

Get credit balance

Return the caller's current credit balance.

Request: GET /api/v1/credits/me

Auth: Bearer required.

Example request

```
curl -s \  
  -H "Authorization: Bearer $TOKEN" \  
  -H "Accept: application/json;" \  
  https://api.51folds.ai/api/v1/credits/me
```

Example response – 200 OK

```
{  
  "data": {  
    "retrievedAt": "",  
    "amount": 0  
  }  
}
```

Response Fields

Field	Type	Description
data.retrievedAt	string	The identifier of the model being re-run.
data.amount	Int	The amount of credit remaining in the account.