

# A Parallel Recommender System Using A Collaborative Filtering Algorithm For Movie Recommender System

Projna Saha

School of Computer Science

Carleton University

[projnasaha@cmail.carleton.ca](mailto:projnasaha@cmail.carleton.ca)

# Types of Recommendation Systems

- **Content-Based Filtering:**

Content-Based recommender system tries to guess the features or behavior of a user given the item's features, he/she reacts positively to [1].

- **Collaborative Filtering:**

Collaborative does not need the features of the items to be given. Every user and item is described by a feature vector or embedding [2].

## Collaborative Filtering



**Day One:** Joe and Julia independently read an article on police brutality



**Day Two:** Joe reads an article about deforestation, and then Julia is recommended the deforestation article

## Content-Based Filtering



**Day One:** Julia watches a Drama



**Day Two:** Dramas are recommended

# Literature Review

## Similarity Computation

- Cosine Vector (CV) Similarity [3]
- Pearson Correlation (PC) Similarity [4][5]
- Spearman Correlation (SC)[6]
- JacRA Similarity [7]

## Rating Prediction

- Weighted Average (WA) [8]
- Mean-Centering (MC) [9][10]
- Z-Score (ZS) [11]

# Hadoop vs Apache [12]

- Hadoop

- Processing data using MapReduce in Hadoop is slow
- Performs batch processing of data
- Hadoop has more lines of code. Since it is written in Java, it takes more time to execute.
- Hadoop supports Kerberos authentication, which is difficult to manage




- Apache

- Spark processes data 100 times faster than MapReduce as it is done in-memory
- Performs both batch processing and real-time processing of data
- Spark has fewer lines of code as it is implemented in Scala
- Spark supports authentication via a shared secret. It can also run on YARN leveraging the capability of Kerberos






# The Task Scheduling Procedure In Spark [13]



A cluster of decorative circles in the top-left corner, including a large light pink circle, a small orange circle, a small light pink circle, a medium purple circle, and a tiny dark purple dot.

# Methodology

# Algorithms That We Have Used




# Our Dataset Statistics vs The Paper We Followed!

Our Dataset	Datasets	# of users	# of items	# of ratings	Sparsity
	MovieLens-100k	943	1682	100000	6.3%
	Netflix-6.2M	95325	412	6198103	15%


Dataset of The Paper We Followed [13]	Datasets	# of users	# of items	# of ratings	Sparsity
	WikiLens	326	5111	26937	1.6%
	MovieLens-100k	943	1682	100000	6.3%
	MovieLens-1M	6040	3900	1000209	4.2%



# Methodology for MovieLens-100k Dataset



# Methodology for Netflix-6.2M Dataset



The slide features a light gray background with decorative elements in the corners. The top-left corner has a cluster of pink, orange, and purple circles. The top-right corner has a cluster of purple, orange, and pink circles. The bottom-right corner has a cluster of blue, pink, and purple circles. The text 'Experimental Results' is centered on the slide, underlined.

# Experimental Results

# Movie Recommender System using KNN Algorithm :: MovieLens-100k

- Used KNN algorithm to compute similarity with Cosine Distance metric.
- We first check if the movie name input is in the database (CSV)
- If exists, then we use our recommendation system to find similar movies
- Sort them based on their similarity distance and output only the top 10 movies with their distances from the input movie
- All the movies in the top 10 are just like “Kolya” itself, therefore I think the result, in this case, is also good.

```
1 get_movie_recommendation('Kolya')
```

	Title	Distance
1	Fly Away Home	0.681671
2	Raise the Red Lantern	0.680329
3	Antonia's Line	0.679670
4	Like Water For Chocolate	0.673561
5	Angels and Insects	0.664926
6	L.A. Confidential	0.664229
7	Mrs. Brown	0.652900
8	Ulee's Gold	0.652874
9	Ridicule	0.652396
10	Lone Star	0.647755

# Movie Recommender System using ALS

## Algorithm :: MovieLens-100k

Selecting the list of users for the movie which id is 17

user_id	title	ratings
475	From Dusk Till Dawn	3.6
78	From Dusk Till Dawn	3.380952380952381
248	From Dusk Till Dawn	3.5714285714285716
88	From Dusk Till Dawn	3.9523809523809526
797	From Dusk Till Dawn	2.6538461538461537
266	From Dusk Till Dawn	3.260869565217391
366	From Dusk Till Dawn	4.393939393939394
494	From Dusk Till Dawn	3.872340425531915
97	From Dusk Till Dawn	4.158730158730159
692	From Dusk Till Dawn	3.275

Selecting the list of movies for the user whose id is 6

movie_id	title	ratings
1368	Mina Tannenbaum	3.6666666666666665
1463	Boys, Les	3.3333333333333335
1158	Fille seule, La	4.0
1202	Maybe, Maybe Not	3.5
207	Cyrano de Bergerac	3.8181818181818183
513	Third Man, The	4.333333333333333
1203	Top Hat	4.0476190476190474
1643	Angel Baby	3.75
652	Rosencrantz and G...	3.8888888888888889
927	Flower of My Secr...	3.1666666666666665

# Movie Recommender System using ALS

## Algorithm :: Netflix-6.2M

Selecting the list of users for the movie which id is 17

user_id	Name	ratings
1264514	National Lampoon's...	4.2745098039215685
364590	National Lampoon's...	4.866666666666666
1723350	National Lampoon's...	4.526315789473684
160876	National Lampoon's...	4.269230769230769
18764	National Lampoon's...	4.1944444444444445
782679	National Lampoon's...	4.36734693877551
1180376	National Lampoon's...	3.8461538461538463
1038898	National Lampoon's...	4.177777777777778
1258697	National Lampoon's...	3.9166666666666665
1657241	National Lampoon's...	4.1568627450980395

Selecting the list of movies for the user whose id is 6


movie_id	Name	ratings
2862	The Silence of th...	4.304120879120879
3290	The Godfather	4.380834346646712
1692	Lonesome Dove	4.078693951248871
2782	Braveheart	4.260301246537396
3456	Lost: Season 1	4.65859938208033
3124	Titanic	3.760035682426405
2452	Lord of the Rings...	4.428412903907633
3391	Where the Red Fer...	3.9453125
1642	Casino: 10th Anni...	3.997315385487957
3153	Doctor Zhivago	3.949515316013959




# Comparison Between Netflix- 6.2M & ML-100K Datasets ALS Method

RMSE, MSE, MAE

Alternating Least Square Method



# Executor Summary of Two Datasets







# Ganglia Cluster Report

# Ganglia Cluster Report :: MovieLens-100k (Host View)

Databricks Runtime  
Version:  
10.1 (includes Apache  
Spark 3.2.0, Scala 2.12)





Overview of cluster @ 2021-11-14 09:18



# Ganglia Cluster Report :: Netflix-6.2M (Host View)


Databricks Runtime  
Version:  
10.1 (includes Apache  
Spark 3.2.0, Scala 2.12)

Overview of cluster @ 2021-11-14 11:22



# MovieLens and Netflix Clusters Configurations - usage Overall

## MOVIELENS & NETFLIX CLUSTERS CONFIGURATIONS





# Limitations & Future Work

---

Unable to create multiple master / worker node in Microsoft Azure Cloud as a student

---

Databricks Community Edition only permits cluster with 8-core CPU with node 2

---

## **Future Work**

---

Hybrid recommender systems

---

Reducing dataset size and user-item segmentation

# References

- [1] R. Ji, Y. Tian, and M. Ma, “Collaborative filtering recommendation algorithm based on user characteristics,” 2020 5th International Conference on Control, Robotics and Cybernetics (CRC), p. 56–60, 2020.
- [2] A. Pal, P. Parhi, and M. Aggarwal, “An improved content based collaborative filtering algorithm for movie recommendations,” 2017 Tenth International Conference on Contemporary Computing (IC3), p. 1–3, 2017.
- [3] K. B. Fard, M. Nilashi, and N. Salim, “Recommender system based on semantic similarity,” International Journal of Electrical and Computer Engineering (IJECE), vol. 3, no. 6, 2013.
- [4] M. Deshpande and G. Karypis, “Item-based top- n recommendation algorithms,” ACM Transactions on Information Systems, vol. 22, no. 1, p. 143–177, 2004.
- [5] P. Ahlgren, B. Jarneving, and R. Rousseau, “Requirements for a cocitation similarity measure, with special reference to Pearson’s correlation coefficient,” Journal of the American Society for Information Science and Technology, vol. 54, no. 6, p. 550–560, Apr 2003.
- [6] X. Wu, Y. Huang, and S. Wang, “A new similarity computation method in collaborative filtering based recommendation system,” 2017 IEEE 86th Vehicular Technology Conference (VTC-Fall), 2017.
- [7] J. Bobadilla, A. Hernando, F. Ortega, and A. Gutiérrez, “Collaborative filtering based on significances,” Information Sciences, vol. 185, no. 1, p. 1–17, 2012.
- [8] A. Bonfietti and M. Lombardi, “The weighted average constraint,” vol. 7514, 10 2012, pp. 191–206.
- [9] M. Hofer, “Mean centering,” The International Encyclopedia of Communication Research Methods, p. 1–3, 2017.
- [10] J. S. Breese, D. Heckerman, and C. Kadie, “Empirical analysis of predictive algorithms for collaborative filtering,” Jan 1998. [Online]. Available: <https://arxiv.org/abs/1301.7363>
- [11] J. L. Herlocker, J. A. Konstan, A. Borchers, and J. Riedl, “An algorithmic framework for performing collaborative filtering,” Proceedings of the 22nd annual international ACM SIGIR conference on Research and development in information retrieval - SIGIR99, 1999.
- [12] A. Wakde, P. Shende, S. Waydande, S. Uttarwar, and G. Deshmukh, “Comparative analysis of Hadoop tools and Spark technology,” in 2018 Fourth International Conference on Computing Communication Control and Automation (ICCUBEA), 2018, pp. 1–4.
- [13] J. Sun, Z. Wang, X. Luo, P. Shi, W. Wang, L. Wang, J.-H. Wang, and W. Zhao, “A parallel recommender system using a collaborative filtering algorithm with correlation for social networks,” IEEE Transactions on Network Science and Engineering, vol. 7, no. 1, p. 91–103, 2020.
- [14] P. Cunningham and S. Delany, “k-nearest neighbour classifiers,” Mult Classif Syst, vol. 54, 04 2007.
- [15] S. Ghosh, N. Nahar, M. Wahab, M. Biswas, M. Hossain, and K. Andersson, Recommendation System for E-commerce Using Alternating Least Squares (ALS) on Apache Spark, 02 2021, pp. 880–893.
- [16] T. Jhalani, V. Kant, and P. Dwivedi, “A linear regression approach to multi-criteria recommender system,” vol. 9714, 06 2016, pp. 235–243.

# Discussion

---

How is Apache Spark different from MapReduce?

---

Why is Apache Spark faster than Apache Hadoop?

---

Is it possible to run Apache Spark without Hadoop?

---

What role does worker node play in Apache Spark Cluster? And what is the need to register a worker node with the driver program?

---

How can you trigger automatic clean-ups in Spark to handle accumulated metadata?



**Thank You**