



1 Overview

This ALOGIC SmartConnect Mini DisplayPort Cable Ver 1.2 - Male to Male cable allows for a connection between a computer enabled with a Mini DisplayPort output like Apple Mac, HP, Lenovo, Dell, Ultrabook, Microsoft Surface and laptop to a display enabled with a VGA input.

2 Features

- * Gold Plated connectors for best connectivity and minimum losses.
- * Length : 3m
- * Retail Poly Bag Packaging.
- * Warranty: Life Time

3 Specifications

- * 28 gauge (AWG) pure copper wire
- * Aluminium and Mylar shielding to help eliminate EMI and RFI
- * Resolution capability of up to 1920 X 1200
- * (1) Mini DisplayPort Male to (1) VGA Male


4 Design:




No.	Part No.	Descriptions	Q'ty
①	01-1058B	Cable(OD:4.2mm)	1
②	02-1444PG	Mini DP Plug	1
③	35-MPDPB-A13	Shell(Mini DP Plug)	1
④	01-1372BK	Cable(OD:5.5mm)	1
⑤	02-1418PG	DVI Plug	1
⑥	35-PMVGAB	Shell(VGA Plug)	1

5 Cable Specifications:

01-1058B



01-1372BK



A	Conductor	Ø 0.06mm/7 34AWG OFC tinned copper wires
	Insulator	Ø 0.5mm FPE+SKIN
	Drain	Ø 0.1mm/7 30AWG OFC tinned copper wires
	Shield	Aluminium foil
B	Conductor	Ø 0.08mm/7 32AWG OFC tinned copper wires
	Insulator	Ø 0.5mm FPE
C	Shield	Aluminium foil
D	Drain	Ø 0.1mm/7 OFC bare copper wires
E	Shield	Ø 0.08mm/16x8 OFC tinned copper braided
F	Filler	PP rope
G	Jacket	Ø 4.2mm PVC in black colour

A	Conductor	Ø 0.08mm/7 32AWG OFC tinned copper wires
	Insulator	Ø 1.1mm FPE
	Shield	Ø 0.1mm/7 16x3 OFC bare copper wires
	Shield	Aluminium foil
B	Electronic Wires	Ø 0.08mm/7 32AWG OFC tinned copper wires
C	Insulator	Ø 0.55mm HDPE
D	Filler	PP
E	Shield	Aluminium Foil
F	Drain	Ø 0.127mm/7 28AWG OFC bare copper wires
G	Shield	Ø 0.12mm/16x5 aluminium braided
H	Jacket	Ø 5.5mm PVC in black colour

6 Part No.

Part No.	Length	Packaging	Colour
MDP-VGA-01-MM	1m	Retail Poly Bag	■ Black
MDP-VGA-02-MM	2m	Retail Poly Bag	■ Black
MDP-VGA-03-MM	3m	Retail Poly Bag	■ Black

7 Connection Guide

