

PLUS USB 3.0 to Gigabit Ethernet & 3 Port USB Hub - Aluminium

Part No.	VPLU3H4A
User Interface:	Output: USB 3.0 Output Port x 4 Input: USB 3.0 Input Port x 1
Power	Bus-powered / Self-powered
Data Rate:	USB3.0 - Supports the following data rate as; Low-speed (1.5 Mbps) / Full-speed (12 Mbps) / High-speed (480 Mbps) / Super- speed (5 Gbps) USB2.0 - Support the following speed data rate as follows; Low-speed (1.5Mbps) / Full-speed (12Mbps) / High-speed (480Mbps)
Compliance:	USB 2.0 / USB 3.0 specification
Physical Characteristics:	Material: Silver Aluminium Unibody Dimensions: 95*30*22(mm) Cable Length: 0.30m Weight: 60gms Certifications: CE/FCC, RoHS
System Requirement:	Windows® 7, Windows® 8, 8.1,10 and Mac OS X 10.8 or above



Super Speed USB 3.0 Speed:

- 4 USB 3.0 ports that support transfer rates of up to 5Gbps per port.
- Uses the latest VL812 controller for market leading performance.

Elegant & Friendly Design:

- Precision unibody enclosure crafted from a single block of aluminium.
- Horizontally-positioned port with wider berth for over-sized USB connectors.
- Compact hub with a small foot print.



Self Powered & Driver Free:

- Plug and play device.
- The device is also self powered through the USB port.