1 **Overview**

This ALOGIC SmartConnect Mini DisplayPort to DVI-D Cable Ver 1.2 - Male to Male cable allows for a connection between a computer enabled with a Mini DisplayPort output like Apple Mac, HP, Lenovo, Dell, Ultrabook and laptop to a display enabled with a DVI input.

2 **Features**

* Gold Plated connectors for best connectivity and minimum loses.
* Retail Poly Bag Packaging.
* Warranty: Life Time

3 **Specifications**

* Aluminium and Mylar shielding to help eliminate EMI and RFI
* Resolution capability of up to 1920×1200
* (1) DisplayPort Male to (1) VGA Male

④ Design:

No.	Part No.	Descriptions	Q'ty
①	01-1058B	Cable(OD:4.2mm)	1
②	02-1444PG	Mini DP Plug	1
③	35-MPDPB-A13	Shell(Mini DP Plug)	1
④	01-1279B	Cable(OD:5.5mm)	1
⑤	02-1418PG	DVI Plug	1
⑥	35-PMDVIB	Shell(DVI Plug)	1

⑤ Cable Specifications:

01-1058B

A	Conductor	∅ 0.06mm/7 34AWG OFC tinned copper wires
A	Insulator	∅ 0.5mm FPE+SKIN
A	Drain	∅ 0.1mm/7 30AWG OFC tinned copper wires
A	Shield	Aluminium foil
B	Conductor	∅ 0.08mm/7 32AWG OFC tinned copper wires
B	Insulator	∅ 0.5mm FPE
C	Shield	Aluminium foil
D	Drain	∅ 0.1mm/7 OFC bare copper wires
E	Shield	∅ 0.08mm/16x8 OFC tinned copper braided
F	Filler	PP rope
G	Jacket	∅ 4.2mm PVC in black colour

01-1279B

A	Conductor	∅ 0.08mm/7 32AWG OFC tinned copper wires
A	Insulator	∅ 0.63mm FPE+SKIN
A	Drain	∅ 0.1mm/7 30AWG OFC tinned copper wires
A	Shield	Aluminium foil
B	Conductor	∅ 0.08mm/7 32AWG OFC tinned copper wires
B	Insulator	∅ 0.63mm HDPE
C	Conductor	∅ 0.08mm/7 32AWG OFC tinned copper wires
C	Insulator	∅ 0.63mm HDPE
D	Shield	Aluminium foil
E	Drain	∅ 0.1mm/7 OFC bare copper wires
F	Shield	∅ 0.08mm/16x8 OFC tinned copper braided
G	Jacket	∅ 4.2mm PVC in black colour

6 **Part No.**

Part No.	Length	Packaging	Colour
MDP-DVI-01-MM	1m	Retail Poly Bag	■ Black
MDP-DVI-02-MM	2m	Retail Poly Bag	■ Black
MDP-DVI-03-MM	3m	Retail Poly Bag	■ Black

7 **Connection Guide**