




## Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

### ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

#### ☐ Interactive controls are keyboard focusable

Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable](#).

#### ☐ Interactive elements indicate their purpose and state

Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints](#).

#### ☐ The page has a logical tab order

Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering](#).

#### ☐ Visual order on the page follows DOM order

DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering](#).

|                                                                                                                                                                               |   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <input type="radio"/> User focus is not accidentally trapped in a region                                                                                                      | ^ |
| A user can tab into and out of any control or region without accidentally trapping their focus. <a href="#">Learn how to avoid focus traps.</a>                               |   |
| <input type="radio"/> The user's focus is directed to new content added to the page                                                                                           | ^ |
| If new content, such as a dialog, is added to the page, the user's focus is directed to it. <a href="#">Learn how to direct focus to new content.</a>                         |   |
| <input type="radio"/> HTML5 landmark elements are used to improve navigation                                                                                                  | ^ |
| Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. <a href="#">Learn more about landmark elements.</a> |   |
| <input type="radio"/> Offscreen content is hidden from assistive technology                                                                                                   | ^ |
| Offscreen content is hidden with display: none or aria-hidden=true. <a href="#">Learn how to properly hide offscreen content.</a>                                             |   |
| <input type="radio"/> Custom controls have associated labels                                                                                                                  | ^ |
| Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <a href="#">Learn more about custom controls and labels.</a>                   |   |
| <input type="radio"/> Custom controls have ARIA roles                                                                                                                         | ^ |
| Custom interactive controls have appropriate ARIA roles. <a href="#">Learn how to add roles to custom controls.</a>                                                           |   |

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review.](#)

## PASSED AUDITS (21)

Hide

|                                                                                                                                                                                                              |   |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <a href="#">[aria-*]</a> attributes match their roles                                                                                                                                                        | ^ |
| Each ARIA role supports a specific subset of aria-* attributes. Mismatching these invalidates the aria-* attributes. <a href="#">Learn how to match ARIA attributes to their roles.</a>                      |   |
| <a href="#">[aria-hidden="true"]</a> is not present on the document <code>&lt;body&gt;</code>                                                                                                                | ^ |
| Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <code>&lt;body&gt;</code> . <a href="#">Learn how aria-hidden affects the document body.</a> |   |
| <a href="#">[aria-*]</a> attributes have valid values                                                                                                                                                        | ^ |
| Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <a href="#">Learn more about valid values for ARIA attributes.</a>                                         |   |

[aria-\*] attributes are valid and not misspelled



Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

Buttons have an accessible name



When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

Image elements have [alt] attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

[user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5.



Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

ARIA attributes are used as specified for the element's role



Some ARIA attributes are only allowed on an element under certain conditions. [Learn more about conditional ARIA attributes.](#)

[aria-hidden="true"] elements do not contain focusable descendents



Focusable descendents within an [aria-hidden="true"] element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how aria-hidden affects focusable elements.](#)

Elements use only permitted ARIA attributes



Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. [Learn more about prohibited ARIA roles.](#)

Background and foreground colors have a sufficient contrast ratio



Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)

Document has a <title> element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

<html> element has a [lang] attribute



|                                                                                                                                                                                                                                                                                                                                                                                    |   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <p>If a page doesn't specify a <code>lang</code> attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. <a href="#">Learn more about the <code>lang</code> attribute.</a></p> |   |
| <p>&lt;html&gt; element has a valid value for its <code>[lang]</code> attribute</p>                                                                                                                                                                                                                                                                                                | ^ |
| <p>Specifying a valid <a href="#">BCP 47 language</a> helps screen readers announce text properly. <a href="#">Learn how to use the <code>lang</code> attribute.</a></p>                                                                                                                                                                                                           |   |
| <p>Form elements have associated labels</p>                                                                                                                                                                                                                                                                                                                                        | ^ |
| <p>Labels ensure that form controls are announced properly by assistive technologies, like screen readers. <a href="#">Learn more about form element labels.</a></p>                                                                                                                                                                                                               |   |
| <p>Links have a discernible name</p>                                                                                                                                                                                                                                                                                                                                               | ^ |
| <p>Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. <a href="#">Learn how to make links accessible.</a></p>                                                                                                                                                    |   |
| <p>Touch targets have sufficient size and spacing.</p>                                                                                                                                                                                                                                                                                                                             | ^ |
| <p>Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. <a href="#">Learn more about touch targets.</a></p>                                                                                                                                                                                         |   |
| <p><code>[lang]</code> attributes have a valid value</p>                                                                                                                                                                                                                                                                                                                           | ^ |
| <p>Specifying a valid <a href="#">BCP 47 language</a> on elements helps ensure that text is pronounced correctly by a screen reader. <a href="#">Learn how to use the <code>lang</code> attribute.</a></p>                                                                                                                                                                         |   |
| <p>Heading elements appear in a sequentially-descending order</p>                                                                                                                                                                                                                                                                                                                  | ^ |
| <p>Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. <a href="#">Learn more about heading order.</a></p>                                                                                                                                                 |   |
| <p>Uses ARIA roles only on compatible elements</p>                                                                                                                                                                                                                                                                                                                                 | ^ |
| <p>Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. <a href="#">Learn more about ARIA roles.</a></p>                                                                                                                                                                  |   |
| <p>Image elements do not have <code>[alt]</code> attributes that are redundant text.</p>                                                                                                                                                                                                                                                                                           | ^ |
| <p>Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. <a href="#">Learn more about the <code>alt</code> attribute.</a></p>                                                        |   |

- `[accesskey]` values are unique



Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#)

- `button`, `link`, and `menuitem` elements have accessible names



When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#)

- Deprecated ARIA roles were not used



Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#)

- Elements with `role="dialog"` or `role="alertdialog"` have accessible names.



ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#)

- ARIA input fields have accessible names



When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#)

- ARIA `meter` elements have accessible names



When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#)

- ARIA `progressbar` elements have accessible names



When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#)

- `[role]`s have all required `[aria-*)` attributes



Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

- Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children.



Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#)

- `[role]`s are contained by their required parent element



Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions.

[Learn more about ARIA roles and required parent element.](#)

☐ [role] values are valid



ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

☐ Elements with the `role=text` attribute do not have focusable descendents.



Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the `role=text` attribute.](#)

☐ ARIA toggle fields have accessible names



When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#)

☐ ARIA `tooltip` elements have accessible names



When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#)

☐ ARIA `treeitem` elements have accessible names



When a `treeitem` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling `treeitem` elements.](#)

☐ The page contains a heading, skip link, or landmark region



Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#)

☐ `<d1>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements.



When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#)

☐ Definition list items are wrapped in `<d1>` elements



Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<d1>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#)

☐ ARIA IDs are unique



The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#)

- No form fields have multiple labels



Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#)

- `<frame>` or `<iframe>` elements have a title



Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

- `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute.



If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

- Input buttons have discernible text.



Adding discernible and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#)

- `<input type="image">` elements have `[alt]` text



When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#)

- Links are distinguishable without relying on color.



Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#)

- Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`).



Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#)

- List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements



Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#)

- The document does not use `<meta http-equiv="refresh">`



Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#)

- `<object>` elements have alternate text



Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <p>meaning to users. <a href="#">Learn more about alt text for object elements.</a></p>                                                                                                                                                                                                                                                                                                                                                                                              |  |
| <p><input type="radio"/> Select elements have associated label elements.</p> <p>Form elements without effective labels can create frustrating experiences for screen reader users. <a href="#">Learn more about the select element.</a></p>                                                                                                                                                                                                                                          |  |
| <p><input type="radio"/> Skip links are focusable.</p> <p>Including a skip link can help users skip to the main content to save time. <a href="#">Learn more about skip links.</a></p>                                                                                                                                                                                                                                                                                               |  |
| <p><input type="radio"/> No element has a <code>[tabindex]</code> value greater than 0</p> <p>A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <a href="#">Learn more about the tabindex attribute.</a></p>                                                                                                                                      |  |
| <p><input type="radio"/> Tables have different content in the summary attribute and <code>&lt;caption&gt;</code>.</p> <p>The summary attribute should describe the table structure, while <code>&lt;caption&gt;</code> should have the onscreen title. Accurate table mark-up helps users of screen readers. <a href="#">Learn more about summary and caption.</a></p>                                                                                                               |  |
| <p><input type="radio"/> Cells in a <code>&lt;table&gt;</code> element that use the <code>[headers]</code> attribute refer to table cells within the same table.</p> <p>Screen readers have features to make navigating tables easier. Ensuring <code>&lt;td&gt;</code> cells using the <code>[headers]</code> attribute only refer to other cells in the same table may improve the experience for screen reader users. <a href="#">Learn more about the headers attribute.</a></p> |  |
| <p><input type="radio"/> <code>&lt;th&gt;</code> elements and elements with <code>[role="columnheader"/"rowheader"]</code> have data cells they describe.</p> <p>Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <a href="#">Learn more about table headers.</a></p>                                                                                     |  |
| <p><input type="radio"/> <code>&lt;video&gt;</code> elements contain a <code>&lt;track&gt;</code> element with <code>[kind="captions"]</code></p> <p>When a video provides a caption it is easier for deaf and hearing impaired users to access its information. <a href="#">Learn more about video captions.</a></p>                                                                                                                                                                |  |



## Best Practices

○ Ensure CSP is effective against XSS attacks ^

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#)

| Description                      | Directive | Severity |
|----------------------------------|-----------|----------|
| No CSP found in enforcement mode |           | High     |

○ Use a strong HSTS policy ^

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#)

| Description                            | Directive         | Severity |
|----------------------------------------|-------------------|----------|
| No `includeSubDomains` directive found | includeSubDomains | Medium   |
| No `preload` directive found           | preload           | Medium   |

○ Ensure proper origin isolation with COOP ^

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#)

| Description          | Directive | Severity |
|----------------------|-----------|----------|
| No COOP header found |           | High     |

○ Mitigate clickjacking with XFO or CSP ^

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking.](#)

| Description                   | Severity |
|-------------------------------|----------|
| No frame control policy found | High     |

## GENERAL

○ Detected JavaScript libraries ^

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#)

| Name    | Version |
|---------|---------|
| Leaflet | 1.9.4   |
| Angular | 15.2.5  |

▲ Missing source maps for large first-party JavaScript

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#)

☒ Show 3rd-party resources (4)

| URL                                                                                            | Map URL                                                                                                             |
|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| be-on-top.io <span>1st Party</span>                                                            |                                                                                                                     |
| /main.e5d632d524....js (be-on-top.io)                                                          |                                                                                                                     |
| Large JavaScript file is missing a source map                                                  |                                                                                                                     |
| McAfee® WebAdvisor <span>Chrome Extension</span>                                               |                                                                                                                     |
| chrome-extension://fheoggkfdfchfphceeifdbepaoicaho/scripts/Sailer-Package/feature_collector.js | chrome-extension://fheoggkfdfchfphceeifdbepaoicaho/sourceMap/chrome/scripts/Sailer-Package/feature_collector.js.map |
| Error: Failed fetching source map (null)                                                       |                                                                                                                     |
| chrome-extension://fheoggkfdfchfphceeifdbepaoicaho/scripts/iframe_form_check.js                | chrome-extension://fheoggkfdfchfphceeifdbepaoicaho/sourceMap/chrome/scripts/iframe_form_check.js.map                |
| Error: Failed fetching source map (null)                                                       |                                                                                                                     |
| chrome-extension://fheoggkfdfchfphceeifdbepaoicaho/scripts/content_navigate_complete.js        | chrome-extension://fheoggkfdfchfphceeifdbepaoicaho/sourceMap/chrome/scripts/content_navigate_complete.js.map        |
| Error: Failed fetching source map (null)                                                       |                                                                                                                     |
| JSDelivr CDN <span>Cdn</span>                                                                  |                                                                                                                     |
| ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)                                               | ...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)                                                                |

#### Uses HTTPS



All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS](#).

#### Avoids deprecated APIs



Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs](#).

#### Avoids third-party cookies



Third-party cookies may be blocked in some contexts. [Learn more about preparing for third-party cookie restrictions](#).

#### Allows users to paste into input fields



Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. [Learn more about user-friendly input fields](#).

#### Avoids requesting the geolocation permission on page load



Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more about the geolocation permission](#).

#### Avoids requesting the notification permission on page load



Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more about responsibly getting permission for notifications](#).

#### Displays images with correct aspect ratio



Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio](#).

#### Serves images with appropriate resolution



Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn how to provide responsive images](#).

#### Has a `<meta name="viewport">` tag with `width` or `initial-scale`



A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag](#).

#### Document uses legible font sizes — 100% legible text



Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text  $\geq 12$ px. [Learn more about legible font sizes](#).

| Source       | Selector | % of Page Text | Font Size |
|--------------|----------|----------------|-----------|
| Legible text |          | 100.00%        | ≥ 12px    |

Page has the HTML doctype

Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration.](#)

Properly defines charset

A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding.](#)

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

No issues in the [Issues](#) panel in Chrome Devtools

Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

#### NOT APPLICABLE (1)

Hide

|                                                                                                                                                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="radio"/> Redirects HTTP traffic to HTTPS                                                                                               |
| <p>Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <a href="#">Learn more.</a></p> |



## SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials.](#)

#### ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

|                                                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="radio"/> Structured data is valid                                                                                                                                      |
| <p>Run the <a href="#">Structured Data Testing Tool</a> and the <a href="#">Structured Data Linter</a> to validate structured data. <a href="#">Learn more about Structured</a></p> |

[Data.](#)

Run these additional validators on your site to check additional SEO best practices.

## PASSED AUDITS (9)

Hide

|                                                                                                                                                                                                                                                          |   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| Page isn't blocked from indexing                                                                                                                                                                                                                         | ^ |
| Search engines are unable to include your pages in search results if they don't have permission to crawl them. <a href="#">Learn more about crawler directives.</a>                                                                                      |   |
| Document has a <title> element                                                                                                                                                                                                                           | ^ |
| The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <a href="#">Learn more about document titles.</a>                                            |   |
| Document has a meta description                                                                                                                                                                                                                          | ^ |
| Meta descriptions may be included in search results to concisely summarize page content. <a href="#">Learn more about the meta description.</a>                                                                                                          |   |
| Page has successful HTTP status code                                                                                                                                                                                                                     | ^ |
| Pages with unsuccessful HTTP status codes may not be indexed properly. <a href="#">Learn more about HTTP status codes.</a>                                                                                                                               |   |
| Links have descriptive text                                                                                                                                                                                                                              | ^ |
| Descriptive link text helps search engines understand your content. <a href="#">Learn how to make links more accessible.</a>                                                                                                                             |   |
| Links are crawlable                                                                                                                                                                                                                                      | ^ |
| Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. <a href="#">Learn how to make links crawlable</a> |   |
| robots.txt is valid                                                                                                                                                                                                                                      | ^ |
| If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <a href="#">Learn more about robots.txt.</a>                                                                            |   |
| Image elements have [alt] attributes                                                                                                                                                                                                                     | ^ |
| Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <a href="#">Learn more about the alt attribute.</a>                                                               |   |
| Document has a valid hreflang                                                                                                                                                                                                                            | ^ |
| hreflang links tell search engines what version of a page they should list in search results for a given language or region. <a href="#">Learn more about hreflang.</a>                                                                                  |   |

Document has a valid `rel=canonical`

Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

Captured at Aug 11, 2025, 3:16 PM GMT+2  
Initial page load

Emulated Moto G Power with Lighthouse 12.6.0  
Slow 4G throttling

Single page session  
Using Chromium 138.0.0.0 with devtools