

# Chapitre 1

Béatrice CARRE

## Introduction

La génération de code se fait en plusieurs passes :

- analyse lexicale et analyse syntaxique de l' idl donnant un ast de type Idl.file.
- vérification des types de l'ast, donnant un nouvel ast de type CIdl.file.
- la génération des fichiers stub java nécessaires pour un appel callback
- la génération à partir de l'ast CIdl.file du fichier .ml
- la génération à partir du CIdl.file du fichier .mli

Ces différentes étapes seront présentées plus en profondeur.

### 1.1 La syntaxe de l'idl

La syntaxe du langage d'interface est donné en annexe, en utilisant la notation BNF.

Les symboles < et > encadrent des règles optionnelles, les terminaux sont en bleu, et les non-terminaux sont en italique.

### 1.2 lexing parsing

La première phase est celle d'analyse lexicale et syntaxique, séparant l'idl en lexèmes et construisant l'AST, défini par Idl.file, dont la structure : est définie en annexe

### 1.3 check

Vient ensuite la phase d'analyse sémantique, analysant l'AST obtenue par la phase précédente, vérifiant si le programme est correct, et construisant une liste de CIdl.clazz, restructurant chaque classe ou interface définie dans l'idl. Le module Cidl définit le nouvel AST allant être manipulé dans les passes de génération de code. Il est décrit en annexe.

## 1.4 génération stub\_file

//TODO

## 1.5 génération .ml

La génération de ce code se fait en plusieurs passes sur l'ast obtenu après ces précédents phases, le CIdl.file.

### 1.5.1 schémas de compilation

La génération de code rend du code OCaml (écrit dans un fichier).  
Nous considérons un environnement contenant les variables suivantes, initialisées à leur valeur par défaut :

$\rho$  = "" : le nom du **package** où trouver les classes définies.  
 $\Gamma$  = false : si la déclaration est une **interface**.  
 $\theta$  = false : si l'élément porte l'attribut **callback**.  
 $\alpha$  = false : si l'élément est déclaré **abstract**.  
 $\delta$  = "JniHierarchy.top" : la classe dont **extends** la classe courante.  
 $\Delta$  = [] : les interfaces qu'**implements** la classe courante.

Et les fonctions suivantes :

init\_env () : réinitialise toutes les variables d'environnement  
init\_class\_env () : réinitialise toutes les variables d'environnement sauf  $\rho$ .  
hd(elt\*) : rend le premier élément de la list elt\*.  
tl(elt\*) : rend la liste elt\* privée de son premier élément.

<b>file</b> $\llbracket package^* \rrbracket \longrightarrow$ $\llbracket hd(package^*) \rrbracket$ init_env (); $\llbracket tl(package^*) \rrbracket$	<b>package</b> $\llbracket package \text{ qname ; decl^* \rrbracket \longrightarrow$ $\llbracket decl^* \rrbracket_{\rho=qname}$
$\llbracket decl^* \rrbracket \longrightarrow$ $\llbracket hd(decl^*) \rrbracket$ init_class_env (); $\llbracket tl(decl^*) \rrbracket$	<b>decl interface</b> $\llbracket \text{interface name} \rrbracket \longrightarrow$ $\llbracket \text{class name} \rrbracket_{\rho, \Gamma=true}$
	<b>decl class</b> $\llbracket [\text{callback}] \text{class name} \rrbracket_{\rho, \Gamma, \theta, \alpha} \longrightarrow$ $\llbracket \text{class name} \rrbracket_{\rho, \Gamma, \theta=true, \alpha}$

```

    decl class
[[class NAME extends E implements I1, I2...{
    attr1; attr2; ...;
    m1; m2; ...;
    init1; init2; ...;
}] $\rho, CB \longrightarrow$ 

let clazz = Jni.find_class PACK/NAME

(** type jni.obj t *)
"type _jni_jNAME = Jni.obj"

(** classe encapsulante *)
"class type jNAME =
  object inherit E
  inherits jI1
  inherits jI2 ...
  method _get_jni_jNAME : _jni_jNAME
  end"

(** upcast jni *)
"let __jni_obj_of_jni_jNAME (java_obj : _jni_jNAME) =
  (Obj.magic : _jni_jNAME -> Jni.obj) java_obj"
(** downcast jni *)
"let __jni_jNAME_of_jni_obj =
  fun (java_obj : Jni.obj) ->
    Jni.is_instance_of java_obj clazz"

(* allocation : si ce n'est pas une interface *)
"let _alloc_jNAME =
  fun () -> (Jni.alloc_object clazz : _jni_jNAME)"

(* capsule wrapper *)
"class _capsule_jNAME = fun (jni_ref : _jni_jNAME) ->
  object (self)
    method _get_jni_jNAME = jni_ref
    method _get_jni_jE = jni_ref
    method _get_jni_jI1 = jni_ref
    method _get_jni_jI2 = jni_ref
    inherit JniHierarchy.top jni_ref
  end"

(** downcast utilisateur *)
"let jNAME_of_top (o : TOP) : jNAME =
  new _capsule_jNAME (__jni_jNAME_of_jni_obj o#_get_jniobj)"
(** instance_of *)
"let _instance_of_jNAME =
  in fun (o : TOP) -> Jni.is_instance_of o#_get_jniobj clazz"

(* tableaux *)
"let _new_jArray_jNAME size =
  let java_obj = Jni.new_object_array size (Jni.find_class \"PACK/NAME\")"

```

```

in
  new JniArray._Array Jni.get_object_array_element Jni.
    set_object_array_element (fun jniobj -> new _capsule_jNAME jniobj)
    (fun obj -> obj#_get_jni_jNAME) java_obj"
"let jArray_init_jNAME size f =
  let a = _new_jArray_jNAME size
  in (for i = 0 to pred size do a#set i (f i) done; a)"

(* inits *)

[[[name init1]<init>(arg*);...]]
[[[name init1]<init>(arg*);...]]
...

(* fonctions et methodes statiques*)

(*TODO*)

```

Ce tableau représente le résultat des fonctions `str`, `jni_type`, `getJni`, `cast` sur les types lors des générations des constructeurs ou des méthodes.

TYPE	str	jni_type	getJni	cast
void	"   V			
boolean	Z	Jni.Boolean _pi	_pi	_pi
byte	B	Jni.Byte _pi	_pi	_pi
char	C	Jni.Char _pi	_pi	_pi
short	S	Jni.Short _pi	_pi	_pi
int	I	Jni.Camlint _pi	_pi	_pi
long	J	Jni.Long _pi	_pi	_pi
float	F	Jni.Float _pi	_pi	_pi
double	D	Jni.Double _pi	_pi	_pi
string	LJava/lang/String;	Jni.Obj _pi	Jni.string_to_java _pi	_pi
pack/Obj	Lpack/Obj;	Jni.Obj _pi	_pi#_get_jni_jname	(_pi : jObj)

### inits

```

[[[name INIT]<init>(A0, A1, ...)] →
"let _init_INIT =
  let id = Jni.get_methodID clazz \"<init>\"
    \"(\"(toStr A0)(toStr A1) ... )V\"
  in
    fun (java_obj : _jni_jNAME) \"(cast A0) (cast A1) ...\" ->
      ...
      let _p1 = \"(getJni A1)\" in
      let _p0 = \"(getJni A0)\" in
      Jni.call_nonvirtual_void_method java_obj clazz id
        [| \"(jni\_type A0)\"; \"(jni\_type A1)\"; ... |]

class INIT _p0 _p1 ... =
  let java_obj = _alloc_jNAME ()

```

```

    in let _ = _init_INIT java_obj _p0 _p1 ...
    in object (self) inherit _capsule_jNAME java_obj
end"

```

## attributs

$\llbracket TYPE\ ATTR; \rrbracket \longrightarrow$

```

...
(* type class *)
"class type jNAME =
...
  method set_ATTR : (j)TYPE -> unit
  method get_ATTR : unit -> (j)TYPE
... "
(* capsule *)
"class _capsule_jNAME =
  let __fid_ATTR = try Jni.get_fieldID clazz "\"ATTR\"" (toStr TYPE) in
  ...
  fun (jni_ref : _jni_jNAME) ->
    object (self)
      method set_ATTR =
        fun "(castArg TYPE)" ->
          let _p = "(getJni TYPE)"
          in Jni.set_object_field jni_ref __fid_ATTR _p
      method get_ATTR =
        fun () ->
          (new _capsule_jNAME (Jni.get_object_field jni_ref __fid_ATTR) :
           jNAME)
      ...
    "

```

## methodes

$\llbracket TYPE METH(ARG1, ARG2, \dots) \rrbracket \longrightarrow$

```

...
(* type class *)
"class type jNAME =
...
  method METH : ARG1 -> ARG2 -> ... -> TYPE
... "
(* capsule *)
"class _capsule_jNAME =
  let __mid_METH = Jni.get_methodID clazz "mETH"
  \\"(\"(toStr ARG1)(toStr ARG2)...\")\"(toStr TYPE)\"\\
  ...
  in
    object (self)
      (*TODO*) " (*method METHObj1Obj2 =
        fun (_p0 : jObj1) ->
          let _p0 = _p0#_get_jni_jObj1
          ...
          in
            (new _capsule_jObj2

```

```

        (Jni.call_ "Object" _method jni_ref __mid_mETHObj1Obj2
         [| Jni.Obj _p0 |]) : jObj2)
*)
method METH =
  fun "(cast A0) (cast A1) ..." =>
    let _p2 = "(getJni ARG2)" in
    let _p1 = "(getJni ARG1)" in
    let _p0 = "(getJni ARG0)"
    in
      Jni.call_ "(aJniType TYPE)" _method jni_ref __mid_METH
        [| "(jni\_type ARG0)"; "(jni\_type ARG1)"; ... |]
//TODO : retour Obj dans methode array callback

```

## 1.6 génération .mli

## 1.7 Ocaml-Java

## 1.8 Génération pour Ocaml-Java

Le type top manipulé sera le type d'instance objet de Ocaml-Java :

```
type top = java`lang`Object java_instance;;
```

Exception :

```
exception Null_object of string
```

```
class
[[class NAME extends E implements I1, I2...{
    attr1; attr2; ...;
    m1; m2; ...;
    init1; init2; ...;
}] ]ρ,CB →
```

```
(** type jni.obj t *)
"type _jni_jNAME = PACK'NAME java_instance;;"
```

```
(** classe encapsulante *)
"class type jNAME =
  object inherit E
    inherits jI1
    inherits jI2 ...
    method _get_jni_jNAME : _jni_jNAME
  end"
```

```
(* capsule wrapper *)
"class _capsule_jNAME =
  fun (jni_ref : _jni_jNAME) ->
    let _ =
      if Java.is_null jni_ref
      then raise (Null_object "mypack/Point")
      else ()
    in

    object (self)
      (* method _get_jni_jNAME = jni_ref
        method _get_jni_jE = jni_ref
        method _get_jni_jI1 = jni_ref
        method _get_jni_jI2 = jni_ref*)
      inherit JniHierarchy.top jni_ref
    end"
```

```
(* downcast utilisateur *)
"let jNAME_of_top (o : TOP) : jNAME =
```

```

    new _capsule_jNAME ( _jni_jNAME_of_jni_obj o#_get_jniobj )"
(* instance_of *)
"let _instance_of_jNAME =
  in fun (o : TOP) -> Jni.is_instance_of o#_get_jniobj clazz"

(* tableaux *)
"let _new_jArray_jNAME size =
  let java_obj = Jni.new_object_array size (Jni.find_class \"PACK/NAME\")
  in
    new JniArray._Array Jni.get_object_array_element Jni.
      set_object_array_element (fun jniobj -> new _capsule_jNAME jniobj)
      (fun obj -> obj#_get_jni_jNAME) java_obj"
"let jArray_init_jNAME size f =
  let a = _new_jArray_jNAME size
  in (for i = 0 to pred size do a#set i (f i) done; a)"

```



# Annexe

## BNF

```
class

file ::= package <package>*
      | decl <decl>*

package ::= package qname ; decl <decl>*

decl ::= class
      | interface

class ::= <[attributes]> <abstract> class name
      < extends qname >
      < implements qname <, qname>* >
      { <class_elt ;>* }
class_elt ::= <[ attributes ]> <static> <final> type name
            | <[ attributes ]> <static> <abstract> type name (<args>)
            | [ attributes ] <init> (<args>)

interface ::= <[ attributes ]> interface name
            < extends qname <, qname>* >
            { <interface_elt;>* }
interface_elt ::=
            <[ attributes ]> type name
            | <[ attributes ]> type name (<args>)

args ::= arg <, arg>*
arg ::= <[ attributes ]> type <name>

attributes ::= attribute <, attribute>*
attribute ::= name ident
            | callback
            | array

type ::= basetype
      | object
      | basetype [ ]
basetype ::= void
           | boolean
           | byte
           | char
           | short
           | int
           | long
           | float
           | double
           | string
object ::= qname
qname ::= name <.name>*
name ::= ident
```

## Module Idl

```
(** module Idl *)

type ident = {
  id_location: Loc.t;
  id_desc: string
}
type qident = {
  qid_location: Loc.t;
  qid_package: string list;
  qid_name: ident;
}
type type_desc =
| Ivoid
| Iboolean
| Ibyte
| Ishort
| Icamlint
| Iint
| Ilong
| Ifloat
| Idouble
| Ichar
| Istring
| Itop
| Iarray of typ
| Iobject of qident
and typ = {
  t_location: Loc.t;
  t_desc: type_desc;
}
type modifier_desc =
| Ifinal
| Istatic
| Iabstract
and modifier = {
  mo_location: Loc.t;
  mo_desc: modifier_desc;
}
type ann_desc =
| Iname of ident
| Icallback
| Icamllarray
and annotation = {
  an_location: Loc.t;
  an_desc: ann_desc;
}

}
type arg = {
  arg_location: Loc.t;
  arg_annot: annotation list;
  arg_type: typ
}
type init = {
  i_location: Loc.t;
  i_annot: annotation list;
  i_args: arg list;
}
type field = {
  f_location: Loc.t;
  f_annot: annotation list;
  f_modifiers: modifier list;
  f_name: ident;
  f_type: typ
}
type mmethod = {
  m_location: Loc.t;
  m_annot: annotation list;
  m_modifiers: modifier list;
  m_name: ident;
  m_return_type: typ;
  m_args: arg list
}
type content =
| Method of mmethod
| Field of field
type def = {
  d_location: Loc.t;
  d_super: qident option;
  d_implements: qident list;
  d_annot: annotation list;
  d_interface: bool;
  d_modifiers: modifier list;
  d_name: ident;
  d_inits: init list;
  d_contents: content list;
}
type package = {
  p_name: string list;
  p_defs: def list;
}
type file = package list
```

## Module CIdl

```
(** module CIdl *)
type typ =
| Cvoid
| Cboolean (** boolean -> bool *)
| Cchar (** char -> char *)
| Cbyte (** byte -> int *)
| Cshort (** short -> int *)
| Ccamlint (** int -> int<31> *)
| Cint (** int -> int32 *)
| Clong (** long -> int64 *)
| Cfloat (** float -> float *)
| Cdouble (** double -> float *)
| Ccallback of Ident.clazz
| Cobject of object_type (** object -> ... *)
and object_type =
| Cname of Ident.clazz (** ... -> object *)
| Cstring (** ... -> string *)
| Cjavaarray of typ (** ... -> t jArray *)
| Carray of typ (** ... -> t array *)
| Ctop

type clazz = {
  cc_abstract: bool;
  cc_callback: bool;
  cc_ident: Ident.clazz;
  cc_extend: clazz option; (* None = top *)
  cc_implements: clazz list;
  cc_all_inherited: clazz list; (* tout jusque top ... (et avec les
    interfaces) sauf elle-meme. *)
  cc_inits: init list;
  cc_methods: mmethod list; (* methodes + champs *)
  cc_public_methods: mmethod list; (* methodes declarees + celles
    heritees *)
  cc_static_methods: mmethod list;
}
and mmethod_desc =
| Cmethod of bool * typ * typ list (* abstract, rtype, args *)
| Cget of typ
| Cset of typ
and mmethod = {
  cm_class: Ident.clazz;
  cm_ident: Ident.mmethod;
  cm_desc: mmethod_desc;
}
and init = {
  cmi_ident: Ident.mmethod;
  cmi_class: Ident.clazz;
  cmi_args: typ list;
}
type file = clazz list
```

## module Ident

```
(* module Ident *)
(* le type des identifiants de classe de l'IDL *)
type clazz = {
  ic_id: int;
  ic_interface: bool;
  ic_java_package: string list;
  ic_java_name: string;
  ic_ml_name: string;
  ic_ml_name_location: Loc.t;
  ic_ml_name_kind: ml_kind;
}
type mmethod = {
  im_java_name: string;
  im_ml_id: int; (** entier unique pour une nom ml *)
  im_ml_name: string;
  im_ml_name_location: Loc.t;
  im_ml_name_kind: ml_kind;
}
```

## idl\_camlgen.make ast

Type jni

*MlClass.make\_jni\_type*

Class type

*MlClass.make\_class\_type*

Cast JNI

*MlClass.make\_jniupcast*

*MlClass.make\_jnidowncast*

Fonction d'allocation

*MlClass.make\_alloc*

*MlClass.make\_alloc\_stub*

Capsule / souche

*MlClass.make\_wrapper*

Downcast utilisateur

*MlClass.make\_downcast*

*MlClass.make\_instance\_of*

Tableaux

*MlClass.make\_array*

Fonction d'initialisation

*MlClass.make\_fun*

Classe de construction

*MlClass.make\_class*

fonctions / methodes static

*MlClass.make\_static*