

Unity Android SDK Integration Guide

This document details the process of integrating the Beachfront .iO Ad SDK with your Android application.

Requirements

- 1. Beachfront .iO app ID & Ad Unit ID Get it from here.
- 2. Beachront SDK Jar
- 3. Android 1.5 and above

Installation

- 1. Access the Beachfront.iO Console & register your application to get your App ID & Ad unit ID;
- 2. Download the Beachfront Android AD SDK & Android Support Library, copy into the /lib folder of your Android Project. Make sure the jar files in lib is selected in the Order and Export tab of the Java Build Path panel.
- 3. Add the BF activity in the application node of AndroidManifesh.xml:

```
<activity
android:name="com.bfio.ad.BFIOActivity"
android:configChanges="keyboardHidden|orientation|screenSize"
/>
```

Make sure to have android:targetSdkVersion should be equal or greater then 13 in the manifest.

```
<uses-sdk android:targetSdkVersion="13" />
```

Add following required permission in your AndroidManifest.xml

```
<uses-permission android:name="android.permission.READ_PHONE_STATE" />
<uses-permission android:name= "android.permission.INTERNET" />
<uses-permission android:name= "android.permission.ACCESS_NETWORK_STATE" />
```

Once you've completed the above steps, you can start displaying ads in your application by following the simple instructions for Interstitial Ad as below:

In your Activity class (the one from which you want to show the ad), declare a BFIOInterstitial instance variable, register your activity as the interstitial's BFIOInterstitial. InterstitialListener and instantiate it in the onCreate(Bundle savedInstanceState) method.

```
public class MainActivity extends Activity implements
BFIOInterstitial.InterstitialListener {

BFIOInterstitial interstitial;

@Override
protected void onCreate(Bundle savedInstanceState)
{
  super.onCreate(savedInstanceState);
  setContentView(R.layout.activity_main);
  interstitial = new BFIOInterstitial(MainActivity.this, this);
}
}
```

Your application is now ready to display an interstitial ad. Call requestInterstitial method to request an interstitial ad. You have to pass the appld & adUnitId

```
interstitial.requestInterstitial("appid", // appID "addUnitId"); //adUnitId
```

In case Ad Server find a AD it will return to

public void onReceiveInterstitial(BFIOInterstitialAd ad);

Otherwise will return to:

public void onInterstitialFailed(BFIOErrorCode errorCode);

To start the Interstitial Call the following method

interstitial.showInterstitial(ad);

```
/**
* On Interstitial Failed
* @param errorCode
public void on InterstitialFailed(BFIOErrorCode errorCode);
/**
*Interstitial Displaying on the screen
public void onInterstitialStarted();
* Interstitial clicked
*/
public void onInterstitialClicked();
* Interstitial dismissed
*
*/
public void onInterstitialDismissed();
/**
* Interstitial completed
public void onInterstitialCompleted();
/**
* On Interstitial Received
public void onReceiveInterstitial(BFIOInterstitialAd ad);
```

Example Code:

```
public class MainActivity extends Activity implements
BFIOInterstitial.InterstitialListener, OnClickListener {
BFIOInterstitial interstitial;
```

```
@Override
protected void onCreate(Bundle savedInstanceState) {
      super.onCreate(savedInstanceState);
      setContentView(R.layout.activity main);
      findViewById(R.layout.activity main);
      interstitial = new BFIOInterstitial(MainActivity.this, this);
}
@Override
publicboolean onCreateOptionsMenu(Menu menu) {
      getMenuInflator().inflate(R.menu.main, menu);
      return true;
}
@Override
protected void onDestroy() {
      interstitial.onDestroy();
      super.onDestroy();
}
@Override
protected void onInterstitialFailed(BFIOErrorCode errorCode) {
      Toast.makeText(MainActivity.this, "Interstitial not Received",
             Toast.LENGTH SHORT).show();
}
@Override
public void onInterstitialClicked() {
      Toast.makeText(MainActivity.this, "Interstitial Clicked",
             Toast.LENGTH SHORT).show();
}
@Override
public void onInterstitialDismissed() {
      Toast.makeText(MainActivity.this, "Interstitial dismissed",
             Toast.LENGTH_SHORT).show();
}
@Override
public void onReceiveInterstitial(BFIOInterstitialAd ad) {
      Toast.makeText(MainActivity.this, "Received Interstitial",
             Toast.LENGTH SHORT).show();
      interstitial.showInterstitial(ad);
}
@Override
public void onClick(View v) {
      switch (v.getId()){
```

```
case R.id.request:
             interstitial.requestInterstitial("appid", // appID
                                        "addUnitId"); // addUnitId
             Toast.makeText(MainActivity.this, "Interstitial request sent",
                                        Toast.LENGTH_SHORT).show();
             break;
             default:
             }
      }
       @Override
       public void onInterstitialCompleted() {
             Toast.makeText(MainActivity.this, "Interstitial play completed",
                                 Toast.LENGTH_SHORT).show();
      }
      @Override
      public void onInterstitialStarted() {
             Toast.makeText(MainActivity.this, "Interstitial started",
                                 Toast.LENGTH_SHORT).show();
      }
}
```