

Javascript, The Swiss Army Knife of Programming Languages

David Morcillo

23-11-2013

About me



- twitter.com/ultrayoshi
- github.com/ultrayoshi

Features

- Loosely typed language

Features

- Loosely typed language
- Object literal notation

Features

- Loosely typed language
- Object literal notation
- Prototypal inheritance

Features

- Loosely typed language
- Object literal notation
- Prototypal inheritance
- Global variables

Features

- Loosely typed language
- Object literal notation
- Prototypal inheritance
- Global variables
- Functions are first class objects

Features

ECMAScript

The standard that defines JavaScript is the third edition of *ECMAScript Programming Language*.

Hello World

index.html

```
<html>
  <head>
    <script>
      document.writeln('Hello, world!');
    </script>
  </head>
  <body>
  </body>
</html>
```

Syntax

Comments

Block comments formed with `/* */` and line-ending comments starting with `//`. Example:

```
/*  
    We are learning Javascript and comments are very important  
*/  
document.writeln('Hello World!'); // Output: Hello World!
```

Syntax

Comments

Block comments formed with `/* */` and line-ending comments starting with `//`. Example:

```
/*
  We are learning Javascript and comments are very important
*/
document.writeln('Hello World!'); // Output: Hello World!
```

Names

Starts with a letter or underscore and optionally followed by on or more letters, digits or underscores. Beware of some reserved words.

bullet	// valid	_mana	// valid
3force	// invalid	lucky42	// valid
rocket-launcher	// invalid	grenade_launcher	// valid

Syntax

Numbers

Single number type represented internally as 64-bit floating point.

```
42
```

```
3.141516
```

```
10e5
```

```
1/0 // Output: Infinity
```

```
0/0 // Output: NaN
```

Syntax

Numbers

Single number type represented internally as 64-bit floating point.

```
42
3.141516
10e5
1/0 // Output: Infinity
0/0 // Output: NaN
```

Strings

Can be wrapped in single quotes or double quotes. It can contains 0 or more characters. All characters in Javascript are 16 bits wide.

```
‘Hello World’
‘Hello World’
‘This is\n a multiline string’
‘You can write ‘ on single quotes string’
```

Syntax

Functions

```
function helloWorld (name) {  
    console.log('Hello ' + name + '!');  
}  
  
helloWorld('David'); // Output 'Hello David!'  
  
var myFunction = function () {  
    console.log('Hi there!');  
};  
  
myFunction(); // Output: 'Hi there!'
```

Syntax

Variables

Use the `var` keyword followed by a name to declare a variable. When used inside of a function, the `var` statement defines the function's private variables.

```
var player; // variable player declared on a global scope

function test() {
  var enemy; // Scoped to function test
}
```


Syntax

Strict (in)equality

```
10 == '10' // Output: true, auto type coercion  
10 === '10' // Output: false strict equality  
10 != '10' // Output: false, auto type coercion  
10 !== '10' // Output: true strict inequality
```

Syntax

Strict (in)equality

```
10 == '10' // Output: true, auto type coercion
10 === '10' // Output: false strict equality
10 != '10' // Output: false, auto type coercion
10 !== '10' // Output: true strict inequality
```

null and undefined

```
console.log(mario); // Error: mario is not defined

function exists (mario) {
  console.log(mario);
}

exists(); // Output undefined

console.log(null == undefined) // Output: true
console.log(null === undefined) // Output: false
```

Syntax

if, else

```
var testOk = true;

if (testOk) {
    console.log('Captain obvious');
} else {
    console.log('I'm bored');
}
```

Here are the *false* values:

- false
- null
- undefined
- The empty string
- The number 0
- The number NaN

All other values are *truthy*.

Syntax

switch

```
var weapon = 'rocketlauncher';

switch(weapon) {
  case 'pistol':
    console.log('piu piu');
    break;
  case 'shotgun':
    console.log('paaam!');
    break;
  case 'rocketlauncher'
    console.log('BOOOOM!');
    break;
  default:
    console.log('falcon punch!');
    break;
}
```

Syntax

while, do while

```
var counter = 0;
while (counter < 10) { // Ends when counter is equal to 10
    console.log(counter);
    counter += 1;
}

do {
    console.log(counter);
    i -= 1;
} while(counter > 0); // Ends when counter is equal to 0
```

Syntax

while, do while

```
var counter = 0;
while (counter < 10) { // Ends when counter is equal to 10
    console.log(counter);
    counter += 1;
}

do {
    console.log(counter);
    i -= 1;
} while(counter > 0); // Ends when counter is equal to 0
```

for

```
var i;

for (i = 0; i < 10; i += 1)
    console.log(i);
}
```


Objects

- Objects in Javascript are mutable keyed collections.

Objects

- Objects in Javascript are mutable keyed collections.
- Arrays, functions and regular expressions are objects.

Objects

- Objects in Javascript are mutable keyed collections.
- Arrays, functions and regular expressions are objects.
- A property name can be any string.

Objects

- Objects in Javascript are mutable keyed collections.
- Arrays, functions and regular expressions are objects.
- A property name can be any string.
- Objects can inherit properties of another through its prototype.

Objects

- Objects in Javascript are mutable keyed collections.
- Arrays, functions and regular expressions are objects.
- A property name can be any string.
- Objects can inherit properties of another through its prototype.

Prototype

All objects created from object literals are linked to `Object.prototype`.

Objects

- Objects in Javascript are mutable keyed collections.
- Arrays, functions and regular expressions are objects.
- A property name can be any string.
- Objects can inherit properties of another through its prototype.

Prototype

All objects created from object literals are linked to `Object.prototype`. If we try to retrieve a property value from an object, and if the object lacks the property name, then Javascript attempts to retrieve the property value from the prototype object.

Objects

Object.create

```
var soldier = {  
  hp: 10,  
  strength: 5,  
  weapon: 'Pistol'  
};  
  
var knight = Object.create(soldier);  
knight.weapon = 'Sword';  
knight.shield = true;  
  
console.log(knight.hp); // Output: 10  
console.log(knight['weapon']); // Output: 'Sword'  
console.log(knight.shield); // Output: true
```

Visit <http://www.objectplayground.com/> for a graphical explanation

Objects

hasOwnProperty

```
console.log(knight.hasOwnProperty('hp')); // Output: false  
console.log(knight.hasOwnProperty('shield')); // Output: true
```

Objects

hasOwnProperty

```
console.log(knight.hasOwnProperty('hp')); // Output: false  
console.log(knight.hasOwnProperty('shield')); // Output: true
```

for in

```
for (attr in knight) {  
    if(knight.hasOwnProperty(attr)) {  
        console.log('Knight property ' + attr + ' with value ' +  
            knight[attr]);  
    }  
}  
// Knight property weapon with value 'Sword'  
// Knight property shield with value true
```


Objects

hasOwnProperty

```
console.log(knight.hasOwnProperty('hp')); // Output: false  
console.log(knight.hasOwnProperty('shield')); // Output: true
```

for in

```
for (attr in knight) {  
    if(knight.hasOwnProperty(attr)) {  
        console.log('Knight property ' + attr + ' with value ' +  
            knight[attr]);  
    }  
}  
// Knight property weapon with value 'Sword'  
// Knight property shield with value true
```

delete

```
console.log(knight.weapon); // Output: 'Sword'  
delete knight.weapon;  
console.log(knight.weapon); // Output: 'Pistol'
```

Functions

Functions are the **fundamental modular unit** of Javascript. They are used for code reuse, information hiding, and composition. The thing that is special about functions is that they can be invoked.

Functions

Functions are the **fundamental modular unit** of Javascript. They are used for code reuse, information hiding, and composition. The thing that is special about functions is that they can be invoked.

Function.prototype and constructor

Functions are objects linked to `Function.prototype`. Every function object is also created with a `prototype` property. Its value is an object with a `constructor` property whose value is the function.

Functions

Functions are the **fundamental modular unit** of Javascript. They are used for code reuse, information hiding, and composition.

The thing that is special about functions is that they can be invoked.

Function.prototype and constructor

Functions are objects linked to `Function.prototype`. Every function object is also created with a `prototype` property. Its value is an object with a `constructor` property whose value is the function.

Functions

Invoking a function suspends the execution of the current function, passing control and parameters to the new function. In addition to the declared parameters, every function receives two additional parameters: `this` and `arguments`.

Functions

Invoking a function suspends the execution of the current function, passing control and parameters to the new function. In addition to the declared parameters, every function receives two additional parameters: `this` and `arguments`.

Invocation (1/4): Method invocation pattern

```
var enemy = {  
  hp: 5,  
  rage: 0,  
  attack: function () {  
    this.rage += 1;  
  }  
};  
  
enemy.attack();  
console.log(enemy.rage); // Output: 1
```

Functions

Invocation (2/4): Function invocation pattern

```
// part of code omitted
physicsManager.collisionsDetected = 0;
physicsManager.checkCollision = function (entity1, entity2) {
  var bbCollision = function (bb1, bb2) {
    // Collision code omitted
    var collision = true;
    if (collision) {
      // WARNING: 'this' is the global object and not 'physicsManager'
      this.collisionsDetected += 1;
    }
    return collision;
  };

  bbCollision(entity1.getBB(), entity2.getBB());
};

if (physicsManager.checkCollision(enemy, player)) {
  player.takeDamage(enemy.strength);
}

console.log(physicsManager.collisionsDetected); // Output: 0
```

Functions

Invocation (2/4): Function invocation pattern (workaround)

```
physicsManager.collisionsDetected = 0;

physicsManager.checkCollision = function (entity1, entity2) {
  var that = this;

  var bbCollision = function (bb1, bb2) {
    // Collision code omitted
    var collision = true;
    if (collision) {
      that.collisionsDetected += 1;
    }
    return collision;
  };

  bbCollision(entity1.getBB(), entity2.getBB());
};

if (physicsManager.checkCollision(enemy, player)) {
  player.takeDamage(enemy.strength);
}
```


Functions

Invocation (3/4): Constructor invocation pattern

```
var Player = function (name) {  
    this.name = name;  
    this.lives = 3;  
};  
  
Player.prototype.sayMyName = function () {  
    console.log('My name is ' + this.name);  
};  
  
var david = new Player('David');  
david.sayMyName(); // Output: 'My name is David'
```

Functions

Invocation (3/4): Constructor invocation pattern (without new)

```
var Player = function (name) {  
    this.name = name;  
    this.lives = 3;  
};  
  
Player.prototype.sayMyName = function () {  
    console.log('My name is ' + this.name);  
};  
  
var manfred = Player('Manfred'); // oops  
try {  
    manfred.sayMyName(); // raise an error because manfred is undefined  
} catch (e) {  
    console.log('[ ' + e.name + ' ] ' + e.message);  
}  
  
// Global variables feast  
console.log(name); // Output: 'Manfred'  
console.log(lives); // Output: 3
```

Functions

Invocation (4/4): Apply invocation pattern

```
var enemy = {  
  rage: 0,  
  attack: function () {  
    this.rage += 1;  
  }  
};  
  
var anotherEnemy = {  
  rage: 10  
};  
  
enemy.attack.apply(anotherEnemy, []);  
  
console.log(anotherEnemy.rage); // Output: 11
```

Functions

Arguments

```
function doActions() {  
    var i, l;  
  
    // WARNING: arguments is an Array-like object  
    for (i = 0, l = arguments.length; i < l; i += 1) {  
        console.log('Doing action ' + arguments[i]);  
    }  
}  
  
doActions('jump', 'attack');  
/*  
    Output:  
    'Doing action jump'  
    'Doing action attack'  
*/
```

Functions

Closure

Javascript does have function scope. That means that the parameters and variables defined in a function are not visible outside of the function, and that a variable defined anywhere within a function is visible everywhere within the function.

```
var player = new Player();

function isGameOver() {
    var enemy = new Enemy();

    function checkHit() {
        return enemy.hit(player);
    }

    return checkHit();
}

isGameOver();
```

Functions

Module pattern

```
var physicsModule = (function () { // IIEF pattern
    var detectedCollisions = 0;

    function checkBBCollision(bb1, bb2) {
        var collision = false;
        // collision code skipped
        if (collision) {
            detectedCollisions += 1;
        }
        return collision;
    }

    function checkCollision(entity1, entity2) {
        checkBBCollision(entity1.getBB(), entity2.getBB());
    }

    return {
        checkCollision: checkCollision
    };
})();

console.log(physicsModule.detectedCollisions); // Output: undefined
console.log(physicsModule.checkBBCollision); // Output: undefined
console.log(typeof physicsModule.checkCollision); // Output: 'function'
```

Inheritance

Javascript provides a much richer set of code reuse patterns. It can ape the classical pattern, but it also supports other patterns that are more expressive.

Inheritance

Javascript provides a much richer set of code reuse patterns. It can ape the classical pattern, but it also supports other patterns that are more expressive.

Javascript is a class-free language

In classical languages, objects are instances of classes, and a class can inherit from another class. Javascript is a prototypal language, which means that objects inherit directly from other objects.

Inheritance

Pseudoclassical pattern

```
var Alien = function (name) {  
    this.name = name;  
};  
  
Alien.prototype.talk = function () {  
    console.log('%?saf? ' + this.name);  
};  
  
var SmartAlien = function (name) {  
    this.name = name;  
};  
  
SmartAlien.prototype = new Alien();  
  
SmartAlien.prototype.speech = function () {  
    this.talk();  
    console.log('...I mean, my name is ' + this.name);  
};  
  
var enemy = new SmartAlien('Roger');  
enemy.speech();  
// Output: '%?saf? Roger  
//         ...I mean, my name is Roger'
```

Inheritance

Prototypal pattern

```
var alien = {  
  name: '%?&789',  
  talk: function () {  
    console.log('%?saf? ' + this.name);  
  }  
};  
  
var smartAlien = Object.create(alien);  
smartAlien.speech = function () {  
  this.talk();  
  console.log('...I mean, my name is ' + this.name);  
};  
  
var enemy = Object.create(smartAlien);  
enemy.name = 'Roger';  
enemy.speech();  
// Output: '%?saf? Roger  
//          ...I mean, my name is Roger'
```

Inheritance

Functional pattern

```
var alien = function (spec) {
  var that = {};

  var killHumans = function () { // Private access
    console.log('*Using ' + spec.weapon + '*');
  };

  that.talk = function () {
    console.log('%&78 ' + spec.name);
    if (spec.weapon) {
      killHumans();
    }
  };

  return that;
};

var enemy = smartAlien({ name: 'Roger' });
enemy.speech();
// Output: '%?saf? Roger
//          *Using Pistol*
//          ...I mean, my name is Roger'
```

```
var smartAlien = function (spec) {
  spec.weapon = 'Pistol'; // Private access
  var that = alien(spec);

  that.speech = function () {
    that.talk();
    console.log('...I mean, my name is ' +
      spec.name);
  };
  return that;
};
```

Arrays

Arrays doesn't exist

Javascript provides an object that has some array-like characteristics. It converts array subscripts into strings that are used to make properties.

Arrays

Arrays doesn't exist

Javascript provides an object that has some array-like characteristics. It converts array subscripts into strings that are used to make properties.

Arrays literals

```
var enemies = [];  
  
console.log(enemies[9999]); // Output: undefined  
  
enemies[0] = 'Sigma';  
console.log(enemies[0]); // Output: 'Sigma'  
  
enemies[1] = 9000; // We can mix different types  
console.log(enemies[1]); // Output: 9000
```

Arrays

Remove elements

```
var enemies = ['Grassman', 'Bowser', 'Sephiroth'],  
    players = ['David', 'Manfred', 'Joanmi'];
```

```
delete enemies[1]; // Bad idea  
console.log(enemies[1]); // Output: undefined  
console.log(enemies.length); // Output: 3
```

```
players.splice(1, 1); // Yeah!  
console.log(players[1]); // Output: 'Joanmi'  
console.log(players.length); // Output: 2
```


What is Node.js?

Website definition

Node.js is a platform built on Chrome's JavaScript runtime for easily building fast, scalable network applications. Node.js uses an event-driven, non-blocking I/O model that makes it lightweight and efficient, perfect for data-intensive real-time applications that run across distributed devices.



Installation

From source-code or pre-built installer

Visit <http://nodejs.org/download/> and choose the package for your platform.

Installation

From source-code or pre-built installer

Visit <http://nodejs.org/download/> and choose the package for your platform.

Using nvm (UNIX environments)

Visit <https://github.com/creationix/nvm> and follow instructions.

Installation

From source-code or pre-built installer

Visit <http://nodejs.org/download/> and choose the package for your platform.

Using `nvm` (UNIX environments)

Visit <https://github.com/creationix/nvm> and follow instructions.

Check installation

```
$ node -v  
v0.8.21  
$ npm -v  
1.2.11
```

Node packages

Node.js has a lot of packages that can be installed using `npm`. You can publish your own code as a node package and it will be available through `npm`.

Node packages

Node.js has a lot of packages that can be installed using `npm`. You can publish your own code as a node package and it will be available through `npm`.

Installing packages

```
$ npm install <package_name>
```


What is Bower?

Website definition

Bower is a package manager for the web. It offers a generic, unopinionated solution to the problem of front-end package management, while exposing the package dependency model via an API that can be consumed by a more opinionated build stack.



Installation

Using npm

```
$ npm install -g bower
```


Installation

Using npm

```
$ npm install -g bower
```

Verify installation

```
$ bower -v  
1.2.7
```

Commands

bower init

Creates a bower.json file for including our application dependencies. Also, it's mandatory in order to register our application as a bower package or used on our internal projects through bower.

```
$ bower init
// Press ENTER for default answers
$ cat bower.json
{
  'name': 'js-workshop-code',
  'version': '0.0.0',
  'homepage': 'https://github.com/ultrayoshi/js-workshop-code',
  'authors': [
    'ultrayoshi <david@imesmes.com>'
  ],
  'license': 'MIT',
  'ignore': [
    '**/*.*',
    'node_modules',
    'bower_components',
    'test',
    'tests'
  ]
}
```

Commands

bower search

Find all packages or a specific package

```
$ bower search jquery
Search results:
jquery git://github.com/components/jquery.git
jquery-ui git://github.com/components/jqueryui
jquery.cookie git://github.com/carhartl/jquery-cookie.git
jquery-placeholder git://github.com/mathiasbynens/jquery-placeholder.git
jquery-file-upload git://github.com/blueimp/jQuery-File-Upload.git
jasmine-jquery git://github.com/velesin/jasmine-jquery
jquery.ui git://github.com/jquery/jquery-ui.git
jquery.scrollTo git://github.com/flesler/jquery.scrollTo.git
jquery-migrate git://github.com/appleboy/jquery-migrate.git
jquery-waypoints git://github.com/imakewebthings/jquery-waypoints.git
...
```

Commands

bower search

Find all packages or a specific package

```
$ bower search jquery
Search results:
jquery git://github.com/components/jquery.git
jquery-ui git://github.com/components/jqueryui
jquery.cookie git://github.com/carhartl/jquery-cookie.git
jquery-placeholder git://github.com/mathiasbynens/jquery-placeholder.git
jquery-file-upload git://github.com/blueimp/jQuery-File-Upload.git
jasmine-jquery git://github.com/velesin/jasmine-jquery
jquery.ui git://github.com/jquery/jquery-ui.git
jquery.scrollTo git://github.com/flesler/jquery.scrollTo.git
jquery-migrate git://github.com/appleboy/jquery-migrate.git
jquery-waypoints git://github.com/imakewebthings/jquery-waypoints.git
...
```

bower home <package>

Opens a package homepage into your favorite browser

```
$ bower home jquery
```

Commands

bower install [package]

Install a package locally

```
$ bower install jquery --save-dev
bower jquery#*                cached git://github.com/components/jquery.git#2.0.3
bower jquery#*                validate 2.0.3 against git://github.com/components/jquery.git#*
bower jquery#~2.0.3           install jquery#2.0.3

jquery#2.0.3 bower_components/jquery
```

--save-dev option add the package as a dependency of your application.
Leave package name blank in order to install all your dependencies.

Commands

bower install [package]

Install a package locally

```
$ bower install jquery --save-dev
bower jquery##          cached git://github.com/components/jquery.git#2.0.3
bower jquery##          validate 2.0.3 against git://github.com/components/jquery.git##
bower jquery#~2.0.3      install jquery#2.0.3

jquery#2.0.3 bower_components/jquery
```

`--save-dev` option add the package as a dependency of your application.
Leave package name blank in order to install all your dependencies.

bower list

List local packages

```
$ bower list
bower check-new      Checking for new versions of the project dependencies..
js-workshop-code#0.0.0 /home/david/code/js-workshop-code
jquery#2.0.3
```


Simple exercise using jQuery

Exercise

- Start with the sample code on tag `boss-stage-1`
- Create a function for creating character objects
- Create another function for creating player objects inheriting from characters
- Create another function for creating enemy objects inheriting from characters
- Use the jQuery sample code and complete 'Attack' and 'Drink potion' actions.