

EXPLOITING TACTILE INFORMATION THROUGH TEMPORAL FEEDBACK OF A SKIN-INSPIRED SENSOR

Dexter R. Shepherd*, Phil Husbands, Chris Johnson, Andy Philippedes

Introduction


Adaptive behaviour relies on environmental information. This project uses tactile skin-inspired sensors for such tasks. In order to extract useful information we have devised a number of pre-processing techniques to gather movement and pressure. We demonstrated this with a robotic arm that would move away from obstacles.

Movement detection

After noise reduction we calculate the centroids of each point. We find the nearest points in a matrix C at time step t. Each coordinate is stored in index i.


$$C_{t,i} = \sqrt{(C_{t,i} - C_{t+1})^2}$$

We calculate the Euclidean distance of each coordinates and all coordinates in the next layer. The shortest distances allows detection of where the dots have moved. From this we can plot movement.




TacTip sensor

TacTips are skin-inspired sensors developed by BRL that use cameras facing a flexible mesh to detect tactile movement that can be interpreted as tactile information.



Noise reduction


The TacTip sensor uses a ring of LEDs to make the white dots visible. Glare can be seen on the lens and gel layer, making binary thresholding challenging. We used an adaptive threshold with blob removal



Touch detection


We can calculate pressure in positions by averaging the pixel intensity from the absolute difference in grid squares and reducing by a global average. Using F a matrix containing pixel values and grid size div.

$$\sum_{x=i}^{div_y+i} \sum_{x=j}^{div_z+j} (F_{i,j}) \times \frac{1}{255 * (div_y) * (div_x)} - \bar{x}$$



Results

The tactile information can be used to recognize information in the environment. We found that the robot arm could sense the touch and direction of the stimuli, so it would move in the opposite way. Future work hopes to explore larger surface areas of skin with different soft-body morphologies.



Bibliography

- Beer, R. D., Quinn, R. D., Chiel, H. J., and Ritzmann, R. E. (1997). Biologically inspired approaches to robotics: What can we learn from insects? Communications of the ACM, 40(3):30–38.
- D'urr, V. and Krause, A. F. (2014). Tactile sensing in insects. In Jaeger, D. and (Eds), R. J., editors, Encyclopedia of computational neuroscience. Springer.
- Lepora, N. F. (2021). Soft biomimetic optical tactile sensing with the tactip: A review. IEEE Sensors Journal, 21(19):21131–21143
- Winstone, B., Griffiths, G., Melhuish, C., Pipe, T., and Rossiter, J. (2012). Tactip—tactile fingertip device, challenges in reduction of size to ready for robot hand integration. In 2012 IEEE International Conference on Robotics and Biomimetics (ROBIO), pages 160–166. IEEE