

16-350

Planning Techniques for Robotics

***Search Algorithms:
Multi-goal A*, IDA****

Maxim Likhachev

Robotics Institute

Carnegie Mellon University

Agenda

- A^* with multiple goals
- Iterative Deepening A^* (IDA*)

Support for Multiple Goal Candidates

- How to compute a least-cost path to any one of the possible goals?
 - Example 1: Computing a least-cost path to a parking spot given multiple parking spaces (some are better, some are worse, some are closer, some are further)
 - Example 2: Catching a moving target whose future trajectory is known (i.e., multiple potential intercept points)
 - Example 3: Mapping/exploration (next class)

A* Search

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;


insert s into $CLOSED$;

for every successor s' of s such that s' not in $CLOSED$

if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;



How to find a least-cost path that is lowest across all possible goals?

Introducing “imaginary” goal

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;


for every successor s' of s such that s' not in $CLOSED$

if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

Equivalent problem but with a single goal!



Introducing “imaginary” goal

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;

for every successor s' of s such that s' not in $CLOSED$


if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

Equivalent problem but with a single goal!

How to prove it?



Support for “unequal” goals

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;


for every successor s' of s such that s' not in $CLOSED$

if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

*What if some goals
are better than others?*



Support for “unequal” goals

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;


for every successor s' of s such that s' not in $CLOSED$

if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

*What if some goals
are better than others?*



Support for “unequal” goals

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;

for every successor s' of s such that s' not in $CLOSED$


if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

Equivalent problem but with a single goal!

How to prove it?



Support for “unequal” goals

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;


for every successor s' of s such that s' not in $CLOSED$

if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

*Once the graph transformation is done,
you can run either forward or backwards search*



Support for “unequal” goals

Main function

$g(s_{start}) = 0$; all other g -values are infinite; $OPEN = \{s_{start}\}$;

ComputePath();

publish solution;

ComputePath function

while(s_{goal} is not expanded and $OPEN \neq \emptyset$)

remove s with the smallest $[f(s) = g(s) + h(s)]$ from $OPEN$;

insert s into $CLOSED$;

for every successor s' of s such that s' not in $CLOSED$


if $g(s') > g(s) + c(s, s')$

$g(s') = g(s) + c(s, s')$;

insert s' into $OPEN$;

*Any impact on how
heuristics is computed?*

*Once the graph transformation is done,
you can run either forward or backwards search*



Agenda

- A^* with multiple goals
- Iterative Deepening A^* (IDA*)

Memory Issues

- A^* does provably minimum number of expansions ($O(n)$) for finding a provably optimal solution
- Memory requirements of weighted A^* are often but not always better

Search with Linear Memory Requirement

- Depth-First Search (w/o coloring all expanded states):
 - explore each every possible path one at a time avoiding looping and keeping in the memory only the best path discovered so far

DFS function

LIFO list = $\{s_{start}\}$; //stack

bestpathsofar = NONE;

While (list \neq 0)

s = list.pop();

if (s = s_{goal})

if (cost of the found path from s_{start} to s < cost of bestpathsofar)

set bestpathsofar to the current path from s_{start} to s

else

for every successor s' of s

list.push(s');

return bestpathsofar;

Search with Linear Memory Requirement

- Depth-First Search (w/o coloring all expanded states):
 - explore each every possible path one at a time avoiding looping and keeping in the memory only the best path discovered so far

DFS function

LIFO list = { s_{start} }; //stack

bestpathsofar = NONE;

While (list \neq 0)

$s = list.pop()$;

if ($s = s_{goal}$)

if (cost of the found path from s_{start} to $s <$ cost of bestpathsofar)

set bestpathsofar to the current path from s_{start} to s

else

for every successor s' of s

$list.push(s')$;

return bestpathsofar;

What is memory complexity?

What are its disadvantages?

Search with Linear Memory Requirement

- Depth-First Search (w/o coloring all expanded states):
 - explore each every possible path one at a time avoiding looping and keeping in the memory only the best path discovered so far
 - Complete and optimal (assuming finite state-spaces)
 - Memory: $O(bm)$, where b – max. branching factor, m – max. pathlength in graph
 - Complexity: $O(b^m)$, since it will repeatedly re-expand states

Search with Linear Memory Requirement

- Depth-First Search (w/o coloring all expanded states):
 - explore each every possible path one at a time avoiding looping and keeping in the memory only the best path discovered so far
 - Complete and optimal (assuming finite state-spaces)
 - Memory: $O(bm)$, where b – max. branching factor, m – max. pathlength in graph
 - Complexity: $O(b^m)$, since it will repeatedly re-expand states
 - Example:
 - graph: a 4-connected grid of 40 by 40 cells, start: center of the grid
 - A* expands up to 800 states, DFS may expand way over $4^{20} > 10^{12}$ states

Search with Linear Memory Requirement

- Depth-First Search (w/o coloring all expanded states):
 - explore each every possible path one at a time avoiding looping and keeping in the memory only the best path discovered so far
 - Complete and optimal (assuming finite state-spaces)
 - Memory: $O(bm)$, where b – max. branching factor, m – max. pathlength in graph
 - Complexity: $O(b^m)$, since it
 - Example:
 - graph: a 4-connected grid of 40 by 40 cells, start: center of the grid
 - A* expands up to 800 states, DFS may expand way over $4^{20} > 10^{12}$ states

What if goal is few steps away in a huge state-space?

Search with Linear Memory Requirement

- IDA* (Iterative Deepening A*) [Korf, '85]:
 1. *set $f_{max} = 1$ (or some other small value)*
 2. *execute (previously explained) DFS that does not expand states with $f > f_{max}$*
 3. *If DFS returns a path to the goal, return it*
 4. *Otherwise $f_{max} = f_{max} + 1$ (or larger increment) and go to step 2*

Search with Linear Memory Requirement

- IDA* (Iterative Deepening A*) [Korf, '85]:
 1. *set $f_{max} = 1$ (or some other small value)*
 2. *execute (previously explained) DFS that does not expand states with $f > f_{max}$*
 3. *If DFS returns a path to the goal, return it*
 4. *Otherwise $f_{max} = f_{max} + 1$ (or larger increment) and go to step 2*
- Complete and optimal in any state-space (with positive costs)
- Memory: $O(bl)$, where b – max. branching factor, l – length of optimal path
- Complexity: $O(kb^l)$, where k is the number of times DFS is called

Summary

- Support for multiple potential goals is a common problem in robotics and can often be easily tackled by the graph transformation (introducing “imaginary” goal)
- In the worst case, memory requirements of A^* are the full size of the graph
- Iterative Deepening A^* (IDA*) – simple alternative with memory requirements linear in the length of the optimal path to the goal.
 - It can perform substantially more work than A^* though