



# Bean Validation specification

Gunnar Morling

Version 2.0.0.Beta1 Public Review Draft 1, 2017-04-24

# Table of Contents

Evaluation license .....	1
1. Introduction .....	5
1.1. Expert group.....	5
1.2. Specification goals.....	7
1.3. Required Java version .....	8
1.4. How this document is organized.....	8
1.5. How to comment .....	8
2. What's new .....	9
2.1. What's new in 2.0.....	9
2.2. What's new in 1.1 .....	9
2.2.1. Openness .....	9
2.2.2. Dependency injection.....	10
2.2.3. Method validation .....	10
2.2.4. Integration with Context and Dependency Injection .....	10
2.2.5. Group conversion .....	11
2.2.6. Message interpolation via the unified expression language .....	11
2.2.7. Others .....	11
3. Constraint definition .....	12
3.1. Constraint annotation.....	12
3.1.1. Constraint definition properties .....	15
3.1.2. Examples .....	19
3.2. Applying multiple constraints of the same type.....	23
3.3. Constraint composition .....	25
3.4. Constraint validation implementation .....	33
3.4.1. Implementation of temporal constraint validators .....	52
3.4.2. Examples .....	53
3.5. The ConstraintValidatorFactory .....	58
4. Value extractor definition.....	60
4.1. @ExtractedValue.....	62
4.2. @UnwrapByDefault .....	63
4.3. Built-in value extractors .....	64
4.4. Examples .....	65
5. Constraint declaration and validation process .....	67
5.1. Requirements on classes to be validated.....	67
5.1.1. Object validation .....	68
5.1.2. Field and property validation .....	68
5.1.3. Graph validation .....	69
5.2. Constraint declaration .....	71
5.3. Inheritance (interface and superclass) .....	71

5.4. Group and group sequence .....	72
5.4.1. Group inheritance .....	73
5.4.2. Group sequence.....	74
5.4.3. Redefining the Default group for a class .....	76
5.4.4. Implicit grouping .....	77
5.4.5. Group conversion .....	79
5.4.6. Formal group definitions .....	83
5.5. Container element constraints .....	85
5.5.1. Implicit unwrapping of containers .....	86
5.6. Method and constructor constraints .....	88
5.6.1. Requirements on methods to be validated .....	88
5.6.2. Declaring parameter constraints .....	88
5.6.3. Declaring return value constraints .....	92
5.6.4. Marking parameters and return values for cascaded validation .....	93
5.6.5. Method constraints in inheritance hierarchies .....	94
5.7. Validation routine .....	98
5.7.1. Object graph validation .....	99
5.7.2. Method and constructor validation .....	102
5.7.3. Traversable property .....	103
5.7.4. ConstraintValidator resolution algorithm.....	110
5.7.5. ValueExtractor resolution .....	112
5.8. Examples .....	117
6. Validation APIs .....	126
6.1. Validator API .....	126
6.1.1. Validation methods.....	129
6.1.2. Methods for validating method and constructor constraints .....	132
6.1.3. groups .....	138
6.2. ConstraintViolation .....	141
6.2.1. Examples.....	160
6.2.2. Examples for method and constructor constraint violations .....	163
6.3. Message interpolation .....	169
6.3.1. Default message interpolation.....	169
6.3.2. Custom message interpolation .....	171
6.3.3. Examples .....	174
6.4. Triggering method validation .....	176
6.5. Bootstrapping .....	180
6.5.1. Examples .....	181
6.5.2. ValidatorFactory .....	184
6.5.3. Configuration .....	190
6.5.4. ValidationProvider and ValidationProviderResolver .....	205
6.5.5. Validation .....	211
6.5.6. XML configuration: META-INF/validation.xml .....	218

6.5.7. Bootstrapping considerations .....	220
7. Constraint metadata request APIs .....	221
7.1. Validator .....	221
7.2. ElementDescriptor .....	222
7.3. BeanDescriptor .....	228
7.4. CascadableDescriptor .....	232
7.5. GroupConversionDescriptor .....	233
7.6. PropertyDescriptor .....	233
7.7. ExecutableDescriptor, MethodDescriptor and ConstructorDescriptor .....	234
7.8. ParameterDescriptor .....	238
7.9. CrossParameterDescriptor .....	239
7.10. ReturnValueDescriptor .....	239
7.11. ContainerDescriptor and ContainerElementTypeDescriptor .....	240
7.12. ConstraintDescriptor .....	241
7.13. Example .....	244
8. Built-in Constraint definitions .....	252
9. XML deployment descriptor .....	277
9.1. Constraint definition and declaration .....	277
9.1.1. Constraint declaration in XML .....	277
9.1.2. Overriding constraint definitions in XML .....	292
9.1.3. Converting the string representation of a value .....	292
9.1.4. XML Schema .....	293
9.2. Configuration schema .....	299
10. Exception model .....	302
10.1. Error report: <code>ConstraintViolationException</code> .....	303
10.2. Constraint definition: <code>ConstraintDefinitionException</code> .....	305
10.3. Constraint declaration: <code>ConstraintDeclarationException</code> and <code>UnexpectedTypeException</code> .....	305
10.4. Group definition: <code>GroupDefinitionException</code> .....	306
10.5. Value extractor definition: <code>ValueExtractorDefinitionException</code> .....	306
10.6. Value extractor declaration: <code>ValueExtractorDeclarationException</code> .....	307
10.7. No Bean Validation Provider detected: <code>NoProviderFoundException</code> .....	308
11. Integration .....	309
11.1. General requirements .....	309
11.1.1. Objects lifecycle .....	309
11.1.2. Method and constructor validation .....	310
11.2. Java EE .....	317
11.3. Context and Dependency Injection (CDI) integration .....	317
11.3.1. <code>ValidatorFactory</code> and <code>Validator</code> .....	317
11.3.2. <code>ConstraintValidatorFactory</code> , <code>MessageInterpolator</code> , <code>ParameterNameProvider</code> , <code>ClockProvider</code> and <code>TraversableResolver</code> .....	318
11.3.3. Method and constructor validation .....	318

11.4. Java Persistence 2.0 integration .....	319
11.5. Java Server Faces 2.0 integration .....	319
11.6. JAX-RS 2 integration .....	319
Appendix A: Terminology .....	320
Appendix B: Standard ResourceBundle messages .....	322
Appendix C: Java Persistence 2.0 and schema generation .....	323
Appendix D: Changelog .....	325

# Evaluation license

Copyright 2007-2017 Red Hat, Inc.

All rights reserved.

## NOTICE

The Specification is protected by copyright and the information described therein may be protected by one or more U.S. patents, foreign patents, or pending applications. Except as provided under the following license, no part of the Specification may be reproduced in any form by any means without the prior written authorization of Red Hat Inc. and its licensors, if any. Any use of the Specification and the information described therein will be governed by the terms and conditions of this Agreement.

Subject to the terms and conditions of this license, including your compliance with Paragraphs 1 and 2 below, Red Hat Inc. hereby grants you a fully-paid, non-exclusive, non-transferable, limited license (without the right to sublicense) under Red Hat Inc.'s intellectual property rights to:

1. Review the Specification for the purposes of evaluation. This includes: (i) developing implementations of the Specification for your internal, non-commercial use; (ii) discussing the Specification with any third party; and (iii) excerpting brief portions of the Specification in oral or written communications which discuss the Specification provided that such excerpts do not in the aggregate constitute a significant portion of the Specification.
2. Distribute implementations of the Specification to third parties for their testing and evaluation use, provided that any such implementation:

(i) does not modify, subset, superset or otherwise extend the Licensor Name Space, or include any public or protected packages, classes, Java interfaces, fields or methods within the Licensor Name Space other than those required/authorized by the Specification or Specifications being implemented;

(ii) is clearly and prominently marked with the word "UNTESTED" or "EARLY ACCESS" or "INCOMPATIBLE" or "UNSTABLE" or "BETA" in any list of available builds and in proximity to every link initiating its download, where the list or link is under Licensee's control; and

(iii) includes the following notice:

"This is an implementation of an early-draft specification developed under the Java Community Process (JCP). The code is not compatible with any specification of the JCP."

The grant set forth above concerning your distribution of implementations of the Specification is contingent upon your agreement to terminate development and distribution of your

implementation of early draft upon final completion of the Specification. If you fail to do so, the foregoing grant shall be considered null and void.

No provision of this Agreement shall be understood to restrict your ability to make and distribute to third parties applications written to the Specification.

Other than this limited license, you acquire no right, para or interest in or to the Specification or any other Red Hat Inc. intellectual property, and the Specification may only be used in accordance with the license terms set forth herein. This license will expire on the earlier of: (a) two (2) years from the date of Release listed above; (b) the date on which the final version of the Specification is publicly released; or (c) the date on which the Java Specification Request (JSR) to which the Specification corresponds is withdrawn. In addition, this license will terminate immediately without notice from Red Hat Inc. if you fail to comply with any provision of this license. Upon termination, you must cease use of or destroy the Specification.

"Licensor Name Space" means the public class or interface declarations whose names begin with "java", "javax", "com.redhat", "com.jboss", "org.jboss", "org.hibernate" or their equivalents in any subsequent naming convention adopted through the Java Community Process, or any recognized successors or replacements thereof.

## TRADEMARKS

No right, para, or interest in or to any trademarks, service marks, or trade names of Red Hat Inc. or Red Hat's licensors is granted hereunder. Java and Java-related logos, marks and names are trademarks or registered trademarks of Oracle and/or its affiliates in the U.S. and other countries.

## DISCLAIMER OF WARRANTIES

THE SPECIFICATION IS PROVIDED "AS IS" AND IS EXPERIMENTAL AND MAY CONTAIN DEFECTS OR DEFICIENCIES WHICH CANNOT OR WILL NOT BE CORRECTED BY RED HAT Inc. RED HAT Inc. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT THAT THE CONTENTS OF THE SPECIFICATION ARE SUITABLE FOR ANY PURPOSE OR THAT ANY PRACTICE OR IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADE SECRETS OR OTHER RIGHTS. This document does not represent any commitment to release or implement any portion of the Specification in any product.

THE SPECIFICATION COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION THEREIN; THESE CHANGES WILL BE INCORPORATED INTO NEW VERSIONS OF THE SPECIFICATION, IF ANY. RED HAT Inc. MAY MAKE IMPROVEMENTS AND/OR CHANGES TO THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THE SPECIFICATION AT ANY TIME. Any use of such changes in the Specification will be governed by the then-current license for the applicable version of the

Specification.

#### LIMITATION OF LIABILITY

TO THE EXTENT NOT PROHIBITED BY LAW, IN NO EVENT WILL RED HAT Inc. OR ITS LICENSORS BE LIABLE FOR ANY DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUE, PROFITS OR DATA, OR FOR SPECIAL, INDIRECT, CONSEQUENTIAL, INCIDENTAL OR PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF LIABILITY, ARISING OUT OF OR RELATED TO ANY FURNISHING, PRACTICING, MODIFYING OR ANY USE OF THE SPECIFICATION, EVEN IF RED HAT Inc. AND/OR ITS LICENSORS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

You will hold Red Hat Inc. (and its licensors) harmless from any claims based on your use of the Specification for any purposes other than the limited right of evaluation as described above, and from any claims that later versions or releases of any Specification furnished to you are incompatible with the Specification provided to you under this license.

#### RESTRICTED RIGHTS LEGEND

If this Software is being acquired by or on behalf of the U.S. Government or by a U.S. Government prime contractor or subcontractor (at any tier), then the Government's rights in the Software and accompanying documentation shall be only as set forth in this license; this is in accordance with 48 C.F.R. 227.7201 through 227.7202-4 (for Department of Defense (DoD) acquisitions) and with 48 C.F.R. 2.101 and 12.212 (for non-DoD acquisitions).

#### REPORT

You may wish to report any ambiguities, inconsistencies or inaccuracies you may find in connection with your evaluation of the Specification ("Feedback"). To the extent that you provide Red Hat Inc. with any Feedback, you hereby: (i) agree that such Feedback is provided on a non-proprietary and non-confidential basis, and (ii) grant Red Hat Inc. a perpetual, non-exclusive, worldwide, fully paid-up, irrevocable license, with the right to sublicense through multiple levels of sublicensees, to incorporate, disclose, and use without limitation the Feedback for any purpose related to the Specification and future versions, implementations, and test suites thereof.

#### GENERAL TERMS

Any action related to this Agreement will be governed by California law and controlling U.S. federal law. The U.N. Convention for the International Sale of Goods and the choice of law rules of any jurisdiction will not apply.

The Specification is subject to U.S. export control laws and may be subject to export or import regulations in other countries. Licensee agrees to comply strictly with all such laws and regulations and acknowledges that it has the responsibility to obtain such licenses to export, re-export or import as may be required after delivery to Licensee.

This Agreement is the parties' entire agreement relating to its subject matter. It supersedes all prior or contemporaneous oral or written communications, proposals, conditions, representations and warranties and prevails over any conflicting or additional terms of any quote, order, acknowledgment, or other communication between the parties relating to its subject matter during the term of this Agreement. No modification to this Agreement will be binding, unless in writing and signed by an authorized representative of each party.

# 1. Introduction

This document is the specification of the Java API for JavaBean validation in Java EE and Java SE. The technical objective of this work is to provide an object level constraint declaration and validation facility for the Java application developer, as well as a constraint metadata repository and query API.

It also offers method and constructor validation facilities to ensure constraints on their parameters and return values.

## 1.1. Expert group

This work has been conducted as part of JSR 380 and formerly JSRs 349 and 303 under the Java Community Process Program. This specification is the result of the collaborative work of the members of the JSR 380 Expert Group and the community at large.

The following persons have actively contributed to Bean Validation 2.0 as members of the JSR 380 expert group and the community at large in alphabetical order:

- Matt Benson
- Emmanuel Bernard (Red Hat, Inc.)
- Linda DeMichiel (Oracle)
- Hendrik Ebbers (Canoo AG)
- Hardy Ferentschik (Red Hat, Inc.)
- Christian Kaltepoth (ingenit GmbH & Co. KG)
- Werner Keil
- Marco Molteni (Genidea Sagl)
- Gunnar Morling (Red Hat, Inc.) - Specification Lead
- Michael Nascimento Santos
- Otavio Santana
- Guillaume Smet (Red Hat, Inc.)
- Tsuyoshi Yoshitomi (Fujitsu Limited)

The following persons have actively contributed to Bean Validation 1.1 as members of the JSR 349 expert group and the community at large in alphabetical order:

- Matt Benson
- Paul Benedict

- Emmanuel Bernard (Red Hat, Inc.) - Specification Lead
- Edward Burns (Oracle)
- Peter Davis
- Linda DeMichiel (Oracle)
- Hardy Ferentschik (Red Hat, Inc.)
- Antonio Goncalves
- Cemalettin Koç
- Rich Midwinter
- Gunnar Morling (individual then Red Hat, Inc.)
- Pete Muir (Red Hat, Inc.)
- Michael Nascimento Santos
- Gerhard Petracek
- Kevin Pollet (SERLI)
- Jagadish Prasath Ramu (Oracle)
- Bill Shannon (Oracle)
- Sebastian Thomschke

Former expert group members of JSR-303 in alphabetical order are:

- Geert Bevin
- Emmanuel Bernard (Red Hat, Inc.) - Specification Lead
- Uri Boness
- Erik Brakkee (Ericsson AB)
- Ed Burns (Sun Microsystems, Inc.)
- Jason Carreira
- Robert Clevenger (Oracle - retired)
- Linda DeMichiel (Sun Microsystems, Inc.)
- Tim Fennel
- Bharath Ganesh (Pramati Technologies)
- Romain Guy (Google Inc.)
- Robert Harrop
- Jacob J. Hookom

- Bob Lee (Google Inc.)
- Craig R. McClanahan (Sun Microsystems, Inc.)
- Niall K. Pemberton
- Steve Peterson
- Dhanji R. Prasanna (Google Inc., formerly individual)
- Gerhard Petracek
- Matt Raible
- Michael Nascimento Santos
- Sebastian Thomschke
- Jon Wetherbee (Oracle)

## 1.2. Specification goals

Validating data is a common task that occurs throughout an application, from the presentation layer to the persistence layer. Often the same validation logic is implemented in each layer, proving to be time consuming and error-prone. To avoid duplication of these validations in each layer, developers often bundle validation logic directly into the domain model, cluttering domain classes with validation code that is, in fact, metadata about the class itself.

This JSR defines a metadata model and API for JavaBean validation. The default metadata source is annotations, with the ability to override and extend the metadata through the use of XML validation descriptors.

The validation API developed by this JSR is not intended for use in any one tier or programming model. It is specifically not tied to either the web tier or the persistence tier, and is available for both server-side application programming, as well as rich client Swing application developers. This API is seen as a general extension to the JavaBeans object model, and as such is expected to be used as a core component in other specifications. Ease of use and flexibility have influenced the design of this specification.

As of version 1.1, Bean Validation constraints can also be applied to the parameters and return values of methods of arbitrary Java types. Thus the Bean Validation API can be used to describe and validate the contract (comprising pre- and postconditions) applying to a given method ("Programming by Contract", PbC). Note that it is *not* the goal of this specification to develop a fully-fledged PbC solution but rather an easy-to-use facility satisfying the most common needs related to applying constraints to method parameters and return values, based on the proven concepts of the Bean Validation API.

## 1.3. Required Java version

The specification uses Java 8.0 language features. There is no requirement that implementations be compatible with Java language versions prior to 8.0.

## 1.4. How this document is organized

This document describes each aspect of the Bean Validation specification in a separate chapter. One should remember that the specification is a consistent whole.

[Constraint definition](#) describes how constraints are defined.

[Value extractor definition](#) describes how extractors for the values of container types are defined.

[Constraint declaration and validation process](#) describes how a JavaBean class is decorated with annotations to describe constraints.

[Validation APIs](#) describes how to programmatically validate a JavaBean.

[Constraint metadata request APIs](#) describes how the metadata query API works.

[Built-in Constraint definitions](#) list all the built-in constraints.

[XML deployment descriptor](#) describes the XML deployment descriptors for the configuration and the mapping.

[Exception model](#) describes the exception model and hierarchy used by Bean Validation.

[Integration](#) describes the different integration points of Bean Validation with other technologies. In some cases one has to refer to the respective specifications for the up-to-date integration rules.

In [Terminology](#), key concepts are summarized. Some reviewers have found that reading the terminology section first helps to better understand the specification.

The changelog can be found at [Changelog](#).

## 1.5. How to comment

The expert group is eager to receive feedback from readers. Feel free to contact us. You can get all the details at <http://beanvalidation.org/contribute/>.

## 2. What's new

### 2.1. What's new in 2.0

The main contribution of Bean Validation 2.0 is leveraging the new language features and API additions of Java 8 for the purposes of validation. Java 8 or later is required to use Bean Validation 2.0.

The changes include:

- Support for validating container elements by annotating type arguments of generic types, e.g. `List<@Positive Integer> positiveNumbers` (see [Container element constraints](#)); this also includes:
  - More flexible cascaded validation of collection types; e.g. values *and* keys of maps can be validated now: `Map<@Valid CustomerType, @Valid Customer> customersByType`
  - Support for `java.util.Optional`
  - Support for the property types declared by JavaFX
  - Support for custom container types by plugging in additional value extractors (see [Value extractor definition](#))
- Support for the new date/time data types for `@Past` and `@Future` (see [Built-in Constraint definitions](#)); fine-grained control over the current time and time zone used for validation (see [Implementation of temporal constraint validators](#))
- New built-in constraints, e.g. `@Email`, `@NotEmpty` and `@NotBlank` (see [Built-in Constraint definitions](#))
- All built-in constraints are marked as repeatable now
- Parameter names are retrieved using reflection (see [Naming parameters](#))
- `ConstraintValidator#initialize()` is a default method (see [Constraint validation implementation](#))

### 2.2. What's new in 1.1

Bean Validation 1.1 improves and builds upon Bean Validation 1.0. The expert group and the community have been working on a few specific areas.

#### 2.2.1. Openness

All of Bean Validation 1.1 work has been done in the open and in an open source way. Source

code for the API, reference implementation, test compatibility kit as well as the specification and the website sources are available in the open. All discussions are done in the open in the publicly available development mailing list. Road map and proposals are also published on the website.

You can find all the details (mailing lists, source repositories etc.) at <http://beanvalidation.org>.

### 2.2.2. Dependency injection

Bean Validation uses a few components `MessageInterpolator`, `TraversableResolver`, `ParameterNameProvider`, `ConstraintValidatorFactory` and `ConstraintValidator`. Bean Validation 1.1 standardizes how these objects are managed by a container and how these objects can benefit from container services. In particular, CDI support within Java EE is being defined.

### 2.2.3. Method validation

Bean Validation 1.1 allows to put constraints to the parameters and return values of arbitrary methods and constructors. That way the Bean Validation API can be used to describe and validate the contract applying to a given method or constructor, that is:

- the preconditions that must be met by the caller before the method or constructor may be invoked and
- the postconditions that are guaranteed to the caller after a method or constructor invocation returns.

This enables a programming style known as "Programming by Contract" (PbC). Compared to traditional means of checking the sanity of argument and return values this approach has several advantages:

- These checks are expressed declaratively and don't have to be performed manually, which results in less code to write, read and maintain.
- The pre- and postconditions applying for a method or constructor don't have to be expressed again in the documentation, since any of its annotations will automatically be included in the generated JavaDoc. This reduces redundancies, thus avoiding efforts and inconsistencies between implementation and documentation.

### 2.2.4. Integration with Context and Dependency Injection

The integration points with Context and Dependency Injection (CDI) have been increased and reworked. This opens up for a more natural and standard integration both in Java EE and Java SE and encompass dependency injection, component lifecycle management and interception for method validation.

## 2.2.5. Group conversion

The specification offers a way to alter the targeted group when validation cascading is happening. This feature is particularly useful to reuse a given object (graph) and to avoid leaking groups between various object subgraphs. It also makes for more readable constraints.

## 2.2.6. Message interpolation via the unified expression language

Constraint violation messages can now use EL expressions for a much more flexible rendering and string formatting. In particular a formatter object is injected in the EL context to convert numbers, dates etc. into the locale specific string representation. Likewise, the validated value is also available in the EL context.

## 2.2.7. Others

Many more minor changes have been done. Check out the change log for more details at [Changelog](#).

# 3. Constraint definition

Constraints are defined by the combination of a constraint annotation and a list of constraint validation implementations. The constraint annotation is applied on types, fields, methods, constructors, parameters or other constraint annotations in case of composition.

Unless stated otherwise the default package name for the Bean Validation APIs is `javax.validation`.

## 3.1. Constraint annotation

A constraint on a JavaBean is expressed through one or more annotations. An annotation is considered a constraint definition if its retention policy contains `RUNTIME` and if the annotation itself is annotated with `javax.validation.Constraint`.

```
/**  
 * Marks an annotation as being a Bean Validation constraint.  
 * <p>  
 * A given constraint annotation must be annotated by a {@code @Constraint}  
 * annotation which refers to its list of constraint validation  
 * implementations.  
 * <p>  
 * Each constraint annotation must host the following attributes:  
 * <ul>  
 *   <li>{@code String message() default [...];} which should default to an  
 *   error  
 *   message key made of the fully-qualified class name of the constraint  
 *   followed by  
 *   {@code .message}. For example {@code  
 * "{com.acme.constraints.NotSafe.message}"}</li>  
 *   <li>{@code Class<?>[] groups() default {};} for user to customize the  
 *   targeted  
 *   groups</li>  
 *   <li>{@code Class<? extends Payload>[] payload() default {};} for  
 *   extensibility purposes</li>  
 * </ul>  
 * <p>  
 * When building a constraint that is both generic and cross-parameter, the  
 * constraint  
 * annotation must host the {@code validationAppliesTo()} property.  
 * A constraint is generic if it targets the annotated element and is cross-  
 * parameter if  
 * it targets the array of parameters of a method or constructor.  
 * <pre>  
 *   ConstraintTarget validationAppliesTo() default  
 ConstraintTarget.IMPLICIT;  
 * </pre>  
 * This property allows the constraint user to choose whether the constraint  
 * targets the return type of the executable or its array of parameters.  
 *  
 * A constraint is both generic and cross-parameter if  
 * <ul>
```

```

*      <li>two kinds of {@code ConstraintValidator}s are attached to the
*      constraint, one targeting {@link ValidationTarget#ANNOTATED_ELEMENT}
*      and one targeting {@link ValidationTarget#PARAMETERS}, </li>
*      <li>or if a {@code ConstraintValidator} targets both
*      {@code ANNOTATED_ELEMENT} and {@code PARAMETERS}.</li>
*    </ul>
*
* Such dual constraints are rare. See {@link SupportedValidationTarget} for
more info.
* <p>
* Here is an example of constraint definition:
* <pre>
* &#64;Documented
* &#64;Constraint(validatedBy = OrderNumberValidator.class)
* &#64;Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
* &#64;Retention(RUNTIME)
* public &#64;interface OrderNumber {
*     String message() default "{com.acme.constraint.OrderNumber.message}";
*     Class<?>[] groups() default {};
*     Class<? extends Payload>[] payload() default {};
* }
* </pre>
*
* @author Emmanuel Bernard
* @author Gavin King
* @author Hardy Ferentschik
*/
@Documented
@Target({ ANNOTATION_TYPE })
@Retention(RUNTIME)
public @interface Constraint {

    /**
     * {@link ConstraintValidator} classes must reference distinct target
types
     * for a given {@link ValidationTarget}
     * If two {@code ConstraintValidator}s refer to the same type,
     * an exception will occur.
     * <p>
     * At most one {@code ConstraintValidator} targeting the array of
parameters of
     * methods or constructors (aka cross-parameter) is accepted. If two or
more
     * are present, an exception will occur.
     *
     * @return array of {@code ConstraintValidator} classes implementing the
constraint
    */
    Class<? extends ConstraintValidator<?, ?>>[] validatedBy();
}

```

A constraint is said to be generic if it has at least one constraint validator targeting the element annotated i.e. targeting the (returned) element annotated by the constraint (a bean, a field, a getter, a method/constructor return value or a method/constructor parameter). A constraint is said to be cross-parameter if it has one constraint validator targeting the array of parameters of a method or constructor (to validate the consistency of several method/constructor

parameters). A Bean Validation constraint is most of the time either a generic constraint or a cross-parameter constraint. In rare situations, a constraint can be both.

Generic constraint annotations can target any of the following `ElementTypes`:

- `FIELD` for constrained attributes
- `METHOD` for constrained getters and constrained method return values
- `CONSTRUCTOR` for constrained constructor return values
- `PARAMETER` for constrained method and constructor parameters
- `TYPE` for constrained beans
- `ANNOTATION_TYPE` for constraints composing other constraints
- `TYPE_USE` for container element constraints

Cross-parameter constraint annotations can target any of the following `ElementTypes`:

- `METHOD`
- `CONSTRUCTOR`
- `ANNOTATION_TYPE` for cross-parameter constraints composing other cross-parameter constraints

A constraint annotation that is both can target the union of the generic and cross-parameter constraint annotations targets.

While other `ElementTypes` are not forbidden, the provider does not have to recognize and process constraints placed on such types.

Since a given constraint definition applies to one or more specific Java types, the JavaDoc for the constraint annotation should clearly state which types are supported. Applying a constraint annotation to an incompatible type will raise an `UnexpectedTypeException`. Care should be taken on defining the list of `ConstraintValidators`. The type resolution algorithm (see `ConstraintValidator resolution algorithm`) could lead to exceptions if the `ConstraintValidator` list leads to ambiguities.

At most one `ConstraintValidator` supporting cross-parameter validation must be present for a given constraint. A `ConstraintDefinitionException` is raised otherwise. The JavaDoc should clearly state if the constraint is a generic and / or a cross-parameter constraint.

If a constraint definition is not valid, a `ConstraintDefinitionException` is raised either at validation time or when the metadata is requested. Invalid constraint definitions causes are multiple but include missing or illegal `message` or `groups` elements (see `Constraint definition properties`).

**NOTE**

Bean Validation defines rules for applying constraint annotations in inheritance hierarchies, described in [Inheritance \(interface and superclass\)](#) and [Method constraints in inheritance hierarchies](#). It is therefore not recommended to specify the meta annotation `java.lang.annotation.Inherited` at constraint annotation types, as it is not relevant in the context of Bean Validation and would conflict with the proposed rules.

### 3.1.1. Constraint definition properties

A constraint definition may have attributes that are specified at the time the constraint is applied to a JavaBean. The properties are mapped as annotation elements. The annotation element names `message`, `groups`, `validationAppliesTo` and `payload` are considered reserved names; annotation elements starting with `valid` are not allowed ; a constraint may use any other element name for its attributes.

#### 3.1.1.1. message

Every constraint annotation must define a `message` element of type `String`.

```
String message() default "{com.acme.constraint.MyConstraint.message}";
```

The `message` element value is used to create the error message. See [Message interpolation](#) for a detailed explanation. It is recommended to default `message` values to resource bundle keys to enable internationalization. It is also recommended to use the following convention: the resource bundle key should be the fully qualified class name of the constraint annotation concatenated to `.message` as shown in the previous program listing.

Built-in Bean Validation constraints follow this convention.

#### 3.1.1.2. groups

Every constraint annotation must define a `groups` element that specifies the processing groups with which the constraint declaration is associated. The type of the `groups` parameter is `Class<?>[]`.

```
Class<?>[] groups() default {};
```

The default value must be an empty array.

If no group is specified when declaring the constraint on an element, the `Default` group is considered declared.

See [groups](#) for more information.

Groups are typically used to control the order in which constraints are evaluated, or to perform validation of the partial state of a JavaBean.

### 3.1.1.3. payload

Constraint annotations must define a **payload** element that specifies the payload with which the constraint declaration is associated. The type of the **payload** parameter is **Payload[]**.

```
Class<? extends Payload>[] payload() default {};
```

The default value must be an empty array.

Each attachable payload extends **Payload**.

```
package javax.validation;

/**
 * Payload type that can be attached to a given
 * constraint declaration.
 * <p>
 * Payloads are typically used to carry on metadata information
 * consumed by a validation client.
 * </p>
 * Use of payloads is not considered portable.
 *
 * @author Emmanuel Bernard
 * @author Gerhard Petracek
 */
public interface Payload {
```

Payloads are typically used by validation clients to associate some metadata information with a given constraint declaration. Payloads are typically non-portable. Describing payloads as interface extensions as opposed to a string-based approach allows an easier and more type-safe approach.

One use case for payload shown in [Use of payload to associate severity to a constraint](#) is to associate a severity to a constraint. This severity can be exploited by a presentation framework to adjust how a constraint failure is displayed.

*Example 1. Use of payload to associate severity to a constraint*

```
package com.acme.severity;

public class Severity {
    public static class Info implements Payload {};
    public static class Error implements Payload {};
}

public class Address {
    @NotNull(message="would be nice if we had one", payload=Severity.
Info.class)
    public String getZipCode() { [...] }

    @NotNull(message="the city is mandatory", payload=Severity.Error
.class)
    String getCity() { [...] }
}
```

The `payload` information can be retrieved from error reports via the `ConstraintDescriptor` either accessed through the `ConstraintViolation` objects (see `ConstraintViolation`) or through the metadata API (see `ConstraintDescriptor`).

#### 3.1.1.4. validationAppliesTo

`validationAppliesTo` is used at constraint declaration time to clarify what the constraint targets (i.e. the annotated element, the method return value or the method parameters).

The element `validationAppliesTo` must only be present for constraints that are both generic and cross-parameter, it is mandatory in this situation. A `ConstraintDefinitionException` is raised if these rules are violated.

The type of the `validationAppliesTo` parameter is `ConstraintTarget`. The default value must be `ConstraintTarget.IMPLICIT`.

*Example 2. validationAppliesTo and ConstraintTarget*

```
ConstraintTarget validationAppliesTo() default ConstraintTarget.IMPLICIT;
```

```
/**  
 * Defines the constraint target.  
 *  
 * @author Emmanuel Bernard  
 * @since 1.1  
 */  
public enum ConstraintTarget {  
  
    /**  
     * Discover the type when no ambiguity is present  
     * <ul>  
     *   <li>if neither on a method nor a constructor, it implies the  
     * annotated element  
     *     * (type, field etc),</li>  
     *     * <li>if on a method or constructor with no parameter, it  
     * implies  
     *     * {@code RETURN_VALUE},</li>  
     *     * <li>if on a method with no return value ({@code void}), it  
     * implies  
     *     * {@code PARAMETERS}.</li>  
     *   </ul>  
     * Otherwise, {@code IMPLICIT} is not accepted and either {@code  
     * RETURN_VALUE} or  
     * {@code PARAMETERS} is required. This is the case for constructors  
     * with parameters  
     * and methods with parameters and return value.  
     */  
    IMPLICIT,  
  
    /**  
     * Constraint applies to the return value of a method or a  
     * constructor.  
     */  
    RETURN_VALUE,  
  
    /**  
     * Constraint applies to the parameters of a method or a constructor  
     */  
    PARAMETERS  
}
```

If a **ConstraintTarget** is used in an illegal situation, a **ConstraintDeclarationException** is raised either at validation time or when the metadata is requested. Examples of illegal situations are:

- using **IMPLICIT** in a situation that cannot be inferred (see the JavaDoc for the detailed rules),

- using **PARAMETERS** on a constructor or method that has no parameter,
- using **RETURN\_VALUE** on a method with no return value,
- using **PARAMETERS** or **RETURN\_VALUE** on a type - class or interface - or on a field.

Constraint users are encouraged to explicitly set the **ConstraintTarget** target when using a constraint supporting both on a method or constructor as it improves readability.

### 3.1.1.5. Constraint specific parameter

The constraint annotation definitions may define additional elements to parameterize the constraint. For example, a constraint that validates the length of a string can use an annotation element named **length** to specify the maximum length at the time the constraint is declared.

## 3.1.2. Examples

*Example 3. Simple constraint definition*

```
//assuming OrderNumberValidator is a generic constraint validator

package com.acme.constraint;

/**
 * Mark a String as representing a well formed order number
 */
@Documented
@Constraint(validatedBy = OrderNumberValidator.class)
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface OrderNumber {

    String message() default "{com.acme.constraint.OrderNumber.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};
}
```

**Simple constraint definition** marks a **String** as a well-formed order number. The constraint validator is implemented by **OrderNumberValidator**.

*Example 4. Simple cross-parameter constraint definition*

```
//assuming DateParametersConsistentValidator is a cross-parameter
//constraint validator

package com.acme.constraint;

/**
 * Cross-parameter constraint ensuring that two date parameters of a
method are in the correct order.
 */
@Documented
@Constraint(validatedBy = DateParametersConsistentValidator.class)
@Target({ METHOD, CONSTRUCTOR, ANNOTATION_TYPE })
@Retention(RUNTIME)
public @interface DateParametersConsistent {

    String message() default
    "{com.acme.constraint.DateParametersConsistent.message}";

    Class<?>[] groups() default {};
    Class<? extends Payload>[] payload() default {};
}
```

[Simple cross-parameter constraint definition](#) shows a cross-parameter constraint which ensures that two date parameters of a method are in the correct order. The constraint validator is implemented by **DateParametersConsistentValidator**.

*Example 5. Constraint that is both generic and cross parameter*

```
//assuming ELAssertValidator is both a generic and cross-parameter
//constraint validator

package com.acme.constraint;

/**
 * EL expression to be validated. This constraint accepts any type and
can validate both the annotated type or apply
 * restrictions across parameters.
 */
@Documented
@Constraint(validatedBy = ELAssertValidator.class)
@Target({ METHOD, FIELD, TYPE, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER })
@Retention(RUNTIME)
public @interface ELAssert {

    String message() default
"com.acme.constraint.DateParametersConsistent.message";

    Class<?>[] groups() default {};
    Class<? extends Payload>[] payload() default {};
    ConstraintTarget validationAppliesTo() default ConstraintTarget
.IMPLICIT;
    String expression();
}
```

```
@ELAssert(
    message="Please check that your passwords match and try again.",
    expression="param[1]==param[2]",
    validationAppliesTo=ConstraintType.PARAMETERS
)
public User createUser(String email, String password, String
repeatPassword) { [...] }
```

**Constraint that is both generic and cross parameter** shows a constraint that can be applied both on the annotated element and across parameters of a method or a constructor. Note in this case the presence of **validationAppliesTo**.

*Example 6. Constraint definition with default parameter*

```
package com.acme.constraint;

/**
 * A frequency in Hz as audible to human ear. Adjustable to the age of
 * the person. Accept Numbers.
 */
@Documented
@Constraint(validatedBy = AudibleValidator.class)
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface Audible {

    Age age() default Age.YOUNG;

    String message() default "{com.acme.constraint.Audible.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    public enum Age {
        YOUNG,
        WONDERING,
        OLD
    }
}
```

[Constraint definition with default parameter](#) ensures that a given frequency is within the scope of human ears. The constraint definition includes an optional parameter that may be specified when the constraint is applied.

*Example 7. Constraint definition with mandatory parameter*

```
package com.acme.constraint;

/**
 * Defines the list of values accepted. Accepts int or Integer objects.
 */
@Documented
@Constraint(validatedBy = DiscreteListOfIntegerValidator.class)
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface Acceptable {

    int[] value();

    String message() default "{com.acme.constraint.Acceptable.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};
}
```

[Constraint definition with mandatory parameter](#) defines a list of acceptable values expressed as an array: the `value` property must be specified when the constraint is applied.

## 3.2. Applying multiple constraints of the same type

It is often useful to declare the same constraint more than once to the same target, with different properties. A common example is the `@Pattern` constraint, which validates that its target matches a specified regular expression. Other constraints have this requirement as well. The same constraint type can belong to different groups and have specific error messages depending on the targeted group.

To support this requirement, the Bean Validation provider treats regular annotations (annotations not annotated by `@Constraint`) whose `value` element has a return type of an array of constraint annotations in a special way. Each element in the `value` array are processed by the Bean Validation implementation as regular constraint annotations. This means that each constraint specified in the `value` element is applied to the target. The annotation must have retention `RUNTIME` and can be applied on a type, field, property, executable parameter, executable return value, executable cross-parameter or another annotation. It is recommended to use the same set of targets as the initial constraint.

Note to constraint designers: each constraint annotation should be coupled with its corresponding multi-valued annotation. The specification recommends, though does not mandate, the definition of an inner annotation named `List`. Each constraint annotation type should be meta-annotated with `java.lang.annotation.Repeatable`, referencing the corresponding `List` annotation. This marks the constraint annotation type as repeatable and

lets users specify the constraint several times without explicitly using the `List` annotation. All built-in annotations follow this pattern.

*Example 8. Multi-valued constraint definition*

```
/**  
 * Validate a zip code for a given country  
 * The only supported type is String  
 */  
@Documented  
@Constraint(validatedBy = ZipCodeValidator.class)  
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,  
TYPE_USE })  
@Retention(RUNTIME)  
@Repeatable(List.class)  
public @interface ZipCode {  
  
    String countryCode();  
  
    String message() default "{com.acme.constraint.ZipCode.message}";  
  
    Class<?>[] groups() default {};  
  
    Class<? extends Payload>[] payload() default {};  
  
    /**  
     * Defines several @ZipCode annotations on the same element  
     * @see (@link ZipCode)  
     */  
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,  
TYPE_USE })  
    @Retention(RUNTIME)  
    @Documented  
    @interface List {  
        ZipCode[] value();  
    }  
}
```

*Example 9. Multi-valued constraint declaration*

```
public class Address {  
    @ZipCode(countryCode = "fr", groups = Default.class, message = "zip  
code is not valid")  
    @ZipCode(  
        countryCode = "fr",  
        groups = SuperUser.class,  
        message = "zip code invalid. Requires overriding before saving."  
    )  
    private String zipCode;  
}
```

In this example, both constraints apply to the `zipCode` field but with different groups and with

different error messages. It is also possible to specify a constraint several times by explicitly using the `@List` annotation (though simply repeating the annotation is the preferred idiom as of Bean Validation 2.0 and Java 8):

*Example 10. Multi-valued constraint declaration using explicit `@List` annotation*

```
public class Address {  
    @ZipCode.List( {  
        @ZipCode(countryCode="fr", groups=Default.class,  
                 message = "zip code is not valid"),  
        @ZipCode(countryCode="fr", groups=SuperUser.class,  
                 message = "zip code invalid. Requires overriding before  
saving.")  
    } )  
    private String zipCode;  
}
```

Using two different multi-constraint annotations for the same underlying constraint type on the same target (i.e. class or property) is not considered portable and is discouraged.

### 3.3. Constraint composition

This specification allows you to compose constraints to create higher level constraints.

Constraint composition is useful in several ways:

- Avoid duplication and facilitate reuse of more primitive constraints.
- Expose primitive constraints as part of a composed constraint in the metadata API and enhance tool awareness.

Composition is done by annotating a constraint annotation with the composing constraint annotations.

*Example 11. Composition is done by annotating the composed constraint*

```
@Pattern(regexp = "[0-9]*")
@Size(min = 5, max = 5)
@Constraint(validatedBy = FrenchZipCodeValidator.class)
@Documented
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface FrenchZipCode {

    String message() default "Wrong zip code";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {
        FrenchZipCode[] value();
    }
}
```

Annotating an element with `@FrenchZipCode` (the composed annotation) is equivalent to annotating it with `@Pattern(regexp="[0-9]*")`, `@Size(min=5, max=5)` (the composing annotations) and `@FrenchZipCode`. More formally, each constraint annotation hosted on a constraint annotation is applied to the target element and this is done recursively. Note that the main annotation and its constraint validation implementation is also applied. By default, each failing constraint generates an error report. Groups from the main constraint annotation are inherited by the composing annotations. Any `groups` definition on a composing annotation is ignored. Payload from the main constraint annotation is inherited by the composing annotations. Any `payload` definition on a composing annotation is ignored. The constraint target from the main constraint annotation is inherited by the composing annotations. Any `validationAppliesTo` definition on a composing annotation is ignored.

The type upon which composed constraint is placed must be compatible with all constraints (composing and composed). A constraint designer should ensure that such a type exists and lists in the JavaDoc all the compatible types.

All composed and composing constraints must have a constraint type in common. In particular, it is not legal to mix a pure generic constraint and a pure cross-parameter constraint.

It is possible to ensure that composing annotations do not raise individual error reports. In this scenario, if one or more composing annotations are invalid, the main constraint is automatically considered invalid and the corresponding error report is generated. To mark a constraint as raising a single constraint error report if either the composed or one of the composing

constraints fail, use the `@ReportAsSingleViolation` annotation.

*Example 12. If any of the composing constraints fail, the error report corresponding to `@FrenchZipCode` is raised and none other.*

```
@Pattern(regexp = "[0-9]*")
@Size(min = 5, max = 5)
@ReportAsSingleViolation
@Constraint(validatedBy = FrenchZipCodeValidator.class)
@Documented
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface FrenchZipCode {

    String message() default "Wrong zip code";

    Class<?>[] groups() default {};
    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {
        FrenchZipCode[] value();
    }
}
```

The definition of `@ReportAsSingleViolation` is as follows.

```
/**
 * A constraint annotation hosting this annotation will return the
 * composed annotation error report if any of the composing annotations fail.
 * The error reports of each individual composing constraint are ignored.
 * <p>
 * Note: Evaluation of composed constraints stops on the first validation
 * error in case the composing constraint is annotated with
 * {@code @ReportAsSingleViolation}.
 *
 * @author Emmanuel Bernard
 */
@Target({ ANNOTATION_TYPE })
@Retention(RUNTIME)
@Documented
public @interface ReportAsSingleViolation { }
```

More specifically, if a composed constraint is marked as `@ReportAsSingleViolation`, the evaluation of the composing constraints stops at the first failing constraint and the error report corresponding to the composed constraint is generated and returned.

Composing annotations can define the value of `message` and custom attributes (excluding `groups`, `payload` and `validationAppliesTo`) but these are fixed in the composed constraint definition.

*Example 13. Composing annotations can use attributes. They are fixed for a given main annotation. All `@FrenchZipCode` constraints have a `@Size` restricted to 5.*

```
@Pattern(regexp = "[0-9]*")
@Size(min = 5, max = 5)
@Constraint(validatedBy = FrenchZipCodeValidator.class)
@Documented
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface FrenchZipCode {

    String message() default "Wrong zip code";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {
        FrenchZipCode[] value();
    }
}
```

It is possible to override attributes and messages defined on a composing annotation. An attribute from the main annotation is used to override one or more attributes of the composing annotations. Such an attribute is annotated with one or more `@OverridesAttribute` annotations.

*Example 14. Attributes from composing annotations can be overridden by attributes from the composed annotation*

```
@Pattern(regexp = "[0-9]*")
@Size
@Constraint(validatedBy = FrenchZipCodeValidator.class)
@Documented
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface FrenchZipCode {

    String message() default "Wrong zip code";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    @OverridesAttribute(constraint = Size.class, name = "min")
    @OverridesAttribute(constraint = Size.class, name = "max")
    int size() default 5;

    @OverridesAttribute(constraint = Size.class, name = "message")
    String sizeMessage() default
    "{com.acme.constraint.FrenchZipCode.zipCode.size}";

    @OverridesAttribute(constraint = Pattern.class, name = "message")
    String numberMessage() default
    "{com.acme.constraint.FrenchZipCode.number.size}";

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        FrenchZipCode[] value();
    }
}
```

The value of the composed constraint attribute annotated with `@OverridesAttribute(@FrenchZipCode.sizeMessage)` is applied to the composing constraint attribute named after `@OverridesAttribute.name` and hosted on the composing constraint of type `@OverridesAttribute.constraint` (`@Size.message`). Similarly, `@FrenchZipCode.numberMessage` value is mapped to `@Pattern.message`.

If left undefined, the default value for `@OverridesAttribute.name` is the name of the composed constraint attribute hosting the `@OverridesAttribute` annotation.

The types of the overridden and overriding attributes must be identical.

**NOTE**

A composing constraint can itself be a composed constraint. In this case, attribute values are overridden recursively according to the described rules. Note however, that a forwarding rule (as defined by `@OverridesAttribute`) is only applied to the direct composing constraints.

Using [Attributes from composing annotations can be overridden by attributes from the composed annotation](#),

```
@FrenchZipCode(size=9, sizeMessage="Zip code should be of size {max}")
```

is equivalent to

```
@FrenchZipCode
```

if `@FrenchZipCode` is defined as

```
@Pattern(regexp = "[0-9]*")
@Size(min = 9, max = 9, message = "Zip code should be of size {max}")
@Constraint(validatedBy = FrenchZipCodeValidator.class)
@Documented
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
@Retention(RUNTIME)
public @interface FrenchZipCode {

    String message() default "Wrong zip code";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {
        FrenchZipCode[] value();
    }
}
```

If a constraint is used more than once as a composing constraint, the multi value constraints model as described in [Applying multiple constraints of the same type](#) is used.

To select a specific composing constraint, `OverridesAttribute.constraintIndex` is used. If the composing constraints are directly given on the composed constraint, `constraintIndex` refers to the left-to-right order of the constraints of this type in which they are given on the composed constraint. If the composing constraints are specified using their corresponding `List` annotation, `constraintIndex` refers to the index within the `value` array.

A composing constraint must not be given directly on the composed constraint and using the corresponding `List` annotation at the same time. A `ConstraintDeclarationException` will be raised in this case.

If `index` is undefined, the single constraint declaration is targeted.

*Example 15. Use of constraintIndex in @OverridesAttribute*

```
@Documented
@Constraint(validatedBy = {})
@Pattern(regexp = "[A-Z0-9._%+-]+@[A-Z0-9.-]+\\.[A-Z]{2,4}") // email
@Pattern(regexp = ".*?emmanuel.*?") // emmanuel
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
public @interface EmmanuelsEmail {

    String message() default "Not emmanuel's email";

    @OverridesAttribute(constraint = Pattern.class, name = "message",
constraintIndex = 0)
    String emailMessage() default "Not an email";

    @OverridesAttribute(constraint = Pattern.class, name = "message",
constraintIndex = 1)
    String emmanuelMessage() default "Not Emmanuel";

    Class<?>[] groups() default {};
    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        EmmanuelsEmail[] value();
    }
}
```

`@OverridesAttribute` definition is as follows:

```

/**
 * Marks an attribute as overriding the attribute of a composing constraint.
 * Both attributes must share the same type.
 *
 * @author Emmanuel Bernard
 */
@Documented
@Retention(RUNTIME)
@Target({ METHOD })
@Repeatable(List.class)
public @interface OverridesAttribute {

    /**
     * @return constraint type the attribute is overriding
     */
    Class<? extends Annotation> constraint();

    /**
     * Name of the Constraint attribute overridden.
     * Defaults to the name of the attribute hosting {@code
     * @OverridesAttribute}.
     *
     * @return name of constraint attribute overridden
     */
    String name();

    /**
     * The index of the targeted constraint declaration when using
     * multiple constraints of the same type.
     * <p>
     * The index represents the index of the constraint in the
     * {@code value()} array.
     * </p>
     * By default, no index is defined and the single constraint declaration
     * is targeted.
     *
     * @return constraint declaration index if multivalued annotation is used
     */
    int constraintIndex() default -1;

    /**
     * Defines several {@link OverridesAttribute} annotations on the same
     * element
     *
     * @see javax.validation.OverridesAttribute
     */
    @Documented
    @Target({ METHOD })
    @Retention(RUNTIME)
    public @interface List {

        OverridesAttribute[] value();
    }
}

```

The following elements uniquely identify an overridden constraint attribute:

- `@OverridesAttribute.constraint`
- `@OverridesAttribute.name`
- `@OverridesAttribute.constraintIndex`

If the composition is invalid, e.g.

- infinitely recursive composition
- wrong attribute overriding
- a single attribute mapped to more than one source attribute
- a composing and composed constraint marked as different constraint types (i.e., generic and cross-parameter)
- etc.

a `ConstraintDefinitionException` is raised either at validation time or when the metadata is requested.

Constraint designers are encouraged to make use of composition (recursively or not) based on the built-in constraints defined by the specification. The composing constraints are exposed through the Bean Validation metadata API (`ConstraintDescriptor`). This metadata is particularly useful for third-party metadata consumers like persistence frameworks generating database schemas (such as Java Persistence) or presentation frameworks.

## 3.4. Constraint validation implementation

A constraint validation implementation performs the validation of a given constraint annotation for a given type. The implementation classes are specified by the `validatedBy` element of the `@Constraint` annotation that decorates the constraint definition. The constraint validation implementation implements the `ConstraintValidator` interface.

```

/**
 * Defines the logic to validate a given constraint {@code A}
 * for a given object type {@code T}.
 * <p>
 * Implementations must comply to the following restriction:
 * <ul>
 *   <li>{@code T} must resolve to a non parameterized type</li>
 *   <li>or generic parameters of {@code T} must be unbounded
 *   wildcard types</li>
 * </ul>
 * <p>
 * The annotation {@link SupportedValidationTarget} can be put on a
 * {@code ConstraintValidator} implementation to mark it as supporting
 * cross-parameter constraints. Check out {@link SupportedValidationTarget}
 * and {@link Constraint} for more information.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 */
public interface ConstraintValidator<A extends Annotation, T> {

    /**
     * Initializes the validator in preparation for
     * {@link #isValid(Object, ConstraintValidatorContext)} calls.
     * The constraint annotation for a given constraint declaration
     * is passed.
     * <p>
     * This method is guaranteed to be called before any use of this instance
for
     * validation.
     * <p>
     * The default implementation is a no-op.
     *
     * @param constraintAnnotation annotation instance for a given constraint
declaration
     */
    default void initialize(A constraintAnnotation) {
    }

    /**
     * Implements the validation logic.
     * The state of {@code value} must not be altered.
     * <p>
     * This method can be accessed concurrently, thread-safety must be ensured
     * by the implementation.
     *
     * @param value object to validate
     * @param context context in which the constraint is evaluated
     *
     * @return {@code false} if {@code value} does not pass the constraint
     */
    boolean isValid(T value, ConstraintValidatorContext context);
}

```

Some restrictions apply on the generic type `T` (used in the `isValid()` method). `T` must

- resolve to a non parameterized type (i.e. because the type is not using generics or because

the raw type is used instead of the generic version)

- or generic parameters of `T` must be unbounded wildcard types (i.e. `<?>`).

**NOTE**

This restriction is not a theoretical limitation and a future version of the specification might allow it.

By default, a `ConstraintValidator` targets the (returned) element annotated by the constraint. You can make a `ConstraintValidator` target the array of parameters of a method or constructor (aka cross-parameter) by annotating the validator implementation with `@SupportedValidationTarget`.

*Example 16. @SupportedValidationTarget annotation and ValidationTarget enum*

```
package javax.validation.constraintvalidation;

/**
 * Defines the target(s) a {@link ConstraintValidator} can validate.
 * <p>
 * A {@code ConstraintValidator} can target the (returned) element
 * annotated by the constraint, the array of parameters of a method
 * or constructor (aka cross-parameter) or both.
 * <p>
 * If {@code @SupportedValidationTarget} is not present, the
 * {@code ConstraintValidator} targets the (returned) element annotated
 * by the constraint.
 * <p>
 * A {@code ConstraintValidator} targeting cross-parameter must accept
 * {@code Object[]} (or {@code Object}) as the type of object it
 * validates.
 *
 * @author Emmanuel Bernard
 * @since 1.1
 */
@Documented
@Target({ TYPE })
@Retention(RUNTIME)
public @interface SupportedValidationTarget {

    ValidationTarget[] value();
}
```

```
package javax.validation.constraintvalidation;

/**
 * List of possible targets for a {@link ConstraintValidator}.
 *
 * @author Emmanuel Bernard
 * @since 1.1
 */
public enum ValidationTarget {

    /**
     * (Returned) element annotated by the constraint.
     */
    ANNOTATED_ELEMENT,

    /**
     * Array of parameters of the annotated method or constructor (aka
     * cross-parameter).
     */
    PARAMETERS
}
```

A **ConstraintValidator** implementation can target both annotated elements and array of parameters.

If a `ConstraintValidator` targets array of parameters (cross-parameter), `T` must resolve to `Object[]` (or `Object`) in order to have the array of parameter values passed to the `isValid()` method. A `ConstraintDefinitionException` is raised otherwise.

*Example 17. Example of cross parameter ConstraintValidator*

```
@SupportedValidationTarget(ValidationTarget.PARAMETERS)
public class ScriptAssertValidator implements ConstraintValidator<ScriptAssert, Object[]> {
    @Override
    public void initialize(ScriptAssert constraintAnnotation) {
        [...]
    }

    @Override
    public boolean isValid(Object[] value, ConstraintValidatorContext context) {
        [...]
    }
}
```

[Valid ConstraintValidator definitions](#) shows some examples of valid definitions.

*Example 18. Valid ConstraintValidator definitions*

```
//String is not making use of generics
public class SizeValidatorForString implements ConstraintValidator<Size,
String> {
    [...]
}

//Collection uses generics but the raw type is used
public class SizeValidatorForCollection implements ConstraintValidator
<Size, Collection> {
    [...]
}

//Collection uses generics and unbounded wildcard type
public class SizeValidatorForCollection implements ConstraintValidator
<Size, Collection<?>> {
    [...]
}

//Validator for cross-parameter constraint
@SupportedValidationTarget(ValidationTarget.PARAMETERS)
public class DateParametersConsistentValidator
    implements ConstraintValidator<DateParametersConsistent, Object[]> {
    [...]
}

//Validator for both annotated elements and executable parameters
@SupportedValidationTarget({ValidationTarget.ANNOTATED_ELEMENT,
ValidationTarget.PARAMETERS})
public class ELScriptValidator implements ConstraintValidator<ELScript,
Object> {
    [...]
}
```

And some invalid definitions in [Invalid ConstraintValidator definitions](#).

*Example 19. Invalid ConstraintValidator definitions*

```
//parameterized type
public class SizeValidatorForString implements<Size, Collection<String>>
{
    [...]
}

//parameterized type using bounded wildcard
public class SizeValidatorForCollection implements<Size, Collection<?
extends Address>> {
    [...]
}

//cross-parameter validator accepting the wrong type
@SupportedValidationTarget(ValidationTarget.PARAMETERS)
public class NumberPositiveValidator implements ConstraintValidator
<NumberPositive, Number> {
    [...]
}
```

The lifecycle of a constraint validation implementation instance is undefined. Bean Validation providers are allowed to cache `ConstraintValidator` instances retrieved from the `ConstraintValidatorFactory`.

The `initialize()` method is called by the Bean validation provider prior to any use of the constraint implementation. As of Bean Validation 2.0, `initialize()` has an empty default implementation, allowing to omit the implementation from validators that don't need to access any constraint attributes.

The `isValid()` method is evaluated by the Bean Validation provider each time a given value is validated. It returns `false` if the value is not valid, `true` otherwise. `isValid()` implementations must be thread-safe.

If the property is of an unanticipated type, an `UnexpectedTypeException` is raised. `ConstraintValidator` implementations raise this exception themselves if they receive an unsupported type. However, constraint designers are encouraged to make use of specialized `ConstraintValidator` implementations and delegate the type resolution to the Bean Validation provider (see the type matching algorithm described in [ConstraintValidator resolution algorithm](#)).

If an exception occurs either in the `initialize()` or `isValid()` method, the runtime exception is wrapped into a `ValidationException` by the Bean Validation engine.

The constraint validation implementation is not allowed to change the state of the value passed to `isValid()`.

While not mandatory, it is considered a good practice to split the core constraint validation from the not null constraint validation (for example, an `@Email` constraint will return `true` on a null object, i.e. will not take care of the `@NotNull` validation).

**NOTE**

`null` can have multiple meanings but is commonly used to express that a value does not make sense, is not available or is simply unknown. Those constraints on the value are orthogonal in most cases to other constraints. For example a String, if present, must be an email but can be null. Separating both concerns is a good practice.

The `ConstraintValidatorContext` object passed to the `isValid()` method carries information and operations available in the context the constraint is validated to.

```
/**  
 * Provides contextual data and operation when applying a given constraint  
validator.  
 *  
 * At least one {@link ConstraintViolation} must be defined (either the  
default one,  
 * or if the default {@code ConstraintViolation} is disabled, a custom one).  
 *  
 * @author Emmanuel Bernard  
 * @author Guillaume Smet  
 */  
public interface ConstraintValidatorContext {  
  
    /**  
     * Disables the default {@link ConstraintViolation} object generation  
(which  
     * is using the message template declared on the constraint).  
     * <p>  
     * Useful to set a different violation message or generate a {@code  
ConstraintViolation}  
     * based on a different property.  
     */  
    void disableDefaultConstraintViolation();  
  
    /**  
     * @return the current un-interpolated default message  
     */  
    String getDefaultConstraintMessageTemplate();  
  
    /**  
     * Returns the provider for obtaining the current time in the form of a  
{@link Clock}, e.g. when validating the  
     * {@code Future} and {@code Past} constraints.  
     *  
     * @return the provider for obtaining the current time, never {@code  
null}. If no specific provider has been  
     * configured during bootstrap, a default implementation using the current  
system time and the current default time  
     * zone as returned by {@link Clock#systemDefaultZone()} will be returned.  
     */
```

```

/*
 * @since 2.0
 */
ClockProvider getClockProvider();

/**
 * Returns a constraint violation builder building a violation report
 * allowing to optionally associate it to a sub path.
 * The violation message will be interpolated.
 * <p>
 * To create the {@link ConstraintViolation}, one must call either one of
 * the {@code addConstraintViolation()} methods available in one of the
 * interfaces of the fluent API.
 * If another method is called after {@code addConstraintViolation()} on
 * {@code ConstraintViolationBuilder} or any of its associated nested
interfaces
 * an {@code IllegalStateException} is raised.
 * <p>
 * If {@link ConstraintValidator#isValid(Object,
ConstraintValidatorContext)} returns
 * {@code false}, a {@code ConstraintViolation} object will be built per
constraint
 * violation report including the default one (unless
 * {@link #disableDefaultConstraintViolation()} has been called).
 * <p>
 * {@code ConstraintViolation} objects generated from such a call
 * contain the same contextual information (root bean, path and so on)
unless
 * the path has been overridden.
 * <p>
 * To create a different {@code ConstraintViolation}, a new constraint
violation builder
 * has to be retrieved from {@code ConstraintValidatorContext}
 *
 * Here are a few usage examples:
 * <pre>
 * //assuming the following domain model
 * public class User {
 *     public Map<String,Address> getAddresses() { ... }
 * }
 *
 * public class Address {
 *     public String getStreet() { ... }
 *     public Country getCountry() { ... }
 * }
 *
 * public class Country {
 *     public String getName() { ... }
 * }
 *
 * //From a property-level constraint on User.addresses
 * //Build a constraint violation on the default path - i.e. the
"addresses" property
 * context.buildConstraintViolationWithTemplate( "this detail is wrong" )
 *         .addConstraintViolation();
 *
 * //From a class level constraint on Address
 * //Build a constraint violation on the default path + "street"
 * //i.e. the street property of Address
 * context.buildConstraintViolationWithTemplate( "this detail is wrong" )

```

```

*           .addPropertyNode( "street" )
*           .addConstraintViolation();
*
* //From a property-level constraint on User.addresses
* //Build a constraint violation on the default path + the bean stored
* //under the "home" key in the map
* context.buildConstraintViolationWithTemplate( "Incorrect home address"
)
*           .addBeanNode()
*           .inIterable().atKey( "home" )
*           .addConstraintViolation();
*
* //From a class level constraint on User
* //Build a constraint violation on the default path +
addresses["home"].country.name
* //i.e. property "country.name" on the object stored under "home" in the
map
* context.buildConstraintViolationWithTemplate( "this detail is wrong" )
*           .addPropertyNode( "addresses" )
*           .addPropertyNode( "country" )
*           .inIterable().atKey( "home" )
*           .addPropertyNode( "name" )
*           .addConstraintViolation();
* </pre>
* <cp>
* Cross-parameter constraints on a method can create a node specific
* to a particular parameter if required. Let's explore a few examples:
* <pre>
* //Cross-parameter constraint on method createUser(String password,
String passwordRepeat)
* //Build a constraint violation on the default path + "passwordRepeat"
* context.buildConstraintViolationWithTemplate("Passwords do not match")
*           .addParameterNode(1)
*           .addConstraintViolation();
*
* //Cross-parameter constraint on a method
* //mergeAddresses(Map<String,Address>; addresses,
Map<String,Address>; otherAddresses)
* //Build a constraint violation on the default path +
"otherAddresses["home"]
* //i.e. the Address bean hosted in the "home" key of the
"otherAddresses" map parameter
* context.buildConstraintViolationWithTemplate(
*           "Map entry home present in both and does not match")
*           .addParameterNode(1)
*           .addBeanNode()
*           .inIterable().atKey("home")
*           .addConstraintViolation();
*
* //Cross-parameter constraint on a method
* //mergeAddresses(Map<String,Address>; addresses,
Map<String,Address>; otherAddresses)
* //Build a constraint violation on the default path +
"otherAddresses["home"].city
* //i.e. on the "city" property of the Address bean hosted in
* //the "home" key of the "otherAddresses" map
* context.buildConstraintViolationWithTemplate(
*           "Map entry home present in both but city does not match")
*           .addParameterNode(1)

```

```

*           .addPropertyNode("city")
*                   .inIterable().atKey("home")
*                   .addConstraintViolation();
* </pre>
*
* @param messageTemplate new un-interpolated constraint message
* @return returns a constraint violation builder
*/
ConstraintViolationBuilder buildConstraintViolationWithTemplate(String
messageTemplate);

/**
 * Returns an instance of the specified type allowing access to
 * provider-specific APIs. If the Bean Validation provider
 * implementation does not support the specified class,
 * {@link ValidationException} is thrown.
 *
* @param type the class of the object to be returned
* @param <T> the type of the object to be returned
* @return an instance of the specified class
* @throws ValidationException if the provider does not support the call
*
* @since 1.1
*/
<T> T unwrap(Class<T> type);

/**
 * {@link ConstraintViolation} builder allowing to optionally associate
 * the violation report to a sub path.
* <p>
* To create the {@code ConstraintViolation}, one must call either one of
* the {@code addConstraintViolation()} methods available in one of the
* interfaces of the fluent API.
* <p>
* If another method is called after {@code addConstraintViolation()} on
* {@code ConstraintViolationBuilder} or any of its associated objects
* an {@code IllegalStateException} is raised.
*/
interface ConstraintViolationBuilder {

    /**
     * Adds a node to the path the {@link ConstraintViolation} will be
     * associated to.
     * <p>
     * {@code name} describes a single property. In particular,
     * dot (.) is not allowed.
     *
     * @param name property name
     * @return a builder representing node {@code name}
     * @deprecated since 1.1 - replaced by {@link
#addPropertyNode(String)},
     *             {@link #addBeanNode()} and {@link
#addParameterNode(int)}
     */
    NodeBuilderDefinedContext addNode(String name);

    /**
     * Adds a property node to the path the {@link ConstraintViolation}
     * will be associated to.
     * <p>

```

```

    * {@code name} describes a single property. In particular,
    * dot (.) is not allowed.
    *
    * @param name property name
    * @return a builder representing node {@code name}
    * @throws IllegalArgumentException if the name is null
    *
    * @since 1.1
    */
NodeBuilderCustomizableContext addPropertyNode(String name);

/**
 * Adds a bean node (class-level) to the path the {@link ConstraintViolation}
 * will be associated to.
 * Note that bean nodes are always leaf nodes.
 *
 * @return a builder representing the bean node
 *
 * @since 1.1
 */
LeafNodeBuilderCustomizableContext addBeanNode();

/**
 * Adds a method parameter node to the path the {@link ConstraintViolation}
 * will be associated to.
 * The parameter index must be valid (i.e. within the boundaries of
 * the method
 * parameter indexes). May only be called from within cross-parameter
 * validators.
 *
 * @param index the parameter index
 * @return a builder representing the index-th parameter node
 * @throws IllegalArgumentException if the index is not valid
 *
 * @since 1.1
 */
NodeBuilderDefinedContext addParameterNode(int index);

/**
 * Adds the new {@link ConstraintViolation} to be generated if the
 * constraint validator marks the value as invalid.
 * <p>
 * Methods of this {@code ConstraintViolationBuilder} instance and its
 * nested
 * objects throw {@code IllegalStateException} from now on.
 *
 * @return the {@code ConstraintValidatorContext} instance the
 * {@code ConstraintViolationBuilder} comes from
 */
ConstraintValidatorContext addConstraintViolation();

/**
 * Represents a node whose context is known
 * (i.e. index, key and isInIterable)
 * and that is a leaf node (i.e. no subnode can be added).
 *
 * @since 1.1
*/

```

```

interface LeafNodeBuilderDefinedContext {

    /**
     * Adds the new {@link ConstraintViolation} to be generated if the
     * constraint validator marks the value as invalid.
     * <p>
     * Methods of the {@code ConstraintViolationBuilder} instance this
     object
     * comes from and the constraint violation builder nested
     * objects throw {@code IllegalStateException} after this call.
     *
     * @return {@code ConstraintValidatorContext} instance the
     *         {@code ConstraintViolationBuilder} comes from
     */
    ConstraintValidatorContext addConstraintViolation();
}

/**
 * Represents a node whose context is
 * configurable (i.e. index, key and isInIterable)
 * and that is a leaf node (i.e. no subnode can be added).
 *
 * @since 1.1
 */
interface LeafNodeBuilderCustomizableContext {

    /**
     * Marks the node as being in an {@code Iterable} or a {@code
     Map}.
     *
     * @return a builder representing iterable details
     */
    LeafNodeContextBuilder inIterable();

    /**
     * Adds the new {@link ConstraintViolation} to be generated if the
     * constraint validator mark the value as invalid.
     * <p>
     * Methods of the {@code ConstraintViolationBuilder} instance this
     object
     * comes from and the constraint violation builder nested
     * objects throw {@code IllegalStateException} after this call.
     *
     * @return {@code ConstraintValidatorContext} instance the
     *         {@code ConstraintViolationBuilder} comes from
     */
    ConstraintValidatorContext addConstraintViolation();
}

/**
 * Represents refinement choices for a node which is
 * in an {@code Iterator} or {@code Map}.
 * <p>
 * If the iterator is an indexed collection or a map,
 * the index or the key should be set.
 * <p>
 * The node is a leaf node (i.e. no subnode can be added).
 *
 * @since 1.1
 */

```

```

interface LeafNodeContextBuilder {

    /**
     * Defines the key the object is into the {@code Map}.
     *
     * @param key map key
     * @return a builder representing the current node
     */
    LeafNodeBuilderDefinedContext atKey(Object key);

    /**
     * Defines the index the object is into the {@code List} or array
     *
     * @param index index
     * @return a builder representing the current node
     */
    LeafNodeBuilderDefinedContext atIndex(Integer index);

    /**
     * Adds the new {@link ConstraintViolation} to be generated if the
     * constraint validator mark the value as invalid.
     * <p>
     * Methods of the {@code ConstraintViolationBuilder} instance this
     object
     * comes from and the constraint violation builder nested
     * objects throw {@code IllegalStateException} after this call.
     *
     * @return {@code ConstraintValidatorContext} instance the
     *         {@code ConstraintViolationBuilder} comes from
     */
    ConstraintValidatorContext addConstraintViolation();
}

/**
 * Represents a node whose context is known
 * (i.e. index, key and isInIterable)
 * and that is not necessarily a leaf node (i.e. subnodes can
 * be added).
 */
interface NodeBuilderDefinedContext {

    /**
     * Adds a node to the path the {@link ConstraintViolation} will be
     associated to.
     * <p>
     * {@code name} describes a single property. In particular,
     * dot (.) is not allowed.
     *
     * @param name property name
     * @return a builder representing node {@code name}
     * @deprecated since 1.1 - replaced by {@link
#addPropertyNode(String)}
     *             and {@link #addBeanNode()}
     */
    NodeBuilderCustomizableContext addNode(String name);

    /**
     * Adds a property node to the path the {@link
ConstraintViolation}
     * will be associated to.

```

```

    * <p>
    * {@code name} describes a single property. In particular,
    * dot (.) is not allowed.
    *
    * @param name property name
    * @return a builder representing node {@code name}
    * @throws IllegalArgumentException if the name is null
    *
    * @since 1.1
    */
NodeBuilderCustomizableContext addPropertyNode(String name);

/**
 * Adds a bean node (class-level) to the path the {@link ConstraintViolation}
 * will be associated to.
 * Note that bean nodes are always leaf nodes.
 *
 * @return a builder representing the bean node
 *
 * @since 1.1
 */
LeafNodeBuilderCustomizableContext addBeanNode();

/**
 * Adds the new {@link ConstraintViolation} to be generated if the
 * constraint validator marks the value as invalid.
 * <p>
 * Methods of the {@code ConstraintViolationBuilder} instance this
object
 * comes from and the constraint violation builder nested
 * objects throw {@code IllegalStateException} after this call.
 *
 * @return {@code ConstraintValidatorContext} instance the
 *         {@code ConstraintViolationBuilder} comes from
 */
ConstraintValidatorContext addConstraintViolation();
}

/**
 * Represents a node whose context is
 * configurable (i.e. index, key and isIterable)
 * and that is not necessarily a leaf node (i.e. subnodes can
 * be added).
 */
interface NodeBuilderCustomizableContext {

    /**
     * Marks the node as being in an {@code Iterable} or a {@code Map}.
     *
     * @return a builder representing iterable details
     */
    NodeContextBuilder inIterable();

    /**
     * Adds a node to the path the {@link ConstraintViolation} will be
associated to.
     *
     * {@code name} describes a single property. In particular,

```

```

        * dot (.) is not allowed.
        *
        * @param name property name
        * @return a builder representing node {@code name}
        * @deprecated since 1.1 - replaced by {@link
#addPropertyNode(String)}
        *
        *          and {@link #addBeanNode()})
        */
    NodeBuilderCustomizableContext addNode(String name);

    /**
     * Adds a property node to the path the {@link
ConstraintViolation}
     * will be associated to.
     *
     * {@code name} describes a single property. In particular,
     * dot (.) is not allowed.
     *
     * @param name property name
     * @return a builder representing node {@code name}
     * @throws IllegalArgumentException if the name is null
     *
     * @since 1.1
     */
    NodeBuilderCustomizableContext addPropertyNode(String name);

    /**
     * Adds a bean node (class-level) to the path the {@link
ConstraintViolation}
     * will be associated to.
     * Note that bean nodes are always leaf nodes.
     *
     * @return a builder representing the bean node
     *
     * @since 1.1
     */
    LeafNodeBuilderCustomizableContext addBeanNode();

    /**
     * Adds the new {@link ConstraintViolation} to be generated if the
     * constraint validator mark the value as invalid.
     * <p>
     * Methods of the {@code ConstraintViolationBuilder} instance this
object
     * comes from and the constraint violation builder nested
     * objects throw {@code IllegalStateException} after this call.
     *
     * @return {@code ConstraintValidatorContext} instance the
     *         {@code ConstraintViolationBuilder} comes from
     */
    ConstraintValidatorContext addConstraintViolation();
}

/**
 * Represents refinement choices for a node which is
 * in an {@code Iterator} or {@code Map}.
 * <p>
 * If the iterator is an indexed collection or a map,
 * the index or the key should be set.
 * <p>

```

```

    * The node is not necessarily a leaf node (i.e. subnodes can
    * be added).
    */
interface NodeContextBuilder {

    /**
     * Defines the key the object is into the {@code Map}.
     *
     * @param key map key
     * @return a builder representing the current node
     */
    NodeBuilderDefinedContext atKey(Object key);

    /**
     * Defines the index the object is into the {@code List} or array.
     *
     * @param index index
     * @return a builder representing the current node
     */
    NodeBuilderDefinedContext atIndex(Integer index);

    /**
     * Adds a node to the path the {@code ConstraintViolation} will be
     associated to.
     *
     * {@code name} describes a single property. In particular,
     * dot (.) is not allowed.
     *
     * @param name property name
     * @return a builder representing node {@code name}
     * @deprecated since 1.1 - replaced by {@link
#addPropertyNode(String)
     *           and {@link #addBeanNode()}}
     */
    NodeBuilderCustomizableContext addNode(String name);

    /**
     * Adds a property node to the path the {@link
ConstraintViolation}
     * will be associated to.
     *
     * {@code name} describes a single property. In particular,
     * dot (.) is not allowed.
     *
     * @param name property name
     * @return a builder representing node {@code name}
     * @throws IllegalArgumentException if the name is null
     *
     * @since 1.1
     */
    NodeBuilderCustomizableContext addPropertyNode(String name);

    /**
     * Adds a bean node (class-level) to the path the {@link
ConstraintViolation}
     * will be associated to.
     * <p>
     * Note that bean nodes are always leaf nodes.
     *
     * @return a builder representing the bean node

```

```

    *
    * @since 1.1
    */
LeafNodeBuilderCustomizableContext addBeanNode();

/**
 * Adds the new {@link ConstraintViolation} to be generated if the
 * constraint validator mark the value as invalid.
 * <p>
 * Methods of the {@code ConstraintViolationBuilder} instance this
object
    * comes from and the constraint violation builder nested
    * objects throw {@code IllegalStateException} after this call.
    *
    * @return {@code ConstraintValidatorContext} instance the
    *         {@code ConstraintViolationBuilder} comes from
    */
ConstraintValidatorContext addConstraintViolation();
}
}
}

```

The `ConstraintValidatorContext` interface provides access to contextual information useful for the validation of specific constraints (e.g. `getClockProvider()`, see [Implementation of temporal constraint validators](#) ).

It also allows redefinition of the default constraint message generated when a constraint is not valid. By default, each invalid constraint leads to the generation of one error object represented by a `ConstraintViolation` object. This object is built from the default constraint message template as defined by the constraint declaration and the context in which the constraint declaration is placed (bean, property, executable parameter, cross-parameter or executable return value).

The `ConstraintValidatorContext` methods let the constraint implementation disable the default `ConstraintViolation` generation and create one or more custom ones. The non-interpolated message passed as a parameter is used to build the `ConstraintViolation` message (the message interpolation operation is applied to it).

By default, the `Path` exposed on the `ConstraintViolation` represents the path to the bean, property, parameter, cross-parameter or return value hosting the constraint (see [ConstraintViolation](#) for more information). You can point it to a subpath of this default path by using the constraint violation builder fluent API.

[Using the fluent API to build custom constraint violations](#) shows a few examples.

*Example 20. Using the fluent API to build custom constraint violations*

```
//assuming the following domain model
public class User {
    public Map<String,Address> getAddresses() { [...] }
```

```

}

public class Address {
    public String getStreet() { [...] }
    public Country getCountry() { [...] }
}

public class Country {
    public String getName() { [...] }
}

//From a property-level constraint on User.addresses
//Build a constraint violation on the default path - i.e. the "addresses"
//property
context.buildConstraintViolationWithTemplate( "this detail is wrong" )
    .addConstraintViolation();

//From a class level constraint on Address
//Build a constraint violation on the default path + "street"
//i.e. the street property of Address
context.buildConstraintViolationWithTemplate( "this detail is wrong" )
    .addPropertyNode( "street" )
    .addConstraintViolation();

//From a property-level constraint on User.addresses
//Build a constraint violation on the default path + the bean stored
//under the "home" key in the map
context.buildConstraintViolationWithTemplate( "Incorrect home address" )
    .addBeanNode()
        .inIterable().atKey( "home" )
    .addConstraintViolation();

//From a class level constraint on User
//Build a constraint violation on the default path +
//addresses["home"].country.name
//i.e. property "country.name" on the object stored under "home" in the
//map
context.buildConstraintViolationWithTemplate( "this detail is wrong" )
    .addPropertyNode( "addresses" )
    .addPropertyNode( "country" )
        .inIterable().atKey( "home" )
    .addPropertyNode( "name" )
    .addConstraintViolation();

//To create a subnode representing a method parameter from a cross-
//parameter constraint violation

//Cross-parameter constraint on method createUser(String password, String
//passwordRepeat)
//Build a constraint violation on the default path + "passwordRepeat"
context.buildConstraintViolationWithTemplate("Passwords do not match")
    .addParameterNode(1)
    .addConstraintViolation();

//Cross-parameter constraint on a method
//mergeAddresses(Map<String,Address> addresses, Map<String,Address>
//otherAddresses)
//Build a constraint violation on the default path +
//"otherAddresses["home"]
//i.e. the Address bean hosted in the "home" key of the "otherAddresses"
//map parameter

```

```

context.buildConstraintViolationWithTemplate(
    "Map entry home present in both and does not match" )
    .addParameterNode( 1 )
    .addBeanNode()
        .inIterable().atKey( "home" )
    .addConstraintViolation();

//Cross-parameter constraint on a method
//mergeAddresses(Map<String,Address> addresses, Map<String,Address>
otherAddresses)
//Build a constraint violation on the default path +
"otherAddresses["home"].city
//i.e. on the "city" property of the Address bean hosted in
//the "home" key of the "otherAddresses" map
context.buildConstraintViolationWithTemplate(
    "Map entry home present in both but city does not match" )
    .addParameterNode( 1 )
    .addPropertyNode( "city" )
        .inIterable().atKey( "home" )
    .addConstraintViolation();

```

If `disableDefaultConstraintViolation()` is called, no custom error is added (using the error builder) and if the constraint is not valid, a `ValidationException` is raised.

### 3.4.1. Implementation of temporal constraint validators

Constraint validators for temporal constraints (either the built-in constraints `@Past` and `@Future` or custom temporal constraints) can obtain the current instant from the `ClockProvider` object exposed by `ConstraintValidatorContext#getClockProvider()`.

```

/**
 * Contract for obtaining the {@link Clock} used as the reference for {@code now}
 * when validating the {@code @Future}
 * and {@code @Past} constraints.
 * <p>
 * The default implementation will return the current system time. Plugging in
 * custom implementations may be useful for
 * instance in batch applications which need to run with a specific logical
 * date, e.g. with yesterday's date when
 * re-running a failed batch job execution.
 * <p>
 * Implementations must be safe for access from several threads at the same
 * time.
 *
 * @author Gunnar Morling
 * @author Guillaume Smet
 * @since 2.0
 */
public interface ClockProvider {

    /**
     * Returns the clock which serves as the reference for {@code now}.
     *
     * @return the clock which serves as the reference for {@code now}; must
     * not be {@code null}
     */
    Clock getClock();
}

```

The `getClock()` method returns a `java.time.Clock` object which represents the current instant, date and time using a time zone. A conforming Bean Validation implementation provides a default clock provider which returns a clock representing the current system time and default time zone. It is recommended that implementations call `Clock#systemDefaultZone()` to obtain the clock.

When bootstrapping a validator factory or validator, an alternative clock provider can be registered (see [Bootstrapping](#)). This can be useful for testing, for applying the time zone of the currently logged in user in a multi-user, multi time zone application or for running batch applications with a logical date and time different from the actual current date and time.

### 3.4.2. Examples

*Example 21. ConstraintValidator implementation*

```
/**  
 * Check that a text is within the authorized syntax  
 */  
public class SyntaxValidator implements ConstraintValidator<Syntax,  
String> {  
    private Set<Format> allowedFormats;  
  
    /**  
     * Configure the constraint validator based on the elements  
     * specified at the time it was defined.  
     * @param constraint the constraint definition  
     */  
    public void initialize(Syntax constraint) {  
        allowedFormats = new HashSet( Arrays.asList( constraint.value() )  
);  
    }  
  
    /**  
     * Validate a specified value.  
     * returns false if the specified value does not conform to the  
     * definition  
     */  
    public boolean isValid(String value, ConstraintValidatorContext  
context) {  
        if ( value == null ) return true;  
  
        return allowedFormats.size() == 0  
            || (! Collections.disjoint( guessFormat(value),  
allowedFormats ) );  
    }  
  
    Set<Format> guessFormats(String text) { [...] }  
}
```

This `ConstraintValidator` checks that a text is within the accepted syntax. It also demonstrates an interesting best practice: return `true` on a null parameter.

The following listing shows a validator implementing the validation logic for a cross-parameter constraint.

*Example 22. Cross-parameter validator implementation*

```
/*
 * Check that two date parameters of a method are in the expected order.
 * Expects the
 * 2nd and 3rd parameter of the validated method to be of type
 * java.util.Date.
 */
@SupportedValidationTarget(ValidationTarget.PARAMETERS)
public class DateParametersConsistentValidator implements
<DateParametersConsistent, Object[]> {

    /**
     * Configure the constraint validator based on the elements
     * specified at the time it was defined.
     * @param constraint the constraint definition
     */
    public void initialize(DateParametersConsistent constraint) {
    }

    /**
     * Validate a specified value.
     * returns false if the specified value does not conform to the
     * definition
     */
    public boolean isValid(Object[] value, ConstraintValidatorContext
context) {
        if ( value.length != 3 ) {
            throw new IllegalStateException( "Unexpected method
signature" );
        }
        // one or both limits are unbounded => always consistent
        if ( value[1] == null || value[2] == null ) return true;
        return ( (Date) value[1] ).before( (Date) value[2] );
    }
}
```

The following listing shows a validator implementing the validation logic for a constraint that is both generic and cross-parameter.

*Example 23. Generic and cross-parameter validator implementation*

```
/**  
 * Checks that an object passes the Expression Language expression  
 * provided by the constraint.  
 */  
@SupportedValidationTarget({@ValidationTarget.ANNOTATED_ELEMENT,  
ValidationTarget.PARAMETERS})  
public class ELScriptValidator implements<ELScript, Object> {  
  
    public void initialize(ELScript constraint) {  
        [...]  
    }  
  
    public boolean isValid(Object value, ConstraintValidatorContext  
context) {  
        [...]  
    }  
}
```

The next example shows how to use **ConstraintValidatorContext**.

*Example 24. Use of ConstraintValidatorContext*

```
/*
 * Check that a text is within the authorized syntax
 * Error messages are using either key:
 *   - com.acme.constraint.Syntax.unknown if no particular syntax is
detected
 *   - com.acme.constraint.Syntax.unauthorized if the syntax is not
allowed
 */
public class FineGrainedSyntaxValidator implements ConstraintValidator
<Syntax, String> {
    private Set<Format> allowedFormats;

    /**
     * Configure the constraint validator based on the elements
     * specified at the time it was defined.
     * @param constraint the constraint definition
     */
    public void initialize(Syntax constraint) {
        allowedFormats = new HashSet( Arrays.asList( constraint.value() ) );
    }

    /**
     * Validate a specified value.
     * returns false if the specified value does not conform to the
definition
     */
    public boolean isValid(String value, ConstraintValidatorContext
context) {
        if ( value == null ) return true;
        Set<Format> guessedFormats = guessFormats(value);

        context.disableDefaultConstraintViolation();
        if ( guessedFormats.size() == 0 ) {
            String unknown = "{com.acme.constraint.Syntax.unknown}";
            context.buildConstraintViolationWithTemplate(unknown)
                .addConstraintViolation();
            return false;
        }
        if ( allowedFormats.size() != 0
            && Collections.disjoint( guessedFormats, allowedFormats ) ) {

            String unauthorized =
"com.acme.constraint.Syntax.unauthorized";
            context.buildConstraintViolationWithTemplate(unauthorized)
                .addConstraintViolation();
            return false;
        }
        return true;
    }

    Set<Format> guessFormats(String text) { [...] }
}
```

The default error message is disabled and replaced by a specific error message depending on the type of constraint violation detected. In this case, only one error report is returned at a given time but a constraint validation implementation can return several error reports.

The following example shows how to obtain the current date and time via the `ClockProvider` when validating a temporal constraint such as `@Past`:

*Example 25. Validation of a temporal constraint*

```
/*
 * Validates that the given {@link ZonedDateTime} is in the past.
 */
public class PastValidatorForZonedDateTime implements
ConstraintValidator<Past, ZonedDateTime> {

    @Override
    public boolean isValid(ZonedDateTime value,
ConstraintValidatorContext context) {
        if ( value == null ) {
            return true;
        }

        ZonedDateTime now = ZonedDateTime.now( context.getClockProvider(
).getClock() );

        return value.isBefore( now );
    }
}
```

## 3.5. The ConstraintValidatorFactory

Constraint validation implementation instances are created by a `ConstraintValidatorFactory`.

The lifecycle of `ConstraintValidator` instances is fully dependent of the Bean Validation provider and piloted by the `ConstraintValidatorFactory` methods. Therefore, `ConstraintValidatorFactory` implementations (such as dependency injection frameworks) must consider these instances as belonging to a dependent scope. Bean Validation providers must release each instance retrieved. The `ConstraintValidatorFactory` instance that has created a `ConstraintValidator` instance must be the one that releases it. In other words, passing an instance of `ConstraintValidator` to a `ConstraintValidatorFactory` that has not created it is an error.

**NOTE** `ConstraintValidator` instances created by the `ValidatorFactory` -level `ConstraintValidatorFactory` can be released when the `ValidatorFactory` is being closed.

#### Example 26. ConstraintValidatorFactory interface

```
/**  
 * Instantiates a {@link ConstraintValidator} instance based off its  
 * class.  
 * The {@code ConstraintValidatorFactory} is <b>not</b> responsible  
 * for calling {@link ConstraintValidator#initialize(java.lang.annotation.Annotation)}.  
 *  
 * @author Dhanji R. Prasanna  
 * @author Emmanuel Bernard  
 * @author Hardy Ferentschik  
 */  
public interface ConstraintValidatorFactory {  
  
    /**  
     * @param key The class of the constraint validator to instantiate  
     * @param <T> The type of the constraint validator to instantiate  
     *  
     * @return A new constraint validator instance of the specified class  
     */  
    <T extends ConstraintValidator<, ?> T getInstance(Class<T> key);  
  
    /**  
     * Signals {@code ConstraintValidatorFactory} that the instance is no  
     * longer  
     * being used by the Bean Validation provider.  
     *  
     * @param instance validator being released  
     *  
     * @since 1.1  
     */  
    void releaseInstance(ConstraintValidator<, ?> instance);  
}
```

The default `ConstraintValidatorFactory` provided by the Bean Validation provider implementation uses the public no-arg constructor of the `ConstraintValidator` class. A custom `ConstraintValidatorFactory` can be provided; for example it may benefit from dependency injection control in constraint implementations (see [Bootstrapping considerations](#)). Any constraint implementation relying on `ConstraintValidatorFactory` behaviors specific to an implementation (dependency injection, no no-arg constructor and so on) is not portable, hence great care should be given before walking that path. Make sure to configure the Bean Validation provider to honor any specific needs your `ConstraintValidator` has. As constraint designer and writer, make sure to document any specific non compliant requirements.

`ConstraintValidatorFactory` should not cache instances as the state of each instance can be altered in the `initialize()` method.

If an exception occurs in the factory while retrieving the `ConstraintValidator` instance, the runtime exception is wrapped in a `ValidationException`. If the instance returned by the factory is null, a `ValidationException` is raised.

## 4. Value extractor definition

Validation of container element constraints as well as cascaded validation of generic container types requires access to the values stored in the container. The retrieval of values stored in a container is handled via implementations of the **ValueExtractor** interface:

```
package javax.validation.valueextraction;

/**
 * Defines the logic used to extract the values from a container object of
type {@code T}.
 * <p>
 * A value extractor is tied to one specific type parameter of {@code T}. The
{@link ExtractedValue} annotation
 * is used to mark that type parameter.
 * <p>
 * The extracted values are passed to the corresponding method of the {@link
ValueReceiver}.
 * <p>
 * A typical value extractor implementation for {@link List} may look like
this:
 * <pre>
 * public class ListValueExtractor implements
ValueExtractor<List<ExtractedValue>> {
*
*     @Override
*     public void extractValues(List<?> originalValue, ValueReceiver
receiver) {
*         for ( int i = 0; i < originalValue.size(); i++ ) {
*             receiver.indexedValue( "<iterable element>", i,
originalValue.get( i ) );
*         }
*     }
* }
* </pre>
*
* @author Gunnar Morling
* @author Guillaume Smet
*/
public interface ValueExtractor<T> {

    /**
     * Extracts the values to validate from the original object.
     *
     * @param originalValue the original value from which we want to extract
the values to validate
     * @param receiver the corresponding {@code ValueReceiver}
     */
    void extractValues(T originalValue, ValueReceiver receiver);

    /**
     * Provides a set of methods receiving value extracted by the {@link
ValueExtractor}.
     * <p>
     * The value has to be passed to the method corresponding best to the type
of the original value.

```

```

/*
interface ValueReceiver {

    /**
     * Receives the value extracted from an object.
     *
     * @param nodeName the name of the node representing the container
     element. It will be added to the {@link Path}
     * @param object the value to validate
     */
    void value(String nodeName, Object object);

    /**
     * Receives the value extracted from an {@link Iterable} object that
     is not indexed (e.g. a {@link Set}).
     *
     * @param nodeName the name of the node representing the container
     element. It will be added to the {@link Path}
     * @param object the value to validate
     */
    void iterableValue(String nodeName, Object object);

    /**
     * Receives the value extracted from an indexed object (e.g. a {@link
     List} or an array).
     *
     * @param nodeName the name of the node representing the container
     element. It will be added to the {@link Path}
     * @param i the index of the value in the original object
     * @param object the value to validate
     */
    void indexedValue(String nodeName, int i, Object object);

    /**
     * Receives the value extracted from a keyed object (e.g. a {@link
     Map}).
     *
     * @param nodeName the name of the node representing the container
     element. It will be added to the {@link Path}
     * @param key the key of the value in the original object
     * @param object the value to validate
     */
    void keyedValue(String nodeName, Object key, Object object);
}
}

```

The validation engine passes the container instance and a value receiver object to the `extractValues()` method. Value extractor implementations must invoke one of the `ValueReceiver` methods for each element contained in the container, passing the element value and, optionally, a node name. When calling

- `value()`, the given value will be passed to the validation engine;
- `iterableValue()`, the given value will be passed to the validation engine and the corresponding property path node (see `ConstraintViolation`) will be marked as iterable, i.e. `Node#isInIterable()` returns `true`;

- `indexedValue()`, the given value will be passed to the validation engine and the corresponding property path node will be marked as iterable and it will have set the given index, i.e. `Node#getIndex()` returns the given index value;
- `keyedValue()`, the given value will be passed to the validation engine and the corresponding property path node will be marked as iterable and it will have set the given key, i.e. `Node#getKey()` returns the given key value.

When passing a non-null node name to any of the receiver methods and when the extractor is called in the course of container element validation (not during cascaded validation), a node of kind `CONTAINER_ELEMENT` will be appended to the property path, with `Node#getName()` returning the specified name. If null is passed as node name, no node will be appended to the property path. The resulting property path will then be the same as if the constraint had been given on the container instead of a container element. That is desirable for pure wrapper types such as `Optional`.

The container value passed to a value extractor is retrieved from the element that hosts the type argument carrying the constraint or `@Valid` annotation:

```
private Map<String, @Valid @RetailOrder Order> ordersByName;

public Map<@NotNull String, Order> getOrdersByName() {
    return ordersByName;
}
```

When validating the `@NotNull` constraint, the map as returned by the getter will be passed to the map key extractor in order to obtain the map keys. When validating the `@RetailOrder` constraint and performing cascaded validation, the map as obtained directly from the field will be passed to the map value extractor in order to obtain the map values.

## 4.1. `@ExtractedValue`

The `@ExtractedValue` annotation is used to denote the element extracted by a given value extractor:

```

package javax.validation.valueextraction;

/**
 * Marks the type parameter of a container type to which a {@link
ValueExtractor} is tied.
 * <p>
 * Must be given exactly once for a value extractor type.
 *
 * @author Gunnar Morling
 * @author Guillaume Smet
 *
 * @see ValueExtractor
 */
@Retention(RetentionPolicy.RUNTIME)
@Target(ElementType.TYPE_USE)
@Documented
public @interface ExtractedValue {

}

```

The `@ExtractedValue` annotation must be specified exactly once for a value extractor type.

`@ExtractedValue` is to be specified on a type argument of the container type as used in the extractor definition. Only wildcard type arguments are supported as target for `@ExtractedValue`.

**NOTE** This implies that only one extractor is supported for a given generic type. I.e. there can be an extractor for `List<?>`, but not one for `List<String>` and one for `List<Integer>`.

In case an illegal value extractor definition is detected, a `ValueExtractorDefinitionException` is raised.

## 4.2. `@UnwrapByDefault`

Value extractor definitions can be marked with the `@UnwrapByDefault` annotation. This causes constraints to be automatically applied to the wrapped value if a constraint is found for an element handled by that extractor (see [Implicit unwrapping of containers](#)):

### Example 27. @UnwrapByDefault annotation

```
package javax.validation.valueextraction;

/**
 * Marks a {@link ValueExtractor} definition so that it is applied
 automatically when detecting constraints declared on
 * the container type supported by the extractor, causing the constraints
 to be applied to the container's elements
 * instead of the container.
 * <p>
 * If needed, this behavior can be changed per constraint using {@link
 Unwrapping.Skip}, causing the constraints to be
 * applied to the container itself:
 *
 * <pre>
 * &#064;SomeConstraint(payload = Unwrapping.Skip.class)
 * SomeContainerType container;
 * </pre>
 *
 * @author Guillaume Smet
 * @since 2.0
 */
@Target({ TYPE })
@Retention(RUNTIME)
@Documented
public @interface UnwrapByDefault {

}
```

```
@UnwrapByDefault
class WrapperExtractor implements ValueExtractor<Wrapper<@ExtractedValue ?>> {

    @Override
    public void extractValues(Wrapper originalValue, ValueReceiver receiver) {
        // ...
    }
}
```

## 4.3. Built-in value extractors

Compatible implementations provide value extractors for the following types out of the box:

- `java.util.Iterable`; `iterableValue()` must be invoked for each contained element, passing the string literal `<iterable element>` as node name
- `java.util.List`; `indexedValue()` must be invoked for each contained element, passing the string literal `<list element>` as node name
- `java.util.Map`; both map keys and map values are to be supported; `keyedValue()` must be invoked by the map key extractor for each contained key, passing the string literal `<map`

`key>` as node name; `keyedValue()` must be invoked by the map value extractor for each contained value, passing the string literal `<map value>` as node name

- `java.util.Optional; value()` must be invoked if a value is present, passing `null` as node name
- `javafx.beans.observable.ObservableValue; value()` must be invoked with the observable value, passing `null` as node name; the extractor must be marked with `@UnwrapByDefault`
- `javafx.beans.property.ReadOnlyListProperty` and `javafx.beans.property.ListProperty; indexedValue()` must be invoked for each contained element, passing the string literal `<list element>` as node name
- `javafx.beans.property.ReadOnlyMapProperty` and `javafx.beans.property.MapProperty;` both map keys and map values are to be supported; `keyedValue()` must be invoked by the map key extractor for each contained key, passing the string literal `<map key>` as node name; `keyedValue()` must be invoked by the map value extractor for each contained value, passing the string literal `<map value>` as node name

Additional value extractors (amending or overriding the set of built-in extractors) can be registered when bootstrapping the validation engine (see [Registering ValueExtractor implementations](#)).

## 4.4. Examples

A value extractor for the elements of `java.util.List`:

```
class ListValueExtractor implements ValueExtractor<List<@ExtractedValue ?>> {  
  
    @Override  
    public void extractValues(List<?> originalValue, ValueReceiver receiver) {  
        for ( int i = 0; i < originalValue.size(); i++ ) {  
            receiver.indexedValue( "<list element>", i, originalValue.get( i )  
        );  
    }  
}
```

A value extractor for `java.util.Optional`:

```
public class OptionalValueExtractor implements ValueExtractor<Optional<@ExtractedValue ?>> {  
    @Override  
    public void extractValues(Optional<?> originalValue, ValueExtractor  
.ValueReceiver receiver) {  
        receiver.value( null, originalValue.isPresent() ? originalValue.get()  
: null );  
    }  
}
```

The following extractor definition is illegal as it specifies `@ExtractedValue` more than once:

```
public class IllegalMapExtractor implements ValueExtractor<Map<@ExtractedValue  
?, @ExtractedValue ?>> { ... }
```

The following extractor definition is unsupported as it specifies `@ExtractedValue` on a non-wildcard type argument:

```
public class StringListValueExtractor implements ValueExtractor<List  
<@ExtractedValue String>> { ... }
```

# 5. Constraint declaration and validation process

The Bean Validation specification defines a framework for declaring constraints on JavaBean classes, fields and properties. Constraints are declared on types and evaluated against instances or graphs of instances.

Bean Validation also offers a way to declare constructor and method constraints where parameters and return values are the constrained elements. We will discuss method constraints declaration in detail in [Method and constructor constraints](#).

Furthermore, constraints can be applied to the elements of generic container types such as [Map](#), [List](#) or [Optional](#). Container element constraints are discussed in detail in [Container element constraints](#).

## 5.1. Requirements on classes to be validated

Objects hosting constraints and expecting to be validated by Bean Validation providers must fulfill the following requirements:

- Properties to be validated must follow the method signature conventions for JavaBeans read properties, as defined by the [JavaBeans specification](#). These properties are commonly referred as getters.
- Static fields and static methods are excluded from validation.
- Constraints can be applied to interfaces and superclasses.

### *What is a getter?*

The JavaBeans specification specifies that a getter is a method whose

#### NOTE

- name starts with `get` and has a return type but no parameter
- name starts with `is`, has no parameter and is returning `boolean`

The target of an annotation definition can be a

- type
- field or property
- constructor or method return value
- constructor or method parameter
- constructor or method cross-parameter

- container element

provided that:

- the constraint definition supports the specified target (`java.lang.annotation.Target`)
- one of the `ConstraintValidators` declared on the constraint supports the declared type of the target or in the case of cross-parameter, one cross-parameter `ConstraintValidator` is present (see [ConstraintValidator resolution algorithm](#) to learn about `ConstraintValidator` resolution)
- in the case of container element constraints, a corresponding value extractor exists (see [ValueExtractor resolution](#) for the details of value extractor resolution)

### 5.1.1. Object validation

Constraint declarations can be applied to a class or an interface. Applying a constraint to a class or interface expresses a validation over the state of the class or the class implementing the interface.

### 5.1.2. Field and property validation

Constraint declarations can be applied on both fields and properties for the same object type. The same constraint should however not be duplicated between a field and its associated property (the constraint validation would be applied twice). It is recommended for objects holding constraint declarations to adhere to a single state access strategy (either annotated fields or properties).

#### *Java Persistence and Bean Validation*

**NOTE** For maximum portability, persistent properties hosting Bean Validation constraints should use the same access strategy used in Java Persistence. In other words, place your Bean Validation constraint annotations on the same element (field or getter) as your Java Persistence annotations.

When a field is annotated with a constraint declaration, field access strategy is used to access the state validated by such constraint.

When a property is annotated with a constraint declaration, property access strategy is used to access the state validated by such constraint.

When using field access strategy, the Bean Validation provider accesses the instance variable directly. When using the property access strategy, the Bean Validation provider accesses the state via the property accessor method. It is required that the class follows the method signature conventions for JavaBeans read properties (as defined by the JavaBeans `Introspector` class) for constrained properties when constrained properties are used. In this

case, for every constraint property of type `T`, there is a getter method named `get<Property-name>`. The method must have no parameters. For `boolean` properties, `is<Property-name>` is an alternative name for the getter method. Specifically, if `getX` is the name of the getter method, where `X` is a string, the name of the persistent property is defined by the result of `java.beans.Introspector.decapitalize(X)`.

The fields or methods visibility are not constrained.

### 5.1.3. Graph validation

In addition to supporting instance validation, validation of graphs of objects is also supported. The result of a graph validation is returned as a unified set of constraint violations. `@Valid` is used to express validation traversal of an association.

*Example 28. @Valid annotation*

```
/*
 * Marks a property, method parameter or method return type for
validation cascading.
 * <p>
 * Constraints defined on the object and its properties are be validated
when the
 * property, method parameter or method return type is validated.
 * <p>
 * This behavior is applied recursively.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 */
@Target({ METHOD, FIELD, CONSTRUCTOR, PARAMETER, TYPE_USE })
@Retention(RUNTIME)
@Documented
public @interface Valid {
}
```

Consider the situation where bean `X` contains a field of type `Y`. By annotating field `Y` with the `@Valid` annotation, the Validator will validate `Y` (and its properties) when `X` is validated. The exact type `Z` of the value contained in the field declared of type `Y` (subclass, implementation) is determined at runtime. The constraint definitions of `Z` are used. This ensures proper polymorphic behavior for associations marked with `@Valid`.

Collection-valued, array-valued and generally `Iterable` fields and properties may also be decorated with the `@Valid` annotation. This causes the contents of the iterator to be validated. Any object implementing `java.lang.Iterable` is supported. This includes specifically:

- arrays of objects
- `java.util.Collection`

- `java.util.Set`
- `java.util.List`
- `java.util.Map` (special treatment see below)

Each object provided by the iterator is validated. For `Map`, the value (retrieved by `getValue`) of each `Map.Entry` is validated (the key is not validated).

Like regular references, its type is determined at runtime and the constraint definitions for this particular type are used.

As of Bean Validation 2.0, `@Valid` can be applied to the elements of any generic container by putting it to the type argument(s) of such container, provided a value extractor implementation (see [Value extractor definition](#)) for that container type is present. There are built-in value extractors for the generic collection types listed above. In addition, there is a built-in extractor for the key objects of maps. See [Built-in value extractors](#) for the complete list of built-in value extractors.

The `@Valid` annotation is applied recursively. A conforming implementation avoids infinite loops according to the rules described in [Object graph validation](#).

#### 5.1.3.1. Examples

*Example 29. Making elements of a list subject to graph validation*

```
public class User {

    // preferred style as of Bean Validation 2
    private List<@Valid PhoneNumber> phoneNumbers;

    // traditional style; continues to be supported
    @Valid
    private List<PhoneNumber> phoneNumbers;
}
```

*Example 30. Making values of a map subject to graph validation*

```
public class User {

    // preferred style as of Bean Validation 2
    private Map<AddressType, @Valid Address> addressesByType;

    // traditional style; continues to be supported
    @Valid
    private Map<AddressType, Address> addressesByType;
}
```

*Example 31. Making keys and values of a map subject to graph validation*

```
public class User {  
    private Map<@Valid AddressType, @Valid Address> addressesByType;  
}
```

*Example 32. Making a nested collection subject to graph validation*

```
public class User {  
    private Map<String, List<@Valid Address>> addressesByType;  
}
```

In the last example, all `Address` objects contained in the lists of the `addressesByType` map will be validated. Two value extractors are invoked for this:

- the extractor for `Map` values will be invoked to obtain all map values (lists of `Address`)
- for each extracted list of addresses, the extractor for `List` elements will be invoked, providing the `Address` objects from each list in the map

## 5.2. Constraint declaration

Constraint declarations are placed on classes or interfaces primarily through annotations. A constraint annotation (see [Constraint annotation](#)), can be applied to a type, on any of the type's fields or on any of the JavaBeans-compliant properties.

When a constraint is defined on a class, the class instance being validated is passed to the `ConstraintValidator`. When a constraint is defined on a field, the value of the field is passed to the `ConstraintValidator`. When a constraint is defined on a getter, the result of the getter invocation is passed to the `ConstraintValidator`.

[Method and constructor constraints](#) discusses in detail constraints on methods and constructors.

## 5.3. Inheritance (interface and superclass)

A constraint declaration can be placed on an interface. For a given class, constraint declarations held on superclasses as well as interfaces are evaluated by the Bean Validation provider. Rules are formally described in [Formal group definitions](#).

The effect of constraint declarations is cumulative. Constraints declared on a superclass getter

will be validated along with any constraints defined on an overridden version of the getter according to the Java Language Specification visibility rules.

## 5.4. Group and group sequence

A group defines a subset of constraints. Instead of validating all constraints for a given object graph, only a subset is validated. This subset is defined by the group or groups targeted. Each constraint declaration defines the list of groups it belongs to. If no group is explicitly declared, a constraint belongs to the `Default` group.

Groups are represented by interfaces.

*Example 33. Definition of groups*

```
/**  
 * Validation group verifying that a user is billable  
 */  
public interface Billable {}  
  
/**  
 * Customer can buy without any harrassing checking process  
 */  
public interface BuyInOneClick {  
}
```

A constraint can belong to one or more groups.

*Example 34. Assign groups to constraints*

```
/**  
 * User representation  
 */  
public class User {  
    @NotNull  
    private String firstname;  
  
    @NotNull(groups = Default.class)  
    private String lastname;  
  
    @NotNull(groups = {Billable.class, BuyInOneClick.class})  
    private CreditCard defaultCreditCard;  
}
```

During the validation call, one or more groups are validated. All the constraints belonging to this set of groups are evaluated on the object graph. In [Assign groups to constraints](#), `@NotNull` is checked on `defaultCreditCard` when either the `Billable` or `BuyInOneClick` group is validated. `@NotNull` on `firstname` and `lastname` are validated when the `Default` group is

validated. Reminder: constraints held on superclasses and interfaces are considered.

**Default** is a group predefined by the specification.

```
package javax.validation.groups;

/**
 * Default Bean Validation group.
 * <p>
 * Unless a list of groups is explicitly defined:
 * <ul>
 *   <li>constraints belong to the {@code Default} group</li>
 *   <li>validation applies to the {@code Default} group</li>
 * </ul>
 * Most structural constraints should belong to the default group.
 *
 * @author Emmanuel Bernard
 */
public interface Default { }
```

### 5.4.1. Group inheritance

In some situations, a group is a superset of one or more groups. This can be described by Bean Validation. A group may inherit one or more groups by using interface inheritance.

*Example 35. Groups can inherit other groups*

```
/**
 * Customer can buy without harrassing checking process
 */
public interface BuyInOneClick extends Default, Billable {}
```

For a given interface **Z**, constraints marked as belonging to the group **Z** (i.e. where the annotation element **groups** contains the interface **Z**) or any of the super interfaces of **Z** (inherited groups) are considered part of the group **Z**.

In the following example:

*Example 36. Use of a inherited group*

```
/**  
 * User representation  
 */  
public class User {  
    @NotNull  
    private String firstname;  
  
    @NotNull(groups = Default.class)  
    private String lastname;  
  
    @NotNull(groups = Billable.class)  
    private CreditCard defaultCreditCard;  
}
```

validating the group `BuyInOneClick` will lead to the following constraints checking:

- `@NotNull` on `firstname` and `lastname`
- `@NotNull` on `defaultCreditCard`

because `Default` and `Billable` are superinterfaces of `BuyInOneClick`.

### 5.4.2. Group sequence

By default, constraints are evaluated in no particular order regardless of which groups they belong to. It is however useful in some situations to control the order of constraints evaluation. There are often scenarios where a preliminary set of constraints should be evaluated prior to other constraints. Here are two examples:

- The second group depends on a stable state to run properly. This stable state is verified by the first group.
- The second group is a heavy consumer of time, CPU or memory and its evaluation should be avoided if possible.

To implement such ordering, a group can be defined as a sequence of other groups. Each group in a group sequence must be processed sequentially in the order defined by `@GroupSequence.value` when the group defined as a sequence is requested. Note that a group member of a sequence can itself be composed of several groups via inheritance or sequence definition. In this case, each composed group must respect the sequence order as well.

Processing a group is defined in [Validation routine](#) ; if one of the groups processed in the sequence generates one or more constraint violations, the groups following in the sequence must not be processed. This ensures that a set of constraints is evaluated only if another set of constraints is valid.

Groups defining a sequence and groups composing a sequence must not be involved in a cyclic dependency:

- either directly or indirectly
- either through cascaded sequence definitions or group inheritance

If a group containing such a circularity is evaluated, a [GroupDefinitionException](#) is raised.

Groups defining a sequence should not directly inherit other groups. In other words, the interface hosting the group sequence should not have any super interface.

Groups defining a sequence should not be used directly in constraint declarations. In other words, the interface hosting the group sequence should not be used in a constraint declaration.

To define a group as a sequence, the interface must be annotated with the [@GroupSequence](#) annotation.

```
/**  
 * Defines group sequence.  
 * <p>  
 * The interface hosting {@code @GroupSequence} is representing  
 * the group sequence.  
 * When hosted on a class, represents the {@link Default} group  
 * for that class.  
 *  
 * @author Emmanuel Bernard  
 * @author Hardy Ferentschik  
 */  
@Target({ TYPE })  
@Retention(RUNTIME)  
@Documented  
public @interface GroupSequence {  
  
    Class<?>[] value();  
}
```

Here is a usage example:

*Example 37. Make use of group sequence*

```
@ZipCodeCoherenceChecker(groups = Address.HighLevelCoherence.class)
public class Address {
    @NotNull @Size(max = 50)
    private String street1;

    @NotNull @ZipCode
    private String zipCode;

    @NotNull @Size(max = 30)
    private String city;

    /**
     * check coherence on the overall object
     * Needs basic checking to be green first
     */
    public interface HighLevelCoherence {}

    /**
     * check both basic constraints and high level ones.
     * high level constraints are not checked if basic constraints fail
     */
    @GroupSequence({Default.class, HighLevelCoherence.class})
    public interface Complete {}
}
```

In [Make use of group sequence](#), when the `Address.Complete` group is validated, all constraints belonging to the `Default` group are validated. If any of them fail, the validation skips the `HighLevelCoherence` group. If all `Default` constraints pass, `HighLevelCoherence` constraints are evaluated.

**NOTE** A given constraint can belong to two or more groups ordered by a sequence. In this case, the constraint is evaluated as part of the first group and ignored in the subsequent group(s). See [Validation routine](#) for more information.

### 5.4.3. Redefining the Default group for a class

In [Make use of group sequence](#), validating the `Default` group does not validate `HighLevelCoherence` constraints. To ensure a complete validation, a user must use the `Complete` group. This breaks some of the encapsulation you could expect. You can work around this by redefining what the `Default` group means for a given class. To redefine `Default` for a class, place a `@GroupSequence` annotation on the class; this sequence expresses the sequence of groups that does substitute `Default` for this class.

#### Example 38. Redefining Default group for Address

```
@GroupSequence({Address.class, HighLevelCoherence.class})
@ZipCodeCoherenceChecker(groups = Address.HighLevelCoherence.class)
public class Address {
    @NotNull @Size(max = 50)
    private String street1;

    @NotNull @ZipCode
    private String zipCode;

    @NotNull @Size(max = 30)
    private String city;

    /**
     * check coherence on the overall object
     * Needs basic checking to be green first
     */
    public interface HighLevelCoherence {}
}
```

In [Redefining Default group for Address](#), when an address object is validated for the group **Default**, all constraints belonging to the group **Default** and hosted on **Address** are evaluated. If none fails, all **HighLevelCoherence** constraints present on **Address** are evaluated. In other words, when validating the **Default** group for **Address**, the group sequence defined on the **Address** class is used.

Since sequences cannot have circular dependencies, using **Default** in the declaration of a sequence is not an option. Constraints hosted on a class **A** and belonging to the **Default** group (by default or explicitly) implicitly belong to the group **A**.

A sequence defined on a class **A** (i.e. redefining the **Default** groups for the class) must contain the group **A**. In other words, the default constraints hosted on a class must be part of the sequence definition. If a **@GroupSequence** redefining the **Default** group for a class **A** does not contain the group **A**, a **GroupDefinitionException** is raised when the class is validated or when its metadata is requested.

#### 5.4.4. Implicit grouping

It is possible to implicitly group several constraints in the same group without explicitly listing such a group in the constraint declaration. Every constraint hosted on an interface **Z** and part of the **Default** group (implicitly or explicitly) belongs to the group **Z**. This is useful to validate the partial state of an object based on a role represented by an interface.

*Example 39. Example of interface / group hosting constraints*

```
/*
 * Auditable object contract
 */
public interface Auditable {
    @NotNull String getCreationDate();
    @NotNull String getLastUpdate();
    @NotNull String getLastModifier();
    @NotNull String getLastReader();
}

/*
 * Represents an order in the system
 */
public class Order implements Auditable {
    private String creationDate;
    private String lastUpdate;
    private String lastModifier;
    private String lastReader;

    private String orderNumber;

    public String getCreationDate() {
        return this.creationDate;
    }

    public String getLastUpdate() {
        return this.lastUpdate;
    }

    public String getLastModifier() {
        return this.lastModifier;
    }

    public String getLastReader() {
        return this.lastReader;
    }

    @NotNull @Size(min=10, max=10)
    public String getOrderNumber() {
        return this.orderNumber;
    }
}
```

When an `Order` object is validated on the `Default` group, the following constraints are validated: `@NotNull` on `getCreationDate`, `getLastUpdate`, `getLastModifier`, `getLastReader`, `getOrderNumber` and `@Size` on `getOrderNumber` as all belong to the `Default` group.

When an `Order` object is validated on the `Auditable` group, the following constraints are validated: `@NotNull` on `getCreationDate`, `getLastUpdate`, `getLastModifier`, `getLastReader`. Only the constraints present on `Auditable` (and any of its super interfaces) and belonging to the `Default` group are validated when the group `Auditable` is requested. It

allows the caller to validate that a given object can be safely audited even if the object state itself is not valid.

#### 5.4.5. Group conversion

When performing cascading validation, it is possible to use a different group than the one originally requested using the group conversion feature. Group conversions are declared by using the `@ConvertGroup` annotation.

*Example 40. @ConvertGroup annotation*

```
package javax.validation.groups;

/**
 * Converts group {@code from} to group {@code to} during cascading.
 * <p>
 * Can be used everywhere {@link Valid} is used and must be on an element
 * annotated with {@code Valid}.
 *
 * @author Emmanuel Bernard
 * @since 1.1
 */
@Target({ TYPE, METHOD, FIELD, CONSTRUCTOR, PARAMETER, TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
public @interface ConvertGroup {

    Class<?> from();

    Class<?> to();

    /**
     * Defines several {@link ConvertGroup} annotations
     * on the same element.
     */
    @Target({ TYPE, METHOD, FIELD, CONSTRUCTOR, PARAMETER, TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    public @interface List {
        ConvertGroup[] value();
    }
}
```

`@ConvertGroup` and `@ConvertGroup.List` can be used everywhere `@Valid` can be used (associations, method/constructor parameters and return value). If these annotations are used without `@Valid`, a `ConstraintDeclarationException` is raised.

When an element is annotated with `@Valid`, validation is propagated. Groups are passed as is to the nested elements unless the `@ConvertGroup` annotation is used.

If the group expected to be passed to the nested element validation is defined as the `from` attribute of a `@ConvertGroup` annotation, the group used to effectively validate the nested element is the corresponding group defined in the `to` attribute.

Rules are not executed recursively. If a rule is found matching, subsequent rules are no longer evaluated. In particular, if a set of `@ConvertGroup` declaration chains group A to B and B to C, the group A will be converted to B and not to C. This both makes rules clearer and let you switch two groups.

It is not legal to have more than one conversion rule containing the same `from` value. In this case, a `ConstraintDeclarationException` is raised.

Like regular constraint declarations, the `from` attribute cannot refer to a group sequence. A `ConstraintDeclarationException` is raised in this situation. The `to` attribute can. The group sequence will then be expanded before validating the associated object.

When validation is done, group sequences are expanded before validating the object and its cascaded objects with the expected groups. Group conversion on an associated object happens on the already expanded groups.

**NOTE** The group referred to in `@ConvertGroup.from` works on expanded groups (i.e., after the group sequence has been expanded), not necessarily groups passed to the various `validate` methods.

The group referred to in `@ConvertGroup.to` will be expanded before validating the cascaded object just like a call to the various `validate` method would have done.

**NOTE** Like most Bean Validation error cases, an illegal set of rules can be discovered statically (at compile time). For example, an annotation processor could detect such errors.

Group circularity in a group conversion are not problematic because:

- NOTE**
- only one rule is applied for a given cascade (rules are not applied recursively)
  - validation cascading is stopped when the same instance / property is validated with the same group in a given path (existing rule)

`@ConvertGroup` and `@ConvertGroup.List` can only be placed where `@Valid` is present to ensure proper respect of the Liskov substitution principle: if rules were to be defined on an overriding method of a method marked as cascading validation, the rules could end up altering the list of constraints validated by the super type and thus violating the Liskov substitution principle.

Likewise, if a sub type overrides/implements a method originally defined in several parallel types of the hierarchy (e.g. two interfaces not extending each other, or a class and an interface not implemented by said class) and if that method's return value has been marked for cascading validation in one of the parallel types, no group conversion rule may be declared for that method's return value in the parallel types of the hierarchy. This again is to avoid an unexpected altering of the post conditions to be guaranteed to the caller.

If any of these rules is violated, a `ConstraintDeclarationException` is raised by default as defined in [Method constraints in inheritance hierarchies](#).

Group conversion is quite useful to facilitate object graph reuse without spreading the validation group definitions across several layers. Let's look at an example.

#### 5.4.5.1. Group conversion examples

In this example we will reuse the `Address` group split and match it to the `User` group split.

*Example 41. Example of group conversion*

```
public interface Complete extends Default {}
public interface BasicPostal {}
public interface FullPostal extends BasicPostal {}

public class Address {
    @NotNull(groups=BasicPostal.class)
    String street1;

    String street2;

    @ZipCode(groups=BasicPostal.class)
    String zipCode;

    @CodeChecker(groups=FullPostal.class)
    String doorCode;
}

public class User {
    @Valid
    @ConvertGroup(from=Default.class, to=BasicPostal.class)
    @ConvertGroup(from=Complete.class, to=FullPostal.class)
    Set<Address> getAddresses() { [...] }
}
```

When validating an instance of `User` with the `Default` group, the associated addresses are validated with the `BasicPostal` group. When validating an instance of `User` with the `Complete` group, the associated addresses are validated with the `FullPostal` group.

Group conversions can also be applied during container element validation:

*Example 42. Example of container element validation with group conversion*

```
public class User {  
    Set<  
        @Valid  
        @ConvertGroup(from=Default.class, to=BasicPostal.class)  
        @ConvertGroup(from=Complete.class, to=FullPostal.class)  
        Address  
    > getAddresses() { [...] }  
}
```

The following example shows an illegal declaration of a group conversion rule on a method's return value:

*Example 43. Example of an illegal group conversion*

```
public interface BasicPostal {}  
  
public class Order { [...] }  
  
public interface RetailOrderService {  
  
    @Valid  
    Order placeOrder(String itemNo, int quantity);  
}  
  
public interface B2BOrderService {  
  
    @Valid  
    @ConvertGroup(from=Default.class, to=BasicPostal.class)  
    Order placeOrder(String itemNo, int quantity);  
}  
  
public class OrderService implements RetailOrderService, B2BOrderService {  
  
    @Override  
    public Order placeOrder(String itemNo, int quantity) {  
        [...]  
    }  
}
```

Here the class `OrderService` implements the two unrelated interfaces `RetailOrderService` and `B2BOrderService`, which both define a method `placeOrder()`, marking the return value as cascaded.

The group conversion declared in `B2BOrderService` is illegal as per the rules defined in the previous section, since the set of applied validation groups might be altered unexpectedly for a client of the `RetailOrderService` interface.

#### 5.4.6. Formal group definitions

The formal rules defining groups are as followed. *Text in italic are comments about the rules.*

For every class **X**:

1. For each superclass **Y** of **X**, the group **Y** contains all constraints of the group **Y** of **Y** *this rule prepares formal concepts for recursive discovery*
2. The group **X** contains the following constraints: group **X** is a group used on sequences redefining the default group on a class (see [Redefining the Default group for a class](#))
  - a. every constraint declared by the class **X** which does not declare a group or does declare the group **Default** explicitly. *all Default constraints hosted on X*
  - b. every constraint declared by any interface implemented by **X** and not annotated **@GroupSequence** which does not explicitly declare a group or does declare the group **Default** explicitly. *all Default constraints hosted on interfaces of X: constraints are inherited by the class hierarchy. Interfaces marked as @GroupSequence are ignored.*
  - c. if **X** has a direct superclass **Y**, every constraint in the group **Y** *all Default constraints hosted on the superclasses of X: constraints are inherited by the class hierarchy*
3. If **X** has no **@GroupSequence** annotation, the group **Default** contains the following constraints: *this rule defines which constraints are evaluated when validating Default on X.*
  - a. every constraint in the group **X**
  - b. if **X** has a direct superclass **Y**, every constraint in the group **Default** of **Y** *this rule is necessary in case Y redefines the group Default*
4. If **X** does have a **@GroupSequence** annotation, the group **Default** contains every constraint belonging to every group declared by the **@GroupSequence** annotation. *this rule describes how a class can redefine the group Default for itself (see [Redefining the Default group for a class](#))*
  - the **@GroupSequence** annotation must declare the group **X**
5. For every interface **Z**, the group **Z** contains the following constraints: *this rule defines how non Default groups are defined*
  - a. every constraint declared by the interface **Z** which does not explicitly declare a group or does declare the group **Default** explicitly. *all Default constraints hosted on Z: this rule formally defines implicit grouping per interface (see [Implicit grouping](#))*
  - b. every constraint (which does not explicitly declare a group) declared by any superinterface not annotated **@GroupSequence** of the interface **Z** *all Default constraints hosted on interfaces of Z: groups can be inherited (see [Group inheritance](#))*

- c. every constraint declared by the class **X** which explicitly declares the group **Z** *every constraint hosted by X and marked as belonging to the group Z*
  - d. every constraint declared by any interface implemented by **X** and not annotated **@GroupSequence** which explicitly declares the group **Z** *every constraint hosted by any interface of X and marked as belonging to the group Z*
  - e. if **X** has a direct superclass **Y**, every constraint in the group **Z** of **Y** *every constraint hosted by any superclass of X and marked as belonging to the group Z*
6. For every interface **Z** annotated **@GroupSequence**, the group **Z** contains every constraint belonging to every group declared by the **@GroupSequence** annotation. *defines the composition side of group sequence but does not define the ordering behavior of sequence (see Group sequence)*

When a given group **G** (represented by an interface **G**) is requested for the validation of a class **X**:

- constraints belonging to the group **G** are evaluated
- if the interface **G** is not annotated **@GroupSequence**, every group represented by the super interface of **G** are requested for validation
- if the interface **G** is annotated with **@GroupSequence**, every group represented by the interfaces declared by the **@GroupSequence** annotation are requested for validation
  - the validation of groups declared to the **@GroupSequence** must happen in the sequencing order declared by **@GroupSequence**: the sequencing order is propagated to the groups composing the sequenced group (via inheritance or group sequence)
  - if a group validation triggers the failure of one or more constraints, groups following in the sequence must not be evaluated.
- if the group **G** represents the **Default** group of **X** overridden by **@GroupSequence**, operations are equivalent

When the **Default** group of a given class **X** is overridden via **@GroupSequence**, its validation is as followed:

- every group represented by the interfaces declared by the **@GroupSequence** annotation are requested for validation
  - the validation of groups declared to the **@GroupSequence** must happen in the sequencing order declared by **@GroupSequence**: the sequencing order is propagated to the groups composing the sequenced group (via inheritance or group sequence)
  - if a group validation triggers the failure of one or more constraints, groups following in the sequence must not be evaluated.

Unless defined by a **@GroupSequence**, evaluation ordering is not constrained. In particular,

several groups can be validated in the same pass. If a group definition leads to a circular sequencing order between groups, a [GroupDefinitionException](#) is raised.

**NOTE**

A group **G** sequenced (directly or indirectly) to be executed before itself is not considered a circular reference.

## 5.5. Container element constraints

Constraints can be applied to the elements of generic containers, e.g. [List](#), [Map](#) or [Optional](#). This is done by putting constraint annotations to the type arguments of such containers. Container element constraints can be used within the following declarations:

- fields,
- properties,
- method or constructor parameters or
- method return values.

*Example 44. Container element constraints*

```
private List<@Email String> emails;

public Optional<@Email String> getEmail() {
    [...]
}

public Map<@NotNull String, @ValidAddress Address> getAddressesByType() {
    [...]
}

public List<@NotBlank String> getMatchingRecords(List<@NotNull @Size(max =20) String> searchTerms) {
    [...]
}
```

When a field, property, executable parameter or method return value which is of a container type gets validated, then all values contained in the container will be validated provided that their container element is constrained. any container element constraints of that element will be validated alongside any other constraints hosted by that element. For container element constraints, the same rules for validation groups and group sequences apply as for any other constraint on the same element.

When a container element is constrained, the validation engine invokes a value extractor (see [Value extractor definition](#)) which retrieves the value(s) from the container so they can be validated. This may be a single value - e.g. in the case of [Optional](#) which wraps exactly one value if the [Optional](#) is not empty - or multiple values in the case of collection types.

Container element constraints can be applied to nested container types:

*Example 45. Container element constraints on nested containers*

```
private Map<String, @NotEmpty List<@ValidAddress Address>>
addressesByType;
```

In such case multiple value extractors will be invoked. In the example above,

- the extractor for `Map` values will be invoked to obtain all map values (lists of `Address`)
- for each extracted list of addresses, the `@NotEmpty` constraint will be validated and the extractor for `List` elements will be invoked, providing the `Address` objects from each list in the map
- the `@ValidAddress` constraint will be applied to all elements of all lists stored in the map

Container element constraints are not supported on wildcard type arguments (with or without bounds), i.e. the following usage is unsupported:

*Example 46. Unsupported usage of a container element constraint on a wildcard type argument*

```
private List<@NotEmpty ?> list;
```

### 5.5.1. Implicit unwrapping of containers

Besides specifying container element constraints on type arguments, it is also possible to declare container element constraints on non-generic container types. This is done by means of *implicit unwrapping*, i.e. a constraint doesn't apply to the annotated container itself but to its elements. An example are JavaFX's non-generic property types such as `StringProperty` or `IntegerProperty`:

*Example 47. Implicit unwrapping of container elements*

```
@Size(max=10) private StringProperty name;
@Positive private IntegerProperty positiveInt;
```

Here the `@Size` and `@Positive` constraints don't apply to the annotated `StringProperty` and `IntegerProperty` themselves, but rather to the wrapped string and integer values, respectively.

For this to work, an unambiguously resolvable value extractor must be defined which carries the

`@UnwrapByDefault` annotation (see [@UnwrapByDefault](#)).

If needed, the target (container or container element) of a constraint declared on a container can be explicitly specified via the `Unwrap` and `Skip` payload definitions:

*Example 48. Payload types for unwrapping control*

```
package javax.validation.valueextraction;

/**
 * Set of interfaces used in the {@code payload()} of a constraint to
 * indicate if a value should be unwrapped before
 * validation.
 * <p>
 * This is used to overwrite the default configuration defined on the
{@link ValueExtractor}.
 *
 * @author Guillaume Smet
 * @since 2.0
 */
public interface Unwrapping {

    /**
     * Unwrap the value before validation.
     *
     * @since 2.0
     */
    public interface Unwrap extends Payload {
    }

    /**
     * Skip the unwrapping if it has been enabled on the {@link
ValueExtractor} by the {@link UnwrapByDefault}
     * annotation.
     *
     * @since 2.0
     */
    public interface Skip extends Payload {
    }

}
```

This is useful for applying a constraint given on a non-generic container to

- the container element if there is no value extractor marked with `@UnwrapByDefault` (by using `Unwrap`)
- the container itself in case there is a value extractor marked with `@UnwrapByDefault` (by using `Skip`)

For instance the `@NotNull` constraint is applied to the `StringProperty` container:

```
@NotNull(payload = Unwrapping.Skip.class) StringProperty name;
```

For the sake of readability, when applying constraints to the elements of a generic container, it is strongly recommended to put the constraints to the type argument instead of the container itself in conjunction with [Unwrapping.Unwrap](#). I.e. you should prefer

**NOTE**

```
List<@Email String> emails;
```

over

```
@Email(payload = Unwrapping.Unwrap.class)
List<String> emails;
```

## 5.6. Method and constructor constraints

**NOTE**

In the following, the term "method constraint" refers to constraints declared on methods as well as constructors.

Method constraints are declared by adding constraint annotations directly to methods or constructors and/or their parameters. In the former case, all the parameters of an executable (cross-parameter constraint) or the return value is constrained, in the latter individual parameters are constrained. As with bean constraints, this can be done using either actual Java annotations or using an XML constraint mapping file (see [Method-level overriding](#)). Bean Validation providers are free to provide additional means of defining method constraints such as an API-based approach.

Getters are not considered constrained methods by default (see [Method and constructor validation](#)).

### 5.6.1. Requirements on methods to be validated

Static methods are ignored by validation. Putting constraints on a static method is not portable. No other restrictions exist from the perspective of this specification, however it is possible that technologies integrating with method validation impose further restrictions to methods for which a validation shall be applied. For instance certain integration technologies might require that methods to be validated must have [public](#) visibility and/or must not be [final](#).

### 5.6.2. Declaring parameter constraints

Parameter constraints are declared by putting constraint annotations on method or constructor

parameters.

*Example 49. Declaring parameter constraints*

```
public class OrderService {  
  
    public OrderService(@NotNull CreditCardProcessor creditCardProcessor)  
    {  
        [...]  
    }  
  
    public void placeOrder(  
        @NotNull @Size(min=3, max=20) String customerCode,  
        @NotNull Item item,  
        @Min(1) int quantity) {  
        [...]  
    }  
}
```

Using constraint annotations, several preconditions are defined here. These preconditions which must be satisfied in order to legally invoke the methods of `OrderService` are:

- The `CreditCardProcessor` passed to the constructor must not be null.
- The customer code passed to the `placeOrder()` method must not be null and must be between 3 and 20 characters long.
- The `Item` passed to the `placeOrder()` method must not be null.
- The quantity value passed to the `placeOrder()` method must be 1 at least.

Note that declaring these constraints does not automatically cause their validation when the concerned methods are invoked. It's the responsibility of an integration layer to trigger the validation of the constraints using a method interceptor, dynamic proxy or similar. See section [Triggering method validation](#) for more details.

TIP

In order to use constraint annotations for method or constructor parameters, their element type must be `ElementType.PARAMETER`. In order to use constraint annotations for cross-parameter validation or on the return values of methods or constructors (see the following sections), their element type must be `ElementType.METHOD` respectively `ElementType.CONSTRUCTOR`. All built-in constraints support these element types and it is considered a best practice to do the same for custom constraints.

### 5.6.2.1. Cross-parameter constraints

Cross-parameter constraints allow to express constraints based on the value of several method parameters, similar to class-level constraints which are based on several properties of a given

class. Cross-parameter constraints are declared by putting cross-parameter constraint annotations on methods or constructors as shown in the following example.

*Example 50. Declaring cross-parameter constraints*

```
public class CalendarService {  
  
    @ConsistentDateParameters  
    public void createEvent(  
        String title,  
        @NotNull Date startDate,  
        @NotNull Date endDate) {  
        [...]  
    }  
}
```

The cross-parameter constraint annotation expresses here that the given start date must be before the passed end date in order to legally invoke the `createEvent()` method. The example also shows that it is often useful to combine constraints directly placed on individual parameters (e.g. `@NotNull`) and cross-parameter constraints.

**TIP**

Cross-parameter constraints as well as return value constraints are declared directly on a method or a constructor. To make it obvious for a reader that an annotation refers to the parameters of a method or constructor and not its return value, it is recommended to choose a name which clearly expresses this intention.

It is not legal to declare a cross-parameter constraint on a method or constructor which has no parameters. A `ConstraintDeclarationException` is raised in this case.

Some constraints can target an executable's return value as well as its array of parameters. They are known to be both generic and cross-parameter constraints. When using such a constraint on an executable to target the parameters, one must set `validationAppliesTo` if there is an ambiguity. The set of ambiguities is described in `validationAppliesTo`. Even without ambiguity, it is recommended to explicitly set `validationAppliesTo` to `ConstraintTarget.PARAMETERS` as it improves readability.

### 5.6.2.2. Naming parameters

In case the validation of a parameter constraint fails, the concerned parameter needs to be identified in the resulting `ConstraintViolation` (see section `ConstraintViolation`). Bean Validation defines the `javax.validation.ParameterNameProvider` API to which the retrieval of parameter names is delegated:

```

/**
 * Provides names for method and constructor parameters.
 * <p>
 * Used by the Bean Validation runtime when creating constraint violation
 * objects for violated method constraints.
 * <p>
 * Implementations must be thread-safe.
 *
 * @author Gunnar Morling
 * @since 1.1
 */
public interface ParameterNameProvider {

    /**
     * Returns the names of the parameters of the given constructor.
     *
     * @param constructor the constructor for which the parameter names shall
     * be
     *          retrieved; never {@code null}
     * @return a list containing the names of the parameters of the given
     *         constructor; may be empty but never {@code null}
     */
    List<String> getParameterNames(Constructor<?> constructor);

    /**
     * Returns the names of the parameters of the given method.
     *
     * @param method the method for which the parameter names shall be
     * retrieved;
     *          never {@code null}
     * @return a list containing the names of the parameters of the given
     *         method;
     *          may be empty but never {@code null}
     */
    List<String> getParameterNames(Method method);
}

```

A conforming Bean Validation implementation provides a default `ParameterNameProvider` implementation which returns parameter names as stored in the class file containing the validated executable, if present. A conforming implementation must either use the Java reflection API or ensure behavioral compatibility to using the reflection API in the following way:

- Obtain the method's or constructor's parameters via `java.lang.reflect.Executable.getParameters()`
- Obtain each parameter's name via `java.lang.reflect.Parameter.getName()`

Depending on whether the class file of the validated executable contains parameter name information or not, the actual parameter names as provided in the executable's definition will be returned or synthetic names in the form `argPARAMETER_INDEX`, where `PARAMETER_INDEX` starts at 0 for the first parameter, e.g. `arg0, arg1` etc.

Bean Validation providers and integrators are free to provide additional implementations (e.g. based on annotations specifying parameter names, debug symbols etc.). If a user wishes to use

another parameter name provider than the default implementation, they may specify the provider to use with help of the bootstrap API (see [Bootstrapping](#)) or the XML configuration (see [XML configuration: META-INF/validation.xml](#)).

If an exception occurs during invocation of the `getParameterNames()` methods, this exception is wrapped into a `ValidationException` by the Bean Validation engine.

### 5.6.3. Declaring return value constraints

Return value constraints are declared by putting constraint annotations directly on a method or constructor.

Some constraints can target both the return value and the array of parameters of an executable. They are known to be both generic and cross-parameter constraints. When using such constraint on an executable to target the return value, one must set `validationAppliesTo` in case there is an ambiguity. The set of ambiguities is described in `validationAppliesTo`. Even without ambiguity, it is recommended to explicitly set `validationAppliesTo` to `ConstraintTarget.RETURN_VALUE` as it improves readability.

*Example 51. Declaring return value constraints*

```
public class OrderService {

    private CreditCardProcessor creditCardProcessor;

    @ValidOnlineOrderService
    public OrderService(OnlineCreditCardProcessor creditCardProcessor) {
        this.creditCardProcessor = creditCardProcessor;
    }

    @ValidBatchOrderService
    public OrderService(BatchCreditCardProcessor creditCardProcessor) {
        this.creditCardProcessor = creditCardProcessor;
    }

    @NotNull
    @Size(min=1)
    public Set<CreditCardProcessor> getCreditCardProcessors() { [...] }

    @NotNull
    @Future
    public Date getNextAvailableDeliveryDate() { [...] }
}
```

Here the following postconditions are defined which are guaranteed to the caller of the methods and constructors of the `OrderService` class:

- The newly created `OrderService` object returned by the first constructor satisfies the conditions of the custom `@ValidOnlineOrderService` constraint.

- The newly created `OrderService` object returned by the second constructor satisfies the conditions of the custom `@ValidBatchOrderService` constraint.
- The set of `CreditCardProcessor` objects returned by `getCreditCardProcessors()` will neither be null nor be empty.
- The `Date` object returned by `getNextAvailableDeliveryDate()` will not be null and will be in the future.

Like parameter constraints, these return value constraints are not per-se validated upon method invocation, but instead an integration layer invoking the validation is required.

#### 5.6.4. Marking parameters and return values for cascaded validation

The `@Valid` annotation is used to declare that a cascaded validation of the given method/constructor parameters or return values is performed by the Bean Validation provider. When marked, the parameter or return value is considered a bean object to validate. The same rules as for standard object graph validation (see [Object graph validation](#)) apply, in particular

- null arguments and null return values are ignored
- The validation is recursive; that is, if validated parameter or return value objects have references marked with `@Valid` themselves, these references will also be validated
- Bean Validation providers must guarantee the prevention of infinite loops during cascaded validation

*Example 52. Marking parameters and return values for cascaded validation*

```
public class OrderService {

    @NotNull @Valid
    private CreditCardProcessor creditCardProcessor;

    @Valid
    public OrderService(@NotNull @Valid CreditCardProcessor
creditCardProcessor) {
        this.creditCardProcessor = creditCardProcessor;
    }

    @NotNull @Valid
    public Order getOrderByPk(@NotNull @Valid OrderPK orderPk) { [...] }

    @NotNull @Valid
    public Set<Order> getOrdersByCustomer(@NotNull @Valid CustomerPK
customerPk) { [...] }
}
```

Here the following recursive validations will happen when validating the methods of the `OrderService` class:

- Validation of the constraints on the object passed for the `creditCardProcessor` parameter of the constructor
- Validation of the constraints on the newly created `OrderService` instance returned by the constructor, i.e. the `@NotNull` constraint on the field `creditCardProcessor` and the constraints on the referenced `CreditCardProcessor` instance (as the field is annotated with `@Valid`).
- Validation of the constraints on the object passed for the `orderPk` parameter and the returned `Order` object of the `getOrderByPk()` method
- Validation of the constraints on the object passed for the `customerPk` parameter and the constraints on each object contained within the returned `Set<Order>` of the `getOrdersByCustomer()` method

Again, solely marking parameters and return values for cascaded validation does not trigger the actual validation.

### 5.6.5. Method constraints in inheritance hierarchies

When defining method constraints within inheritance hierarchies (that is, class inheritance by extending base classes and interface inheritance by implementing or extending interfaces) one has to obey the [Liskov substitution](#) principle which mandates that:

- a method's preconditions (as represented by parameter constraints) must not be strengthened in sub types
- a method's postconditions (as represented by return value constraints) must not be weakened in sub types

TIP

Very informally speaking, the Liskov substitution principle says that where a given type T is used, it should be possible to replace T with a sub-type S of T ("Behavioral subtyping"). If S overrides/implements a method from T and S would strengthen the method's preconditions (e.g. by adding parameter constraints) this principle would be violated as client code working correctly against T might fail when working against S. Also if S overrides/implements a method from T and S weakens the method's postconditions this principle would be violated. However S may strengthen the method's postconditions (by adding return value constraints), as client code working against T still will work against S.

Therefore the following rules with respect to the definition of method level constraints in inheritance hierarchies apply:

- In sub types (be it sub classes/interfaces or interface implementations), no parameter constraints may be declared on overridden or implemented methods, nor may parameters

be marked for cascaded validation. This would pose a strengthening of preconditions to be fulfilled by the caller.

- If a sub type overrides/implements a method originally defined in several parallel types of the hierarchy (e.g. two interfaces not extending each other, or a class and an interface not implemented by said class), no parameter constraints may be declared for that method at all nor parameters be marked for cascaded validation. This again is to avoid an unexpected strengthening of preconditions to be fulfilled by the caller.
- In sub types (be it sub classes/interfaces or interface implementations), return value constraints may be declared on overridden or implemented methods and the return value may be marked for cascaded validation. Upon validation, all return value constraints of the method in question are validated, wherever they are declared in the hierarchy. This only poses possibly a strengthening but no weakening of the method's postconditions guaranteed to the caller.
- One must not mark a method return value for cascaded validation more than once in a line of a class hierarchy. In other words, overriding methods on sub types (be it sub classes/interfaces or interface implementations) cannot mark the return value for cascaded validation if the return value has already been marked on the overridden method of the super type or interface.

Out of the box, a conforming Bean Validation provider must throw a [ConstraintDeclarationException](#) when discovering that any of these rules are violated. In addition providers may implement alternative, potentially more liberal, approaches for handling constrained methods in inheritance hierarchies. Possible means for activating such alternative behavior include provider-specific configuration properties or annotations. Note that client code relying on such alternative behavior is not portable between Bean Validation providers.

The above rules do not apply when validating constructor constraints as constructors do not override one another. Parameter and return value constraints can be applied to any constructor in the type hierarchy, but only the constraints defined directly on the validated constructor are evaluated.

#### 5.6.5.1. Examples

This sections provides some examples of illegal constraint definitions which violate the rules stated above in one way or another.

*Example 53. Illegally declared parameter constraints on interface implementation*

```
public interface OrderService {  
  
    void placeOrder(String customerCode, Item item, int quantity);  
}  
  
public class SimpleOrderService implements OrderService {  
  
    @Override  
    public void placeOrder(  
        @NotNull @Size(min=3, max=20) String customerCode,  
        @NotNull Item item,  
        @Min(1) int quantity) {  
        [...]  
    }  
}
```

The constraints in `SimpleOrderService` are illegal, as they strengthen the preconditions of the `placeOrder()` method as constituted by the interface `OrderService`.

*Example 54. Illegally declared parameter constraints on sub class*

```
public class OrderService {  
  
    void placeOrder(String customerCode, Item item, int quantity) { [...] }  
}  
  
public class SimpleOrderService extends OrderService {  
  
    @Override  
    public void placeOrder(  
        @NotNull @Size(min=3, max=20) String customerCode,  
        @NotNull Item item,  
        @Min(1) int quantity) {  
        [...]  
    }  
}
```

The constraints in `SimpleOrderService` are illegal, as they strengthen the preconditions of the `placeOrder()` method as constituted by the super class `OrderService`.

*Example 55. Illegally declared parameter constraints on parallel types*

```
public interface OrderService {  
  
    void placeOrder(String customerCode, Item item, int quantity);  
}  
  
public interface OrderPlacementService {  
  
    public void placeOrder(  
        @NotNull @Size(min=3, max=20) String customerCode,  
        @NotNull Item item,  
        @Min(1) int quantity);  
}  
  
public class SimpleOrderService implements OrderService,  
OrderPlacementService {  
  
    @Override  
    public void placeOrder(String customerCode, Item item, int quantity)  
    {  
        [...]  
    }  
}
```

Here the class `SimpleOrderService` implements the interfaces `OrderService` and `OrderPlacementService`, which themselves are unrelated to each other but both define a method `placeOrder()` with an identical signature. This hierarchy is illegal with respect to the parameter constraints as a client of `SimpleOrderService` would have to fulfill the constraints defined on the interface `OrderPlacementService` even if the client only expects `OrderService`.

*Example 56. Correctly declared return value constraints on sub class*

```
public class OrderService {  
  
    Order placeOrder(String customerCode, Item item, int quantity) {  
        [...]  
    }  
}  
  
public class SimpleOrderService extends OrderService {  
  
    @Override  
    @NotNull  
    @Valid  
    public Order placeOrder(String customerCode, Item item, int quantity)  
    {  
        [...]  
    }  
}
```

The return value constraints in `DefaultOrderService` are legal, as they strengthen the postconditions of the `placeOrder()` method as constituted by the super class `OrderService` but don't weaken them.

## 5.7. Validation routine

For a given group, the validation routine applied on a given bean instance is expected to execute the following constraint validations in no particular order:

- for all *reachable* fields, execute all field level validations (including the ones expressed on superclasses) matching the targeted group unless the given validation constraint has already been processed during this validation routine for a given navigation path (see [Object graph validation](#)) as part of a previous group match.
- for all *reachable* getters, execute all getter level validations (including the ones expressed on interfaces and superclasses) matching the targeted group unless the given validation constraint has already been processed during this validation routine for a given navigation path (see [Object graph validation](#)) as part of a previous group match.
- execute all class level validations (including the ones expressed on interfaces and superclasses) matching the targeted group unless the given validation constraint has already been processed during this validation routine for a given navigation path (see [Object graph validation](#)) as part of a previous group match.
- for all *reachable* and *cascadable* associations, execute all cascading validations (see [Object graph validation](#)) including the ones expressed on interfaces and superclasses (see [Formal group definitions](#)). Note that group conversion can apply (see [Group conversion](#)).

Reachable fields, getters and associations as well as cascadable associations are defined in [Traversable property](#).

Note that this implies that a given validation constraint will not be processed more than once per validation per path. Some implementations might even process a single constraint only once across paths provided that they return the expected set of `ConstraintViolation`.

Unless ordered by group sequences, groups can be validated in no particular order. This implies that the validation routine can be run for several groups in the same pass.

The object validation routine is described as such. For each constraint declaration:

- determine for the constraint declaration, the appropriate `ConstraintValidator` to use (see [ConstraintValidator resolution algorithm](#)).
- execute the `isValid` operation (from the constraint validation implementation) on the appropriate data (see [Constraint validation implementation](#))
- if `isValid()` returns `true`, continue to the next constraint,

- if `isValid()` returns `false`, the Bean Validation provider populates `ConstraintViolation` object(s) according to the rules defined in [Constraint validation implementation](#) and appends these objects to the list of constraint violations.

### 5.7.1. Object graph validation

The `@Valid` annotation on a given association (i.e. object reference or collection, array, `Iterable` of objects), dictates the Bean Validator implementation to apply recursively the Bean Validation routine on (each of) the associated object(s). This mechanism is recursive: an associated object can itself contain cascaded references.

Null references are ignored.

To prevent infinite loops, the Bean Validation implementation must ignore the cascading operation if the associated object instance has already been validated in the current navigation path (starting from the root object). See [Object graph limits](#) for an example. A navigation path is defined as a set of `@Valid` associations starting from the root object instance and reaching the associated instance. A given navigation path cannot contain the same instance multiple times (the complete validated object graph can though). See [Object graph limits](#) for an example.

**NOTE** This object graph navigation can lead to multiple validations of the same constraint and the same object instance but the set of constraint validation is deterministic and the algorithm prevents infinite loops.

### Example 57. Object graph limits

```
#assuming the following object graph

Order -(lines)##; Orderline1
Order -(lines)##; Orderline2
Orderline1 -(order)##; Order
Orderline2 -(order)##; Order
Order -(customer)##; User
Order -(shippingAddress)##; Address1
Order -(billingAddress)##; Address2
Address1 -(inhabitant)##; User
Address2 -(inhabitant)##; User
User -(addresses)##; Address1
User -(addresses)##; Address2

#validation branches are as followed
Order -(lines)##; Orderline1
    - order is ignored: Order is already present in the branch

Order -(lines)##; Orderline2
    - order is ignored: Order is already present in the branch

Order -(customer)##; User -(addresses)##; Address1
    - inhabitant is ignored: User is already present in the branch

Order -(customer)##; User -(addresses)##; Address2
    - inhabitant is ignored: User is already present in the branch

Order -(shippingAddress)##; Address1 -(inhabitant)##; User
    - addresses to Address1 is ignored: Address1 is already present in the
branch

Order -(shippingAddress)##; Address1 -(inhabitant)##; User
    - addresses to Address2 is ignored: Address2 is already present in the
branch

Order -(billingAddress)##; Address2 -(inhabitant)##; User
    - addresses to Address2 is ignored: Address2 is already present in the
branch

Order -(billingAddress)##; Address2 -(inhabitant)##; User
    - inhabitant is ignored: User is already present in the branch
```

The **ConstraintViolation** objects are built when a failing constraint on an associated object is found. They reflect the path to reach the object from the root validated object (See [ConstraintViolation](#)).

**@Valid** is an orthogonal concept to the notion of group. If two groups are in sequence, the first group must pass for all associated objects before the second group is evaluated. Note however that the **Default** group sequence overriding is local to the class it is defined on and is not propagated to the associated objects. The following example illustrates this:

*Example 58. Class Driver with redefined default group*

```
@GroupSequence({ Minimal.class, Driver.class })
public class Driver {
    @Min(value = 18, groups = Minimal.class)
    int age;

    @AssertTrue
    Boolean passedDrivingTest;

    @Valid
    Car car;

    // setter/getters
}
```

*Example 59. Class Car with redefined default group*

```
@GroupSequence({ Car.class, Later.class })
public class Car {
    @NotNull
    String type;

    @AssertTrue(groups = Later.class)
    Boolean roadWorthy;

    // setter/getters
}
```

*Example 60. Defining a group sequence*

```
@GroupSequence({ Minimal.class, Later.class })
public interface SequencedGroups { }
```

*Example 61. Group sequence overriding is not propagated to associated objects*

```
Validator validator = Validation.buildDefaultValidatorFactory()
    .getValidator();

Driver driver = new Driver();
driver.setAge(16);
Car porsche = new Car();
driver.setCar(porsche);

Set<ConstraintViolation<Driver>> violations = validator.validate( driver );
assert violations.size() == 2;

violations = validator.validate( driver, SequencedGroups.class );
assert violations.size() == 1;
```

The default group sequence is redefined for the `Driver` as well as `Car`. When the default group is requested via `validator.validate( driver )` the group `Minimal` gets validated in class `Driver`. The constraint will fail since the driver's age in the example is only 16. The constraint on `passedDrivingTest` will not be evaluated due to the redefined default sequence of `Driver`. However, there is one more constraint violation, namely the `@NotNull` on `Car.type`. The reason for this is that the group `Default` gets propagated to `Car` (not `Minimal`). Class `Driver` defines its own group sequence which means that `only @NotNull` on `type` gets evaluated.

In the second call to `validate` the group `SequencedGroups` is requested which defines a sequence of `Minimal` followed by `Later`. In this case there is only one constraint violation. Again `@Min` on `age` fails, but in this case the group `Minimal` gets propagated to `Car` which does not have any constraints defined against this group. Constraints belonging to the group `Later` won't get validated until all constraints belonging to `Minimal` pass.

### 5.7.2. Method and constructor validation

For a given group, the validation routine applied to validate parameters of a method or constructor is expected to execute the following constraint validations in no particular order:

- execute all parameter validations (in case of overriding method validation, including the ones expressed on overridden methods of the interfaces and superclasses) matching the targeted group unless the given validation constraint has already been processed during this validation routine for a given navigation path (see [Object graph validation](#)) as part of a previous group match.
- execute all cross parameter validations (in case of overriding method validation, including the ones expressed on overridden methods of the interfaces and superclasses) matching the targeted group unless the given validation constraint has already been processed

during this validation routine for a given navigation path (see [Object graph validation](#)) as part of a previous group match.

- for all parameters marked for cascaded validation, execute all cascading validations (see [Object graph validation](#)), in case of overriding method validation including the ones expressed on overridden methods of the interfaces and superclasses (see [Formal group definitions](#)). Note that group conversion can apply (see [Group conversion](#)).

For a given group, the validation routine applied to validate the return value of a method or constructor is expected to execute the following constraint validations in no particular order:

- execute all return value validations (including the ones expressed on interfaces and superclasses) matching the targeted group unless the given validation constraint has already been processed during this validation routine for a given navigation path (see [Object graph validation](#)) as part of a previous group match.
- if the return value is marked for cascaded validation, execute all cascading validations (see [Object graph validation](#)) including the ones expressed on interfaces and superclasses (see [Formal group definitions](#)). Note that group conversion can apply (see [Group conversion](#)).

Note that this implies that a given validation constraint will not be processed more than once per validation per path. Some implementations might even process a single constraint only once across paths provided that they return the expected set of [ConstraintViolation](#).

Unless ordered by group sequences, groups can be validated in no particular order. This implies that the validation routine can be run for several groups in the same pass.

The object validation routine is as defined in described in [Validation routine](#).

### 5.7.3. Traversable property

In some cases, the state of some properties should not be accessed. For example, if a property loaded by a Java Persistence provider is a lazy property or a lazy association, accessing its state would trigger a load from the database. An undesired behavior.

Bean Validation offers a way to control which property can and cannot be accessed via the [TraversableResolver.isReachable\(\)](#) contract.

Likewise, it is sometimes undesirable to cascade validation despite the use of [@Valid](#). Java Persistence 2 for example does not cascade to associated entities during flush. You can control this behavior by implementing [TraversableResolver.isCascadable\(\)](#).

```
/**  
 * Contract determining if a property can be accessed by the Bean Validation  
 * provider.  
 * This contract is called for each property that is being either validated or  
 * cascaded.
```

```

* <p>
* A traversable resolver implementation must be thread-safe.
*
* @author Emmanuel Bernard
*/
public interface TraversableResolver {
    /**
     * Determines if the Bean Validation provider is allowed to reach the
     property state.
     *
     * @param traversableObject object hosting {@code traversableProperty}
     *                         or {@code null} if {@code validateValue} is called
     * @param traversableProperty the traversable property
     * @param rootBeanType type of the root object passed to the Validator
     *                     or hosting the method or constructor validated
     * @param pathToTraversableObject path from the root object to
     *                                {@code traversableObject}
     *                                (using the path specification defined by Bean Validator)
     * @param elementType either {@code FIELD} or {@code METHOD}
     * @return {@code true} if the Bean Validation provider is allowed to
     *         reach the property state, {@code false} otherwise
     */
    boolean isReachable(Object traversableObject,
                        Node traversableProperty,
                        Class<?> rootBeanType,
                        Path pathToTraversableObject,
                        ElementType elementType);

    /**
     * Determines if the Bean Validation provider is allowed to cascade
     validation on
     * the bean instance returned by the property value
     * marked as {@code @Valid}.
     * <p>
     * Note that this method is called only if
     * {@link #isReachable(Object, javax.validation.Path.Node, Class, Path,
     java.lang.annotation.ElementType)}
     * returns {@code true} for the same set of arguments and if the property
     * is marked as {@link Valid}.
     *
     * @param traversableObject object hosting {@code traversableProperty}
     *                         or {@code null} if {@code validateValue} is called
     * @param traversableProperty the traversable property
     * @param rootBeanType type of the root object passed to the Validator
     *                     or hosting the method or constructor validated
     * @param pathToTraversableObject path from the root object to
     *                                {@code traversableObject}
     *                                (using the path specification defined by Bean Validator)
     * @param elementType either {@code FIELD} or {@code METHOD}
     * @return {@code true} if the Bean Validation provider is allowed to
     *         cascade validation, {@code false} otherwise
     */
    boolean isCascadable(Object traversableObject,
                        Node traversableProperty,
                        Class<?> rootBeanType,
                        Path pathToTraversableObject,
                        ElementType elementType);
}

```

`isReachable()` is called for every property about to be accessed either for validation or for cascading. A property is *reachable* if this method returns `true`.

`isCascadable()` is called for every property about to be cascaded (i.e. marked as `@Valid`). A property is *cascadable* if it is reachable and if the `isCascadable` method returns `true`.

**NOTE** `isCascadable()` for a given property is only called if `isReachable()` returns `true`. In other words, `isReachable()` is always called before `isCascadable()` for a given property.

`traversableObject` is the object instance being evaluated. `null` if the check is triggered as part of a `validateValue()` call.

`traversableProperty` is the `Node` representing the property hosted by the `traversableObject` being considered for traversal. The name of a property is defined in [Field and property validation](#).

`rootBeanType` is the class of the root being validated, i.e. either the type of the object passed to the `validate` method or the type declaring the validated method/constructor in case of method validation.

`pathToTraversableObject` is the `Path` from the `rootBeanType` down to the `traversableObject`. If the root object is `traversableObject`, `pathToTraversableObject` is composed of a single `Node` whose name is `null`. The path is described following the conventions described in [ConstraintViolation \(getPath\)](#).

`elementType` is the `java.lang.annotation.ElementType` the annotation is placed on. It can be either `FIELD` or `METHOD`. Any other value is not expected.

The Bean Validation provider must not access the state of a property, nor validate its constraints if the property is not traversable. A property is traversable if `TraversableResolver` returns `true` for this property.

If an exception occurs when the `TraversableResolver` is called, the exception is wrapped into a `ValidationException`.

The following elements are not passed through the traversable resolver filter:

- the bean instance validated
- the method and constructor parameter values being validated
- the method and constructor return value being validated

But the properties of these elements (if validated) are. In this case the complete path is provided via `pathToTraversableObject`.

The traversable resolver used by default by a Bean Validation provider behaves as followed:

- if Java Persistence is available in the runtime environment, a property is considered reachable if Java Persistence considers the property as loaded. A typical implementation will use `Persistence.getPersistenceUtil().isLoaded(Object, String)` to implement such contract.
- if Java Persistence is not available in the runtime environment, all properties are considered reachable.
- all properties are considered cascadable.

An example implementation of such a resolver is shown in [Java Persistence aware TraversableResolver](#).

*Example 62. Java Persistence aware TraversableResolver*

```
public class JPATraversableResolver implements TraversableResolver {  
  
    public boolean isReachable(Object traversableObject,  
                             Path.Node traversableProperty,  
                             Class<?> rootBeanType,  
                             Path pathToTraversableObject,  
                             ElementType elementType) {  
        return traversableObject == null ||  
               Persistence.getPersistenceUtil().isLoaded(  
                   traversableObject,  
                   traversableProperty.getName());  
    }  
  
    public boolean isCascadable(Object traversableObject,  
                               Path.Node traversableProperty,  
                               Class<?> rootBeanType,  
                               Path pathToTraversableObject,  
                               ElementType elementType) {  
        return true;  
    }  
}
```

See [Bootstrapping](#) to learn how to pass a custom `TraversableResolver`.

#### 5.7.3.1. Examples

The following example assumes the object graph defined in [Definitions used in the example](#) and assumes the validation operation is applied on an address object.

*Example 63. Definitions used in the example*

```
public class Country {  
    @NotNull private String name;
```

```

@Size(max=2) private String ISO2Code;
@Size(max=3) private String ISO3Code;

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getISO2Code() {
        return ISO2Code;
    }

    public void setISO2Code(String ISO2Code) {
        this.ISO2Code = ISO2Code;
    }

    public String getISO3Code() {
        return ISO3Code;
    }

    public void setISO3Code(String ISO3Code) {
        this.ISO3Code = ISO3Code;
    }
}

public class Address {
    @NotNull @Size(max=30)
    private String addressline1;
    @Size(max=30)
    private String addressline2;
    @Size(max=11)
    private String zipCode;
    @Valid
    private Country country;

    private String city;

    public String getAddressline1() {
        return addressline1;
    }

    public void setAddressline1(String addressline1) {
        this.addressline1 = addressline1;
    }

    public String getAddressline2() {
        return addressline2;
    }

    public void setAddressline2(String addressline2) {
        this.addressline2 = addressline2;
    }

    public String getZipCode() {
        return zipCode;
    }

    public void setZipCode(String zipCode) {

```

```

        this.zipCode = zipCode;
    }

    @Size(max=30) @NotNull
    public String getCity() {
        return city;
    }

    public void setCity(String city) {
        this.city = city;
    }

    public Country getCountry() {
        return country;
    }

    public void setCountry(Country country) {
        this.country = country;
    }
}

```

When the Bean Validation provider is about to check constraints of `ISO3Code`, it calls the `TraversableResolver.isReachable()` method to ensure that the `ISO3Code` property is reachable with the following parameter values:

- `traversableObject`: `country`. The instance returned by `address.getCountry()`.
- `traversableProperty`: a `PropertyNode` whose name is "ISO3Code". Represents the property of `traversableObject` being verified.
- `rootBeanType`: `Address.class`. The type of the root object being validated.
- `pathToTraversableObject`: a `Path` containing a single `PropertyNode` whose name is "country". The path from `address` to the `country` instance.
- `elementType`: `ElementType.FIELD`. The `ISO3Code` property is annotated on its field.

When the Bean Validation provider is about to cascade validation on `country` (`Address` object), it calls the `TraversableResolver.isReachable()` method to ensure that the `country` property is reachable and if this method returns `true`, it calls `TraversableResolver.isCascadable()` with the following parameter values:

- `traversableObject`: `address`. The address instance.
- `traversableProperty`: a `PropertyNode` whose name is "country". Represents the property of `traversableObject` being verified.
- `rootBeanType`: `Address.class`. The type of the root object being validated.
- `pathToTraversableObject`: a `Path` containing a single `BeanNode` whose name is `null`.
- `elementType`: `ElementType.FIELD`. The `country` property is annotated on its field.

The following example shows invocations of the `TraversableResolver` as to be performed by

the Bean Validation provider during method validation. The example is based on the object graph defined in [Definitions used in the example](#) and the `AddressService` class shown in [Exemplary class AddressService](#). It assumes that a call of `persistAddress()` is subject to method parameter validation.

*Example 64. Exemplary class AddressService*

```
public class AddressService {  
    public void persistAddress(@NotNull @Valid Address address) {  
        [...]  
    }  
}
```

When the Bean Validation provider is about to validate the `@NotNull` constraint on the `address` parameter, no call to `isReachable()` is expected, since parameters are assumed to always be reachable. Similarly, no call to `isCascadable()` is expected when performing cascaded validation of the `address` parameter, since parameters are assumed to always be cascadable.

When the Bean Validation provider is about to validate constraints on the field `addressline1` of the passed `Address` object, it calls the `isReachable()` method to ensure that the property is reachable with the following parameter values:

- `traversableObject`: `address`. The instance passed to `persistAddress()`.
- `traversableProperty`: a `PropertyNode` whose name is "addressline1". Represents the property of `traversableObject` being verified.
- `rootBeanType`: `AddressService.class`. The type of the root object being validated.
- `pathToTraversableObject`: a `Path` comprising a `MethodNode` (named "persistService") and a `ParameterNode` (with parameter index 0). The path from `AddressService` to the `Address` instance.
- `elementType`: `ElementType.FIELD`. The `addressline1` property is annotated on its field.

When the Bean Validation provider is about to perform a cascaded validation of the `country` property of the passed `Address` object, it calls the `isReachable()` method to ensure that the property is reachable. If this method returns `true`, it calls `TraversableResolver.isCascadable()` with the following parameter values:

- `traversableObject`: `address`. The instance passed to `persistAddress()`.
- `traversableProperty`: a `PropertyNode` whose name is "country". Represents the property of `traversableObject` being verified.

- `rootBeanType: AddressService.class`. The type of the root object being validated.
- `pathToTraversableObject`: a `Path` comprising a `MethodNode` (named "persistService") and a `ParameterNode` (with parameter index 0). The path from `AddressService` to the `Address` instance.
- `elementType: ElementType.FIELD`. The `country` property is annotated on its field.

#### 5.7.4. ConstraintValidator resolution algorithm

A constraint is associated to one or more `ConstraintValidator` implementations. Each `ConstraintValidator<A, T>` accepts the type `T`. The `ConstraintValidator` executed depends on the type hosting the constraint. For a given constraint evaluation, a single `ConstraintValidator` is considered.

The list of `ConstraintValidators` can contain at most one which targets cross-parameter. If the constraint targets the parameters of an executable either implicitly or by the use of `validationAppliesTo` in the constraint - see `validationAppliesTo`, then the cross-parameter `ConstraintValidator` is used. If none is present, a `ConstraintDefinitionException` is raised. If more than one cross-parameter `ConstraintValidator` is present, a `ConstraintDefinitionException` is raised.

If the constraint is a generic constraint, the following rules apply. If the constraint declaration is hosted on a class or an interface, the targeted type is the class or the interface. If the constraint is hosted on a class attribute, the type of the attribute is the targeted type. If the constraint is hosted on a getter, the return type of the getter is the targeted type. In other words, the resolution algorithm considers the type as defined in the method signature and not the runtime type of the value.

The rules written below describe formally the following statement: the `ConstraintValidator` chosen to validate the generic constraint on a declared type `T` is the one where the `ConstraintValidator` targets the annotated element, where the type supported by the `ConstraintValidator` is a supertype of `T` and where there is no other `ConstraintValidator` whose supported type is a supertype of `T` and not a supertype of the chosen `ConstraintValidator` supported type.

When validating a generic constraint `A` placed on a target declaring the type `T`, the following resolution rules apply:

- Only `ConstraintValidator` implementations targeting annotated elements are considered.
- Primitive types are considered equivalent to their respective primitive wrapper class.
- A `ConstraintValidator<A, U>` is said to be *compliant* with `T` if `T` is a subtype of `U` (according to the [Java Language Specification 3rd edition chapter 4.10 Subtyping](#)). Note that `T` is a subtype of `U` if `T = U`.

- If no `ConstraintValidator` compliant with `T` is found among the `ConstraintValidators` listed by the constraint `A`, an `UnexpectedTypeException` is raised.
- A `ConstraintValidator<A, U>` compliant with `T` is considered *strictly more specific* than a `ConstraintValidator<A, V>` compliant with `T` if `U` is a strict subtype of `V`. `U` is a strict subtype of `V` if `U` is a subtype of `V` and `U != V` (according to the [Java Language Specification 3rd edition chapter 4.10 Subtyping](#)).
- A `ConstraintValidator<A, U>` compliant with `T` is considered maximally specific if no other `ConstraintValidator<A, V>` compliant with `T` is strictly more specific than `ConstraintValidator<A, U>`.
- If more than one maximally specific `ConstraintValidator` is found, an `UnexpectedTypeException` is raised.

**NOTE** While the Java compiler itself cannot determine if a constraint declaration will lead to a `UnexpectedTypeException`, rules can be statically checked. A tool such as an IDE or a Java 6 annotation processor can apply these rules and prevent compilation in case of ambiguity. The specification encourages Bean Validation providers to provide such a tool to their users.

Let's see a couple of declarations and their respective `ConstraintValidator` resolution. Assuming the definitions shown in `ConstraintValidator` and type resolution:

*Example 65. ConstraintValidator and type resolution*

```
[...]
@Constraint(validatedBy={
    SizeValidatorForCollection.class,
    SizeValidatorForSet.class,
    SizeValidatorForSerializable.class })
public @interface Size { [...] }

public class SizeValidatorForCollection implements ConstraintValidator
<Size, Collection> {
    [...]
}
public class SizeValidatorForSet implements ConstraintValidator<Size,
Set> {
    [...]
}
public class SizeValidatorForSerializable implements ConstraintValidator
<Size, Serializable> {
    [...]
}

public interface SerializableCollection extends Serializable, Collection
{
}
```

The resolutions shown in [Resolution of ConstraintValidator for various constraints declarations](#) occur.

*Table 1. Resolution of ConstraintValidator for various constraints declarations*

Declaration	Resolution
<code>@Size Collection getAddresses() { [...] }</code>	<code>SizeValidatorForCollection: direct match</code>
<code>@Size Collection&lt;?&gt; getAddresses() { [...] }</code>	<code>SizeValidatorForCollection: Collection is a direct supertype of Collection&lt;?&gt;</code>
<code>@Size Collection&lt;Address&gt; getAddresses() { [...] }</code>	<code>SizeValidatorForCollection: Collection is a direct supertype of Collection&lt;Address&gt;</code>
<code>@Size Set&lt;Address&gt; getAddresses() { [...] }</code>	<code>SizeValidatorForSet: direct supertype of Set&lt;Address&gt;</code>
<code>@Size SortedSet&lt;Address&gt; getAddresses() { [...] }</code>	<code>SizeValidatorForSet: Set is the closest supertype of SortedSet&lt;Address&gt;</code>
<code>@Size SerializableCollection getAddresses() { [...] }</code>	<code>UnexpectedTypeException: SerializableCollection is a subtype of both Collection and Serializable and neither Collection nor Serializable are subtypes of each other.</code>
<code>@Size String getName() { [...] }</code>	<code>UnexpectedTypeException: none of the ConstraintValidator types are supertypes of String.</code>

## 5.7.5. ValueExtractor resolution

When detecting a container element constraint or a container element marked with `@Valid`, the value extractor for obtaining the container's elements must be determined.

A value extractor handles one container type and - in the case of a generic container type - one type parameter of that container type. The applicable extractor is identified based on the container type and - in the case of a generic container type - the type argument hosting the container element constraint or `@Valid`.

Exactly one value extractor must be identified when processing a container element constraint or container element marked with `@Valid`.

### 5.7.5.1. Registering ValueExtractor implementations

Value extractors can be registered with the validation engine in the following ways (in increasing order of priority):

- Provided by the validation engine itself (see [Built-in value extractors](#))
- Via the Java service loader mechanism; for this the file `META-INF/services/javax.validation.valueextraction.ValueExtractor` must be provided, with the fully-qualified name(s) of one or more extractor implementations as its contents
- By specifying the fully-qualified class name of one or several extractors in `META-INF/validation.xml` (see [XML configuration: META-INF/validation.xml](#))
- By invoking the method `Configuration#addValueExtractor(ValueExtractor<?>)` (to apply it at the validation factory level)
- By invoking the method `ValidatorContext#addValueExtractor(ValueExtractor<?>)` (to apply it for a single `Validator`)

A value extractor for a given type and type parameter specified at a higher priority overrides any other extractors for the same type and type parameter given at lower priorities. If e.g. a value extractor defined as class `MyListValueExtractor` implements `ValueExtractor<List<@ExtractedValue ?>> { ... }` is given via `ValidatorContext#addValueExtractor(ValueExtractor<?>)`, it will take precedence over any other value extractor implementing `List<@ExtractedValue ?>` given via `Configuration#addValueExtractor(ValueExtractor<?>)`, `META-INF/validation.xml` or the service loader mechanism as well as the built-in extractor for `List` values.

#### 5.7.5.2. ValueExtractor resolution algorithm for container element constraints

For a container with the declared type `C` whose element type is hosting a constraint, the following resolution rules apply for identifying the value extractor:

- A `ValueExtractor<T>` is said to be *type-compliant* with `C`, if `C` is a subtype of `T` (according to the [Java Language Specification 3rd edition chapter 4.10 Subtyping](#)). Note that `C` is a subtype of `T` if `C = T`.
- A `ValueExtractor` implementation is said to be *container-element-compliant* with `C`, if `C` is a generic container type and the value extractor implementation handles a type parameter that maps to the constrained type argument.
- If no `ValueExtractor` type-compliant and container-element-compliant with `C` is found among the available value extractors, a `ConstraintDeclarationException` is raised.
- A `ValueExtractor<U>` type-compliant with `C` is considered *strictly more specific* than a `ValueExtractor<V>` compliant with `C` if `U` is a strict subtype of `V`. `U` is a strict subtype of `V` if `U` is a subtype of `V` and `U != V`.
- A `ValueExtractor<U>` type-compliant with `C` is considered maximally specific if no other `ValueExtractor<V>` type-compliant with `C` is strictly more specific than `ValueExtractor<U>`.

- If more than one maximally specific and container-element-compliant `ValueExtractor` is found, a `ConstraintDeclarationException` is raised.

*Implementation note*

**NOTE** Extractor retrieval for container element constraints is based on the declared type of constrained elements, hence it is recommended that implementations perform the resolution once and then cache the value extractor for a given constraint.

#### 5.7.5.3. ValueExtractor resolution algorithm for cascaded validation

For a container with the declared type `C` and the runtime type `C'` whose element type is marked for cascaded validation, the following resolution rules apply for identifying the value extractor:

- A `ValueExtractor<T>` is said to be *type-compliant* with `C'`, if `C'` is a subtype of `T`. Note that `C'` is a subtype of `T` if `C' = T`.
- A `ValueExtractor` implementation is said to be *container-element-compliant* with `C`, if it handles a type parameter that maps to the type argument marked with `@Valid`.
- If no `ValueExtractor` type-compliant with `C'` and container-element-compliant with `C` is found among the available value extractors, a `ConstraintDeclarationException` is raised.
- A `ValueExtractor<U>` type-compliant with `C'` is considered *strictly more specific* than a `ValueExtractor<V>` compliant with `C'` if `U` is a strict subtype of `V`. `U` is a strict subtype of `V` if `U` is a subtype of `V` and `U != V`.
- A `ValueExtractor<U>` type-compliant with `C'` is considered maximally specific if no other `ValueExtractor<V>` type-compliant with `C'` is strictly more specific than `ValueExtractor<U>`.
- If more than one maximally specific and container-element-compliant `ValueExtractor` is found, a `ConstraintDeclarationException` is raised.

*Implementation note*

**NOTE** Extractor retrieval for container element constraints is based on the runtime type of the elements marked with `@Valid` (this is to be consistent with the semantics of property paths for cascaded validation), hence it is not possible to perform the extractor resolution only once per usage of `@Valid` and cache the result.

#### 5.7.5.4. ValueExtractor resolution algorithm for constraints on non-generic containers

When detecting a constraint given as a *declaration annotation* and not as a *type annotation* (i.e. it is given on field, parameter etc. and not given on an a type argument of a generic type), the

applicable value extractor, if any, is determined as follows:

- If the constraint carries the `Unwrapping.Skip` payload, no value extractor is applied.
- If the constraint carries the `Unwrapping.Unwrap` payload and there is exactly one maximally-specific type-compliant value extractor, this extractor is applied; if there is no type-compliant extractor or multiple maximally-specific type-compliant extractors exist, a `ConstraintDeclarationException` is raised.
- If the constraint carries neither the `Unwrapping.Unwrap` nor the `Unwrapping.Skip` payload:
  - If there is exactly one maximally-specific type-compliant value extractor marked with `@UnwrapByDefault`, this extractor is applied;
  - Otherwise, no value extractor is applied.

#### 5.7.5.5. Examples

Let's consider a couple of value extractor definitions and their respective `ValueExtractor` resolution against container element constraint declarations:

*Example 66. ValueExtractor resolution*

```
public interface ConcurrentList<T> {
    [...]
}

public class MyList<T> implements List<T>, ConcurrentList<T> {
    [...]
}

public interface Table<R, C, V> {
    [...]
}

interface ConfusingMap<K, V> extends Map<V, K> {
    [...]
}

interface SingleTypeMap<T> extends Map<T, T> {
    [...]
}

interface StringMap extends Map<String, String> {
    [...]
}

interface Property<T> {
    [...]
}

class StringProperty implements Property<String> {
    [...]
}
```

```

public class IterableValueExtractor implements ValueExtractor<Iterable<@ExtractedValue ?>> {
    [...]
}

public class ListValueExtractor implements ValueExtractor<List<@ExtractedValue ?>> {
    [...]
}

public class ConcurrentListValueExtractor implements ValueExtractor<ValueExtractor<ConcurrentList<@ExtractedValue ?>>> {
    [...]
}

public class MapKeyExtractor implements ValueExtractor<Map<@ExtractedValue ?, ?>> {
    [...]
}

public class MapValueExtractor implements ValueExtractor<Map<?, @ExtractedValue ?>> {
    [...]
}

public class TableValueExtractor implements ValueExtractor<Table<?, ?, @ExtractedValue ?>> {
    [...]
}

@UnwrapByDefault
public class PropertyValueExtractor implements ValueExtractor<Property<@ExtractedValue ?>> {
    [...]
}

```

The following value extractor resolutions occur:

*Table 2. Resolution of ValueExtractor for various container element constraints*

Declaration	Resolution
List<@Email String> emails	ListValueExtractor; strictly more specific than IterableValueExtractor
Iterable<@Valid Address> addresses = new ArrayList<>()	ListValueExtractor (the runtime type <code>ArrayList</code> is used for resolving value extractors for cascaded validation)
Map<@Email String, String> emails	MapKeyExtractor; equally specific as MapValueExtractor, but the latter isn't container-element-compliant
ConfusingMap<@Email String, String> map	MapValueExtractor; the constrained type argument maps to the type parameter <code>V</code> of Map

Declaration	Resolution
<code>@Email StringProperty</code>	<code>PropertyValueExtractor</code> ; the extractor is marked with <code>@UnwrapByDefault</code> , i.e. implicit unwrapping is performed
<code>Optional&lt;@Email String&gt; getEmail() {...}</code>	<code>ConstraintDeclarationException</code> ; no compliant extractor exists
<code>Table&lt;@Min(1) String, String, String&gt; table</code>	<code>ConstraintDeclarationException</code> ; <code>TableValueExtractor</code> is type-compliant but not container-element-compliant
<code>MyList&lt;@Email String&gt; emails</code>	<code>ConstraintDeclarationException</code> ; <code>ListValueExtractor</code> and <code>ConcurrentListValueExtractor</code> are equally specific
<code>SingleTypeMap&lt;@NotEmpty String&gt; map</code>	<code>ConstraintDeclarationException</code> ; <code>MapKeyExtractor</code> and <code>MapValueExtractor</code> are equally specific and both container-element-compliant
<code>@NotEmpty(payload=Unwrapping.Unwrap.class) StringMap</code>	<code>ConstraintDeclarationException</code> ; more than one maximally-specific extractor is found ( <code>MapKeyExtractor</code> and <code>MapValueExtractor</code> )

## 5.8. Examples

The first example demonstrates how beans, fields and getters are annotated to express some constraints.

*Example 67. Place constraint declarations on the element to validate*

```
@ZipCodeCityCoherenceChecker
public class Address {
    @NotNull @Size(max=30)
    private String addressline1;

    @Size(max=30)
    private String addressline2;

    private String zipCode;

    private String city;

    public String getAddressline1() {
        return addressline1;
    }

    public void setAddressline1(String addressline1) {
        this.addressline1 = addressline1;
    }

    public String getAddressline2() {
        return addressline2;
    }

    public void setAddressline2(String addressline2) {
        this.addressline2 = addressline2;
    }

    public String getZipCode() {
        return zipCode;
    }

    public void setZipCode(String zipCode) {
        this.zipCode = zipCode;
    }

    @Size(max=30) @NotNull
    public String getCity() {
        return city;
    }

    public void setCity(String city) {
        this.city = city;
    }
}
```

During the validation routine execution on an **Address** object,

- **addressline1** field value is passed to the **@NotNull** as well as **@Size** constraint validation implementations.
- **addressline2** field value is passed to the **@Size** constraint validation implementation.
- **getCity** value is passed to the **@Size** and **@NotNull** constraint validation

implementations.

- `@ZipCodeCoherenceChecker` is a constraint whose validation implementation's `isValid` method receives the `Address` object.

The second example demonstrates object graph validation.

*Example 68. Define object graph validation*

```
public class Country {  
    @NotNull  
    private String name;  
    @Size(max=2) private String ISO2Code;  
    @Size(max=3) private String ISO3Code;  
  
    public String getName() {  
        return name;  
    }  
  
    public void setName(String name) {  
        this.name = name;  
    }  
  
    public String getISO2Code() {  
        return ISO2Code;  
    }  
  
    public void setISO2Code(String ISO2Code) {  
        this.ISO2Code = ISO2Code;  
    }  
  
    public String getISO3Code() {  
        return ISO3Code;  
    }  
  
    public void setISO3Code(String ISO3Code) {  
        this.ISO3Code = ISO3Code;  
    }  
}  
  
public class Address {  
    @NotNull @Size(max=30)  
    private String addressline1;  
    @Size(max=30)  
    private String addressline2;  
    @Size(max=11)  
    private String zipCode;  
    @NotNull @Valid  
    private Country country;  
  
    private String city;  
  
    public String getAddressline1() {  
        return addressline1;  
    }  
  
    public void setAddressline1(String addressline1) {  
        this.addressline1 = addressline1;  
    }  
}
```

```

}

public String getAddressline2() {
    return addressline2;
}

public void setAddressline2(String addressline2) {
    this.addressline2 = addressline2;
}

public String getZipCode() {
    return zipCode;
}

public void setZipCode(String zipCode) {
    this.zipCode = zipCode;
}

@Size(max=30) @NotNull
public String getCity() {
    return city;
}

public void setCity(String city) {
    this.city = city;
}

public Country getCountry() {
    return country;
}

public void setCountry(Country country) {
    this.country = country;
}
}

```

During the validation routine execution on an `Address` object, constraints on `addressLine1`, `addressLine2`, `zipCode`, `getCity` and `country` are processed as well as the validation of the `Country` object itself, more specifically `country.name` is checked for `@NotNull`, `ISO2Code` and `ISO3Code` are checked for `@Size`.

Assuming that `@NotEmpty` is defined as such

```

@Documented
@NotNull
@Size(min = 1)
@ReportAsSingleViolation
@Constraint(validatedBy = NotEmpty.NotEmptyValidator.class)
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
@Retention(RUNTIME)
public @interface NotEmpty {

    String message() default "{com.acme.constraint.NotEmpty.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {
        NotEmpty[] value();
    }

    class NotEmptyValidator implements ConstraintValidator<NotEmpty, String> {

        @Override
        public void initialize(NotEmpty constraintAnnotation) {}

        @Override
        public boolean isValid(String value, ConstraintValidatorContext context) {
            return true;
        }
    }
}

```

The third example demonstrates superclass, inheritance and composite constraints.

*Example 69. Use inheritance, constraints on superclasses and composite constraints*

```

public interface Person {
    @NotEmpty
    String getFirstName();

    String getMiddleName();

    @NotEmpty
    String getLastNames();
}

public class Customer implements Person {
    private String firstName;
    private String middleName;
    private String lastName;
    @NotNull
    private String customerId;
}

```

```

@Password(robustness=5)
private String password;

public String getFirstName() {
    return firstName;
}

public void setFirstName(String firstName) {
    this.firstName = firstName;
}

public String getMiddleName() {
    return middleName;
}

public void setMiddleName(String middleName) {
    this.middleName = middleName;
}

public String getLastName() {
    return lastName;
}

public void setLastName(String lastName) {
    this.lastName = lastName;
}

public String getCustomerId() {
    return customerId;
}

public void setCustomerId(String customerId) {
    this.customerId = customerId;
}

public String getPassword() {
    return password;
}

public void setPassword(String password) {
    this.password = password;
}
}

public class PreferredGuest extends Customer {
    @CreditCard
    private String guestCreditCardNumber;

    public String getGuestCreditCardNumber() {
        return guestCreditCardNumber;
    }

    public void setGuestCreditCardNumber(String guestCreditCardNumber) {
        this.guestCreditCardNumber = guestCreditCardNumber;
    }
}

public class CommonGuest extends Customer {}

```

When validating a `PreferredGuest` the following constraints are processed:

- `@NotEmpty`, `@NotNull` and `@Size(min=1)` on `firstName`
- `@NotEmpty`, `@NotNull` and `@Size(min=1)` on `lastName`
- `@NotNull` on `customerId`, `@Password` on `password`
- `@CreditCard` on `guestCreditCardNumber`

When validating `CommonGuest`, the following constraints are processed:

- `@NotEmpty`, `@NotNull` and `@Size(min=1)` on `firstName`
- `@NotEmpty`, `@NotNull` and `@Size(min=1)` on `lastName`
- `@NotNull` on `customerId`, `@Password` on `password`

The fourth example demonstrates the influence of group sequence.

*Example 70. Use groups and group sequence to define constraint ordering*

```
@GroupSequence({First.class, Second.class, Last.class})
public interface Complete {}

public class Book {
    @NotEmpty(groups=First.class)
    private String title;

    @Size(max=30, groups=Second.class)
    private String subtitle;

    @Valid
    @NotNull(groups=First.class)
    private Author author;

    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public String getSubtitle() {
        return subtitle;
    }

    public void setSubtitle(String subtitle) {
        this.subtitle = subtitle;
    }

    public Author getAuthor() {
        return author;
    }

    public void setAuthor(Author author) {
```

```

        this.author = author;
    }

}

public class Author {
    @NotEmpty(groups=Last.class)
    private String firstName;

    @NotEmpty(groups=First.class)
    private String lastName;

    @Size(max=30, groups=Last.class)
    private String company;

    public String getFirstName() {
        return firstName;
    }

    public void setFirstName(String firstName) {
        this.firstName = firstName;
    }

    public String getLastName() {
        return lastName;
    }

    public void setLastName(String lastName) {
        this.lastName = lastName;
    }

    public String getCompany() {
        return company;
    }

    public void setCompany(String company) {
        this.company = company;
    }
}

```

Assuming the validation of the **Complete** group on the following book instance:

```

Author author = new Author();
author.setLastName( "Baudelaire" );
author.setFirstName( "" );
Book book = new Book();
book.setAuthor( author );

```

the validation routine will return the following failure:

- **@NotNull** failure (from **@NotEmpty**) on the **title** field

As both **title** and **author.lastname** are checked as part of the **First** group. If the instance is updated:

```
book.setTitle( "Les fleurs du mal" );
author.setCompany("Some random publisher with a very very very long name");
```

the validation routine will return the following failures:

- `author.firstName` fails to pass the `@Size(min=1)` (from `@NotEmpty`) constraint
- `author.company` fails to pass the `@Size` constraint

As the `First` and `Second` groups pass without failure, the `Last` group is going through validation.

# 6. Validation APIs

The default package for the Bean Validation APIs is `javax.validation`.

## 6.1. Validator API

The main Bean Validation API is the `javax.validation.Validator` interface.

A `Validator` instance is able to validate instances of beans and their associated objects if any. It is recommended to leave the caching of `Validator` instances to the `ValidatorFactory`. `Validator` implementations must be thread-safe.

*Example 71. Validator interface*

```
/**  
 * Validates bean instances. Implementations of this interface must be  
thread-safe.  
 *  
 * @author Emmanuel Bernard  
 * @author Hardy Ferentschik  
 * @author Gunnar Morling  
 */  
public interface Validator {  
  
    /**  
     * Validates all constraints on {@code object}.  
     *  
     * @param object object to validate  
     * @param groups the group or list of groups targeted for validation  
     * (defaults to  
     *      {@link Default})  
     * @param <T> the type of the object to validate  
     * @return constraint violations or an empty set if none  
     * @throws IllegalArgumentException if object is {@code null}  
     *      or if {@code null} is passed to the varargs groups  
     * @throws ValidationException if a non recoverable error happens  
     *      during the validation process  
     */  
    <T> Set<ConstraintViolation<T>> validate(T object, Class<?>...  
groups);  
  
    /**  
     * Validates all constraints placed on the property of {@code object}  
     * named {@code propertyName}.  
     *  
     * @param object object to validate  
     * @param propertyName property to validate (i.e. field and getter  
     * constraints)  
     * @param groups the group or list of groups targeted for validation  
     * (defaults to  
     *      {@link Default})  
     * @param <T> the type of the object to validate  
     * @return constraint violations or an empty set if none  
     */  
}
```

```

    * @throws IllegalArgumentException if {@code object} is {@code null},
    *           if {@code propertyName} is {@code null}, empty or not a
    valid object property
    *           or if {@code null} is passed to the varargs groups
    * @throws ValidationException if a non recoverable error happens
    *           during the validation process
    */
    <T> Set<ConstraintViolation<T>> validateProperty(T object,
                                                       String propertyName,
                                                       Class<?>... groups);

    /**
     * Validates all constraints placed on the property named {@code
     propertyName}
     * of the class {@code beanType} would the property value be {@code
     value}.
     * <p>
     * {@link ConstraintViolation} objects return {@code null} for
     * {@link ConstraintViolation#getRootBean()} and {@link
     ConstraintViolation#getLeafBean()}.
     *
     * @param beanType the bean type
     * @param propertyName property to validate
     * @param value property value to validate
     * @param groups the group or list of groups targeted for validation
     (defaults to
     *   {@link Default}).
     * @param <T> the type of the object to validate
     * @return constraint violations or an empty set if none
     * @throws IllegalArgumentException if {@code beanType} is {@code null},
     *           if {@code propertyName} is {@code null}, empty or not a
     valid object property
     *           or if {@code null} is passed to the varargs groups
     * @throws ValidationException if a non recoverable error happens
     *           during the validation process
     */
    <T> Set<ConstraintViolation<T>> validateValue(Class<T> beanType,
                                                       String propertyName,
                                                       Object value,
                                                       Class<?>... groups);

    /**
     * Returns the descriptor object describing bean constraints.
     * <p>
     * The returned object (and associated objects including
     * {@link ConstraintDescriptor}s) are immutable.
     *
     * @param clazz class or interface type evaluated
     * @return the bean descriptor for the specified class
     * @throws IllegalArgumentException if clazz is {@code null}
     * @throws ValidationException if a non recoverable error happens
     *           during the metadata discovery or if some
     *           constraints are invalid.
     */
    BeanDescriptor getConstraintsForClass(Class<?> clazz);

    /**
     * Returns an instance of the specified type allowing access to

```

```

 * provider-specific APIs.
 * <p>
 * If the Bean Validation provider implementation does not support
 * the specified class, {@link ValidationException} is thrown.
 *
 * @param type the class of the object to be returned
 * @param <T> the type of the object to be returned
 * @return an instance of the specified class
 * @throws ValidationException if the provider does not support the
call
 */
<T> T unwrap(Class<T> type);

/**
 * Returns the contract for validating parameters and return values
of methods
 * and constructors.
 *
 * @return contract for method and constructor validation
 *
 * @since 1.1
 */
ExecutableValidator forExecutables();
}

```

The methods `validate()`, `validateProperty()` and `validateValue()` are used for the validation of Java beans respectively single bean properties. See the next section for more details.

`forExecutables()` provides access to the contract for validating method and constructor parameters and return values. The individual methods for method and constructor validation are described in [Methods for validating method and constructor constraints](#).

`getConstraintsForClass()` returns constraint-related metadata for given types and is described in detail in [Constraint metadata request APIs](#).

`unwrap()` is provided as a way to access objects of a given type specific to a Bean Validation provider typically as a complement to the `Validator` contract. Using this method makes your code non portable.

*Example 72. Using unwrap to access a provider specific contract*

```

//if using the ACME provider
ACMEValidator acmeValidator = factory.unwrap(ACMEValidator.class);
acmeValidator.setSpecificConfiguration( [...] );

```

### 6.1.1. Validation methods

`<T> Set<ConstraintViolation<T>> validate(T object, Class<?>... groups)` is used to validate a given object. This method implements the logic described in [Validation routine](#). An `IllegalArgumentException` is thrown when null is passed for the `object` parameter or the varargs `groups` parameter. A `Set` containing all `ConstraintViolation` objects representing the failing constraints is returned, an empty `Set` is returned otherwise.

`<T> Set<ConstraintViolation<T>> validateProperty(T object, String propertyName, Class<?>... groups)` validates a given field or property of an object. An `IllegalArgumentException` is thrown when `validateProperty()` is called and `object` is null or `propertyName` is null, empty or invalid or null is passed to the varargs `groups` parameter. The property name is the JavaBeans property name (as defined by the JavaBeans `Introspector` class). This method implements the logic described in [Validation routine](#) but only to the given property. `@Valid` is not honored by this method. This method is useful for partial object validation.

`<T> Set<ConstraintViolation<T>> validateValue(Class<T> beanType, String propertyName, Object value, Class<?>... groups)` validates the property referenced by `propertyName` present on `beanType` or any of its superclasses, if the property value were `value`. An `IllegalArgumentException` is thrown when `validateValue()` is called and `beanType` is null or `propertyName` is null, empty or invalid or null is passed to the varargs `groups` parameter. This method implements the logic described in [Validation routine](#) and apply it only to the given property and for the given value. `@Valid` is not honored by this method. This method is useful for ahead of time validation (i.e. before the JavaBean is populated or updated).

If multiple constrained fields or getters share the same name and hide one another in the class hierarchy according to the Java visibility rules, the list of constraints evaluated is unspecified. This will be clarified in a later version of this specification. Note that method overriding is not impacted.

**NOTE** If getters and fields share the same name and are present at different levels of the hierarchy, the list of constraints evaluated is unspecified. This will be clarified in a later version of this specification.

However, constraints hosted on the most specific (hierarchy wise) element type are always evaluated.

**NOTE** `validateProperty()` and `validateValue()` accept property names and not full paths. Bean Validation implementations might accept string representations of paths but this behavior is not portable.

If some unrecoverable failure happens during validation, a `ValidationException` is raised. This exception can be specialized in some situations (invalid group definition, invalid constraint

definition, invalid constraint declaration). See [Exception model](#) or the relative sections for more information.

#### 6.1.1.1. Examples

All the examples will be based on the following class definition, constraint declarations and address instance.

```

public class Address {
    @NotNull @Size(max=30)
    private String addressline1;

    @Size(max=30)
    private String addressline2;

    private String zipCode;

    private String city;

    public String getAddressline1() {
        return addressline1;
    }

    public void setAddressline1(String addressline1) {
        this.addressline1 = addressline1;
    }

    public String getAddressline2() {
        return addressline2;
    }

    public void setAddressline2(String addressline2) {
        this.addressline2 = addressline2;
    }

    public String getZipCode() {
        return zipCode;
    }

    public void setZipCode(String zipCode) {
        this.zipCode = zipCode;
    }

    @Size(max=30) @NotNull
    public String getCity() {
        return city;
    }

    public void setCity(String city) {
        this.city = city;
    }
}

Address address = new Address();
address.setAddressline1( null );
address.setAddressline2( null );
address.setCity("Llanfairpwllgwyngyllgogerychwyrndrobwylldantysiliogogoch
");
//town in North Wales

```

The following code will return two `ConstraintViolation` objects. One for `addressline1` violating `@NotNull` and one for `city` violating `@Size`.

```
validator.validate(address).size() == 2
```

The following code will return one `ConstraintViolation` since `city` violates `@Size` and only `city` is validated.

```
validator.validateProperty(address, "city").size() == 1
```

The following code will return no `ConstraintViolation` objects because the value "Paris" for `city` would not raise any constraint failures.

```
validator.validateValue("city", "Paris").size() == 0
```

### 6.1.2. Methods for validating method and constructor constraints

The methods for the validation of parameters and return values of methods and constructors can be found on the interface `javax.validation.executable.ExecutableValidator`.

*Example 73. ExecutableValidator interface*

```
package javax.validation.executable;

/**
 * Validates parameters and return values of methods and constructors.
 * Implementations of this interface must be thread-safe.
 *
 * @author Gunnar Morling
 * @since 1.1
 */
public interface ExecutableValidator {

    /**
     * Validates all constraints placed on the parameters of the given
     * method.
     *
     * @param <T> the type hosting the method to validate
     * @param object the object on which the method to validate is
     * invoked
     * @param method the method for which the parameter constraints is
     * validated
     * @param parameterValues the values provided by the caller for the
     * given method's
     *         parameters
     * @param groups the group or list of groups targeted for validation
     * (defaults to
     *         {@link Default})
     * @return a set with the constraint violations caused by this
     * validation;
     *         will be empty if no error occurs, but never {@code null}
     * @throws IllegalArgumentException if {@code null} is passed for any
     * of the parameters
     *         or if parameters don't match with each other
     * @throws ValidationException if a non recoverable error happens
     * during the
     *         validation process
}
```

```

/*
<T> Set<ConstraintViolation<T>> validateParameters(T object,
                                                       Method method,
                                                       Object[]
parameterValues,
                                                       Class<?>...
groups);

/**
 * Validates all return value constraints of the given method.
 *
 * @param <T> the type hosting the method to validate
 * @param object the object on which the method to validate is
invoked
 * @param method the method for which the return value constraints is
validated
 * @param returnValue the value returned by the given method
 * @param groups the group or list of groups targeted for validation
(defaults to
 *           {@link Default})
 * @return a set with the constraint violations caused by this
validation;
 *         will be empty if no error occurs, but never {@code null}
 * @throws IllegalArgumentException if {@code null} is passed for any
of the object,
 *         method or groups parameters or if parameters don't match
with each other
 * @throws ValidationException if a non recoverable error happens
during the
 *         validation process
*/
<T> Set<ConstraintViolation<T>> validateReturnValue(T object,
                                                       Method method,
                                                       Object
returnValue,
                                                       Class<?>...
groups);

/**
 * Validates all constraints placed on the parameters of the given
constructor.
 *
 * @param <T> the type hosting the constructor to validate
 * @param constructor the constructor for which the parameter
constraints is validated
 * @param parameterValues the values provided by the caller for the
given constructor's
 *           parameters
 * @param groups the group or list of groups targeted for validation
(defaults to
 *           {@link Default})
 * @return a set with the constraint violations caused by this
validation;
 *         Will be empty if no error occurs, but never {@code null}
 * @throws IllegalArgumentException if {@code null} is passed for any
of the parameters
 *         or if parameters don't match with each other
 * @throws ValidationException if a non recoverable error happens
during the
 *         validation process
*/

```

```

    */
    <T> Set<ConstraintViolation<T>> validateConstructorParameters
(Constructor<? extends T> constructor,
Object[] parameterValues,
Class<?>... groups);

/**
 * Validates all return value constraints of the given constructor.
 *
 * @param <T> the type hosting the constructor to validate
 * @param constructor the constructor for which the return value
constraints is validated
 * @param createdObject the object instantiated by the given method
 * @param groups the group or list of groups targeted for validation
(defaults to
     *          {@link Default})
 * @return a set with the constraint violations caused by this
validation;
 *         will be empty, if no error occurs, but never {@code null}
 * @throws IllegalArgumentException if {@code null} is passed for any
of the parameters
 *         or if parameters don't match with each other
 * @throws ValidationException if a non recoverable error happens
during the
     *         validation process
 */
<T> Set<ConstraintViolation<T>> validateConstructorReturnValue
(Constructor<? extends T> constructor,
T
createdObject,
Class<?>... groups);
}

```

<T> Set<ConstraintViolation<T>> validateParameters(T object, Method method, Object[] parameterValues, Class<?>... groups) validates the arguments (as given in `parameterValues`) for the parameters of a given method (identified by `method`). Cross-parameter constraints are also validated. A set containing all `ConstraintViolation` objects representing the failing constraints is returned, an empty set is returned if no constraint violations occurred. An `IllegalArgumentException` will be thrown if null is passed for any of the parameters or if the parameters don't match with each other (i.e. `object` and `method` don't match, `parameterValues` and `method` don't match).

<T> Set<ConstraintViolation<T>> validateReturnValue(T object, Method method, Object returnValue, Class<?>... groups) validates the return value (specified by `returnValue`) of a given method (identified by `method`). A set containing all `ConstraintViolation` objects representing the failing constraints is returned, an empty set is returned if no constraint violations occurred. An `IllegalArgumentException` will be thrown if null is passed for any of the parameters `object`, `method` and `groups` or if the parameters don't match with each other (i.e. `object` and `method` don't match, `returnValue` and `method`

don't match).

```
<T>                                         Set<ConstraintViolation<T>>
validateConstructorParameters(Constructor<T>      constructor,      Object[]
parameterValues,  Class<?>...  groups) validates the arguments (as given in
parameterValues) for the parameters of a given constructor (identified by constructor).
Cross-parameter constraints are also validated. A set containing all ConstraintViolation
objects representing the failing constraints is returned, an empty set is returned if no constraint
violations occurred. An IllegalArgumentException will be thrown if null is passed for any of
the parameters or if the parameters don't match with each other (i.e. parameterValues and
constructor don't match).
```

```
<T>                                         Set<ConstraintViolation<T>>
validateConstructorReturnValue(Constructor<T>      constructor,      T
createdObject,  Class<?>...  groups) validates the object (specified by
createdObject) of a given constructor (identified by constructor). A set containing all
ConstraintViolation objects representing the failing constraints is returned, an empty set is
returned if no constraint violations occurred. An IllegalArgumentException will be thrown
if null is passed for any of the parameters or if the parameters don't match with each other (i.e.
createdObject and constructor don't match).
```

None of those methods honor the XML configuration around executable validation nor the presence of `@ValidateOnExecution`. In other words, elements will be validated regardless of these settings when explicitly calling the validation methods.

#### 6.1.2.1. Examples

All the examples will be based on the following class definitions, constraint declarations and instances.

```

public class OrderService {

    @NotNull
    private CreditCardProcessor creditCardProcessor;

    @Valid
    public OrderService(@NotNull CreditCardProcessor creditCardProcessor) {
        [...]
    }

    @NotNull
    public Order placeOrder(
        @NotNull @Size(min=3, max=20) String customerCode,
        @NotNull @Valid Item item,
        @Min(1) int quantity) {

        [...]
    }
}

public class Item {

    @NotNull;
    private String name;

    public String getName() { return name; }
    public void setName(String name) { this.name = name; }
}

Item item1 = new Item();
item1.setName("Kiwi");

Item item2 = new Item();
item2.setName(null);

Constructor<OrderService> constructor = [...]; //get constructor object
Method placeOrder = [...]; //get method object

OrderService orderService = new OrderService(new DefaultCreditCardProcessor())
);

ExecutableValidator executableValidator = Validation
    .buildDefaultValidatorFactory().getValidator().forExecutables();

```

The following method parameter validation will return one `ConstraintViolation` object as the customer code is null:

```

//orderService.placeOrder(null, item1, 1);
executableValidator.validateParameters(
    orderService, placeOrder, new Object[] { null, item1, 1 }).size() == 1;

```

The following method parameter validation will return one `ConstraintViolation` object as the `item` parameter is marked for cascaded validation and the given `Item` instance is not valid (its name is null):

```
//orderService.placeOrder("CUST-123", item2, 1);
executableValidator.validateParameters(
    orderService, placeOrder, new Object[] { "CUST-123", item2, 1 }).size() ==
1;
```

The following constructor parameter validation will return one `ConstraintViolation` object as null is passed for the `creditCardProcessor` parameter:

```
//new OrderService(null);
executableValidator.validateConstructorParameters(constructo, new Object[] {
    null })
.size() == 1;
```

Assuming the `placeOrder()` method returned `null`, the following return value validation will return one `ConstraintViolation`:

```
executableValidator.validateReturnValue(orderService, placeOrder, null).size()
== 1;
```

Assuming the constructor of `OrderService` failed to store the given credit card processor into the `creditCardProcessor` field, the following validation of the constructor return value would fail as the constructor is marked with `@Valid` and the `@NotNull` constraint of the `OrderService` class would be violated:

```
executableValidator.validateConstructorReturnValue(constructo, orderService)
.size() == 1;
```

Let's now look at how a validation interceptor would use these methods.

```

@Interceptor
public class SampleMethodInterceptor {
    @Inject
    private Validator validator;

    @AroundInvoke
    public Object validateMethodInvocation(InvocationContext ctx) throws
Exception {
        //validate parameters
        Set<ConstraintViolation<Object>> violations;
        violations = validator.forExecutables().validateParameters(
            ctx.getTarget(),
            ctx.getMethod(),
            ctx.getParameters()
        );

        //if a violation occurs for parameters, raise an exception
        if ( !violations.isEmpty() ) {
            throw new ConstraintViolationException(
                buildMessage( ctx.getMethod(), ctx.getParameters(),
violations ),
                violations
            );
        }

        //execute the method proper
        Object result = ctx.proceed();

        //validate the return type
        violations = validator.forExecutables().validateReturnValue(
            ctx.getTarget(),
            ctx.getMethod(),
            result
        );

        //if a violation occurs for the return type, raise an exception
        if ( !violations.isEmpty() ) {
            throw new ConstraintViolationException(
                buildMessage( ctx.getMethod(), ctx.getParameters(),
violations ),
                violations
            );
        }

        //return the result
        return result;
    }
}

```

### 6.1.3. groups

Groups allow you to restrict the set of constraints applied during validation. Groups targeted are passed as parameters to the `validate()`, `validateProperty()` and `validateValue()` methods as well as the methods to validate method/constructor constraints (see [Methods for validating method and constructor constraints](#)). All constraints belonging to the targeted group(s) are applied during the [Validation routine](#). If no group is passed, the `Default` group is

assumed. `groups` describes how to define groups on constraints.

When more than one group is evaluated and passed to the various validate methods, order is not constrained. It is equivalent to the validation of a group `G` inheriting all groups (i.e. implementing all interfaces) passed to the validation method.

#### 6.1.3.1. Examples

```
/** Validates a minimal set of constraints */
public interface Minimal {}  
  
public class Address {  
  
    @NotEmpty(groups = Minimal.class)
    @Size(max=50)
    private String street1;  
  
    @NotEmpty
    private String city;  
  
    @NotEmpty(groups = {Minimal.class, Default.class})
    private String zipCode;  
  
    [...]
}
```

In the previous example, `@NotEmpty` (and its composing constraints) on `street1` applies to the group `Minimal`, `@Size` on `street1` applies to the group `Default` and `@NotEmpty` (and its composing constraints) on `zipCode` applies to the groups `Default` and `Minimal`.

```
validator.validate(address);
```

validates the group `Default` (implicitly) and applies `@Size` on `street1`, `@NotEmpty` (and its composing constraints) on `city`, `@NotEmpty` (and its composing constraints) on `zipCode`. Particularly, `@NotEmpty` (and its composing constraints) on `street1` are not applied.

```
validator.validate(address, Minimal.class);
```

applies `@NotEmpty` (and its composing constraints) on `street1` and `@NotEmpty` (and its composing constraints) on `zipCode` because they belong to the `Minimal` group.

```
validator.validate(address, Minimal.class, Default.class);
```

validates both `Default` and `Minimal` groups. The routine applies `@NotEmpty` (and its composing constraints) and `@Size` on `street1`, `@NotEmpty` (and its composing constraints) on `city`, `@NotEmpty` (and its composing constraints) on `zipCode`. Note that if `zipCode` is empty, only one `ConstraintViolation` object will represent the failure and the not empty validation

will only be executed once.

Let's look at a more complex example involving group sequence.

```
public class Address {  
    @NotEmpty(groups = Minimal.class)  
    @Size(max=50, groups=FirstStep.class)  
    private String street1;  
  
    @NotEmpty(groups=SecondStep.class)  
    private String city;  
  
    @NotEmpty(groups = {Minimal.class, SecondStep.class})  
    private String zipCode;  
  
    [...]  
  
    public interface FirstStep {}  
  
    public interface SecondStep {}  
  
    @GroupSequence({FirstStep.class, SecondStep.class})  
    public interface Total {}  
}
```

When running:

```
validator.validate(address, Minimal.class, Total.class);
```

the validation process will process `@NotEmpty` (and its composing constraints) and `@Size` from `street1` and `@NotEmpty` (and its composing constraints) from `zipCode`. If `@Size` from `street1` does not generate a failure, then `@NotEmpty` (and its composing constraints) from `city` will be processed as part of `SecondStep`. Note that `@NotEmpty` (and its composing constraints) from `zipCode` are not reprocessed as they have already been processed before.

When running:

```
validator.validate(address, Total.class, SecondStep.class);
```

`@NotEmpty` (and its composing constraints) from `city` and `@NotEmpty` (and its composing constraints) from `zipCode` will be processed even if `@Size` from `street1` fails: while `SecondStep` is in the `Total` group sequence and hence should not be triggered if `FirstStep` has a failure, it also has been requested outside the sequence (in this case explicitly).

**NOTE** If the group definition is invalid, a `GroupDefinitionException` is raised.

## 6.2. ConstraintViolation

`ConstraintViolation` is the class describing a single constraint failure. A set of `ConstraintViolation` is returned for an object validation.

```
/**
 * Describes a constraint violation. This object exposes the constraint
 * violation context as well as the message describing the violation.
 *
 * @author Emmanuel Bernard
 */
public interface ConstraintViolation<T> {

    /**
     * @return the interpolated error message for this constraint violation
     */
    String getMessage();

    /**
     * @return the non-interpolated error message for this constraint
     * violation
     */
    String getMessageTemplate();

    /**
     * Returns the root bean being validated. For method validation, returns
     * the object the method is executed on.
     * <p>
     * Returns {@code null} when:
     * <ul>
     *   <li>the {@code ConstraintViolation} is returned after calling
     *   {@link Validator#validateValue(Class, String, Object,
     Class[])}</li>
     *   <li>the {@code ConstraintViolation} is returned after validating a
     *   constructor.</li>
     * </ul>
     *
     * @return the validated object, the object hosting the validated element
     * or {@code null}
     */
    T getRootBean();

    /**
     * Returns the class of the root bean being validated.
     * For method validation, this is the object class the
     * method is executed on.
     * For constructor validation, this is the class the constructor
     * is declared on.
     *
     * @return the class of the root bean or of the object hosting the
     * validated element
     */
    Class<T> getRootBeanClass();

    /**
     * Returns:
     * <ul>
```

```

*      <li>the bean instance the constraint is applied on if it is
*      a bean constraint</li>
*      <li>the bean instance hosting the property the constraint
*      is applied on if it is a property constraint</li>
*      <li>{@code null} when the {@code ConstraintViolation} is returned
*      after calling {@link Validator#validateValue(Class, String, Object,
Class[])}
*
*      </li>
*      <li>the object the method is executed on if it is
*      a method parameter, cross-parameter or return value constraint</li>
*      <li>{@code null} if it is a constructor parameter or
*      cross-parameter constraint</li>
*      <li>the object the constructor has created if it is a
*      constructor return value constraint</li>
*  </ul>
*
*  * @return the leaf bean
*/
Object getLeafBean();

/**
 * Returns an {@code Object[]} representing the constructor or method
invocation
 * arguments if the {@code ConstraintViolation} is returned after
validating the
 * method or constructor parameters.
 * Returns {@code null} otherwise.
 *
 * @return parameters of the method or constructor invocation or {@code
null}
 *
 * @since 1.1
*/
Object[] getExecutableParameters();

/**
 * Returns the return value of the constructor or method invocation
 * if the {@code ConstraintViolation} is returned after validating the
method
 * or constructor return value.
 * <p>
 * Returns {@code null} if the method has no return value.
 * Returns {@code null} otherwise.
 *
 * @return the method or constructor return value or {@code null}
 *
 * @since 1.1
*/
Object getExecutableReturnValue();

/**
 * @return the property path to the value from {@code rootBean}
*/
Path getPropertyPath();

/**
 * Returns the value failing to pass the constraint.
 * For cross-parameter constraints, an {@code Object[]} representing
 * the method invocation arguments is returned.
 */

```

```

    * @return the value failing to pass the constraint
    */
Object getInvalidValue();

/**
 * Returns the constraint metadata reported to fail.
 * The returned instance is immutable.
 *
 * @return constraint metadata
 */
ConstraintDescriptor<?> getConstraintDescriptor();

/**
 * Returns an instance of the specified type allowing access to
 * provider-specific APIs. If the Bean Validation provider
 * implementation does not support the specified class,
 * {@link ValidationException} is thrown.
 *
 * @param type the class of the object to be returned
 * @param <U> the type of the object to be returned
 * @return an instance of the specified class
 * @throws ValidationException if the provider does not support the call
 *
 * @since 1.1
 */
<U> U unwrap(Class<U> type);
}

```

The `getMessage()` method returns the interpolated (localized) message for the failing constraint (see [Message interpolation](#) for more information on message interpolator). This can be used by clients to expose user friendly messages.

The `getMessageTemplate()` method returns the non-interpolated error message (usually the `message` attribute on the constraint declaration). Frameworks can use this as an error code key.

The `getRootBean()` method returns the root object being validated that led to the failing constraint (i.e. the object the client code passes to the `Validator.validate()` method). For method validation, returns the object the method is executed on. For constructors or when `Validator.validateValue()` is used, returns `null`.

The `getRootBeanClass()` method returns the class of the root bean being validated. For method validation, this is the object class the method is executed on. For constructor validation, this is the class the constructor is declared on.

The `getLeafBean()` method returns the following object:

- If a bean constraint, the bean instance the constraint is applied on.
- If a property constraint, the bean instance hosting the property the constraint is applied on.
- If a property constraint, `null` when the `ConstraintViolation` is returned after calling `Validator.validateValue()`.

- If a method parameter, cross-parameter or return value constraint, the object the method is executed on.
- If a constructor parameter or cross-parameter constraint, `null`.
- If a constructor return value constraint, the object the constructor has created.

The `getExecutableParameters()` returns the parameters provided to the method or constructor invocation or `null` if not validating the method or constructor parameters.

The `getExecutableReturnValue()` returns the return value of the method or constructor invocation or `null` if the method has no return value or if not validating the method or constructor return value.

The `getInvalidValue()` method returns the value (field, property, method/constructor parameter, method/constructor return value or validated object) being passed to `isValid()`. For a cross-parameter constraint failure, an `Object[]` representing the method/constructor invocation arguments is returned.

`getConstraintDescriptor()` provides access to the failing constraint metadata (see [ConstraintDescriptor](#)).

The `getPropertyPath()` method returns the `Path` object representing the navigation path from the root object to the failing object.

`unwrap()` is provided as a way to access objects of a given type specific to a Bean Validation provider typically as a complement to the `ConstraintViolation` contract. Using this method makes your code non portable.

#### *Example 74. Path, Node and ElementKind interfaces*

```
 /**
 * Represents the navigation path from an object to another
 * in an object graph.
 * Each path element is represented by a {@code Node}.
 * <p>
 * The path corresponds to the succession of nodes
 * in the order they are returned by the {@code Iterator}.
 *
 * @author Emmanuel Bernard
 * @author Gunnar Morling
 * @author Guillaume Smet
 */
public interface Path extends Iterable<Path.Node> {

    /**
     * Returns a human-readable representation of this path.
     * <p>
     * Clients should not rely on any specific structure of the returned
     * value. Instead they should iterate through the
     * path nodes and obtain any required information by calling the
}
```

```

methods on {@link Node} and its sub-types.

*
* @return a human-readable representation of this path
* @since 2.0
*/
@Override
String toString();

/**
 * Represents an element of a navigation path.
*/
interface Node {

    /**
     * Returns the name of the element which the node represents:
     * <ul>
     *   <li>{@code null} if it is a leaf node which represents an
entity / bean.
     *   * In particular, the node representing the root object.</li>
     *   <li>The property name for a property.</li>
     *   <li>The method name for a method.</li>
     *   <li>The unqualified name of the type declaring the
constructor
     *   * for a constructor.</li>
     *   <li>The parameter named as defined by the {@link
ParameterNameProvider}
     *   * for a method or constructor parameter.</li>
     *   <li>The literal {@code <cross-parameter>} for a method or
constructor
     *   * cross-parameter.</li>
     *   <li>The literal {@code <return value>} for a method or
constructor return
     *   * value.</li>
     * </ul>
     *
     * @return name of the element which the node represents
*/
    String getName();

    /**
     * @return {@code true} if the node represents an object
contained in an
     *          {@code Iterable} or in a {@code Map}, {@code false}
otherwise
     */
    boolean isInIterable();

    /**
     * @return the index the node is placed in if contained in an
array or
     *          {@code List}; {@code null} otherwise
     */
    Integer getIndex();

    /**
     * @return the key the node is placed in if contained in a {@code
Map},
     *          {@code null} otherwise
     */
    Object getKey();
}

```

```

    /**
     * The kind of element represented by the node. The following
     relationship
     * between an {@link ElementKind} and its {@code Node} subtype
     exists:
     * <ul>
     *   <li>{@link ElementKind#BEAN}: {@link BeanNode}</li>
     *   <li>{@link ElementKind#PROPERTY}: {@link
     PropertyNode}</li>
     *   <li>{@link ElementKind#METHOD}: {@link MethodNode}</li>
     *   <li>{@link ElementKind#CONSTRUCTOR}: {@link
     ConstructorNode}</li>
     *   <li>{@link ElementKind#PARAMETER}: {@link
     ParameterNode}</li>
     *   <li>{@link ElementKind#CROSS_PARAMETER}: {@link
     CrossParameterNode}</li>
     *   <li>{@link ElementKind#RETURN_VALUE}: {@link
     ReturnValueNode}</li>
     *   <li>{@link ElementKind#CONTAINER_ELEMENT}: {@link
     ContainerElementNode}</li>
     * </ul>
     * <p>
     * This is useful to narrow down the {@code Node} type and access
     node specific
     * information:
     * <pre>
     * switch(node.getKind() {
     * case METHOD:
     *     name = node.getName();
     *     params = node.as(MethodNode.class).getParameterTypes();
     * case PARAMETER:
     *     index = node.as(ParameterNode.class).getParameterIndex();
     * [...]
     * }
     * </pre>
     * @return the {@code ElementKind}
     *
     * @since 1.1
     */
    ElementKind getKind();

    /**
     * Narrows the type of this node down to the given type. The
     appropriate
     * type should be checked before by calling {@link #getKind()}.
     *
     * @param <T> the type to narrow down to
     * @param nodeType class object representing the descriptor type
     to narrow down to
     *               to
     *
     * @return this node narrowed down to the given type.
     *
     * @throws ClassCastException If this node is not assignable to
     the type {@code T}
     * @since 1.1
     */
    <T extends Node> T as(Class<T> nodeType);

```

```

    /**
     * Returns a human-readable representation of this node.
     * <p>
     * Clients should not rely on any specific structure of the
     returned value. Instead they should obtain any
     * required information by calling the methods on this interface
and its sub-types.
     *
     * @return a human-readable representation of this node
     * @since 2.0
     */
    @Override
    String toString();
}

/**
 * Node representing a method.
 *
 * @since 1.1
 */
interface MethodNode extends Node {

    /**
     * @return the list of parameter types
     */
    List<Class<?>> getParameterTypes();
}

/**
 * Node representing a constructor.
 *
 * @since 1.1
 */
interface ConstructorNode extends Node {

    /**
     * @return the list of parameter types
     */
    List<Class<?>> getParameterTypes();
}

/**
 * Node representing the return value of a method or constructor.
 *
 * @since 1.1
 */
interface ReturnValueNode extends Node {
}

/**
 * Node representing a parameter of a method or constructor.
 *
 * @since 1.1
 */
interface ParameterNode extends Node {

    /**
     * @return the parameter index in the method or constructor
definition
     */
}

```

```

        int getParameterIndex();
    }

    /**
     * Node representing the element holding cross-parameter constraints
     * of a method or constructor.
     *
     * @since 1.1
     */
    interface CrossParameterNode extends Node {
}

    /**
     * Node representing a bean.
     *
     * @since 1.1
     */
    interface BeanNode extends Node {

        /**
         * @return the type of the container the node is placed in, if
         * contained in a container type such as
         * {@code Optional}, {@code List} or an array, {@code null}
         * otherwise
         *
         * @since 2.0
         */
        Class<?> getContainerClass();

        /**
         * @return the index of the type parameter affected by the
         * violated constraint, if contained in a generic
         * container type such as {@code Optional}, {@code List} or
         * {@code Map}.
         *
         * @since 2.0
         */
        Integer getTypeArgumentIndex();
    }

    /**
     * Node representing a property.
     *
     * @since 1.1
     */
    interface PropertyNode extends Node {

        /**
         * @return the type of the container the node is placed in, if
         * contained in a container type such as
         * {@code Optional}, {@code List} or an array, {@code null}
         * otherwise
         *
         * @since 2.0
         */
        Class<?> getContainerClass();

        /**
         * @return the index of the type parameter affected by the
         * violated constraint, if contained in a generic
    
```

```

    * container type such as {@code Optional}, {@code List} or
{@code Map}, {@code null} otherwise
     * @since 2.0
     */
    Integer getTypeArgumentIndex();
}

/**
 * Node representing an element in a container such as {@code
Optional}, {@code List} or an array
 *
 * @since 2.0
 */
interface ContainerElementNode extends Node {

    /**
     * @return the type of the container the node is placed in
     */
    Class<?> getContainerClass();

    /**
     * @return the index of the type parameter affected by the
violated constraint, if contained in a generic
     * container type such as {@code Optional}, {@code List} or
{@code Map}, {@code null} if contained in an array
     */
    Integer getTypeArgumentIndex();
}
}

```

```

/**
 * Enum of possible kinds of elements encountered in Bean Validation.
 * <p>
 * Mostly elements that can be constrained and described in the metadata
 * but also elements that can be part of a {@link Path} and represented
 * by a {@link Path.Node}
 *
 * @author Emmanuel Bernard
 * @author Gunnar Morling
 * @author Guillaume Smet
 *
 * @since 1.1
 */
public enum ElementKind {
    /**
     * A Java Bean or object.
     */
    BEAN,

    /**
     * A property of a Java Bean.
     */
    PROPERTY,

    /**
     * A method.
     */
    METHOD,

    /**
     * A constructor.
     */
    CONSTRUCTOR,

    /**
     * A parameter of a method or constructor.
     */
    PARAMETER,

    /**
     * Element holding cross-parameter constraints of a method or
     * constructor.
     */
    CROSS_PARAMETER,

    /**
     * The return value of a method or constructor.
     */
    RETURN_VALUE,

    /**
     * An element stored in a container, e.g. a key or value of a {@code
     * Map} or an element of a {@code List}.
     *
     * @since 2.0
     */
    CONTAINER_ELEMENT
}

```

`Path` is an iterable of `Node` objects. `Node` offers the following methods:

- `getName()` returns the name of the element which the node represents:
  - `null` if it is a leaf node which represents an entity / bean. In particular, the node representing the root object.
  - The property name for a property.
  - The method name for a method.
  - The unqualified name of the type declaring the constructor for a constructor.
  - The parameter named as defined by the `ParameterNameProvider` (see [Naming parameters](#)) for a method or constructor parameter.
  - The literal `<cross-parameter>` for a method or constructor cross-parameter.
  - The literal `<return value>` for a method or constructor return value.
  - The name set by the applied value extractor for a container element constraint, e.g. `<map value>` if the default value extractor for map values is applied
- `isIterable()` returns `true` if the node represents an object contained in an `Iterable` or in a `Map`, `false` otherwise.
- `getIndex()` returns the index of the node if it is contained in an array or `List`. Returns `null` otherwise.
- `getKey()` returns the key of the node if it is contained in a `Map`. Returns `null` otherwise.
- `getKind()` returns the `ElementKind` corresponding to the actual node type. This can be used in conjunction with the method `as()` to narrow the type and access node specific methods
- `as(Class<? extends Node>)` returns the node instance narrowed to the type passed as a parameter or `ClassCastException` if the type and node don't match.

Nodes are of the following possible types:

- `BeanNode`
- `PropertyNode`
- `MethodNode`
- `ConstructorNode`
- `ParameterNode`
- `CrossParameterNode`
- `ReturnValueNode`
- `ContainerElementNode`

It is possible to narrow a node instance to its precise type and extract node specific information by the use of `Node.getKind()` and `Node.as(Class<? extends Node>)`.

In particular, `MethodNode` and `ConstructorNode` host `getParameterTypes()` which return the method or constructor parameter list. Likewise `ParameterNode` hosts `getParameterIndex()` which returns the parameter index in the method or constructor parameter list.

`BeanNode`, `PropertyNode` and `ContainerElementNode` host `getContainerClass()` and `getTypeArgumentIndex()`. If the constrained element is contained in a generic container such as `Optional`, `List` or `Map`, the former returns the class of the container and the latter returns the index of the affected type argument.

*Example 75. Narrow a node to its specific type*

```
Node node = [...];
switch ( node.getKind() ) {
    case METHOD:
        MethodNode methodNode = node.as(MethodNode.class);
        methodName = methodNode.getName();
        params = methodNode.getParameterTypes().toArray(
            new Class<?>[methodNode.getParameterTypes().size()] );
        break;
    case CONSTRUCTOR:
        ConstructorNode constructorNode = node.as(ConstructorNode.class);
        methodName = constructorNode.getName();
        params = constructorNode.getParameterTypes().toArray(
            new Class<?>[constructorNode.getParameterTypes().size()] );
        break;
    case PARAMETER:
        arg = node.as(ParameterNode.class).getParameterIndex();
        break;
    case CONTAINER_ELEMENT:
        ContainerElementNode containerElementNode = node.as
(ContainerElementNode.class);
        containerClass = containerElementNode.getContainerClass();
        typeArgumentIndex = containerElementNode.getTypeArgumentIndex();
        break;
    case CROSS_PARAMETER:
        [...]
    case RETURN_VALUE:
        [...]
    case PARAMETER:
        [...]
    case BEAN:
        [...]
    case PROPERTY:
        [...]
}
```

`Path` objects are built according to the following rules:

- The runtime type is considered, not the static type. For example if a property is declared `Collection<String>` but its runtime type is `ArrayList<String>`, the property is considered an `ArrayList<String>`.
- If the failing object is the root object, a `BeanNode` with name set to `null` is added to the `Path`. The `ElementKind` of the node is `ElementKind.BEAN`.
- When an association is traversed:
  - a `PropertyNode` object whose `name` equals the name of the association property (field name or Java Bean property name) is added to `Path`. The `ElementKind` of the node is `ElementKind.PROPERTY`.
  - if the association is a `List` or an array, the following `Node` object added contains the index value in `getIndex()`.
  - if the association is a `Map`, the following `Node` object added (representing a given map entry) contains the key value in `getKey()`
  - for all `Iterable` or `Map`, the following `Node` object added is marked as `inIterable` (`isInIterable()`)
  - if the traversed object is of a container type (e.g. a `List` or `Map`), the following `Node` object added returns the type of the traversed container via `getContainerClass()` and the index of the type argument to which the constraint applies via ``getTypeArgumentIndex()`
- For a property level constraint (field and getter)
  - a `PropertyNode` object is added to `Path` whose `name` equals the name of the property (field name or Java Bean property name). The `ElementKind` of the node is `ElementKind.PROPERTY`.
  - the property path is considered complete
- For a class level constraint:
  - a `BeanNode` object is added to `Path` whose `name` is null. The `ElementKind` of the node is `ElementKind.BEAN`.
  - the property path is considered complete
- For a method/constructor constraint (parameter, cross-parameter or return value constraint on a method or constructor):
  - a `MethodNode` respectively a `ConstructorNode` object is added to the `Path` which represents the validated method respectively constructor. The `name` of the node equals the validated method name or the validated constructor's unqualified class name, the `ElementKind` of the node is `ElementKind.METHOD` respectively `ElementKind.CONSTRUCTOR`.

- if the constraint is on a parameter, a `ParameterNode` object is added to the `Path` which represents the validated parameter. The `name` of the node equals the parameter name as determined by the current parameter name provider (see [Naming parameters](#)). The `ElementKind` of the node is `ElementKind.PARAMETER`.
- if the constraint is a cross-parameter constraint, a `CrossParameterNode` object is added to the `Path` which represents the validated cross-parameter element. The `name` of the node has the constant value `<cross-parameter>`. The `ElementKind` of the node is `ElementKind.CROSS_PARAMETER`.
- if the constraint is on the return value, a `ReturnValueNode` object is added to the `Path` which represents the validated return value. The `name` of the node has the constant value `<return value>`. The `ElementKind` of the node is `ElementKind.RETURN_VALUE`.
- the property path is considered complete
- If a parameter or the return value of a method or constructor is traversed:
  - a `MethodNode` respectively `ConstructorNode` object is added to the `Path` which represents the concerned method respectively constructor. The `name` of the node equals the concerned method name or the constructor's unqualified class name, the `ElementKind` of the node is `ElementKind.METHOD` or `ElementKind.CONSTRUCTOR`, respectively.
  - if a parameter is traversed, a `ParameterNode` object is added to the `Path` which represents the traversed parameter. The `name` of the node equals the parameter name as determined by the current parameter name provider. The `ElementKind` of the node is `ElementKind.PARAMETER`.
  - if a return value is traversed, a `ReturnValueNode` object is added to the `Path` which represents the traversed return value. The `name` of the node has the constant value `<return value>`. The `ElementKind` of the node is `ElementKind.RETURN_VALUE`.
  - if the parameter/return value is a `List` or an array, the following `Node` object added contains the index value in `getIndex()`.
  - if the parameter/return value is a `Map`, the following `Node` object added (representing a given map entry) contains the key value in `getKey()`.
  - for all `Iterable` or `Map`, the following `Node` object added is marked as `inIterable` (`isInIterable()`).
- For a container element constraint:
  - a `ContainerElementNode` object is added to `Path` whose `name` is the node name produced by the corresponding value extractor (see [Value extractor definition](#)). The `ElementKind` of the node is `ElementKind.CONTAINER_ELEMENT`. `getContainerClass()` returns the type of the container hosting the constraint. `getTypeArgumentIndex()` returns the index of the type argument hosting the

constraint, if the element is stored in a generic container.

- the property path is considered complete

If additional path nodes are added in a constraint validator implementation using the node builder API (see [Constraint validation implementation](#)), the following rules apply:

- if the default path ends with a `BeanNode`, this node is removed and the first added node (a `PropertyNode`) inherits its `inIterable`, `key` and `index` values. `inIterable`, `key` and `index` value must not be specified directly on this first node by the user.
- if the default path ends with a `CrossParameterNode`, this node is removed.
- then the additional nodes are appended to the (possibly amended) path generated by the Bean Validation engine as previously described:
  - A `PropertyNode` is appended in case `addPropertyNode(String)` is invoked. The node name is equal to the name provided. The `ElementKind` of the node is `ElementKind.PROPERTY`.
  - A `BeanNode` is appended in case `addBeanNode()` is invoked. The node name is `null`. The `ElementKind` of the node is `ElementKind.BEAN`.
  - A `ParameterNode` is appended in case `addParameterNode(int)` is invoked. The node name is equal to the parameter name at the provided index. The name is determined by the current parameter name provider. The `ElementKind` of the node is `ElementKind.PARAMETER`. The previous node (removed) must be a `CrossParameterNode`.
- if `inIterable()` is invoked, the node returns `true` for `isInIterable()`, `false` otherwise.
- if `atIndex(Integer)` is invoked, the node returns the provided integer for `getIndex()`, `null` otherwise.
- if `atKey(Object)` is invoked, the node returns the provided object for `getKey()`, `null` otherwise.

**NOTE**

A given `Node` object derives its `inIterable`, `key` and `index` properties from the previous association, method parameter or return value traversed.

**NOTE**

From `getRootBean()`, `getPropertyName()`,  
`getExecutableParameters()` and `getExecutableReturnValue()`, it is possible to rebuild the context of the failure.

**NOTE**

**ConstraintViolations** occurred during standard bean validation can be distinguished from violations occurred during method/constructor validation by analyzing the **ElementKind** of the **Node** of the first node in the violation's property path. In case of constructor or method validation, that **ElementKind** will be either **CONSTRUCTOR** or **METHOD**.

Let there be the following object definitions:

*Example 76. Object model definition for examples*

```
@SecurityChecking
public class Author {
    private String firstName;

    @NotEmpty(message="lastname must not be null")
    private String lastName;

    @Size(max=30)
    private String company;

    [...]

    @OldAndNewPasswordsDifferent @NewPasswordsIdentical
    public void renewPassword(String oldPassword, String newPassword,
String retypedNewPassword);
}

@AvailableInStore(groups={Availability.class})
public class Book {
    @NotEmpty(groups={FirstLevelCheck.class, Default.class})
    private String title;

    @Valid
    @NotNull
    private List<Author> authors;

    @Valid
    private Map<String, Review> reviewsPerSource;

    @Valid
    private Review pickedReview;

    [...]
}

public class Review {
    @Min(0) private int rating;
    [...]
}

public class Library {

    public Library(@NotNull String name, @NotNull String location) {
        [...]
    }
}
```

```

public void addBook(@NotNull @Valid Book book) {
    [...]
}

public void addAllBooks(@NotNull @Valid List<Book> books) {
    [...]
}

@NotNull public String getLocation() {
    [...]
}

@Valid public Map<Author, Book> getMostPopularBookPerAuthor() {
    [...]
}

```

Assuming a `Book` instance gets validated, the property paths to the different constraints would be as described in [propertyPath examples](#):

*Table 3. propertyPath examples*

Constraint	propertyPath
<code>@AvailableInStore</code> on <code>Book</code>	<code>BeanNode(name=null,inIterable=false, index=null, key=null, kind=ElementKind.BEAN)</code>
<code>@NotEmpty</code> on <code>Book.title</code>	<code>PropertyNode(name=title,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)</code>
<code>@NotNull</code> on <code>Book.authors</code>	<code>PropertyNode(name=authors,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)</code>
<code>@SecurityChecking</code> on the fourth author, <code>Author</code>	<code>PropertyNode(name=authors,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)</code> <code>BeanNode(name=null,inIterable=true, index=3, key=null, kind=ElementKind.BEAN)</code>
<code>@Size</code> on the fourth author, <code>Author.lastname</code>	<code>PropertyNode(name=authors,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)</code> <code>PropertyNode(name=lastname,inIterable=true, index=4, key=null, kind=ElementKind.PROPERTY)</code>
<code>@NotEmpty</code> on the first author, <code>Author.company</code>	<code>PropertyNode(name=authors,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)</code> <code>PropertyNode(name=company,inIterable=true, index=0, key=null, kind=ElementKind.PROPERTY)</code>

Constraint	propertyPath
@Min on the review associated to Consumer Report, <code>Review.rating</code>	PropertyNode(name=reviewsPerSource,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY) PropertyNode(name=rating,inIterable=true, index=null, key="Consumer Report", kind=ElementKind.PROPERTY)
@Min on the picked review, <code>Review.rating</code>	PropertyNode(name=pickedReview,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY) PropertyNode(name=rating,inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)

Assuming the constructor and methods of the `Library` class are subject to method constraint validation, the following property paths would exist for the different constraints:

Table 4. Property path examples for constrained methods or constructors

Constraint	propertyPath
@NotNull on the <code>location</code> parameter of the constructor	ConstructorNode(name=Library, inIterable=false, index=null, key=null, kind=ElementKind.CONSTRUCTOR, parameterTypes=[String.class,String.class]) ParameterNode(name=arg1, inIterable=false, index=null, key=null, kind=ElementKind.PARAMETER, parameterIndex=1)
@NotNull on the <code>book</code> parameter of the <code>addBook()</code> method	MethodNode(name=addBook, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes=[Book.class]) ParameterNode(name=arg0, inIterable=false, index=null, key=null, kind=ElementKind.PARAMETER, parameterIndex=0)
@NotEmpty on <code>Book.title</code> during validation of <code>addBook()</code>	MethodNode(name=addBook, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes=[Book.class]) ParameterNode(name=arg0, inIterable=false, index=null, key=null, kind=ElementKind.PARAMETER, parameterIndex=0) PropertyNode(name=title, inIterable=false, index=null, key=null, kind=ElementKind.PROPERTY)

Constraint	propertyPath
<code>@NotEmpty</code> on fourth book, <code>Book.title</code> during validation of <code>addAllBooks()</code>	<pre>MethodNode(name=addAllBooks, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes=[List.class]) ParameterNode(name=arg0, inIterable=false, index=null, key=null, kind=ElementKind.PARAMETER, parameterIndex=0) PropertyNode(name=title,inIterable=true, index=3, key=null, kind=ElementKind.PROPERTY)</pre>
<code>@NotNull</code> on the return value of <code>getLocation()</code> method	<pre>the MethodNode(name=getLocation, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes[]) ReturnValueNode(name=&lt;return value&gt;, inIterable=false, index=null, key=null, kind=ElementKind.RETURN_VALUE)</pre>
<code>@NotEmpty</code> on most popular book of author "John Doe", <code>Book.title</code> during validation of <code>getMostPopularBookPerAuthor()</code>	<pre>MethodNode(name=getMostPopularBookPerA uthor, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes[]) ReturnValueNode(name=&lt;return value&gt;, inIterable=false, index=null, key=null, kind=ElementKind.RETURN_VALUE) PropertyNode(name=title,inIterable=true, index=null, key=Author(firstName=John, lastName=Doe), kind=ElementKind.PROPERTY)</pre>
<code>@OldAndNewPasswordsDifferent</code> when executing <code>Author.renewPassword()</code> with <code>oldPassword</code> , <code>newPassword</code> and <code>retypedNewPassword</code> set to "foo". <code>@OldAndNewPasswordsDifferent</code> is a cross-parameter constraint.	<pre>MethodNode(name=renewPassword, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes=[String.class, String.class, String.class]) CrossParameterNode(name=&lt;cross- parameter&gt;, inIterable=false, index=null, key=null, kind=ElementKind.CROSS_PARAMETER)</pre>
<code>@NewPasswordsIdentical</code> when executing <code>Author.renewPassword()</code> with <code>oldPassword</code> as "foo", <code>newPassword</code> as "bar" and <code>retypedNewPassword</code> as "baz". <code>@NewPasswordsIdentical</code> is a cross-parameter constraint creating a constraint violation on the <code>retypedNewPassword</code> parameter.	<pre>MethodNode(name=renewPassword, inIterable=false, index=null, key=null, kind=ElementKind.METHOD, parameterTypes=[String.class, String.class, String.class]) ParameterNode(name=arg2, inIterable=false, index=null, key=null, kind=ElementKind.PARAMETER, parameterIndex=2)</pre>

**NOTE**

Bean Validation implementations should ensure that a `ConstraintViolation` implementation is `Serializable` provided that the root bean, the leaf bean, the invalid value and keys in the `Path` object are `Serializable` objects.

If a user wishes to send `ConstraintViolation` remotely, it should make sure the object graph validated is itself `Serializable`.

### 6.2.1. Examples

These examples assume the following definition of `@NotEmpty`.

```
package com.acme.constraint;

@Documented
@NotNull
@Size(min = 1)
@ReportAsSingleViolation
@Constraint(validatedBy = NotEmpty.NotEmptyValidator.class)
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
@Retention(RUNTIME)
public @interface NotEmpty {

    String message() default "{com.acme.constraint.NotEmpty.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        NotEmpty[] value();
    }

    class NotEmptyValidator implements ConstraintValidator<NotEmpty, String> {

        @Override
        public void initialize(NotEmpty constraintAnnotation) {
        }

        @Override
        public boolean isValid(String value, ConstraintValidatorContext context) {
            return true;
        }
    }
}
```

and the following class definitions

```

public class Author {

    private String firstName;

    @NotEmpty(message = "lastname must not be null")
    private String lastName;

    @Size(max = 30)
    private String company;

    public String getFirstName() {
        return firstName;
    }

    public void setFirstName(String firstName) {
        this.firstName = firstName;
    }

    public String getLastname() {
        return lastName;
    }

    public void setLastName(String lastName) {
        this.lastName = lastName;
    }

    public String getCompany() {
        return company;
    }

    public void setCompany(String company) {
        this.company = company;
    }
}

public class Book {

    @NotEmpty(groups = { FirstLevelCheck.class, Default.class })
    private String title;

    @Valid
    @NotNull
    private Author author;

    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public Author getAuthor() {
        return author;
    }

    public void setAuthor(Author author) {
        this.author = author;
    }
}

Author author = new Author();

```

```

author.setCompany("ACME");
Book book = new Book();
book.setTitle("");
book.setAuthor(author);

Set<ConstraintViolation> constraintViolations = validator.validate(book);

```

`ConstraintViolations` is a set of size 2. One of the entries represents the failure of `@NotEmpty` (or more precisely `@Size(min=1)`) a composing constraint of `@NotEmpty` on the `title` property.

The `ConstraintViolation` object for this failure passes the following assertions:

*Example 77. Test assertions on ConstraintViolation*

```

//assuming an english locale, the interpolated message is returned
assert "may not be null or empty".equals( constraintViolation.getMessage()
() );
assert book == constraintViolation.getRootBean();
assert book == constraintViolation.getLeafBean();

//the offending value
assert book.getTitle().equals( constraintViolation.getInvalidValue() );

//the offending property
Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator
();
Node node = nodeIter.next();
assert "title".equals( node.getName() );
assert ElementKind.PROPERTY.equals( node.getKind() );

assert false == nodeIter.hasNext();

```

The second failure, `@NotEmpty` (or more precisely `@NotNull` a composing constraint of `@NotEmpty`) on the author's `lastname`, will produce the `ConstraintViolation` object satisfying the following assertions:

```

assert "lastname must not be null".equals( constraintViolation.getMessage() );
assert book == constraintViolation.getRootBean();
assert author == constraintViolation.getLeafBean();

//the offending value
assert book.getAuthor().getLastName() == constraintViolation.getInvalidValue(
);

//the offending property
Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "author".equals( node.getName() );
assert ElementKind.PROPERTY.equals( node.getKind() );

node = nodeIter.next();
assert "lastName".equals( node.getName() );
assert ElementKind.PROPERTY.equals( node.getKind() );

assert false == nodeIter.hasNext();

```

## 6.2.2. Examples for method and constructor constraint violations

The following examples assume the constraint, class and object definitions given in the previous section. Additionally the following class and object definitions are assumed:

```

public class Library {

    @PublicLibrary
    public Library() {
        [...]
    }

    public Library(@NotNull @Valid List<Book> books) {
        [...]
    }

    public void addBook(@NotNull @Valid Book book) {
        [...]
    }

    @Valid public Map<Author, Book> getMostPopularBookPerAuthor() {
        [...]
    }
}

public class User {

    @OldAndNewPasswordsDifferent
    public void renewPassword(String oldPassword, String newPassword, String retypedNewPassword);
}

Library library = new Library();
author.setLastName("Doe");

```

Assuming the following invocation of `addBook()` is subject to method parameter validation:

```
library.addBook(null);
```

Then one `ConstraintViolation` object would be returned by `ExecutableValidator.validateParameters()` which satisfies the following assertions:

```
//assuming an english locale, the interpolated message is returned
assert "may not be null".equals( constraintViolation.getMessage() );

assert library == constraintViolation.getRootBean();
assert Library.class == constraintViolation.getRootBeanClass();
assert library == constraintViolation.getLeafBean();
assert null == constraintViolation.getInvalidValue();

assert new Object[]{ null }.equals( constraintViolation
    .getExecutableParameters() );
assert null == constraintViolation.getExecutableReturnValue();

Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "addBook".equals( node.getName() );
assert ElementKind.METHOD.equals( node.getKind() );

node = nodeIter.next();
//assuming the default parameter name provider is used
assert "arg0".equals( node.getName() );
assert ElementKind.PARAMETER.equals( node.getKind() );

assert false == nodeIter.hasNext();
```

Assuming the following invocation of `addBook()` is subject to method parameter validation:

```
library.addBook(book);
```

Then one `ConstraintViolation` object would be returned by `ExecutableValidator.validateParameters()` which satisfies the following assertions:

```

//assuming an english locale, the interpolated message is returned
assert "may not be null or empty".equals( constraintViolation.getMessage() );

assert library == constraintViolation.getRootBean();
assert Library.class == constraintViolation.getRootBeanClass();
assert book == constraintViolation.getLeafBean();
assert book.getTitle().equals( constraintViolation.getInvalidValue() );

assert new Object[]{ book }.equals( constraintViolation
    .getExecutableParameters() );
assert null == constraintViolation.getExecutableReturnValue();

Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "addBook".equals( node.getName() );
assert ElementKind.METHOD.equals( node.getKind() );

node = nodeIter.next();
//assuming the default parameter name provider is used
assert "arg0".equals( node.getName() );
assert ElementKind.PARAMETER.equals( node.getKind() );

node = nodeIter.next();
assert "title".equals( node.getName() );
assert ElementKind.PROPERTY.equals( node.getKind() );

assert false == nodeIter.hasNext();

```

Assuming the following invocation of `User.renewPassword()` is subject to method parameter validation and the `@OldAndNewPasswordsDifferent` constraint is violated:

```

User user = [...];
user.renewPassword("foo", "foo", "foo");

```

Then one `ConstraintViolation` object would be returned by `ExecutableValidator.validateParameters()` which satisfies the following assertions:

```

assert user == constraintViolation.getRootBean();
assert User.class == constraintViolation.getRootBeanClass();
assert user == getLeafBean();
assert new Object[]{"foo", "foo", "foo"}.equals( constraintViolation
.getInvalidValue() );

assert new Object[]{"foo", "foo", "foo"}.equals( constraintViolation
.getExecutableParameters() );
assert null == constraintViolation.getExecutableReturnValue();

Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "renewPassword".equals( node.getName() );
assert ElementKind.METHOD.equals( node.getKind() );

node = nodeIter.next();
assert "<cross-parameter>" == node.getName();
assert ElementKind.CROSS_PARAMETER.equals( node.getKind() );

assert false == nodeIter.hasNext();

```

Assuming the following invocation of the `Library` constructor accepting a list of books is subject to constructor parameter validation:

```
Library anotherLibrary = new Library(null);
```

Then one `ConstraintViolation` object would be returned by `ExecutableValidator.validateConstructorParameters()` which satisfies the following assertions:

```

//assuming an english locale, the interpolated message is returned
assert "may not be null".equals( constraintViolation.getMessage() );

assert null == constraintViolation.getRootBean();
assert Library.class == constraintViolation.getRootBeanClass();
assert null == constraintViolation.getLeafBean();
assert null == constraintViolation.getInvalidValue();

assert new Object[]{ null }.equals( constraintViolation
    .getExecutableParameters() );
assert null == constraintViolation.getExecutableReturnValue();

Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "Library".equals( node.getName() );
assert ElementKind.CONSTRUCTOR.equals( node.getKind() );

node = nodeIter.next();
//assuming the default parameter name provider is used
assert "arg0".equals( node.getName() );
assert ElementKind.PARAMETER.equals( node.getKind() );

assert false == nodeIter.hasNext();

```

Assuming the following invocation of `getMostPopularBookPerAuthor()` is subject to method return value validation and returns a `Map` containing one entry with key `author` and value `book`:

```

Map<Author, Book> mostPopularBookPerAuthor = library
    .getMostPopularBookPerAuthor();

```

Then one `ConstraintViolation` object would be returned by `ExecutableValidator.validateReturnValue()` which satisfies the following assertions:

```

//assuming an english locale, the interpolated message is returned
assert "may not be null or empty".equals( constraintViolation.getMessage() );

assert library == constraintViolation.getRootBean();
assert Library.class == constraintViolation.getRootBeanClass();
assert book == constraintViolation.getLeafBean();
assert book.getTitle().equals( constraintViolation.getInvalidValue() );

assert null == constraintViolation.getExecutableParameters();
assert mostPopularBookPerAuthor == constraintViolation
    .getExecutableReturnValue();

Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "getMostPopularBookPerAuthor".equals( node.getName() );
assert ElementKind.METHOD.equals( node.getKind() );

node = nodeIter.next();
assert "<return value>" == node.getName();
assert ElementKind.RETURN_VALUE.equals( node.getKind() );

node = nodeIter.next();
assert "title".equals( node.getName() );
assert ElementKind.PROPERTY.equals( node.getKind() );
assert author.equals( node.getKey() );
assert true == node.isIterable();

assert false == nodeIter.hasNext();

```

Assuming the following invocation of the `Library` default constructor is subject to constructor return value validation and returns an instance which violates the `@PublicLibrary` constraint:

```
Library publicLibrary = new Library();
```

Then one `ConstraintViolation` object would be returned by `ExecutableValidator.validateConstructorReturnValue()` which satisfies the following assertions:

```

assert null == constraintViolation.getRootBean();
assert Library.class == constraintViolation.getRootBeanClass();
assert publicLibrary == constraintViolation.getLeafBean();
assert publicLibrary == constraintViolation.getInvalidValue();

assert null == constraintViolation.getExecutableParameters();
assert library == constraintViolation.getExecutableReturnValue();

Iterator<Node> nodeIter = constraintViolation.getPropertyPath().iterator();

Node node = nodeIter.next();
assert "Library".equals( node.getName() );
assert ElementKind.CONSTRUCTOR.equals( node.getKind() );

node = nodeIter.next();
assert "<return value>" == node.getName();
assert ElementKind.RETURN_VALUE.equals( node.getKind() );

assert false == nodeIter.hasNext();

```

## 6.3. Message interpolation

A message interpolator is responsible for transforming the so called message descriptor specified via the message attribute of the constraint into a fully expanded, human-readable error message.

### 6.3.1. Default message interpolation

Every conforming Bean Validation implementation includes a default message interpolator which has to comply with the algorithm defined here to interpolate message descriptors. As precondition for message interpolation the following applies:

- Each constraint defines a message descriptor via its `message` property.
- Every constraint definition defines a default message descriptor for that constraint.
- Messages can be overridden at constraint declaration time by setting the `message` property on the constraint.

The message descriptor is a string literal and may contain one or more message parameters or expressions. Message parameters and expressions are string literals enclosed in `{}` or `${} respectively. The following character escaping rules apply:`

- `\{` is considered as the literal `{` instead of being considered as the beginning of a message parameter
- `\}` is considered as the literal `}` instead of being considered as the end of a message parameter
- `\\\` is considered as the literal `\` instead of being considered as the escaping character

- `\$` is considered as the literal `$` instead of being considered as the beginning of a message expression

Below are two examples using message parameters and expressions. The second is evaluated using Expression Language as defined in [Message expressions using Expression Language \(EL\)](#).

*Example 78. Message using parameters*

```
Value must be between {min} and {max}
```

*Example 79. Message using expressions*

```
Must be greater than ${inclusive == true ? 'or equal to ' : ''}{value}
```

### 6.3.1.1. Default message interpolation algorithm

The default message interpolator uses the following steps:

1. Message parameters are extracted from the message string and used as keys to search the `ResourceBundle` named `ValidationMessages` (often materialized as the property file `/ValidationMessages.properties` and its locale variations) using the defined locale (see [Locale for default message interpolation](#)). If a property is found, the message parameter is replaced with the property value in the message string. Step 1 is applied recursively until no replacement is performed (i.e. a message parameter value can itself contain a message parameter).
2. Message parameters are extracted from the message string and used as keys to search the Bean Validation provider's built-in `ResourceBundle` using the defined locale (see [Locale for default message interpolation](#)). If a property is found, the message parameter is replaced with the property value in the message string. Contrary to step 1, step 2 is not processed recursively.
3. If step 2 triggers a replacement, then step 1 is applied again. Otherwise step 4 is performed.
4. Message parameters are extracted from the message string. Those matching the name of an attribute of the constraint are replaced by the value of that attribute in the constraint declaration. Parameter interpolation has precedence over message expressions. For example for the message descriptor  `${value}`, trying to evaluate `{value}` as message parameter has precedence over evaluating  `${value}` as message expression.
5. Message expressions are extracted from the message string and evaluated using Expression Language. See also [Message expressions using Expression Language \(EL\)](#).

- NOTE** The proposed algorithm ensures that custom resource bundle always have priority over built-in resource bundle at all level of the recursive resolution. It also ensures that constraint declarations attributes values are not interpolated further.
- NOTE** The precedence of message parameter over expression interpolation ensures backwards compatibility to Bean Validation 1.0.

### 6.3.1.2. Locale for default message interpolation

The locale to be used for message interpolation is defined as following:

- if the locale is passed explicitly to the interpolator method via `interpolate(String, Context, Locale)`, this provided instance is used.
- otherwise, the default `Locale` as provided by `Locale.getDefault()` is used.

### 6.3.1.3. Message expressions using Expression Language (EL)

The default message interpolation allows the use of Expression Language (EL) as defined in JSR 341. Expressions to be evaluated by EL need to be enclosed in `${}` within the message descriptor. The following properties and beans have to be made available in the EL context:

- the attribute values of the constraint declaration mapped to their attribute name
- the validated value mapped under the name `validatedValue`.
- a bean mapped to the name `formatter` exposing the vararg method `format(String format, Object... args)`. This method must behave like `java.util.Formatter.format(String format, Object... args)`. The locale used for formatting is defined by [Locale for default message interpolation](#). The `formatter` bean allows to format property values, for example in the case of the validated value being 98.12345678, `${formatter.format('%1$.2f', validatedValue)}` would format it to 98.12 (two digits after the decimal point, where the use of '!' vs',' would be locale specific).

If an exception occurs during message interpolation, e.g. due invalid expressions or references to an unknown property, the message expression stays unchanged.

## 6.3.2. Custom message interpolation

A custom message interpolator may be provided (e.g., to interpolate contextual data, or to adjust the default `Locale` used). A message interpolator implements the `MessageInterpolator` interface.

```

/**
 * Interpolates a given constraint violation message.
 * <p>
 * Implementations should be as tolerant as possible on syntax errors.
 * Implementations must be thread-safe.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 */
public interface MessageInterpolator {

    /**
     * Interpolates the message template based on the constraint validation
     context.
     * <p>
     * The locale is defaulted according to the {@code MessageInterpolator}
     * implementation. See the implementation documentation for more detail.
     *
     * @param messageTemplate the message to interpolate
     * @param context contextual information related to the interpolation
     *
     * @return interpolated error message
     */
    String interpolate(String messageTemplate, Context context);

    /**
     * Interpolates the message template based on the constraint validation
     context.
     * The {@code Locale} used is provided as a parameter.
     *
     * @param messageTemplate the message to interpolate
     * @param context contextual information related to the interpolation
     * @param locale the locale targeted for the message
     *
     * @return interpolated error message
     */
    String interpolate(String messageTemplate, Context context, Locale
locale);

    /**
     * Information related to the interpolation context.
     */
    interface Context {
        /**
         * @return {@link ConstraintDescriptor} corresponding to the
constraint being validated
        */
        ConstraintDescriptor<?> getConstraintDescriptor();

        /**
         * @return value being validated
         */
        Object getValidatedValue();

        /**
         * Returns an instance of the specified type allowing access to
         * provider-specific APIs. If the Bean Validation provider
         * implementation does not support the specified class,
         * {@link ValidationException} is thrown.
         */
    }
}

```

```

    * @param type the class of the object to be returned
    * @param <T> the type of the object to be returned
    * @return an instance of the specified class
    * @throws ValidationException if the provider does not support the
call
    *
    * @since 1.1
    */
<T> T unwrap(Class<T> type);
}
}

```

`messageTemplate` is the value of the `message` attribute of the constraint declaration or provided to the `ConstraintValidatorContext` methods.

The `Context` object contains contextual information related to the interpolation.

`getConstraintDescriptor()` returns the `ConstraintDescriptor` object representing the metadata of the failing constraint (see [Constraint metadata request APIs](#)).

`getValidatedValue()` returns the value being validated.

`MessageInterpolator.interpolate(String, Context)` is invoked for each constraint violation report generated. The default `Locale` is implementation specific.

`MessageInterpolator.interpolate(String, Context, Locale)` can be invoked by a wrapping `MessageInterpolator` to enforce a specific `Locale` value by bypassing or overriding the default `Locale` strategy (see [Use MessageInterpolator to use a specific Locale value](#)).

A message interpolator implementation must be thread-safe.

The message interpolator is provided to the `ValidatorFactory` at construction time using `Configuration.messageInterpolator(MessageInterpolator)`. This message interpolator is shared by all `Validator` objects generated by this `ValidatorFactory`.

It is possible to override the `MessageInterpolator` implementation for a given `Validator` instance by invoking `ValidatorFactory.usingContext().messageInterpolator(messageInterpolator).getValidator()`.

It is recommended that `MessageInterpolator` implementations delegate final interpolation to the Bean Validation default `MessageInterpolator` to ensure standard Bean Validation interpolation rules are followed. The default implementation is accessible through `Configuration.getDefaultMessageInterpolator()`.

If the interpolation process leads to an exception, the exception is wrapped into a `ValidationException`.

### 6.3.3. Examples

These examples describe message interpolation based on the default message interpolator's built-in messages (see [Standard ResourceBundle messages](#)), and the [ValidationMessages.properties](#) file shown in table [message interpolation](#). The current locale is assumed English.

```
//ValidationMessages.properties  
myapp.creditcard.error=credit card number not valid
```

*Table 5. message interpolation*

Failing constraint declaration	interpolated message
@NotNull	must not be null
@Max(30)	must be less than or equal to 30
@Size(min=5, max=15, message="Key must have {{min}}-{{max}} characters")	Key must have {5} - {15} characters
@Digits(integer=9, fraction=2)	numeric value out of bounds (<9 digits>. <2 digits> expected)
@CreditCard(message={myapp.creditcard.error})	credit card number not valid

Here is an approach to specify the [Locale](#) value to choose on a given [Validator](#) using a [Locale aware MessageInterpolator](#). See [Bootstrapping](#) for more details on the APIs.

*Example 80. Use MessageInterpolator to use a specific Locale value*

```
/*
 * Delegates to a MessageInterpolator implementation but enforces a given
 * Locale
 */
public class LocaleSpecificMessageInterpolator implements
MessageInterpolator {
    private final MessageInterpolator defaultInterpolator;
    private final Locale defaultLocale;

    public LocaleSpecificMessageInterpolator(MessageInterpolator
interpolator, Locale locale) {
        this.defaultLocale = locale;
        this.defaultInterpolator = interpolator;
    }

    /**
     * enforces the locale passed to the interpolator
     */
    public String interpolate(String message,
                           Context context) {
        return defaultInterpolator.interpolate(message,
                                              context,
                                              this.defaultLocale);
    }

    // no real use, implemented for completeness
    public String interpolate(String message,
                           Context context,
                           Locale locale) {
        return defaultInterpolator.interpolate(message, context, locale);
    }
}

Locale locale = getMyCurrentLocale();
MessageInterpolator interpolator = new LocaleSpecificMessageInterpolator(
    validatorFactory
    .getMessageInterpolator(),
    locale);

Validator validator = validatorFactory.usingContext()
    .messageInterpolator(interpolator)
    .getValidator();
```

Most of the time, however, the relevant `Locale` will be provided by your application framework transparently. This framework will implement its own version of `MessageInterpolator` and pass it during the `ValidatorFactory` configuration. The application will not have to set the `Locale` itself. This example shows how a container framework would implement `MessageInterpolator` to provide a user specific default locale.

*Example 81. Contextual container possible **MessageInterpolator** implementation*

```
public class ContextualMessageInterpolator implements MessageInterpolator {
    private final MessageInterpolator delegate;

    public ContextualMessageInterpolator(MessageInterpolator delegate) {
        this.delegate = delegate;
    }

    public String interpolate(String message, Context context) {
        Locale locale = Container.getManager().getUserLocale();
        return this.delegate.interpolate(
            message, context, locale );
    }

    public String interpolate(String message, Context context, Locale
locale) {
        return this.delegate.interpolate(message, context, locale);
    }
}

//Build the ValidatorFactory
Configuration<?> configuration = Validation.byDefaultProvider().
configure();
ValidatorFactory factory = configuration
    .messageInterpolator(
        new ContextualMessageInterpolator(
            configuration.getDefaultMessageInterpolator() ) )
    .buildValidatorFactory();

//The container uses the factory to validate constraints using the
specific MessageInterpolator
Validator validator = factory.getValidator();
```

## 6.4. Triggering method validation

Bean Validation itself doesn't trigger the evaluation of method constraints. That is, just annotating any methods or constructors with parameter or return value constraints doesn't automatically enforce these constraints, just as annotating any fields or properties with bean constraints doesn't enforce these either.

Instead method constraints must be validated by invoking the appropriate methods on `javax.validation.executable.ExecutableValidator`. Typically this won't happen by manually calling these methods but rather automatically upon invocation of the constrained methods or constructors, using approaches and techniques such as CDI/EJB interceptors, aspect-oriented programming or dynamic proxies.

The validation of method / constructor constraints comprises the following steps:

- Intercept the method call to be validated
- Validate the parameter values provided by the method caller using `ExecutableValidator.validateParameters()` or `ExecutableValidator.validateConstructorParameters()`.
- If this validation yields a non-empty set of constraint violations, throw a `ConstraintViolationException` wrapping the violations. Otherwise proceed with the actual method invocation.
- Validate the result returned by the invoked method using `ExecutableValidator.validateReturnValue()` or `ExecutableValidator.validateConstructorReturnValue()`.
- If this validation yields a non-empty set of constraint violations, throw a `ConstraintViolationException` wrapping the violations. Otherwise return the invocation result to the method caller.

By throwing a `ConstraintViolationException` if either of the validation steps fails, it is ensured that the control flow

- only arrives at the method's body if the caller has satisfied the method's preconditions and
- only returns to the method caller if the method's postconditions are guaranteed.

By default, integrators intercept and validate methods hosting either a constraint or being marked for cascaded validation (`@Valid`) whether it be on the method itself or on any of its parameters. The `Default` group is used for validation out of the box.

Integrators are encouraged to use Bean Validation's metadata API to find whether or not a method or a constructor should be intercepted. This guarantees that XML descriptors as well as future mapping strategies are taken into account. Note that the metadata API does not take into account the fact that a method or constructor validation has been enabled or disabled by the techniques described in [Method and constructor validation](#).

Here is an example of what such metadata usage would be:

*Example 82. Using metadata API to figure out if method interception is required*

```
//For methods

// is there any constrained method on this type
// assuming we don't validate on getter execution
public boolean interceptMethods(Class<?> type) {
    return validator.getConstraintsForClass( type ).getConstrainedMethods(MethodType.NON_GETTER).size() > 0;
}

// is this method constrained
public boolean interceptMethod(Class<?> type, Method method) {
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    MethodDescriptor methodDescriptor = bean.getConstraintsForMethod(
        method.getName(), method.getParameterTypes() );
    return methodDescriptor != null;
}

// should method parameters be validated
public boolean requiresParametersValidation(Class<?> type, Method method)
{
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    MethodDescriptor methodDescriptor = bean.getConstraintsForMethod(
        method.getName(), method.getParameterTypes() );
    if ( methodDescriptor != null ) {
        return methodDescriptor.hasConstrainedParameters();
    }
    else {
        return false;
    }
}

// should method return value be validated?
public boolean requiresReturnValueValidation(Class<?> type, Method method) {
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    MethodDescriptor methodDescriptor = bean.getConstraintsForMethod(
        method.getName(), method.getParameterTypes() );
    if ( methodDescriptor != null ) {
        return methodDescriptor.hasConstrainedReturnValue();
    }
    else {
        return false;
    }
}
```

*Example 83. Using metadata API to figure out if constructor interception is required*

```
//For constructors

// is there any constrained constructor on this type
public <T> boolean interceptConstructors(Class<T> type) {
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    return bean.getConstrainedConstructors().size() > 0;
}

// is this constructor constrained
public <T> boolean interceptConstructor(Class<T> type, Constructor<T> ctor) {
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    ConstructorDescriptor constructorDescriptor = bean
        .getConstraintsForConstructor(
            ctor.getParameterTypes() );
    return constructorDescriptor != null;
}

// should constructor parameters be validated
public <T> boolean requiresParametersValidation(Class<T> type,
Constructor<T> ctor) {
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    ConstructorDescriptor constructorDescriptor = bean
        .getConstraintsForConstructor(
            ctor.getParameterTypes() );
    if ( constructorDescriptor != null ) {
        return constructorDescriptor.hasConstrainedParameters();
    }
    else {
        return false;
    }
}

// should constructor return value be validated?
public <T> boolean requiresReturnValueValidation(Class<T> type,
Constructor<T> ctor) {
    BeanDescriptor bean = validator.getConstraintsForClass( type );
    ConstructorDescriptor constructorDescriptor = bean
        .getConstraintsForConstructor(
            ctor.getName(),
            ctor.getParameterTypes()
        );
    if ( constructorDescriptor != null ) {
        return constructorDescriptor.hasConstrainedReturnValue();
    }
    else {
        return false;
    }
}
```

**NOTE**

Calls to the metadata API is likely only going to be needed during the initialization phase of the interception framework. Results can then be cached.

**NOTE**

Only methods or constructors intercepted by the underlying interception technology can be validated.

The integration technology must put the validation interceptor as late as possible (if not last) in the interception stack. In particular, validation of parameters should be done after the security and transaction start logic. Likewise, return value validation should be done before the transaction stop logic. Putting the validation interceptor as late as possible in the stack ensures this.

*Why have the validation interceptor after other interceptors?*

There are several reasons for delaying validation compared to other interceptors:

**NOTE**

- You don't want to start business code before security has been cleared
- You might need transaction support in your validations
- You want transaction to fail if the return value is invalid
- Generally speaking, it makes more sense to apply technical layers around the more business focused constraints

## 6.5. Bootstrapping

The bootstrapping API aims at providing a `ValidatorFactory` object which is used to create `Validator` instances. The bootstrap process is decoupled from the provider implementation initialization: a bootstrap implementation must be able to bootstrap any Bean Validation provider implementation. The bootstrap sequence has been designed to achieve several goals:

- plug multiple implementations
- choose a specific implementation
- extensibility: an application using a specific provider implementation can use specific configurations
- share and reuse of metadata across `Validators`
- leave as much freedom as possible to implementations
- provide integration mechanisms to Java EE (starting from version 6) and other containers
- type safety

The main artifacts involved in the bootstrap process are:

- **Validation**: API entry point. Lets you optionally define the Bean Validation provider targeted as well as a provider resolution strategy. `Validation` generates `Configuration`

objects and can bootstrap any provider implementation.

- **ValidationProvider**: contract between the bootstrap procedure and a Bean Validation provider implementation.
- **ValidationProviderResolver**: returns a list of all Bean Validation providers available in the execution context (generally the classpath).
- **Configuration**: collects the configuration details that will be used to build **ValidatorFactory**. A specific sub interface of **Configuration** must be provided by Bean Validation providers. This sub interface typically hosts provider specific configurations.
- **ValidatorFactory**: result of the bootstrap process. Build **Validator** instances from a given Bean Validation provider.
- **META-INF/validation.xml**: a configuration file Bean Validation users can use to customize the configuration of the default **ValidatorFactory**.

Let's first see the API in action through some examples before diving into the concrete definitions.

### 6.5.1. Examples

The most simple approach is to initialize the default Bean Validation provider or the one defined in the XML configuration file. The **ValidatorFactory** is then ready to provide **Validator** instances.

*Example 84. Simple Bean Validation bootstrap sequence*

```
ValidatorFactory factory = Validation.buildDefaultValidatorFactory();

//cache the factory somewhere
Validator validator = factory.getValidator();

//when the application shuts down, close ValidatorFactory
factory.close();
```

The **ValidatorFactory** object is thread-safe. Building **Validator** instances is typically a cheap operation. Building a **ValidatorFactory** is typically more expensive. Make sure to check your Bean Validation implementation documentation for more accurate details.

The second example shows how a container can customize aspects like message interpolation, constraint validator instantiation and others.

*Example 85. Customize message resolution, traversable resolver etc.*

```
//some customization from a container
ValidatorFactory factory = Validation
    .byDefaultProvider().configure()
        .messageInterpolator( new ContainerMessageInterpolator() )
        .constraintValidatorFactory( new
ContainerComponentConstraintValidatorFactory() )
            .traversableResolver( new JPAAwareTraversableResolver() )
            .parameterNameProvider( new
AnnotationBasedParameterNameProvider() )
                .clockProvider( new BatchJobClockProvider() )
                .addValueExtractor( new TableValueExtractor() )
                .addValueExtractor( new MultiMapValueExtractor() )
            .buildValidatorFactory();

//cache the factory somewhere
Validator validator = factory.getValidator();

//when the application shuts down, close ValidatorFactory
factory.close();
```

The third example shows how to bootstrap Bean Validation in an environment not following the traditional Java classloader strategies (such as tools or alternative service containers like OSGi). They can provide some alternative provider resolution strategy to discover Bean Validation providers.

*Example 86. Customize the Bean Validation provider resolution mechanism*

```
//osgi environment
ValidatorFactory factory = Validation
    .byDefaultProvider()
        .providerResolver( new OSGiServiceDiscoverer() )
        .configure()
    .buildValidatorFactory();

//cache the factory somewhere
Validator validator = factory.getValidator();

//when the bundle shuts down, close ValidatorFactory
factory.close();
```

The next example shows how a client can choose a specific Bean Validation provider and configure provider specific properties programmatically in a type-safe way.

*Example 87. Use a specific provider and add specific configuration*

```
ValidatorFactory factory = Validation
    .byProvider( ACMEProvider.class ) //choose a specific provider
    .configure()
        .messageInterpolator( new ContainerMessageInterpolator() )
//default configuration option
        .addConstraint(Address.class, customConstraintDescriptor)
//ACME specific method
        .buildValidatorFactory();

//same initialization decomposing calls
ACMEConfiguration acmeConfiguration = Validation
    .byProvider( ACMEProvider.class )
    .configure();

ValidatorFactory factory = acmeConfiguration
    .messageInterpolator( new ContainerMessageInterpolator() )
//default configuration option
    .addConstraint(Address.class, customConstraintDescriptor)
//ACME specific method
    .buildValidatorFactory();

< /**
 * ACME specific validator configuration and configuration options
 */
public interface ACMEConfiguration extends Configuration
<ACMEConfiguration> {
    /**
     * Programmatically add constraints. Specific to the ACME provider.
     */
    ACMEConfiguration addConstraint(Class<?> entity,
                                    ACMEConstraintDescriptor
constraintDescriptor);
}

< /**
 * ACME validation provider
 * Note how ACMEConfiguration and ACMEProvider are linked together
 * via the generic parameter.
 */
public class ACMEProvider implements ValidationProvider<
ACMEConfiguration> {
    [...]
}
```

The last example shows how a `Validator` can use a specific `MessageInterpolator` implementation.

*Example 88. Use a specific MessageInterpolator instance for a given Validator*

```
ValidatorFactory factory = [...];
MessageInterpolator customInterpolator = new
LocaleSpecificMessageInterpolator(
    locale,
    factory.getMessageInterpolator()
);

Validator localizedValidator =
factory.usingContext()
    .messageInterpolator(customInterpolator)
    .getValidator();
```

In the same way, a custom `TraversableResolver` can be passed.

We will now explore the various interfaces, their constraints and usage. We will go from the `ValidatorFactory` to the `Validation` class walking up the bootstrap chain.

### 6.5.2. ValidatorFactory

`ValidatorFactory` objects build and provide initialized instances of `Validator` to Bean Validation clients. Each `Validator` instance is configured for a given context (message interpolator, traversable resolver etc.). Clients should cache `ValidatorFactory` objects and reuse them for optimal performances. The API is designed to allow implementors to share constraint metadata in `ValidatorFactory`. `ValidatorFactory` instances must be closed (by calling the `close()` method) by its creator when no longer in use.

`ValidatorFactory` implementations must be thread-safe. `ValidatorFactory` implementations can cache `Validator` instances if needed.

*Example 89. ValidatorFactory interface*

```
/**
 * Factory returning initialized {@code Validator} instances.
 * <p>
 * Implementations are thread-safe and instances are typically cached and
reused.
 *
 * @author Emmanuel Bernard
 * @author Gunnar Morling
 * @author Hardy Ferentschik
 * @author Guillaume Smet
 */
public interface ValidatorFactory extends AutoCloseable {

    /**
     * Returns an initialized {@link Validator} instance using the
     * factory defaults for message interpolator, traversable resolver
```

```

* and constraint validator factory.
* <p>
* Validator instances can be pooled and shared by the
implementation.
*
* @return an initialized {@code Validator} instance
*/
Validator getValidator();

/**
* Defines a new validator context and returns a {@code Validator}
* compliant this new context.
*
* @return a {@link ValidatorContext} instance
*/
ValidatorContext usingContext();

/**
* Returns the {@link MessageInterpolator} instance configured at
* initialization time for the {@code ValidatorFactory}.
* This is the instance used by {@link #getValidator()}.
*
* @return {@code MessageInterpolator} instance
*/
MessageInterpolator getMessageInterpolator();

/**
* Returns the {@link TraversableResolver} instance configured
* at initialization time for the {@code ValidatorFactory}.
* This is the instance used by {@link #getValidator()}.
*
* @return {@code TraversableResolver} instance
*/
TraversableResolver getTraversableResolver();

/**
* Returns the {@link ConstraintValidatorFactory} instance
* configured at initialization time for the
* {@code ValidatorFactory}.
* This is the instance used by {@link #getValidator()}.
*
* @return {@code ConstraintValidatorFactory} instance
*/
ConstraintValidatorFactory getConstraintValidatorFactory();

/**
* Returns the {@link ParameterNameProvider} instance configured at
* initialization time for the {@code ValidatorFactory}.
* This is the instance used by #getValidator().
*
* @return {@code ParameterNameProvider} instance
*
* @since 1.1
*/
ParameterNameProvider getParameterNameProvider();

/**
* Returns the {@link ClockProvider} instance configured at
* initialization time for the {@code ValidatorFactory}.
* This is the instance used by #getValidator().
*/

```

```

/*
 * @return {@code ClockProvider} instance
 *
 * @since 2.0
 */
ClockProvider getClockProvider();

/**
 * Returns an instance of the specified type allowing access to
 * provider-specific APIs. If the Bean Validation provider
 * implementation does not support the specified class, a
 * {@code ValidationException} is thrown.
 *
 * @param type the class of the object to be returned
 * @param <T> the type of the object to be returned
 * @return an instance of the specified class
 * @throws ValidationException if the provider does not
 *         support the call.
 */
public <T> T unwrap(Class<T> type);

/**
 * Closes the {@code ValidatorFactory} instance.
 *
 * After the {@code ValidatorFactory} instance is closed, calling the
 * following
 * methods is not allowed:
 * <ul>
 *   <li>methods of this {@code ValidatorFactory} instance</li>
 *   <li>methods of {@link Validator} instances created by this
 *{@code ValidatorFactory}</li>
 * </ul>
 *
 * @since 1.1
 */
@Override
public void close();
}

```

A `ValidatorFactory` is provided by a `Configuration` object.

`unwrap()` is provided as a way to access objects of a given type specific to a Bean Validation provider typically as a complement to the `ValidatorFactory` contract. Using this method makes your code non portable.

*Example 90. Using unwrap to access a provider specific contract*

```

//if using the ACME provider
ACMEValidatorFactory acmeFactory = factory.unwrap(ACMEValidatorFactory
.class);
acmeFactory.setSpecificConfiguration( [...] );

```

`close()` closes the `ValidatorFactory` instance which becomes unavailable and should be immediately discarded. This is also true of all the `Validator` instances it has spawned. The behavior is undefined and non portable if these instances are used after the `ValidatorFactory` has been closed.

`getMessageInterpolator()` returns the `MessageInterpolator` instance configured during the initialization of the `ValidatorFactory`. It is particularly useful to build a `Validator` specific `MessageInterpolator` wrapping the one from the `ValidatorFactory`.

`getTraversableResolver()` returns the `TraversableResolver` instance configured during the initialization of the `ValidatorFactory`. It is particularly useful to build a `Validator` specific `TraversableResolver` wrapping the one from the `ValidatorFactory`.

`getConstraintValidatorFactory()` returns the `ConstraintValidatorFactory` instance configured during the initialization of the `ValidatorFactory`. It is particularly useful to build a `Validator` specific `ConstraintValidatorFactory` wrapping the one from the `ValidatorFactory`.

`getParameterNameProvider()` returns the `ParameterNameProvider` instance configured during the initialization of the `ValidatorFactory`. It is particularly useful to build a `Validator` specific `ParameterNameProvider` wrapping the one from the `ValidatorFactory`.

`getClockProvider()` returns the `ClockProvider` instance configured during the initialization of the `ValidatorFactory`. It is particularly useful to build a `Validator` specific `ClockProvider` wrapping the one from the `ValidatorFactory`.

`ValidatorContext` returned by `usingContext()` can be used to customize the state in which the `Validator` must be initialized. This is used to customize the `MessageInterpolator`, the `TraversableResolver`, the `ParameterNameProvider`, the `ClockProvider` or the `ConstraintValidatorFactory`.

*Example 91. ValidatorContext interface*

```
/**  
 * Represents the context that is used to create {@link Validator}  
 * instances.  
 *  
 * A client may use methods of the {@code ValidatorContext} returned by  
 * {@link ValidatorFactory#usingContext()} to customize  
 * the context used to create {@code Validator} instances  
 * (for instance establish different message interpolators or  
 * traversable resolvers).  
 *  
 * @author Emmanuel Bernard  
 * @author Gunnar Morling  
 * @author Guillaume Smet  
 */
```

```

public interface ValidatorContext {

    /**
     * Defines the message interpolator implementation used by the
     * {@link Validator}.
     * <p>
     * If not set or if {@code null} is passed as a parameter,
     * the message interpolator of the {@link ValidatorFactory}
     * is used.
     *
     * @param messageInterpolator the {@link MessageInterpolator} used by
     * the {@code Validator}
     *
     * @return self following the chaining method pattern
     */
    ValidatorContext messageInterpolator(MessageInterpolator
messageInterpolator);

    /**
     * Defines the traversable resolver implementation used by the
     * {@link Validator}.
     * <p>
     * If not set or if {@code null} is passed as a parameter,
     * the traversable resolver of the {@link ValidatorFactory} is used.
     *
     * @param traversableResolver the {@code TraversableResolver} used by
     * the {@code Validator}
     * @return self following the chaining method pattern
     */
    ValidatorContext traversableResolver(TraversableResolver
traversableResolver);

    /**
     * Defines the constraint validator factory implementation used by
     * the
     * {@link Validator}.
     * If not set or if {@code null} is passed as a parameter,
     * the constraint validator factory of the {@link ValidatorFactory}
     * is used.
     *
     * @param factory the {@link ConstraintValidatorFactory} used by the
     * {@code Validator}
     * @return self following the chaining method pattern
     */
    ValidatorContext constraintValidatorFactory
(ConstraintValidatorFactory factory);

    /**
     * Defines the parameter name provider implementation used by the
     * {@link Validator}. If not set or if {@code null} is passed as a
     * parameter,
     * the parameter name provider of the {@link ValidatorFactory} is
     * used.
     *
     * @param parameterNameProvider parameter name provider
     * implementation.
     * @return self following the chaining method pattern
     *
     * @since 1.1
     */
}

```

```

ValidatorContext parameterNameProvider(ParameterNameProvider
parameterNameProvider);

/**
 * Defines the {@link ClockProvider} implementation used by the
{@link Validator}.
 * If not set or if {@code null} is passed as a parameter,
 * the clock provider of the {@link ValidatorFactory} is used.
 *
 * @param clockProvider {@code ClockProvider} implementation
 * @return self following the chaining method pattern
 *
 * @since 2.0
 */
ValidatorContext clockProvider(ClockProvider clockProvider);

/**
 * Adds a value extractor to be used by the {@link Validator}. Has
 * priority over any extractor for the same type and type parameter
 * detected through the service loader, given in the XML
configuration or
 * configured for the validator factory.
 *
 * @param extractor value extractor implementation
 * @return self following the chaining method pattern
 * @throws ValueExtractorDeclarationException If more than one
extractor for
 *         the same type and type use is added
 * @since 2.0
 */
ValidatorContext addValueExtractor(ValueExtractor<?> extractor);

/**
 * Returns an initialized {@link Validator} instance respecting the
defined state.
 * {@code Validator} instances can be pooled and shared by the
implementation.
 *
 * @return contextualized {@code Validator}
 */
Validator getValidator();
}

```

The `MessageInterpolator`, the `TraversableResolver`, the `ConstraintValidatorFactory`, the `ParameterNameProvider` or the `ClockProvider` passed to the `ValidatorContext` are used instead of the `ValidatorFactory`'s `MessageInterpolator`, `TraversableResolver`, `ConstraintValidatorFactory`, `ParameterNameProvider` or `ClockProvider` instances.

#### Example 92. Use of ValidatorFactory

```
ValidatorFactory factory = [...];
Validator validatorUsingDefaults = factory.getValidator();
Validator validatorUsingCustomTraversable = factory
    .usingContext()
    .traversableResolver( new JPATraversableResolver() )
    .getValidator();
```

See [Use MessageInterpolator to use a specific Locale value](#) for an example using `ValidatorFactory.getMessageInterpolator()`.

### 6.5.3. Configuration

The responsibility of the `Configuration` is to collect configuration information, to determine the correct provider implementation and to delegate the `ValidatorFactory` creation to the selected provider. More concretely `Configuration` lets you define:

- the message interpolator instance
- the traversable resolver instance
- the constraint validator factory instance
- the parameter name provider instance
- the clock provider instance
- value extractor instances
- XML constraint mappings
- provider specific properties
- whether or not `META-INF/validation.xml` is considered

`Configuration` does provide a `MessageInterpolator` implementation following the default Bean Validation `MessageInterpolator` rules as defined in [Default message interpolation](#). You can access it by calling `getDefaultMessageInterpolator()`. Such an implementation is useful to let a custom `MessageInterpolator` delegate to the standard `MessageInterpolator` (see [Custom message interpolation](#) and an example making use of `getDefaultMessageInterpolator()` in [Contextual container possible MessageInterpolator implementation](#)).

`Configuration` does provide a `TraversableResolver` implementation following the default Bean Validation `TraversableResolver` rules as defined in [Traversable property](#). You can access it by calling `getDefaultTraversableResolver()`. Such an implementation is useful to let a custom `TraversableResolver` delegate to the standard `TraversableResolver`.

`Configuration` does provide a `ConstraintValidatorFactory` implementation following the default Bean Validation `ConstraintValidatorFactory` rules as defined in [The ConstraintValidatorFactory](#). You can access it by calling `getDefaultConstraintValidatorFactory()`. Such an implementation is useful to let a custom `ConstraintValidatorFactory` delegate to the standard `ConstraintValidatorFactory`.

`Configuration` does provide a `ParameterNameProvider` implementation following the default Bean Validation `ParameterNameProvider` rules as defined in [Naming parameters](#). You can access it by calling `getDefaultParameterNameProvider()`. Such an implementation is useful to let a custom `ParameterNameProvider` delegate to the standard `ParameterNameProvider`.

`Configuration` does provide a `ClockProvider` implementation following the default Bean Validation `ClockProvider` rules as defined in [Implementation of temporal constraint validators](#). You can access it by calling `getDefaultClockProvider()`.

Via `getBootstrapConfiguration()`, `Configuration` also exposes data stored in `META-INF/validation.xml` (see [XML configuration: META-INF/validation.xml](#)). This is particularly useful for containers wishing to control the instance creation and lifecycle (more information at [Bootstrapping considerations](#)).

**NOTE**

`BootstrapConfiguration.getDefaultValidatedExecutableTypes()` and `BootstrapConfiguration.isExecutableValidationEnabled()` are not used by the Bean Validation engine but exposed here for interception technologies - see [Method and constructor validation](#).

Via `addValueExtractor()`, additional value extractor implementations can be added to the configuration. A value extractor for a given type and type parameter takes precedence over any extractor for the same type and type parameter detected through the service loader or given in the XML configuration.

Using `addMapping()`, additional constraint mapping XML descriptors can be added to the configuration (see [XML configuration: META-INF/validation.xml](#)). The given input streams should support the `mark()` and `reset()` methods defined by `java.io.InputStream`. Streams not supporting the `mark()` and `reset()` methods will be wrapped with an `InputStream` implementation supporting these methods by the Bean Validation provider in order to allow the streams to be read several times.

Clients call `Configuration.buildValidatorFactory()` to retrieve the initialized `ValidatorFactory` instance. It is legal to invoke `buildValidatorFactory()` several times, e.g. in order to retrieve several `ValidatorFactory` instances with a slightly different configuration (see [Using Configuration to create several validator factories](#)).

*Example 93. Configuration and BootstrapConfiguration interfaces*

```

/**
 * Receives configuration information, selects the appropriate
 * Bean Validation provider and builds the appropriate {@link
ValidatorFactory}.
* <p>
* Usage:
* <pre>
* Configuration<?> configuration = //provided by one of the
Validation bootstrap methods
*     ValidatorFactory = configuration
*         .messageInterpolator( new CustomMessageInterpolator() )
*         .buildValidatorFactory();
* </pre>
* <p>
* By default, the configuration information is retrieved from
* {@code META-INF/validation.xml}.
* It is possible to override the configuration retrieved from the XML
file
* by using one or more of the {@code Configuration} methods.
* <p>
* The {@link ValidationProviderResolver} is specified at configuration
time
* (see {@link ValidationProvider}).
* If none is explicitly requested, the default {@code
ValidationProviderResolver} is used.
* <p>
* The provider is selected in the following way:
* <ul>
*     <li>if a specific provider is requested programmatically using
*         {@link Validation#byProvider(Class)}, find the first provider
implementing
*             the provider class requested and use it</li>
*     <li>if a specific provider is requested in {@code META-
INF/validation.xml},
*         find the first provider implementing the provider class requested
and use it</li>
*     <li>otherwise, use the first provider returned by the {@code
ValidationProviderResolver}</li>
* </ul>
* <p>
* Implementations are not meant to be thread-safe.
*
* @author Emmanuel Bernard
* @author Gunnar Morling
* @author Hardy Ferentschik
* @author Guillaume Smet
*/
public interface Configuration<T extends Configuration<T>> {

    /**
     * Ignores data from the {@code META-INF/validation.xml} file if this
     * method is called.
     * <p>
     * This method is typically useful for containers that parse
     * {@code META-INF/validation.xml} themselves and pass the
information
     * via the {@code Configuration} methods.
     *
     * @return {@code this} following the chaining method pattern.
*/

```

```

T ignoreXmlConfiguration();

/**
 * Defines the message interpolator used. Has priority over the
configuration
 * based message interpolator.
 * <p>
 * If {@code null} is passed, the default message interpolator is
used
 * (defined in XML or the specification default).
 *
 * @param interpolator message interpolator implementation
 * @return {@code this} following the chaining method pattern
 */
T messageInterpolator(MessageInterpolator interpolator);

/**
 * Defines the traversable resolver used. Has priority over the
configuration
 * based traversable resolver.
 * <p>
 * If {@code null} is passed, the default traversable resolver is
used
 * (defined in XML or the specification default).
 *
 * @param resolver traversable resolver implementation
 * @return {@code this} following the chaining method pattern
 */
T traversableResolver(TraversableResolver resolver);

/**
 * Defines the constraint validator factory. Has priority over the
configuration
 * based constraint factory.
 * <p>
 * If {@code null} is passed, the default constraint validator
factory is used
 * (defined in XML or the specification default).
 *
 * @param constraintValidatorFactory constraint factory
implementation
 * @return {@code this} following the chaining method pattern
 */
T constraintValidatorFactory(ConstraintValidatorFactory
constraintValidatorFactory);

/**
 * Defines the parameter name provider. Has priority over the
configuration
 * based provider.
 * <p>
 * If {@code null} is passed, the default parameter name provider is
used
 * (defined in XML or the specification default).
 *
 * @param parameterNameProvider parameter name provider
implementation
 * @return {@code this} following the chaining method pattern.
 *
 * @since 1.1

```

```

/*
T parameterNameProvider(ParameterNameProvider parameterNameProvider);

/**
 * Defines the clock provider. Has priority over the configuration
 * based provider.
 * <p>
 * If {@code null} is passed, the default clock provider is used
 * (defined in XML or the specification default).
 *
 * @param clockProvider clock provider implementation
 * @return {@code this} following the chaining method pattern.
 *
 * @since 2.0
*/
T clockProvider(ClockProvider clockProvider);

/**
 * Adds a value extractor. Has priority over any extractor for the
same
 * type and type parameter detected through the service loader or
given in
 * the XML configuration.
 *
 * @param extractor value extractor implementation
 * @return {@code this} following the chaining method pattern.
 * @throws ValueExtractorDeclarationException If more than one
extractor for
 *          the same type and type use is added
 * @since 2.0
*/
T addValueExtractor(ValueExtractor<?> extractor);

/**
 * Add a stream describing constraint mapping in the Bean Validation
XML
 * format.
 * <p>
 * The stream should be closed by the client API after the
 * {@link ValidatorFactory} has been built. The Bean Validation
provider
 * must not close the stream.
 *
 * @param stream
 *          XML mapping stream; the given stream should support the
 *          mark/reset contract (see {@link
InputStream#markSupported()});
 *          if it doesn't, it will be wrapped into a stream supporting
the
 *          mark/reset contract by the Bean Validation provider
 *
 * @return {@code this} following the chaining method pattern
 * @throws IllegalArgumentException if {@code stream} is null
*/
T addMapping(InputStream stream);

/**
 * Adds a provider specific property. This property is equivalent to
 * XML configuration properties.
 * If the underlying provider does not know how to handle the

```

```

property,
    * it must silently ignore it.
    * <p>
    * Note: Using this non type-safe method is generally not
recommended.
    * <p>
    * It is more appropriate to use, if available, the type-safe
equivalent provided
    * by a specific provider via its {@link Configuration} subclass.
    * <pre>
    * ValidatorFactory factory =
Validation.byProvider(ACMEProvider.class)
    *     .configure()
    *         .providerSpecificProperty(ACMESTate.FAST)
    *         .buildValidatorFactory();
    * </pre>
    * This method is typically used by containers parsing {@code META-
INF/validation.xml}
    * themselves and injecting the state to the {@code Configuration}
object.
    * <p>
    * If a property with a given name is defined both via this method
and in the
    * XML configuration, the value set programmatically has priority.
    * <p>
    * If {@code null} is passed as a value, the value defined in XML is
used. If no value
    * is defined in XML, the property is considered unset.
    *
    * @param name property name
    * @param value property value
    * @return {@code this} following the chaining method pattern
    * @throws IllegalArgumentException if {@code name} is null
    */
T addProperty(String name, String value);

/**
 * Returns an implementation of the {@link MessageInterpolator}
interface
    * following the default {@code MessageInterpolator} defined in the
    * specification:
    * <ul>
    *     <li>use the {@code ValidationMessages} resource bundle to load
keys</li>
    *     <li>use {@code Locale.getDefault()}</li>
    * </ul>
    *
    * @return default {@code MessageInterpolator} implementation
compliant with the
    * specification
    */
MessageInterpolator getDefaultMessageInterpolator();

/**
 * Returns an implementation of the {@link TraversableResolver}
interface
    * following the default {@code TraversableResolver} defined in the
    * specification:
    * <ul>
    *     <li>if Java Persistence is available in the runtime

```

```

environment,
    *      a property is considered reachable if Java Persistence
considers
        *      the property as loaded</li>
        *      <li>if Java Persistence is not available in the runtime
environment,
            *      all properties are considered reachable</li>
            *      <li>all properties are considered cascadable.</li>
        * </ul>
        *
        * @return default {@code TraversableResolver} implementation
compliant with the
        *      specification
    */
TraversableResolver getDefaultTraversableResolver();

/**
 * Returns an implementation of the {@link
ConstraintValidatorFactory} interface
 * following the default {@code ConstraintValidatorFactory} defined
in the
    * specification:
    * <ul>
        *      <li>uses the public no-arg constructor of the {@link
ConstraintValidator}</li>
    * </ul>
    *
    * @return default {@code ConstraintValidatorFactory} implementation
compliant with the
    *      specification
*/
ConstraintValidatorFactory getDefaultConstraintValidatorFactory();

/**
 * Returns an implementation of the {@link ParameterNameProvider}
 * interface following the default {@code ParameterNameProvider}
 * defined in the specification:
 * <ul>
    *      <li>returns the actual parameter names as provided in the
validated
        *      executable's definition, if the class file of the executable
contains
            *      parameter name information</li>
            *      <li>
                *      otherwise returns names in the form {@code
arg<lt;PARAMETER_INDEX>>},
                    *      where {@code PARAMETER_INDEX} starts at 0 for the first
parameter,
                    *      e.g. {@code arg0}, {@code arg1} etc.</li>
            * </ul>
            *
            * @return default {@code ParameterNameProvider} implementation
compliant with
            *      the specification
            *
            * @since 1.1
    */
ParameterNameProvider getDefaultParameterNameProvider();

/**

```

```

    * Returns an implementation of the {@link ClockProvider}
    * interface following the default {@code ClockProvider}
    * defined in the specification:
    * <ul>
    *   <li>returns a clock representing the current system time and
default time
    *     zone.</li>
    * </ul>
    *
    * @return default {@code ClockProvider} implementation compliant
with
    *       the specification
    *
    * @since 2.0
    */
ClockProvider getDefaultClockProvider();

/**
 * Returns configuration information stored in the {@code META-
INF/validation.xml} file.
 * <p>
 * <b>Note</b>:
 * <br>
 * Implementations are encouraged to lazily build this object to
delay parsing.
 *
 * @return returns an instance of {@link BootstrapConfiguration};
this method never
    *       returns {@code null}; if there is no {@code META-
INF/validation.xml} the
    *       different getters of the returned instance will return
{@code null}
    *       respectively an empty set or map
    *
    * @since 1.1
    */
BootstrapConfiguration getBootstrapConfiguration();

/**
 * Build a {@link ValidatorFactory} implementation.
 *
 * @return the {@code ValidatorFactory}
 * @throws ValidationException if the {@code ValidatorFactory} cannot
be built
 */
ValidatorFactory buildValidatorFactory();
}

```

```

/**
 * Represents the user specified default configuration in
 * {@code META-INF/validation.xml}.
 * <p>
 * Note that modifications to the returned objects do not have any
effect.
 * Instead use the methods provided on {@link Configuration} in order to
 * apply modifications to the configuration.
 *
 * @author Emmanuel Bernard

```

```

 * @author Gunnar Morling
 * @author Hardy Ferentschik
 * @author Guillaume Smet
 * @since 1.1
 */
public interface BootstrapConfiguration {

    /**
     * Class name of the {@link ValidationProvider} implementation
     * or {@code null} if none is specified.
     *
     * @return validation provider class name
     */
    String getDefaultProviderClassName();

    /**
     * Class name of the {@link ConstraintValidatorFactory}
     * implementation
     * or {@code null} if none is specified.
     *
     * @return constraint validator factory class name
     */
    String getConstraintValidatorFactoryClassName();

    /**
     * Class name of the {@link MessageInterpolator} implementation
     * or {@code null} if none is specified.
     *
     * @return message interpolator class name or {@code null}
     */
    String getMessageInterpolatorClassName();

    /**
     * Class name of the {@link TraversableResolver} implementation
     * or {@code null} if none is specified.
     *
     * @return traversable resolver class name or {@code null}
     */
    String getTraversableResolverClassName();

    /**
     * Class name of the {@link ParameterNameProvider} implementation
     * or {@code null} if none is specified.
     *
     * @return parameter name provider class name or {@code null}
     */
    String getParameterNameProviderClassName();

    /**
     * Class name of the {@link ClockProvider} implementation or
     * {@code null} if none is specified.
     *
     * @return clock provider class name or {@code null}
     *
     * @since 2.0
     */
    String getClockProviderClassName();

    /**
     * Returns the class names of {@link ValueExtractor}s.

```

```

/*
 * @return the value extractor class names or an empty set if none
are specified
 * @since 2.0
 */
Set<String> getValueExtractorClassNames();

/**
 * Returns a set of resource paths pointing to XML constraint mapping
files.
 * The set is empty if none are specified.
 *
 * @return set of constraint mapping resource paths
 */
Set<String> getConstraintMappingResourcePaths();

/**
 * Returns true if the validation execution is explicitly marked as
enabled
 * or if it is left undefined.
 *
 * @return whether validation execution is globally enabled
 */
boolean isExecutableValidationEnabled();

/**
 * Returns the set of executable types that should be considered
 * unless explicitly overridden via {@link ValidateOnExecution}
 * <p>
 * Returns a set containing {@link ExecutableType#CONSTRUCTORS} and
 * {@link ExecutableType#NON_GETTER_METHODS} if unspecified in the
configuration.
 *
 * @return set of validated executable types
 */
Set<ExecutableType> getDefaultValidatedExecutableTypes();

/**
 * Returns properties as a map of string based key/value pairs.
 * The map is empty if no property has been specified.
 *
 * @return the properties map
 */
Map<String, String> getProperties();
}

```

A Bean Validation provider must define a sub interface of `Configuration` uniquely identifying the provider. This subclass is linked to its provider via the `ValidationProvider` generic parameter. The `Configuration` sub interface typically hosts provider specific configuration methods.

To facilitate the use of provider specific configuration methods, `Configuration` uses generics: `Configuration<T extends Configuration<T>>`; the generic return type `T` is returned by chaining methods. The provider specific sub interface must resolve the generic `T` as itself as shown in [Example of provider specific Configuration sub interface](#).

*Example 94. Example of provider specific Configuration sub interface*

```
/**  
 * Unique identifier of the ACME provider  
 * also hosts some provider specific configuration methods  
 */  
public interface ACMEConfiguration  
    extends Configuration<ACMEConfiguration> {  
  
    /**  
     * Enables constraints implementation dynamic reloading when using  
     ACME  
     * default to false  
     */  
    ACMEConfiguration enableDynamicReloading(boolean);  
}
```

When `Configuration.buildValidatorFactory()` is called, the initialized `ValidatorFactory` is returned. More specifically, the requested Bean Validation provider is determined and the result of `validationProvider.buildValidatorFactory(ConfigurationState)` is returned. `ConfigurationState` gives access to the configuration artifacts defined in `META-INF/validation.xml` (unless XML configuration is ignored) and provided programmatically to `Configuration`. Generally speaking, programmatically defined elements have priority over XML defined configuration elements (read the `Configuration` JavaDoc and see `XML configuration: META-INF/validation.xml` for more information).

**NOTE** A typical implementation of `Configuration` also implements `ConfigurationState`, hence `this` can be passed to `buildValidatorFactory(ConfigurationState)`.

Streams represented in the XML configuration and opened by the `Configuration` implementation must be closed by the `Configuration` implementation after the `ValidatorFactory` creation (or if an exception occurs). Streams provided programmatically are the responsibility of the application.

*Example 95. ConfigurationState interface*

```
package javax.validation.spi;  
  
/**  
 * Contract between a {@link Configuration} and a  
 * {@link ValidationProvider} to create a {@link ValidatorFactory}.  
 * <p>  
 * The configuration artifacts defined in the XML configuration and  
 provided to the
```

```

* {@code Configuration} are merged and passed along via
* {@code ConfigurationState}.
*
* @author Emmanuel Bernard
* @author Hardy Ferentschik
* @author Gunnar Morling
* @author Guillaume Smet
*/
public interface ConfigurationState {

    /**
     * Returns {@code true} if {@link Configuration#ignoreXmlConfiguration()} has been called.
     * <p>
     * In this case, the {@link ValidatorFactory} must ignore
     * {@code META-INF/validation.xml}.
     *
     * @return {@code true} if {@code META-INF/validation.xml} should be
     ignored
     */
    boolean isIgnoreXmlConfiguration();

    /**
     * Returns the message interpolator of this configuration.
     * <p>
     * Message interpolator is defined in the following decreasing
     priority:
     * <ul>
     *   <li>set via the {@link Configuration} programmatic API</li>
     *   <li>defined in {@code META-INF/validation.xml} provided that
     *   {@code ignoreXmlConfiguration} is false. In this case the
     instance
     *   is created via its no-arg constructor.</li>
     *   <li>{@code null} if undefined.</li>
     * </ul>
     *
     * @return message interpolator instance or {@code null} if not
     defined
     */
    MessageInterpolator getMessageInterpolator();

    /**
     * Returns a set of configuration streams.
     * <p>
     * The streams are defined by:
     * <ul>
     *   <li>mapping XML streams passed programmatically in {@link Configuration}</li>
     *   <li>mapping XML streams located in the resources defined in
     *   {@code META-INF/validation.xml} (constraint-mapping
     element)</li>
     * </ul>
     * <p>
     * Streams represented in the XML configuration and opened by the
     * {@code Configuration} implementation must be closed by the
     * {@code Configuration} implementation after the {@link
     ValidatorFactory}
     * creation (or if an exception occurs). All streams are guaranteed
     to
     * adhere to the mark/reset contract (see {@link

```

```

InputStream#markSupported())
    * by the Bean Validation provider.
    *
    * @return set of input stream
    */
Set<InputStream> getMappingStreams();

/**
 * Returns a set of value extractors.
 * <p>
 * The extractors are retrieved from the following sources in
decreasing
 * order:
 * <ul>
 *      <li>extractors passed programmatically to {@link
Configuration}</li>
 *      <li>extractors defined in {@code META-INF/validation.xml}
provided
 *          * that {@code ignoredXmlConfiguration} is {@code false}</li>
 *          * <li>extractors loaded through the Java service loader</li>
 *      </ul>
 * An extractor for a given type and type parameter passed in
 * programmatically takes precedence over any extractor for the same
type
 * and type parameter defined in {@code META-INF/validation.xml} or
loaded
 * through the service loader. Extractors defined in
 * {@code META-INF/validation.xml} take precedence over any extractor
for
 * the same type and type parameter loaded through the service
loader.
 * <p>
 * Extractors defined in {@code META-INF/validation.xml} or loaded
through
 * the service loader are instantiated using their no-arg
constructor.
 *
 * @return set of value extractors; may be empty but never {@code
null}
 */
Set<ValueExtractor<?>> getValueExtractors();

/**
 * Returns the constraint validator factory of this configuration.
 * <p>
 * The {@link ConstraintValidatorFactory} implementation is defined
in the following
 * decreasing priority:
 * <ul>
 *      <li>set via the {@link Configuration} programmatic API</li>
 *      <li>defined in {@code META-INF/validation.xml} provided that
 *          {@code ignoredXmlConfiguration} is {@code false}. In this case
the instance
 *          * is created via its no-arg constructor.</li>
 *          * {@code null} if undefined.</li>
 *      </ul>
 *
 * @return factory instance or {@code null} if not defined
 */
ConstraintValidatorFactory getConstraintValidatorFactory();

```

```

/**
 * Returns the traversable resolver for this configuration.
 * <p>
 * {@link TraversableResolver} is defined in the following decreasing
priority:
* <ul>
*   <li>set via the {@link Configuration} programmatic API</li>
*   <li>defined in {@code META-INF/validation.xml} provided that
*   {@code ignoreXmlConfiguration} is {@code false}. In this case
the
*     instance is created via its no-arg constructor.</li>
*     <li>{@code null} if undefined.</li>
* </ul>
*
* @return traversable resolver instance or {@code null} if not
defined
*/
TraversableResolver getTraversableResolver();

/**
 * Returns the parameter name provider for this configuration.
 * <p>
 * {@link ParameterNameProvider} is defined in the following
decreasing priority:
* <ul>
*   <li>set via the {@link Configuration} programmatic API</li>
*   <li>defined in {@code META-INF/validation.xml} provided that
*   {@code ignoreXmlConfiguration} is {@code false}. In this case
the instance
*     is created via its no-arg constructor.</li>
*     <li>{@code null} if undefined.</li>
* </ul>
*
* @return parameter name provider instance or {@code null} if not
defined
*
* @since 1.1
*/
ParameterNameProvider getParameterNameProvider();

/**
 * Returns the clock provider for this configuration.
 * <p>
 * {@link ClockProvider} is defined in the following decreasing
priority:
* <ul>
*   <li>set via the {@link Configuration} programmatic API</li>
*   <li>defined in {@code META-INF/validation.xml} provided that
*   {@code ignoreXmlConfiguration} is {@code false}. In this case
the instance
*     is created via its no-arg constructor.</li>
*     <li>{@code null} if undefined.</li>
* </ul>
*
* @return clock provider instance or {@code null} if not defined
*
* @since 2.0
*/
ClockProvider getClockProvider();

```

```

    /**
     * Returns a map of non type-safe custom properties.
     * <p>
     * Properties defined via:
     * <ul>
     *   <li>{@link Configuration#addProperty(String, String)}</li>
     *   <li>{@code META-INF/validation.xml} provided that
     *       {@code ignoreXmlConfiguration} is {@code false}.</li>
     * </ul>
     * <p>
     * If a property is defined both programmatically and in XML,
     * the value defined programmatically has priority.
     *
     * @return {@code Map} whose key is the property key and the value
     *         the property value
     */
    Map<String, String> getProperties();
}

```

The requested provider implementation is resolved according to the following rules in the following order:

- Use the provider implementation requested if `Configuration` has been created from `Validation.byProvider(Class)`.
- Use the provider implementation described in the XML configuration (under `validation-config.default-provider` see [XML configuration: META-INF/validation.xml](#)) if defined: the value of this element is the fully qualified class name of the `ValidationProvider` implementation uniquely identifying the provider.
- Use the first provider implementation returned by `validationProviderResolver.getValidationProviders()`.

The `ValidationProviderResolver` is specified when `Configuration` instances are created (see `ValidationProvider`). If no `ValidationProviderResolver` instance has been specified, the default `ValidationProviderResolver` is used.

`Configuration` instances are provided to the Bean Validation client through the `Validation` methods. `Configuration` instances are created by `ValidationProvider`.

If a problem occurs while building the `ValidatorFactory`, a `ValidationException` is raised. This can be due to various reasons including:

- malformed XML configuration
- malformed XML mapping
- inability to find the provider (or a provider)
- inability to instantiate extension classes provided in the XML configuration

- inconsistent XML mapping (entity declared more than once, incorrect field etc.)
- invalid constraint declaration or definition

Other exception causes may occur.

Here is an example of **Configuration** use.

*Example 96. Use Configuration*

```
Configuration<?> configuration = [...];
ValidatorFactory factory = configuration
    .messageInterpolator( new WBMessageInterpolator() )
    .traversableResolver( new JPAAwareTraversableResolver() )
    .buildValidatorFactory();
```

The following shows an example of setting up a **Configuration**, retrieving a validator factory from it, subsequently altering the configuration and then retrieving another factory:

*Example 97. Using Configuration to create several validator factories*

```
Configuration<?> configuration = [...];
ValidatorFactory factory1 = configuration
    .messageInterpolator( new WBMessageInterpolator() )
    .buildValidatorFactory();

ValidatorFactory factory2 = configuration
    .traversableResolver( new JPAAwareTraversableResolver() )
    .buildValidatorFactory();
```

Here, **factory1** is set up using a custom message interpolator, while **factory2** is set up using the same message interpolator and additionally using a custom traversable resolver.

## 6.5.4. ValidationProvider and ValidationProviderResolver

**ValidationProvider** is the contract between the bootstrap process and a specific Bean Validation provider. **ValidationProviderResolver** implements the discovery mechanism for Bean Validation provider implementations. Any Bean Validation client can implement such a discovery mechanism but it is typically implemented by containers having specific classloader structures and restrictions.

### 6.5.4.1. ValidationProviderResolver

**ValidationProviderResolver** returns the list of Bean Validation providers available at runtime and more specifically a **ValidationProvider** instance for each provider available in

the context. This service can be customized by implementing `ValidationProviderResolver`. Implementations must be thread-safe.

*Example 98. ValidationProviderResolver*

```
/*
 * Determines the list of Bean Validation providers available in the
runtime environment
* <p>
* Bean Validation providers are identified by the presence of
* {@code META-INF/services/javax.validation.spi.ValidationProvider}
* files following the Service Provider pattern described
* <a href="http://docs.oracle.com/javase/6/docs/technotes/guides/jar/jar.html#Service%20Provider">here</a>.
* <p>
* Each {@code META-INF/services/javax.validation.spi.ValidationProvider}
file contains the list of
* {@link ValidationProvider} implementations each of them representing a
provider.
* <p>
* Implementations must be thread-safe.
*
* @author Emmanuel Bernard
*/
public interface ValidationProviderResolver {

    /**
     * Returns a list of {@link ValidationProvider} available in the
runtime environment.
     *
     * @return list of validation providers
     */
    List<ValidationProvider<?>> getValidationProviders();
}
```

By default, providers are resolved using the Service Provider pattern described in <http://docs.oracle.com/javase/6/docs/technotes/guides/jar/jar.html#Service%20Provider>. Bean Validation providers must supply a service provider configuration file by creating a text file `javax.validation.spi.ValidationProvider` and placing it in the `META-INF/services` directory of one of its jar files. The content of the file contains the name of the provider implementation class of the `javax.validation.spi.ValidationProvider` interface.

Bean Validation provider jars may be installed or made available in the same ways as other service providers, e.g. as extensions or added to the application classpath according to the guidelines in the JAR file specification.

The default `ValidationProviderResolver` implementation will locate all the Bean Validation providers by their provider configuration files visible in the classpath. The default `ValidationProviderResolver` implementation is recommended and custom `ValidationProviderResolver` implementations should be rarely used. A typical use of a

custom resolution is resolving providers in a classloader constrained container like OSGi or in a tool environment (IDE).

The default `ValidationProviderResolver` can be accessed via `BootStrapState.getDefaultValidationProviderResolver()`. This method is typically used by the Bean Validation provider `Configuration` implementation.

#### 6.5.4.2. ValidationProvider

`ValidationProvider` represents the SPI (Service Provider Interface) defining the contract between the provider discovery and initialization mechanism, and the provider. A `ValidationProvider` does:

- Provide a generic `Configuration` implementation (i.e. not tied to a given provider).
- Provide a provider specific `Configuration` implementation. This `Configuration` will specifically build `ValidatorFactory` instances of the provider it comes from.
- Build a `ValidatorFactory` object from the configuration provided by `ConfigurationState`.

*Example 99. ValidationProvider*

```
package javax.validation.spi;

/**
 * Contract between the validation bootstrap mechanism and the provider
 * engine.
 * <p>
 * Implementations must have a public no-arg constructor. The
 * construction of a provider
 * should be as "lightweight" as possible.
 *
 * {@code T} represents the provider specific Configuration subclass
 * which typically host provider's additional configuration methods.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 */
public interface ValidationProvider<T extends Configuration<T>> {

    /**
     * Returns a {@link Configuration} instance implementing {@code T},
     * the {@code Configuration} sub-interface.
     * The returned {@code Configuration} instance must use the current
     * provider
     * ({@code this}) to build the {@code ValidatorFactory} instance.
     *
     * @param state bootstrap state
     * @return specific {@code Configuration} implementation
     */
    T createSpecializedConfiguration(BootstrapState state);

    /**

```

```

    * Returns a {@link Configuration} instance. This instance is not
bound to
    * use the current provider. The choice of provider follows the
algorithm described
    * in {@code Configuration}
    * <p>
    * The {@link ValidationProviderResolver} used by {@code
Configuration}
    * is provided by {@code state}.
    * If null, the default {@code ValidationProviderResolver} is used.
    *
    * @param state bootstrap state
    * @return non specialized Configuration implementation
    */
Configuration<?> createGenericConfiguration(BootstrapState state);

/**
 * Build a {@link ValidatorFactory} using the current provider
implementation.
 * <p>
 * The {@code ValidatorFactory} is assembled and follows the
configuration passed
 * via {@link ConfigurationState}.
 * <p>
 * The returned {@code ValidatorFactory} is properly initialized and
ready for use.
 *
 * @param configurationState the configuration descriptor
 * @return the instantiated {@code ValidatorFactory}
 * @throws ValidationException if the {@code ValidatorFactory} cannot
be built
 */
ValidatorFactory buildValidatorFactory(ConfigurationState
configurationState);
}

```

*Example 100. BootstrapState interface*

```
package javax.validation.spi;

/**
 * Defines the state used to bootstrap the {@link Configuration}.
 *
 * @author Emmanuel Bernard
 * @author Sebastian Thomschke
 */
public interface BootstrapState {

    /**
     * User defined {@code ValidationProviderResolver} strategy
     * instance or {@code null} if undefined.
     *
     * @return ValidationProviderResolver instance or null
     */
    ValidationProviderResolver getValidationProviderResolver();

    /**
     * Specification default {@code ValidationProviderResolver}
     * strategy instance.
     *
     * @return default implementation of ValidationProviderResolver
     */
    ValidationProviderResolver getDefaultValidationProviderResolver();
}
```

A client can request a specific Bean Validation provider by using `<T extends Configuration<T>, U extends ValidationProvider<T>>` `Validation.byProvider(Class<U>)` or by defining the provider in the XML configuration file. The key uniquely identifying a Bean Validation provider is the `ValidationProvider` implementation specific to this provider.

A `ValidationProvider` implementation is linked (via its generic parameter) to a specific sub interface of `Configuration`. The Bean Validation bootstrap API makes use of this link to return the specific `Configuration` subinterface implementation in a type-safe way when a specific provider is requested. The sub interface does not have to add any new methods but is the natural holder for provider specific configuration methods.

*Example 101. Example of provider specific Configuration sub interface*

```
/**  
 * Unique identifier of the ACME provider  
 * also hosts some provider specific configuration methods  
 */  
public interface ACMEConfiguration  
    extends Configuration<ACMEConfiguration> {  
  
    /**  
     * Enables constraints implementation dynamic reloading when using  
     ACME  
     * default to false  
     */  
    ACMEConfiguration enableDynamicReloading(boolean);  
  
}  
  
/**  
 * ACME validation provider  
 * Note how ACMEConfiguration and ACMEProvider are linked together  
 * via the generic parameter.  
 */  
public class ACMEProvider implements ValidationProvider<  
ACMEConfiguration> {  
    [...]  
}
```

**NOTE** `Configuration` references itself in the generic definition. Methods of `Configuration` will return the `ACMEConfiguration` making the API easy to use even for vendor specific extensions.

The provider discovery mechanism uses the following algorithm:

- Retrieve available providers using `ValidationProviderResolver.getValidationProviders()`.
- The first `ValidationProvider` matching the requested provider is returned. Providers are evaluated in the order they are returned by `ValidationProviderResolver`. A provider instance is considered matching if it is assignable to the requested provider class.

When the default Bean Validation provider is requested, the first `ValidationProvider` returned by the `ValidationProviderResolver` strategy is returned.

Every Bean Validation provider must provide a `ValidationProvider` implementation containing a public no-arg constructor and add the corresponding `META-INF/services/javax.validation.spi.ValidationProvider` file descriptor in one of its jars.

If a problem occurs while building the `ValidatorFactory`, a `ValidationException` is raised.

This can be due to various reasons including:

- malformed XML mapping
- inability to find the provider (or a provider)
- inability to instantiate extension classes provided in the XML configuration
- inconsistent XML mapping (entity declared more than once, incorrect field etc.)
- invalid constraint declaration or definition

### 6.5.5. Validation

The `Validation` class is the entry point used to bootstrap Bean Validation providers. The first entry point, `buildDefaultValidatorFactory()`, is considered to be the default `ValidatorFactory` and is equivalent to the `ValidatorFactory` returned by `Validation.newBuilderProvider().configure().buildValidatorFactory()`.

*Example 102. Validation methods available*

```
/**  
 * This class is the entry point for Bean Validation.  
 * <p>  
 * There are three ways to bootstrap it:  
 * <ul>  
 *   <li>The easiest approach is to build the default {@link  
 ValidatorFactory}.  
 *     <pre>  
 * ValidatorFactory factory = Validation.buildDefaultValidatorFactory();  
 * </pre>  
 *     In this case, the default validation provider resolver  
 *     will be used to locate available providers.  
 *     <p>  
 *     The chosen provider is defined as followed:  
 *     <ul>  
 *       <li>if the XML configuration defines a provider, this provider  
 is used</li>  
 *       <li>if the XML configuration does not define a provider or if  
 no XML  
 *         configuration is present the first provider returned by the  
 *         {@link ValidationProviderResolver} instance is used.</li>  
 *     </ul>  
 *   </li>  
 *   <li>  
 *     The second bootstrap approach allows to choose a custom  
 *     {@code ValidationProviderResolver}. The chosen  
 *     {@link ValidationProvider} is then determined in the same way  
 *     as in the default bootstrapping case (see above).  
 *     <pre>  
 * Configuration<?> configuration = Validation  
 *   .newBuilder()  
 *   .providerResolver( new MyResolverStrategy() )  
 *   .configure();  
 * ValidatorFactory factory = configuration.buildValidatorFactory();
```

```

* </pre>
*   </li>
*   <li>
*     The third approach allows you to specify explicitly and in
*     a type safe fashion the expected provider.
*     <p>
*       Optionally you can choose a custom {@code
ValidationProviderResolver}.
*     <pre>
* ACMEConfiguration configuration = Validation
*   .byProvider(ACMEProvider.class)
*   .providerResolver( new MyResolverStrategy() ) // optionally set
the provider resolver
*   .configure();
* ValidatorFactory factory = configuration.buildValidatorFactory();
* </pre>
*   </li>
* </ul>
* <p>
* Note:
* <ul>
*   <li>
*     The {@code ValidatorFactory} object built by the bootstrap process
should be cached
*     and shared among {@code Validator} consumers.
*   </li>
*   <li>This class is thread-safe.</li>
* </ul>
*
* @author Emmanuel Bernard
* @author Hardy Ferentschik
*/
public class Validation {

    /**
     * Builds and returns a {@link ValidatorFactory} instance based on
the
     * default Bean Validation provider and following the XML
configuration.
     * <p>
     * The provider list is resolved using the default validation
provider resolver
     * logic.
     * <p>
     * The code is semantically equivalent to
     * {@code
Validation.byIdDefaultProvider().configure().buildValidatorFactory()}.
     *
     * @return {@code ValidatorFactory} instance
     *
     * @throws NoProviderFoundException if no Bean Validation provider
was found
     * @throws ValidationException if a Bean Validation provider was
found but the
     * {@code ValidatorFactory} cannot be built
     */
    public static ValidatorFactory buildDefaultValidatorFactory() {
        [...]
    }
}

```

```

    /**
     * Builds a {@link Configuration}. The provider list is resolved
     * using the strategy provided to the bootstrap state.
     * <pre>
     * Configuration<?> configuration = Validation
     *   .byDefaultProvider()
     *   .providerResolver( new MyResolverStrategy() )
     *   .configure();
     * ValidatorFactory factory = configuration.buildValidatorFactory();
     * </pre>
     * The provider can be specified in the XML configuration. If the XML
     * configuration does not exist or if no provider is specified,
     * the first available provider will be returned.
     *
     * @return instance building a generic {@code Configuration}
     *         compliant with the bootstrap state provided
     */
    public static GenericBootstrap byDefaultProvider() {
        [...]
    }

    /**
     * Builds a {@link Configuration} for a particular provider
     * implementation.
     * <p>
     * Optionally overrides the provider resolution strategy used to
     * determine the provider.
     * <p>
     * Used by applications targeting a specific provider
     * programmatically.
     * <pre>
     * ACMEConfiguration configuration =
     *   Validation.byProvider(ACMEProvider.class)
     *   .providerResolver( new MyResolverStrategy() )
     *   .configure();
     * </pre>,
     * where {@code ACMEConfiguration} is the
     * {@code Configuration} sub interface uniquely identifying the
     * ACME Bean Validation provider. and {@code ACMEProvider} is the
     * {@link ValidationProvider} implementation of the ACME provider.
     *
     * @param providerType the {@code ValidationProvider} implementation
     * type
     * @param <T> the type of the {@code Configuration} corresponding to
     * this {@code ValidationProvider}
     * @param <U> the type of the {@code ValidationProvider}
     * implementation
     *
     * @return instance building a provider specific {@code
     Configuration}
     *         sub interface implementation
     */
    public static <T extends Configuration<T>, U extends
ValidationProvider<T>>
        ProviderSpecificBootstrap<T> byProvider(Class<U> providerType) {
            [...]
        }
        [...]
    }

```

The second entry point lets the client provide a custom `ValidationProviderResolver` instance. This instance is passed to `GenericBootstrap`. `GenericBootstrap` builds a generic `Configuration` using the first `ValidationProvider` returned by `ValidationProviderResolution` and calling `ValidationProvider.createGenericConfiguration(BootstrapState state)`. `BootstrapState` holds the `ValidationProviderResolution` instance passed to `GenericBootstrap` and will be used by the `Configuration` instance when resolving the provider to use. Note that `ValidationProvider.createGenericConfiguration` returns a `Configuration` object not bound to any particular provider.

### Example 103. GenericBootstrap interface

```
package javax.validation.bootstrap;

/**
 * Defines the state used to bootstrap Bean Validation and
 * creates a provider agnostic {@link Configuration}.
 *
 * @author Emmanuel Bernard
 */
public interface GenericBootstrap {

    /**
     * Defines the provider resolution strategy.
     * This resolver returns the list of providers evaluated
     * to build the {@link Configuration}.
     * <p>
     * If no resolver is defined, the default {@link
     ValidationProviderResolver}
     * implementation is used.
     *
     * @param resolver the {@code ValidationProviderResolver} to use for
     bootstrapping
     * @return {@code this} following the chaining method pattern
     */
    GenericBootstrap providerResolver(ValidationProviderResolver
resolver);

    /**
     * Returns a generic {@link Configuration} implementation.
     * At this stage the provider used to build the {@link
     ValidatorFactory}
     * is not defined.
     * <p>
     * The {@code Configuration} implementation is provided by the first
     provider
     * returned by the {@link ValidationProviderResolver} strategy.
     *
     * @return a {@code Configuration} implementation compliant with the
     bootstrap state
     * @throws NoProviderFoundException if no Bean Validation provider
     was found
     * @throws ValidationException if a Bean Validation provider was
     found but the
     *         {@code Configuration} object cannot be built; this is
     generally due to an
     *         issue with the {@code ValidationProviderResolver}
     */
    Configuration<?> configure();
}
```

The last entry point lets the client define the specific Bean Validation provider requested as well as a custom `ValidationProviderResolver` implementation if needed. The entry point method, `Validation.byProvider(Class<U> providerType)`, takes the provider specific `ValidationProvider` implementation type and returns a `ProviderSpecificBootstrap`

object that guarantees to return an instance of the specific `Configuration` sub interface. Thanks to the use of generics, the client API does not have to cast to the `Configuration` sub interface.

A `ProviderSpecificBootstrap` object can optionally receive a `ValidationProviderResolver` instance.

*Example 104. ProviderSpecificBootstrap interface*

```
package javax.validation.bootstrap;

/**
 * Defines the state used to bootstrap Bean Validation and
 * creates a provider specific {@link Configuration}
 * of type {@code T}.
 * <p>
 * The specific {@code Configuration} is linked to the provider via the
generic
 * parameter of the {@link ValidationProvider} implementation.
 * <p>
 * The requested provider is the first provider instance assignable to
 * the requested provider type (known when {@link
ProviderSpecificBootstrap} is built).
 * The list of providers evaluated is returned by {@link
ValidationProviderResolver}.
 * If no {@code ValidationProviderResolver} is defined, the
 * default {@code ValidationProviderResolver} strategy is used.
 *
 * @author Emmanuel Bernard
 */
public interface ProviderSpecificBootstrap<T extends Configuration<T>> {

    /**
     * Optionally defines the provider resolver implementation used.
     * If not defined, use the default {@link ValidationProviderResolver}
     *
     * @param resolver {@code ValidationProviderResolver} implementation
used
     *
     * @return {@code this} following the chaining method pattern
     */
    public ProviderSpecificBootstrap<T> providerResolver(
        ValidationProviderResolver resolver);

    /**
     * Determines the provider implementation suitable for {@code T} and
delegates
     * the creation of this specific {@link Configuration} subclass to
the provider.
     *
     * @return {@code Configuration} sub interface implementation
     *
     * @throws ValidationException if the {@code Configuration} object
cannot be built;
     *         this is generally due to an issue with the {@code
ValidationProviderResolver}
     */
    public T configure();
}
```

**ProviderSpecificBootstrap.configure()** must return the result of **ValidationProvider.createSpecializedConfiguration(BootstrapState state)**.

The `state` parameter holds the `ValidationProviderResolver` passed to `ProviderSpecificBootstrap`. The validation provider instance used is the one assignable to the type passed as a parameter in `Validation.byProvider(Class)`. The validation provider is selected according to the algorithm described in `ValidationProvider`.

The `Validation` implementation must not contain any non private attribute or method aside from the three public static bootstrap methods:

- `public static ValidatorFactory buildDefaultValidatorFactory()`
- `public static GenericBootstrap byDefaultProvider()`
- `public static <T extends Configuration<T>, U extends ValidationProvider<T>> ProviderSpecificBootstrap<T> byProvider(Class<U> providerType)`

The bootstrap API is designed to allow complete portability among Bean Validation provider implementations. The bootstrap implementation must ensure it can bootstrap third party providers.

When bootstrapping a Bean Validation provider, if the `ValidationProviderResolver` either fails or if the expected provider is not found, a `ValidationException` is raised.

### 6.5.6. XML configuration: META-INF/validation.xml

Unless explicitly ignored by calling `Configuration.ignoreXMLConfiguration()`, a `Configuration` takes into account the configuration available in `META-INF/validation.xml`. This configuration file is optional but can be used by applications to refine some of the Bean Validation behavior. If more than one `META-INF/validation.xml` file is found in the classpath, a `ValidationException` is raised.

Unless stated otherwise, XML based configuration settings are overridden by values explicitly set via the `Configuration` API. For example, the `MessageInterpolator` defined via `Configuration.messageInterpolator(MessageInterpolator)` has priority over the `message-interpolator` definition.

**default-provider:** represents the class name of the provider specific `ValidationProvider` implementation class. If defined, the specific provider is used (unless a specific provider has been chosen via the programmatic approach).

**message-interpolator:** represents the fully qualified class name of the `MessageInterpolator` implementation. When defined in XML, the implementation must have a public no-arg constructor.

**traversable-resolver:** represents the fully qualified class name of the `TraversableResolver` implementation. When defined in XML, the implementation must have a public no-arg constructor.

`constraint-validator-factory`: represents the fully qualified class name of the `ConstraintValidatorFactory` implementation. When defined in XML, the implementation must have a public no-arg constructor.

`parameter-name-provider`: represents the fully qualified class name of the `ParameterNameProvider` implementation. When defined in XML, the implementation must have a public no-arg constructor.

`clock-provider`: represents the fully qualified class name of the `ClockProvider` implementation. When defined in XML, the implementation must have a public no-arg constructor.

`value-extractor`: represents the fully qualified class name of a `ValueExtractor` implementation. When defined in XML, the implementation must have a public no-arg constructor. `value-extractor` can be given several times for declaring multiple extractors. An extractor for a given type and type parameter configured via XML takes precedence over any extractor for the same type and type parameter detected through the service loader or provided by the Bean Validation implementation itself. If more than one value extractor for the same type and type parameter is configured via XML, a `ValidationException` is raised.

`executable-validation`: allows to disable executable validation entirely via its attribute `enabled="false"` and optionally contains `default-executable-types`. `enabled` defaults to `true`.

`default-executable-types`: declared under `executable-validation`, contains the list of `executable-type` that are considered by default by the integration technology validating executables upon execution.

`constraint-mapping`: represents the resource path of an XML mapping file. More than one `constraint-mapping` element can be present. Mappings provided via `Configuration.addMapping(InputStream)` are added to the list of mappings described via `constraint-mapping`.

`property`: represents a key/value pair property providing room to provider specific configurations. Vendors should use vendor namespaces for properties (e.g., `com.acme.validation.logging`). Entries that make use of the namespace `javax.validation` and its subnamespaces must not be used for vendor-specific information. The namespace `javax.validation` is reserved for use by this specification. Properties defined via `Configuration.addProperty(String, String)` are added to the properties defined via `property`. If a property with the same name are defined in both XML and via the programmatic API, the value provided via programmatic API has priority.

All these top level elements are optional.

If a public no-arg constructor is missing on any of the classes referenced by the relevant XML

elements, a `ValidationException` is raised during the `Configuration.buildValidatorFactory()` call.

*Example 105. Example of META-INF/validation.xml file*

```
<?xml version="1.0" encoding="UTF-8"?>
<validation-config
    xmlns="http://xmlns.jcp.org/xml/ns/validation/configuration"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/configuration
validation-configuration-2.0.xsd"
    version="2.0">
    <default-provider>com.acme.ACMEProvider</default-provider>
    <message-interpolator>com.acme.ACMEAwareMessageInterpolator</message-
interpolator>

    <executable-validation>
        <default-validated-executable-types>
            <executable-type>NONE</executable-type>
        </default-validated-executable-types>
    </executable-validation>

    <constraint-mapping>META-INF/validation/order-constraints.xml<
/constraint-mapping>
    <constraint-mapping>META-INF/validation/catalog-constraints.xml<
/constraint-mapping>
    <constraint-mapping>META-INF/validation/customer-constraints.xml<
/constraint-mapping>

        <property name="com.acme.validation.logging">WARN</property>
        <property name="com.acme.validation.safetyChecking">failOnError<
/property>
    </validation-config>
```

The XML schema is described in [Configuration schema](#).

### 6.5.7. Bootstrapping considerations

The Bean Validation bootstrap API can be used directly by any application or made available through a container or other framework. In all cases, the following rules apply:

- `ValidatorFactory` is a thread-safe object that should be built once per deployment unit
- `ValidatorFactory` should be closed when it is no longer needed (e.g. when the unit is undeployed or the server stopped).
- `Validator` is a thread-safe and lightweight object which can be cached by the `ValidatorFactory` instance.

# 7. Constraint metadata request APIs

The Bean Validation specification provides a way to query the constraint repository. This API is expected to be used for tooling support as well as integration with other frameworks, libraries and JSRs. The Bean Validation specification aims to provide both a validation engine and a metadata repository for object constraints. Frameworks (EE or SE) in need for constraint definition, validation and metadata will be able to rely on the Bean Validation specification for these services avoiding any unnecessary duplication work from an application and infrastructure point of view.

## 7.1. Validator

The main API to access all metadata related to a given object is `Validator` (see [Bootstrapping](#) for more information on how to retrieve a `Validator` instance).

A `Validator` instance hosts the method to access to the metadata repository for a given class. It is recommended to leave the caching of `Validator` instances to the `ValidatorFactory`. `Validator` implementations are thread-safe.

*Example 106. Validator interface (metadata request API)*

```
/*
 * Validates bean instances. Implementations of this interface must be
thread-safe.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 * @author Gunnar Morling
 */
public interface Validator {

    [...] //See 5.1

    /**
     * Returns the descriptor object describing bean constraints.
     * <p/>
     * The returned object (and associated objects including
     * {@link ConstraintDescriptor}s) are immutable.
     *
     * @param clazz class or interface type evaluated
     * @return the bean descriptor for the specified class
     * @throws IllegalArgumentException if clazz is {@code null}
     * @throws ValidationException if a non recoverable error happens
     *         during the metadata discovery or if some
     *         constraints are invalid.
     */
    BeanDescriptor getConstraintsForClass(Class<?> clazz);
}
```

`getConstraintsForClass()` returns a `BeanDescriptor` object describing the bean level constraints (see [Object validation](#)) and providing access to the property level constraints metadata. An `IllegalArgumentException` is raised if the `clazz` parameter is null.

If a constraint definition or declaration hosted by the requested class (or any of its superclasses and interfaces according to the constraint propagation rules) is invalid, a `ValidationException` is raised. This can be a subclass of `ValidationException` like `ConstraintDefinitionException`, `ConstraintDeclarationException` or `UnexpectedTypeException`.

All descriptor types accessible via `getConstraintsForClass()` and introduced in the following sections are located in the package `javax.validation.metadata`.

## 7.2. ElementDescriptor

`ElementDescriptor` is the root interface describing elements hosting constraints. It is used to describe the list of constraints for a given element (whether it be a class, property, method etc.).

*Example 107. ElementDescriptor interface*

```
package javax.validation.metadata;

/**
 * Describes a validated element (class, property, method etc.).
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 * @author Gunnar Morling
 */
public interface ElementDescriptor {

    /**
     * @return returns {@code true} if at least one constraint
     * declaration is present
     *         for this element in the class hierarchy, {@code false}
     * otherwise
     */
    boolean hasConstraints();

    /**
     * @return the statically defined returned type
     */
    Class<?> getElementClass();

    /**
     * Returns all constraint descriptors for this element in the class
     * hierarchy
     * or an empty {@code Set} if none are present.
     *
     * @return {@code Set} of constraint descriptors for this element
     */
    Set<ConstraintDescriptor<?>> getConstraintDescriptors();
```

```

    /**
     * Finds constraints and potentially restricts them to certain
     * criteria.
     *
     * @return {@code ConstraintFinder} object
     */
    ConstraintFinder findConstraints();

    /**
     * Declares restrictions on retrieved constraints.
     * Restrictions are cumulative.
     * <p>
     * A {@code ConstraintFinder} is not thread-safe. The set of matching
     * {@link ConstraintDescriptor} is.
     */
    interface ConstraintFinder {

        /**
         * Restricts to the constraints matching a given set of groups
         * for this element.
         * <p>
         * This method respects group conversion, group sequences
         * and group inheritance (including class-level {@link Default}
         * group
         * overriding) but does not return {@link ConstraintDescriptor}s
         * in any particular order.
         * Specifically, ordering of the group sequence is not respected.
         *
         * @param groups groups targeted
         * @return {@code this} following the chaining method pattern
         */
        ConstraintFinder unorderedAndMatchingGroups(Class<?>... groups);

        /**
         * Restricts to the constraints matching the provided scope for
         * this element.
         *
         * Defaults to {@link Scope#HIERARCHY}
         *
         * @param scope expected scope
         * @return {@code this} following the chaining method pattern
         */
        ConstraintFinder lookingAt(Scope scope);

        /**
         * Restricts to the constraints hosted on the listed {@code
         * types}
         * for a given element.
         * <p>
         * Defaults to all possible types of the element.
         * <p>
         * Typically used to restrict to fields ({@code FIELD})
         * or getters ({@code METHOD}).
         *
         * @param types targeted types
         *
         * @return {@code this} following the chaining method pattern
         */
        ConstraintFinder declaredOn(ElementType... types);
    }
}

```

```

    /**
     * Retrieves the constraint descriptors following the defined
     * restrictions and hosted on the element described by
     * {@link ElementDescriptor}.
     *
     * @return matching constraint descriptors
     */
    Set<ConstraintDescriptor<?>> getConstraintDescriptors();

    /**
     * Returns {@code true} if at least one constraint declaration
     * matching the restrictions is present on the element,
     * {@code false} otherwise.
     *
     * @return {@code true} if there is at least one constraint
     */
    boolean hasConstraints();
}
}

```

```

package javax.validation.metadata;

/**
 * Scope looked at when discovering constraints.
 *
 * @author Emmanuel Bernard
 */
public enum Scope {

    /**
     * Look for constraints declared on the current class element
     * and ignore inheritance and elements with the same name in
     * the class hierarchy.
     */
    LOCAL_ELEMENT,

    /**
     * Look for constraints declared on all elements of the class hierarchy
     * with the same name.
     */
    HIERARCHY
}

```

`getElementClass()` returns

- the object type when invoked on `BeanDescriptor`,
- the type of a property or parameter when invoked on `PropertyDescriptor` or `ParameterDescriptor` respectively,
- `Object[].class` when invoked on `CrossParameterDescriptor`,
- the return type when invoked on `ConstructorDescriptor`, `MethodDescriptor` or `ReturnValueDescriptor`.

`getConstraintDescriptors()` returns all the `ConstraintDescriptors` (see `ConstraintDescriptor`) hosted on the given element in the class hierarchy, each `ConstraintDescriptor` describing one of the constraints declared on the given element.

`hasConstraints()` returns `true` if the given element in the class hierarchy holds at least one constraint declaration.

If you need to query the metadata API in a more fine grained way for example by restricting the constraints to the one described on fields or on getters or by restricting to a given set of groups, you can use the `ConstraintFinder` fluent API by calling `findConstraints()`.

`unorderedAndMatchingGroups()` restricts the results to the `ConstraintDescriptors` (see `ConstraintDescriptor`) matching the given groups. Order is not respected but group inheritance and inheritance via sequence (including the `Default` group overriding at the class level) are honored.

`declaredOn()` lets you restrict the list of element types constraints are hosted on. This is particularly useful to retrieve property constraints only hosted on fields (`ElementType.FIELD`) or only hosted on getters (`ElementType.METHOD`).

`lookingAt()` lets you restrict which constraints are considered. Either constraints belonging to the element but hosted on the class represented by the given descriptor (`Scope.LOCAL_ELEMENT`), or constraints belonging to the element but hosted anywhere in the class hierarchy (`Scope.HIERARCHY`).

Here is an example restricting the list of constraints on getters, matching the default group and declared physically on the `name` getter of `Customer` (and not any of the getters on the super classes).

*Example 108. Using the fluent API to restrict matching constraints*

```
public class User {  
  
    @Size(max=50)  
    String getName() {  
        [...]  
    }  
  
    [...]  
}  
  
public class Customer extends User {  
  
    @NotNull  
    String getName() {  
        [...]  
    }  
}  
  
PropertyDescriptor pd =  
    validator.getConstraintsForClass(Customer.class)  
.getConstraintsForProperty("name");  
Set<ConstraintDescriptor<?>> constraints =  
    pd.findConstraints()  
        .declaredOn(ElementType.METHOD)  
        .unorderedAndMatchingGroups(Default.class)  
        .lookingAt(Scope.LOCAL_ELEMENT)  
        .getConstraintDescriptors();  
  
assert 1 == constraints.size();  
  
constraints = pd.getConstraintDescriptors();  
//equivalent to pd.findConstraints().getConstraintDescriptors();  
assert 2 == constraints.size();
```

The following example shows how the fluent API is used to retrieve parameter, cross-parameter and return value constraints, taking into account locally declared constraints as well as constraints declared in the inheritance hierarchy.

*Example 109. Using the fluent API to select method and constructor constraints*

```
public class User {  
  
    public User(@Size(max=50) String name) {  
        [...]  
    }  
  
    @PasswordParametersMatch  
    @NotNull  
    public String resetPassword(  
        @NotNull @Size(min=8) String password,  
        @NotNull @Size(min=8) String confirmation) {  
        [...]  
    }  
}
```

```

    }

}

public class Customer extends User {

    public Customer(@NotNull String name) {
        [...]
    }

    @Size(min=8)
    public String resetPassword(String password, String confirmation) {
        [...]
    }
}

MethodDescriptor methodDescriptor = validator
    .getConstraintsForClass( Customer.class )
    .getConstraintsForMethod( "resetPassword", String.class, String.class
);

//one cross-parameter constraint
assert 1 == methodDescriptor.getCrossParameterDescriptor()
    .getConstraintDescriptors().size();

//one local return value constraint
assert 1 == methodDescriptor.getReturnValueDescriptor()
    .findConstraints()
    .lookingAt( Scope.LOCAL_ELEMENT )
    .getConstraintDescriptors()
    .size();

//two return value constraints in the complete hierarchy
assert 2 == methodDescriptor.getReturnValueDescriptor()
    .findConstraints()
    .lookingAt( Scope.HIERARCHY )
    .getConstraintDescriptors()
    .size();

//two parameter constraints, defined on overridden method
assert 2 == methodDescriptor.getParameterDescriptors()
    .get( 0 )
    .getConstraintDescriptors()
    .size();

ConstructorDescriptor constructorDescriptor = validator
    .getConstraintsForClass( Customer.class )
    .getConstraintsForConstructor( String.class );

//one parameter constraint; constraints from super constructor don't
//apply
assert 1 == constructorDescriptor.getParameterDescriptors()
    .get( 0 )
    .findConstraints()
    .lookingAt( Scope.HIERARCHY )
    .getConstraintDescriptors()
    .size();

```

## 7.3. BeanDescriptor

The `BeanDescriptor` interface describes a constrained Java Bean. This interface is returned by `Validator.getConstraintsForClass(Class<?>)`.

*Example 110. BeanDescriptor interface*

```
package javax.validation.metadata;

/**
 * Describes a constrained Java Bean and the constraints associated to
it. All
 * objects returned by the methods of this descriptor (and associated
objects
 * including {@link ConstraintDescriptor}s) are immutable.
 *
 * @author Emmanuel Bernard
 * @author Gunnar Morling
 */
public interface BeanDescriptor extends ElementDescriptor {

    /**
     * Returns {@code true} if the bean involves validation:
     * <ul>
     *   <li>a constraint is hosted on the bean itself</li>
     *   <li>a constraint is hosted on one of the bean properties</li>
     *   <li>or a bean property is marked for cascaded validation
     *{@link Valid}</li>
     * </ul>
     * <p>
     * Constrained methods and constructors are ignored.
     *
     * @return {@code true} if the bean involves validation, {@code false}
     * otherwise
     */
    boolean isBeanConstrained();

    /**
     * Returns the property descriptor for a given property.
     * <p>
     * Returns {@code null} if the property does not exist or has no
     * constraint nor is marked as cascaded (see {@link
     #getConstrainedProperties()})
     * Properties of super types are considered.
     *
     * @param propertyName property evaluated
     * @return the property descriptor for a given property
     * @throws IllegalArgumentException if {@code propertyName} is {@code null}
     */
    PropertyDescriptor getConstraintsForProperty(String propertyName);

    /**
     * Returns a set of property descriptors having at least one
     * constraint defined
     * or marked as cascaded ({@link Valid}).
     */

}
```

```

* <p>
* If no property matches, an empty set is returned.
* Properties of super types are considered.
*
* @return the set of {@linkPropertyDescriptor}s for the constraint
properties; if
*         there are no constraint properties, the empty set is
returned
*/
Set<PropertyDescriptor> getConstrainedProperties();

/**
 * Returns a method descriptor for the given method.
* <p>
* Returns {@code null} if no method with the given name and
parameter types
* exists or the specified method neither has parameter or return
value constraints nor a parameter
* or return value marked for cascaded validation.
* Methods of super types are considered.
*
* @param methodName the name of the method
* @param parameterTypes the parameter types of the method
* @return a method descriptor for the given method
* @throws IllegalArgumentException if {@code methodName} is {@code null}
...
MethodDescriptor getConstraintsForMethod(String methodName, Class<?>
... parameterTypes);

/**
 * Returns a set with descriptors for the constrained methods of the
bean
* represented by this descriptor.
* <p>
* Constrained methods have at least one parameter or return value
constraint
* or at least one parameter or return value marked for cascaded
validation.
* Methods of super types are considered.
* <p>
* Only methods matching the given method type(s) are considered.
*
* @param methodType method type to consider
* @param methodTypes remaining optional method types to consider
* @return a set with descriptors for the constrained methods of this
bean;
*         will be empty if this bean has no constrained methods of
the considered
*         method type(s) but never {@code null}
*
* @since 1.1
*/
Set<MethodDescriptor> getConstrainedMethods(MethodType methodType,
MethodType... methodTypes);

/**
 * Returns a constructor descriptor for the given constructor.

```

```

    * <p>
    * Returns {@code null} if no constructor with the given parameter
types
        * exists or the specified constructor neither has parameter or
return value
            * constraints nor a parameter or return value marked for cascaded
            * validation.
        * Constructor of super types are considered.
        *
        * @param parameterTypes the parameter types of the constructor
        * @return a constructor descriptor for the given constructor
        *
        * @since 1.1
    */
ConstructorDescriptor getConstraintsForConstructor(Class<?>...
parameterTypes);

/**
 * Returns a set with descriptors for the constrained constructors of
the
 * bean represented by this descriptor.
 * <p>
 * Constrained constructors have at least one parameter or return
value constraint
 * or at least one parameter or return value marked for cascaded
validation.
 *
 * @return a set with descriptors for the constrained constructor of
this
 *         bean; will be empty if this bean has no constrained
constructor
 *         but never {@code null}
 *
 * @since 1.1
*/
Set<ConstructorDescriptor> getConstrainedConstructors();
}

```

### Example 111. MethodType

```
package javax.validation.metadata;

/**
 * Represents the type of a method: getter or non getter.
 *
 * @author Emmanuel Bernard
 * @since 1.1
 */
public enum MethodType {

    /**
     * A method following the getter pattern. A getter according to the
     * JavaBeans specification is a method whose:
     * <ul>
     *   <li>name starts with get, has a return type but no
     parameter</li>
     *   <li>name starts with is, has a return type and is returning
{@code boolean}.</li>
     * </ul>
     */
    GETTER,

    /**
     * A method that does not follow the getter pattern. A getter
according to the
     * JavaBeans specification is a method whose:
     * <ul>
     *   <li>name starts with get, has a return type but no
     parameter</li>
     *   <li>name starts with is, has a return type and is returning
{@code boolean}.</li>
     * </ul>
     */
    NON_GETTER
}
```

`isBeanConstrained()` returns `true` if the given class (and superclasses and interfaces) has at least one class-level or property-level constraint or validation cascade. If the method returns `false`, the Bean Validation engine can safely ignore the bean as it will not be impacted by validation.

`getConstraintsForProperty()` returns a `PropertyDescriptor` object describing the property level constraints (See [Field and property validation](#)). The property is uniquely identified by its name as per the JavaBeans convention: field level and getter level constraints of the given name are all returned. An `IllegalArgumentException` is raised if the `propertyName` parameter is null.

`getConstrainedProperties()` returns the `PropertyDescriptor`s of the bean properties having at least one constraint or being cascaded (`@Valid` annotation).

`getConstraintsForMethod()` returns a `MethodDescriptor` object describing the method constraints of the given method. The method is uniquely identified by its name and the types of its parameters.

`getConstrainedMethods()` returns the `MethodDescriptors` of the methods matching the `MethodTypes` provided as parameter and having at least one constraint or cascaded parameter or return value.

`getConstraintsForConstructor()` returns a `ConstructorDescriptor` object describing the method constraints of the given constructor. The constructor is uniquely identified by its name and the types of its parameters.

`getConstrainedConstructors()` returns the `ConstructorDescriptors` of the constructors having at least one constraint or cascaded parameter or return value.

## 7.4. CascadableDescriptor

The `CascadableDescriptor` interface describes a cascadable element, i.e. an element which can be marked with `@Valid` in order to perform a cascaded validation of the element as described in [Graph validation](#).

```
package javax.validation.metadata;

/**
 * Represents a cascadable element.
 *
 * @author Gunnar Morling
 * @since 1.1
 */
public interface CascadableDescriptor {

    /**
     * Whether this element is marked for cascaded validation or not.
     *
     * @return {@code true}, if this element is marked for cascaded validation,
     *         {@code false} otherwise
     */
    boolean isCascaded();

    /**
     * Returns the group conversions configured for this element.
     *
     * @return a set containing this element's group conversions; an empty set
     *         may be returned if no conversions are configured but never
     *         {@code null}
     */
    Set<GroupConversionDescriptor> getGroupConversions();
}
```

The `isCascaded()` method returns `true` if the element is marked for cascaded validation.

The method `getGroupConversions()` returns a set with the group conversions declared for the cascadable element. An empty set will be returned if no group conversions are configured.

## 7.5. GroupConversionDescriptor

The `GroupConversionDescriptor` interface describes a group conversion rule configured for a cascadable element as described in [Group conversion](#). It is returned by `CascadableDescriptor.getGroupConversions()`.

```
package javax.validation.metadata;

/**
 * A group conversion rule to be applied during cascaded validation. Two group
 * conversion descriptors are considered equal if they have the same
 * {@code from} and {@code to} group respectively.
 *
 * @author Gunnar Morling
 * @see ConvertGroup
 * @since 1.1
 */
public interface GroupConversionDescriptor {

    /**
     * Returns the source group of this conversion rule.
     *
     * @return the source group of this conversion rule
     */
    Class<?> getFrom();

    /**
     * Returns the target group of this conversion rule.
     *
     * @return the target group of this conversion rule
     */
    Class<?> getTo();
}
```

The `getFrom()` method returns the source of a group conversion rule.

The `getTo()` method returns the target of a group conversion rule.

## 7.6. PropertyDescriptor

The `PropertyDescriptor` interface describes a constrained property of a Java Bean.

This interface is returned by `BeanDescriptor.getConstraintsForProperty(String)` or `BeanDescriptor.getConstrainedProperties()`. Constraints declared on the attribute and the getter of the same name according to the JavaBeans rules are returned by this descriptor.

```

package javax.validation.metadata;

/**
 * Describes a Java Bean property hosting validation constraints.
 *
 * Constraints placed on the attribute and the getter of a given property
 * are all referenced.
 *
 * @author Emmanuel Bernard
 */
public interface PropertyDescriptor extends ElementDescriptor,
CascadableDescriptor, ContainerDescriptor {

    /**
     * Name of the property according to the Java Bean specification.
     *
     * @return property name
     */
    String getPropertyName();
}

```

`getPropertyName()` returns the property name as described in [ConstraintViolation](#).

## 7.7. ExecutableDescriptor, MethodDescriptor and ConstructorDescriptor

The [ExecutableDescriptor](#) interface describes a constrained method or constructor of a Java type.

```

package javax.validation.metadata;

/**
 * Provides the common functionality of {@link MethodDescriptor} and
 * {@link ConstructorDescriptor}.
 *
 * @author Gunnar Morling
 *
 * @since 1.1
 */
public interface ExecutableDescriptor extends ElementDescriptor {

    /**
     * Returns the method name in case this descriptor represents a method or
     * the non-qualified name of the declaring class in case this descriptor
     * represents a constructor.
     *
     * @return the name of the executable represented by this descriptor
     */
    String getName();

    /**
     * Returns a list of descriptors representing this executable's
     * parameters, in the order of their declaration, including synthetic
     */
}

```

```

* parameters.
*
* @return a list of descriptors representing this executable's
*         parameters; an empty list will be returned if this executable
has
*         no parameters, but never {@code null}
*/
List<ParameterDescriptor> getParameterDescriptors();

/**
* Returns a descriptor containing the cross-parameter constraints
* of this executable.
*
* @return a descriptor containing the cross-parameter constraints of
*         this executable
*/
CrossParameterDescriptor getCrossParameterDescriptor();

/**
* Returns a descriptor for this executable's return value.
* <p>
* An executable without return value will return a descriptor
* representing {@code void}. This descriptor will have no constraint
* associated.
*
* @return a descriptor for this executable's return value
*/
ReturnValueDescriptor getReturnValueDescriptor();

/**
* Returns {@code true} if the executable parameters are constrained
either:
* <ul>
*   <li>because of a constraint on at least one of the parameters</li>
*   <li>because of a cascade on at least one of the parameters (via
*       {@link Valid})</li>
*   <li>because of at least one cross-parameter constraint</li>
* </ul>
* <p>
* Also returns {@code false} if there is no parameter.
*
* @return {@code true} if the executable parameters are constrained
*/
boolean hasConstrainedParameters();

/**
* Returns {@code true} if the executable return value is constrained
* either:
* <ul>
*   <li>because of a constraint on the return value</li>
*   <li>because validation is cascaded on the return value (via
*       {@link Valid})</li>
* </ul>
* <p>
* Also returns {@code false} if there is no return value.
*
* @return {@code true} if the executable return value is constrained
*/
boolean hasConstrainedReturnValue();

```

```

    /**
     * Returns {@code false}.
     * <p>
     * An executable per se does not host constraints, use
     * {@link #getParameterDescriptors()}, {@link
     #getCrossParameterDescriptor()}
     * and {@link #getReturnValueDescriptor()} to discover constraints.
     *
     * @return {@code false}
     */
    @Override
    boolean hasConstraints();

    /**
     * Returns an empty {@code Set}.
     * <p>
     * An executable per se does not host constraints, use
     * {@link #getParameterDescriptors()}, {@link
     #getCrossParameterDescriptor()}
     * and {@link #getReturnValueDescriptor()} to discover constraints.
     *
     * @return an empty {@code Set}
     */
    @Override
    Set<ConstraintDescriptor<?>> getConstraintDescriptors();

    /**
     * Returns a finder that will always return an empty {@code Set}.
     * <p>
     * An executable per se does not host constraints, use
     * {@link #getParameterDescriptors()}, {@link
     #getCrossParameterDescriptor()}
     * and {@link #getReturnValueDescriptor()} to discover constraints.
     *
     * @return {@code ConstraintFinder} object
     */
    @Override
    ConstraintFinder findConstraints();
}

```

`getName()` returns the name of the represented method (e.g. "placeOrder") respectively the non-qualified name of the declaring class of the represented constructor (e.g. "OrderService").

`getParameterDescriptors()` returns a list of `ParameterDescriptors` representing the method's or constructor's parameters in order of their declaration, including synthetic parameters. An empty list will be returned in case the method or constructor has no parameters.

`getCrossParameterDescriptor()` returns a descriptor containing cross-parameter constraints of the method or constructor. If no cross-parameter constraint is present, the descriptor will return an empty set of constraint descriptors.

`getReturnValueDescriptor()` returns a descriptor for the method's or constructor's return value. A descriptor representing the special class `void`, without any constraint descriptors, will be returned for executables which have no return value.

`hasConstrainedParameters()` returns `true` if any of the parameters is constrained or cascaded or if the represented executable has at least one cross-parameter constraint. Returns `false` if there is no parameter.

`hasConstrainedReturnValue()` returns `true` if the return value is constrained or cascaded. Returns `false` if there is no return value.

The methods `hasConstraints()`, `getConstraintDescriptors()` and `findConstraints()` defined on `ElementDescriptor` are redefined to clarify that executables do not host constraints directly and thus will always return `false` or an empty set of constraints, respectively. Constraint descriptors for individual parameters can be obtained from the corresponding `ParameterDescriptor` object, constraint descriptors for cross-parameter constraints can be obtained from the corresponding `CrossParameterDescriptor` object and constraint descriptors for the return value can be obtained from `ReturnValueDescriptor`.

The interfaces `MethodDescriptor` and `ConstructorDescriptor` are derived from `ExecutableDescriptor` and allow to distinguish between descriptors representing methods and descriptors representing constructors.

```
package javax.validation.metadata;

/**
 * Describes a validated method.
 *
 * @author Gunnar Morling
 * @author Emmanuel Bernard
 * @since 1.1
 */
public interface MethodDescriptor extends ExecutableDescriptor { }
```

```
package javax.validation.metadata;

/**
 * Describes a validated constructor.
 *
 * @author Gunnar Morling
 * @author Emmanuel Bernard
 * @since 1.1
 */
public interface ConstructorDescriptor extends ExecutableDescriptor { }
```

`MethodDescriptor` objects are returned by `BeanDescriptor.getConstraintsForMethod(String, Class<?>...)` and `BeanDescriptor.getConstrainedMethods(MethodType, MethodType...)`, while `ConstructorDescriptor` objects are returned by

`BeanDescriptor.getConstraintsForConstructor(Class<?>...)` and  
`BeanDescriptor.getConstrainedConstructors()`.

None of the metadata API methods honor the XML configuration around executable validation nor the presence of `@ValidateOnExecution`. In other words, all constrained methods and constructors will be returned by the metadata API regardless of these settings.

## 7.8. ParameterDescriptor

The `ParameterDescriptor` interface describes a constrained parameter of a method or constructor.

This interface is returned by `MethodDescriptor.getParameterDescriptors()` and `ConstructorDescriptor.getParameterDescriptors()`.

```
package javax.validation.metadata;

/**
 * Describes a validated method or constructor parameter.
 *
 * @author Gunnar Morling
 * @since 1.1
 */
public interface ParameterDescriptor extends ElementDescriptor,
CascadableDescriptor, ContainerDescriptor {

    /**
     * Returns this parameter's index within the parameter array of the method
     * or constructor holding it.
     *
     * @return this parameter's index
     */
    int getIndex();

    /**
     * Returns this parameter's name as retrieved by the current parameter
     * name resolver.
     *
     * @return this parameter's name
     */
    String getName();
}
```

`getIndex()` returns the index of the represented parameter within the parameter array of the method or constructor holding it.

`getName()` returns the name of the represented parameter.

## 7.9. CrossParameterDescriptor

The `CrossParameterDescriptor` interface describes a element containing all cross-parameter constraints of a method or constructor.

This interface is returned by `MethodDescriptor.getCrossParameterDescriptor()` and `ConstructorDescriptor.getCrossParameterDescriptor()`.

```
package javax.validation.metadata;

/**
 * Describes an element holding cross-parameter constraints of a method or
constructor
 *
 * @author Emmanuel Bernard
 * @since 1.1
 */
public interface CrossParameterDescriptor extends ElementDescriptor {

    /**
     * @return {@code Object[].class} – the type of the parameter array
     */
    @Override
    Class<?> getElementClass();
}
```

`getElementClass()` returns `Object[]`.

## 7.10. ReturnValueDescriptor

The `ReturnValueDescriptor` interface describes the return value of a method or constructor.

This interface is returned by `MethodDescriptor.getReturnValueDescriptor()` and `ConstructorDescriptor.getReturnValueDescriptor()`.

```
package javax.validation.metadata;

/**
 * Describes a validated return value of a method or constructor.
 *
 * @author Gunnar Morling
 * @since 1.1
 */
public interface ReturnValueDescriptor extends ElementDescriptor,
CascadableDescriptor, ContainerDescriptor {
}
```

## 7.11. ContainerDescriptor and ContainerElementTypeDescriptor

The `ContainerDescriptor` interface describes those elements that can host container element constraints (see [Container element constraints](#)).

`ContainerDescriptor` is extended by `PropertyDescriptor`, `ParameterDescriptor`, `ReturnValueDescriptor` and `ContainerElementTypeDescriptor`.

```
package javax.validation.metadata;

/**
 * Represents an element that might be a container, thus allowing container
element constraints.
 *
 * @author Guillaume Smet
 * @since 2.0
 */
public interface ContainerDescriptor {

    /**
     * Returns the list of descriptors representing the container element
     * types (e.g. type arguments of a generic type) of this container, if
any,
     * in the order of their declaration.
     *
     * @return the list of descriptors representing the container element
types of
     *         this container; an empty list will be returned if there are no
     *         container element types, but never {@code null}
     */
    List<ContainerElementTypeDescriptor> getContainerElementTypes();
}
```

`getContainerElementTypes()` returns a list of descriptors representing all the type arguments of the container type, in the order of their declaration.

The `ContainerElementTypeDescriptor` interface describes the potential container element constraints applied to one type argument of a container type.

This interface is returned by `ContainerDescriptor.getContainerElementTypes()`.

```

package javax.validation.metadata;

/**
 * Describes a validated container element type.
 *
 * @author Guillaume Smet
 * @since 2.0
 */
public interface ContainerElementTypeDescriptor extends ElementDescriptor,
CascadableDescriptor, ContainerDescriptor {

    /**
     * @return the index of the type argument corresponding to this container
     * element type
     */
    Integer getTypeArgumentIndex();
}

```

`getTypeArgumentIndex()` returns the index of the type argument corresponding to this descriptor instance.

## 7.12. ConstraintDescriptor

A `ConstraintDescriptor` object describes a given constraint declaration (i.e. a constraint annotation).

```

package javax.validation.metadata;

/**
 * Describes a single constraint and its composing constraints.
 * <p>
 * {@code T} is the constraint's annotation type.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 */
public interface ConstraintDescriptor<T extends Annotation> {

    /**
     * Returns the annotation describing the constraint declaration.
     * If a composing constraint, attribute values are reflecting
     * the overridden attributes of the composing constraint
     *
     * @return the annotation for this constraint
     */
    T getAnnotation();

    /**
     * The non-interpolated error message
     *
     * @return the non-interpolated error message
     *
     * @since 1.1
     */
}

```

```

String getMessageTemplate();

/**
 * The set of groups the constraint is applied on.
 * If the constraint declares no group, a set with only the {@link
Default}
 * group is returned.
 *
 * @return the groups the constraint is applied on
 */
Set<Class<?>> getGroups();

/**
 * The set of payload the constraint hosts.
 *
 * @return payload classes hosted on the constraint or an empty set if
none
 */
Set<Class<? extends Payload>> getPayload();

/**
 * The {@link ConstraintTarget} value of {@code validationAppliesTo} if
the constraint
 * hosts it or {@code null} otherwise.
 *
 * @return the {@code ConstraintTarget} value or {@code null}
 *
 * @since 1.1
 */
ConstraintTarget getValidationAppliesTo();

/**
 * List of the constraint validation implementation classes.
 *
 * @return list of the constraint validation implementation classes
 */
List<Class<? extends ConstraintValidator<T, ?>>>
getConstraintValidatorClasses();

/**
 * Returns a map containing the annotation attribute names as keys and the
 * annotation attribute values as value.
 * <p>
 * If this constraint is used as part of a composed constraint, attribute
 * values are reflecting the overridden attribute of the composing
constraint.
 *
 * @return a map containing the annotation attribute names as keys
 *         and the annotation attribute values as value
 */
Map<String, Object> getAttributes();

/**
 * Return a set of composing {@link ConstraintDescriptor}s where each
 * descriptor describes a composing constraint. {@code
ConstraintDescriptor}
 * instances of composing constraints reflect overridden attribute values
in
 * {@link #getAttributes()} and {@link #getAnnotation()}.
 *

```

```

    * @return a set of {@code ConstraintDescriptor} objects or an empty set
    *         in case there are no composing constraints
    */
    Set<ConstraintDescriptor<?>> getComposingConstraints();

    /**
     * @return {@code true} if the constraint is annotated with {@link
     ReportAsSingleViolation}
     */
    boolean isReportAsSingleViolation();

    /**
     * @return a {@link ValidateUnwrappedValue} defining the unwrapping
     behavior.
     *
     * @since 2.0
     */
    ValidateUnwrappedValue validateUnwrappedValue();
}

```

`getAnnotation()` returns the annotation instance (or an annotation instance representing the given constraint declaration). If `ConstraintDescriptor` represents a composing annotation (see [Constraint composition](#)), the returned annotation must reflect parameter overriding. In other words, the annotation parameter values are the overridden values.

`getAttributes()` returns a map containing the annotation attribute names as a key, and the annotation attribute values as a value (this API is anticipated to be simpler to use by tools than reflection over the annotation instance). If `ConstraintDescriptor()` represents a composing annotation (see [Constraint composition](#)), the returned `Map` must reflect attribute overriding.

`getMessageTemplate()` returns the non-interpolated error message.

`getGroups()` returns the groups the constraint is supposed to be applied upon. If no group is set on the constraint declaration, the `Default` group is returned. The groups of a composing constraint are the groups of the composed constraint.

`getPayload()` returns the payloads associated to the constraint or an empty set if none. The payload from the main constraint annotation is inherited by the composing annotations. Any payload definition on a composing annotation is ignored.

`getValidationAppliesTo()` returns the `ConstraintTarget` returned by `validationAppliesTo` if the constraint hosts the attribute or `null` otherwise. The constraint target from the main constraint annotation is inherited by the composing annotation. Any constraint target definition on a composing annotation is ignored.

`isReportAsSingleViolation()` returns `true` if the constraint is annotated with `@ReportAsSingleViolation`.

`getComposingConstraints()` return a set of composing `ConstraintDescriptors` where each descriptor describes a composing constraint.

`getConstraintValidatorClasses()` returns the `ConstraintValidator` classes associated with the constraint.

`validateUnwrappedValue()` returns a `ValidateUnwrappedValue` instance describing the unwrapping behavior.

```
package javax.validation.metadata;

/**
 * The unwrapping behavior that can be applied to a specific constraint.
 *
 * @author Guillaume Smet
 * @since 2.0
 */
public enum ValidateUnwrappedValue {

    /**
     * Respects the default behavior of the {@link ValueExtractor}.
     */
    DEFAULT,

    /**
     * The value is unwrapped before validation.
     */
    YES,

    /**
     * The value is not unwrapped before validation.
     */
    NO;
}
```

## 7.13. Example

Assuming the following constraint definitions

```
package com.acme.constraint;

@Documented
@NotNull
@Size(min = 1)
@ReportAsSingleViolation
@Constraint(validatedBy = NotEmpty.NotEmptyValidator.class)
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
@Retention(RUNTIME)
public @interface NotEmpty {

    String message() default "{com.acme.constraint.NotEmpty.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};
}
```

```

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER, TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        NotEmpty[] value();
    }

    class NotEmptyValidator implements ConstraintValidator<NotEmpty, String> {

        @Override
        public void initialize(NotEmpty constraintAnnotation) {
        }

        @Override
        public boolean isValid(String value, ConstraintValidatorContext
context) {
            return true;
        }
    }
}

@Documented
@Constraint(validatedBy = ValidInterval.Validator.class)
@Target({ METHOD, ANNOTATION_TYPE, CONSTRUCTOR })
@Retention(RUNTIME)
public @interface ValidInterval {

    String message() default "{com.acme.constraint.ValidInterval.message}";

    Class<?>[] groups() default {};

    Class<? extends Payload>[] payload() default {};

    int startParameter();

    int endParameter();

    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        ValidInterval[] value();
    }

    @SupportedValidationTarget(PARAMETERS)
    class Validator implements ConstraintValidator<ValidInterval, Object[]> {

        private int start;
        private int end;

        @Override
        public void initialize(ValidInterval constraintAnnotation) {
            this.start = constraintAnnotation.startParameter();
            this.end = constraintAnnotation.endParameter();
        }

        @Override
        public boolean isValid(Object[] value, ConstraintValidatorContext
context) {
    }
}

```

```
        return Integer.parseInt( String.valueOf( value[start] ) ) <
Integer.parseInt( String.valueOf( value[end] ) );
    }
}
}
```

and the following class definitions

```
public class Author {

    private String firstName;

    @NotEmpty(message = "lastname must not be null")
    private String lastName;

    @Size(max = 30)
    private String company;

    public String getFirstName() {
        return firstName;
    }

    public void setFirstName(String firstName) {
        this.firstName = firstName;
    }

    public String getLastName() {
        return lastName;
    }

    public String getCompany() {
        return company;
    }

    public void setCompany(String company) {
        this.company = company;
    }
}

public class Book {

    public interface FirstLevelCheck {
    }

    public interface SecondLevelCheck {
    }

    public static class Chapter {
        // [...]
    }

    private String title;
    private String description;

    @Valid
    @NotNull
    private Author author;

    private Map<@Valid Chapter, @Size(min=1) List<@NotBlank String>>
}
```

```

keywordsPerChapter;

    @Valid
    public Book(
        String title,
        @Size(max = 30) String description,
        @Valid @ConvertGroup(from = Default.class, to = SecondLevelCheck
.class) Author author) {
        // [...]
    }

    public Book() {
        // [...]
    }

    @NotEmpty(groups = { FirstLevelCheck.class, Default.class })
    @Size(max = 30)
    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    public Author getAuthor() {
        return author;
    }

    public void setAuthor(Author author) {
        this.author = author;
    }

    public String getDescription() {
        return description;
    }

    public void setDescription(String description) {
        this.description = description;
    }

    @ValidInterval(startParameter = 1, endParameter = 2)
    public void addChapter(String title, int startPage, int endPage) {
        // [...]
    }
}

```

The following assertions are true.

```

BeanDescriptor bookDescriptor = validator.getConstraintsForClass(Book.class);

assert ! bookDescriptor.hasConstraints();

assert bookDescriptor.isBeanConstrained();
assert bookDescriptor.getConstrainedMethods( MethodType.NON_GETTER ).size() >
0;

assert bookDescriptor.getConstraintDescriptors().size() == 0; //no bean-level
constraint

```

```

//more specifically "author", "title" and "keywordsPerChapter"
assert bookDescriptor.getConstrainedProperties().size() == 2;

//not a property
assert bookDescriptor.getConstraintsForProperty( "doesNotExist" ) == null;

//property with no constraint
assert bookDescriptor.getConstraintsForProperty( "description" ) == null;

PropertyDescriptor propertyDescriptor = bookDescriptor
.getConstraintsForProperty( "title" );
assert propertyDescriptor.getConstraintDescriptors().size() == 2;
assert "title".equals( propertyDescriptor.getPropertyName() );

//assuming the implementation returns the @NotEmpty constraint first
ConstraintDescriptor<?> constraintDescriptor = propertyDescriptor
.getConstraintDescriptors()
.iterator().next();
assert constraintDescriptor.getAnnotation().annotationType().equals( NotEmpty
.class );
assert constraintDescriptor.getGroups().size() == 2; //FirstLevelCheck and
Default
assert constraintDescriptor.getComposingConstraints().size() == 2;
assert constraintDescriptor.isReportAsSingleViolation() == true;

//@NotEmpty cannot be null
boolean notNullPresence = false;
for ( ConstraintDescriptor<?> composingDescriptor :
constraintDescriptor.getComposingConstraints() ) {
    if ( composingDescriptor.getAnnotation().annotationType().equals( NotNull
.class ) ) {
        notNullPresence = true;
    }
}
assert notNullPresence;

//assuming the implementation returns the Size constraint second
constraintDescriptor = propertyDescriptor.getConstraintDescriptors().iterator
().next();
assert constraintDescriptor.getAnnotation().annotationType().equals( Size
.class );
assert constraintDescriptor.getAttributes().get( "max" ) == Integer.valueOf(
30 );
assert constraintDescriptor.getGroups().size() == 1;

propertyDescriptor = bookDescriptor.getConstraintsForProperty( "author" );
assert propertyDescriptor.getConstraintDescriptors().size() == 1;
assert propertyDescriptor.isCascaded();

propertyDescriptor = bookDescriptor.getConstraintsForProperty( "title" );

// no container element types
assert propertyDescriptor.getContainerElementTypes().isEmpty();

propertyDescriptor = bookDescriptor.getConstraintsForProperty(
"keywordsPerChapter" );

// 2 container element types: one for the map key and one for the map value
assert propertyDescriptor.getContainerElementTypes().size() == 2;

```

```

// @Valid on the map key
ContainerElementTypeDescriptor mapKeyElementDescriptor =
    propertyDescriptor.getContainerElementTypes().get( 0 );
assert mapKeyElementDescriptor.isCascaded() == true;

// @Size on the map value
ContainerElementTypeDescriptor mapValueElementDescriptor =
    propertyDescriptor.getContainerElementTypes().get( 1 );
Set<ConstraintDescriptor<?>> mapKeyConstraints =
    mapValueElementDescriptor.getConstraintDescriptors();
assert mapKeyConstraints.size() == 1;
assert mapKeyConstraints.iterator().next().getAnnotation().annotationType() ==
Size.class;

// 1 container element type for the nested list
assert mapValueElementDescriptor.getContainerElementTypes().size() == 1;

// @NotBlank on the nested list elements
ContainerElementTypeDescriptor listElementDescriptor =
    mapValueElementDescriptor.getContainerElementTypes().get( 0 );
Set<ConstraintDescriptor<?>> listElementConstraints =
    listElementDescriptor.getConstraintDescriptors();
assert listElementConstraints.size() == 1;
assert listElementConstraints.iterator().next().getAnnotation().annotationType() ==
NotBlank.class;

// no further nested container element constraints
assert listElementDescriptor.getContainerElementTypes().isEmpty();

//getTitle() and addChapter()
assert bookDescriptor.getConstrainedMethods( MethodType.GETTER, MethodType
.NON_GETTER ).size() ==
2;

//the constructor accepting title, description and author
assert bookDescriptor.getConstrainedConstructors().size() == 1;

ConstructorDescriptor constructorDescriptor = bookDescriptor
.getConstraintsForConstructor(
    String.class, String.class, Author.class
);
assert constructorDescriptor.getName().equals( "Book" );
assert constructorDescriptor.getElementClass() == Book.class;
assert constructorDescriptor.hasConstrainedParameters() == true;

//return value is marked for cascaded validation
assert constructorDescriptor.hasConstrainedReturnValue() == true;

//constraints are retrieved via the sub-descriptors for parameters etc.
assert constructorDescriptor.hasConstraints() == false;

//one descriptor for each parameter
assert constructorDescriptor.getParameterDescriptors().size() == 3;

// "description" parameter
ParameterDescriptor parameterDescriptor = constructorDescriptor
.getParameterDescriptors()
.get( 1 );

//Assuming the default parameter name provider

```

```

assert parameterDescriptor.getName().equals("arg1");
assert parameterDescriptor.getElementClass() == String.class;
assert parameterDescriptor.getIndex() == 1;
assert parameterDescriptor.hasConstraints() == true;

Set<ConstraintDescriptor<?>> parameterConstraints =
    parameterDescriptor.getConstraintDescriptors();
assert parameterConstraints.iterator().next().getAnnotation().annotationType()
== Size.class;

// "author" parameter
parameterDescriptor = constructorDescriptor.getParameterDescriptors().get(2);
assert parameterDescriptor.hasConstraints() == false;
assert parameterDescriptor.isCascaded() == true;

// group conversion on "author" parameter
GroupConversionDescriptor groupConversion =
    parameterDescriptor.getGroupConversions().iterator().next();
assert groupConversion.getFrom() == Default.class;
assert groupConversion.getTo() == SecondLevelCheck.class;

// constructor return value
ReturnValueDescriptor returnValueDescriptor = constructorDescriptor
    .getReturnValueDescriptor();
assert returnValueDescriptor.hasConstraints() == false;
assert returnValueDescriptor.isCascaded() == true;

// a getter is also a method which is constrained on its return value
MethodDescriptor methodDescriptor = bookDescriptor.getConstraintsForMethod(
    "getTitle");
assert methodDescriptor.getName().equals("getTitle");
assert methodDescriptor.getElementClass() == String.class;
assert methodDescriptor.hasConstrainedParameters() == false;
assert methodDescriptor.hasConstrainedReturnValue() == true;
assert methodDescriptor.hasConstraints() == false;

returnValueDescriptor = methodDescriptor.getReturnValueDescriptor();
assert returnValueDescriptor.getElementClass() == String.class;
assert returnValueDescriptor.getConstraintDescriptors().size() == 2;
assert returnValueDescriptor.isCascaded() == false;

// void method which has a cross-parameter constraint
methodDescriptor = bookDescriptor.getConstraintsForMethod(
    "addChapter", String.class, int.class
);
assert methodDescriptor.getElementClass() == void.class;
assert methodDescriptor.hasConstrainedParameters() == true;
assert methodDescriptor.hasConstrainedReturnValue() == false;

// cross-parameter constraints accessible via separate descriptor
assert methodDescriptor.hasConstraints() == false;

assert methodDescriptor.getReturnValueDescriptor().getElementClass() == void
    .class;

// cross-parameter descriptor
CrossParameterDescriptor crossParameterDescriptor =
    methodDescriptor.getCrossParameterDescriptor();
assert crossParameterDescriptor.getElementClass() == Object[].class;
assert crossParameterDescriptor.hasConstraints() == true;

```

```
ConstraintDescriptor<?> crossParameterConstraint =
    crossParameterDescriptor.getConstraintDescriptors().iterator().next();
assert crossParameterConstraint.getAnnotation().annotationType() ==
ValidInterval.class;
```

## 8. Built-in Constraint definitions

The specification defines a small set of built-in constraints. Their usage is encouraged both in regular constraint declarations and as composing constraints. Using this set of constraints will enhance portability of your constraints across constraint-consuming frameworks relying on the metadata API (such as client side validation frameworks or database schema generation frameworks).

Built-in annotations are annotated with an empty `@Constraint` annotation to avoid any dependency between the specification API and a specific implementation. Each Bean Validation provider must recognize built-in constraint annotations as valid constraint definitions and provide compliant constraint implementations for each. The built-in constraint validation implementation is having a lower priority than an XML mapping definition. In other words `ConstraintValidator` implementations for built-in constraints can be overridden by using the XML mapping (see [Overriding constraint definitions in XML](#)).

All built-in constraints are in the `javax.validation.constraints` package. Here is the list of constraints and their declaration.

*Example 112. @Null constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be {@code null}.
 * Accepts any type.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Null {

    String message() default "
{javax.validation.constraints.Null.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Defines several {@link Null} annotations on the same element.
     *
     * @see javax.validation.constraints.Null
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Null[] value();
    }
}
```

*Example 113. @NotNull constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must not be {@code null}.
 * Accepts any type.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface NotNull {

    String message() default
    "{javax.validation.constraints.NotNull.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Defines several {@link NotNull} annotations on the same element.
     *
     * @see javax.validation.constraints.NotNull
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        NotNull[] value();
    }
}
```

*Example 114. @AssertTrue constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be true.
 * Supported types are {@code boolean} and {@code Boolean}.
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface AssertTrue {

    String message() default
    "{javax.validation.constraints.AssertTrue.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Defines several {@link AssertTrue} annotations on the same
     * element.
     *
     * @see AssertTrue
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        AssertTrue[] value();
    }
}
```

*Example 115. @AssertFalse constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be false.
 * Supported types are {@code boolean} and {@code Boolean}.
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface AssertFalse {

    String message() default
    "{javax.validation.constraints.AssertFalse.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Defines several {@link AssertFalse} annotations on the same
     * element.
     *
     * @see javax.validation.constraints.AssertFalse
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        AssertFalse[] value();
    }
}
```

*Example 116. @Min constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be a number whose value must be higher or
 * equal to the specified minimum.
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code BigDecimal}</li>
 *   <li>{@code BigInteger}</li>
 *   <li>{@code byte}, {@code short}, {@code int}, {@code long}, and
their respective
 *   wrappers</li>
 * </ul>
 * Note that {@code double} and {@code float} are not supported due to
rounding errors
 * (some providers might provide some approximative support).
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Min {

    String message() default "{javax.validation.constraints.Min.message}"
    ;

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * @return value the element must be higher or equal to
     */
    long value();

    /**
     * Defines several {@link Min} annotations on the same element.
     *
     * @see Min
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Min[] value();
    }
}
```

*Example 117. @Max constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be a number whose value must be lower or
 * equal to the specified maximum.
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code BigDecimal}</li>
 *   <li>{@code BigInteger}</li>
 *   <li>{@code byte}, {@code short}, {@code int}, {@code long}, and
their respective
 *   wrappers</li>
 * </ul>
 * Note that {@code double} and {@code float} are not supported due to
rounding errors
 * (some providers might provide some approximative support).
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Max {

    String message() default "{javax.validation.constraints.Max.message}"
    ;

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * @return value the element must be lower or equal to
     */
    long value();

    /**
     * Defines several {@link Max} annotations on the same element.
     *
     * @see Max
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Max[] value();
    }
}
```

*Example 118. @DecimalMin constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be a number whose value must be higher or
 * equal to the specified minimum.
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code BigDecimal}</li>
 *   <li>{@code BigInteger}</li>
 *   <li>{@code CharSequence}</li>
 *   <li>{@code byte}, {@code short}, {@code int}, {@code long}, and
their respective
 *   wrappers</li>
 * </ul>
 * Note that {@code double} and {@code float} are not supported due to
rounding errors
 * (some providers might provide some approximative support).
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface DecimalMin {

    String message() default
    "{javax.validation.constraints.DecimalMin.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * The {@code String} representation of the min value according to
the
     * {@code BigDecimal} string representation.
     *
     * @return value the element must be higher or equal to
     */
    String value();

    /**
     * Specifies whether the specified minimum is inclusive or exclusive.
     * By default, it is inclusive.
     *
     * @return {@code true} if the value must be higher or equal to the
specified minimum,
     *         {@code false} if the value must be higher
     *
     * @since 1.1
    
```

```

    */
    boolean inclusive() default true;

    /**
     * Defines several {@link DecimalMin} annotations on the same
     * element.
     *
     * @see DecimalMin
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
    TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        DecimalMin[] value();
    }
}

```

*Example 119. @DecimalMax constraint*

```

package javax.validation.constraints;

/**
 * The annotated element must be a number whose value must be lower or
 * equal to the specified maximum.
 * <p>
 * Supported types are:
 * <ul>
 *      <li>{@code BigDecimal}</li>
 *      <li>{@code BigInteger}</li>
 *      <li>{@code CharSequence}</li>
 *      <li>{@code byte}, {@code short}, {@code int}, {@code long}, and
their respective
 *      wrappers</li>
 * </ul>
 * Note that {@code double} and {@code float} are not supported due to
rounding errors
 * (some providers might provide some approximative support).
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface DecimalMax {

    String message() default
    "{javax.validation.constraints.DecimalMax.message}";

    Class<?>[] groups() default { };
}

```

```

    Class<? extends Payload>[] payload() default { };

    /**
     * The {@code String} representation of the max value according to
     * the
     *   * {@code BigDecimal} string representation.
     *
     * @return value the element must be lower or equal to
     */
    String value();

    /**
     * Specifies whether the specified maximum is inclusive or exclusive.
     * By default, it is inclusive.
     *
     * @return {@code true} if the value must be lower or equal to the
     * specified maximum,
     *         {@code false} if the value must be lower
     *
     * @since 1.1
     */
    boolean inclusive() default true;

    /**
     * Defines several {@link DecimalMax} annotations on the same
     * element.
     *
     * @see DecimalMax
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
    TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        DecimalMax[] value();
    }
}

```

*Example 120. @Negative constraint*

```

package javax.validation.constraints;

/**
 * The annotated element must be a negative number.
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code BigDecimal}</li>
 *   <li>{@code BigInteger}</li>
 *   <li>{@code byte}, {@code short}, {@code int}, {@code long}, {@code float},
 *   {@code double} and their respective
 *   wrappers</li>
 * </ul>
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Gunnar Morling
 * @since 2.0
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Negative {

    String message() default
    "{javax.validation.constraints.Negative.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Whether the annotated element must be strictly negative (0 is
     * considered as an invalid value) or not (0 is a
     * valid value).
     *
     * @return whether the annotated element must be strictly negative
     */
    boolean strict() default false;

    /**
     * Defines several {@link Negative} constraints on the same element.
     *
     * @see Negative
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Negative[] value();
    }
}

```

*Example 121. @Positive constraint*

```

package javax.validation.constraints;

/**
 * The annotated element must be a positive number.
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code BigDecimal}</li>
 *   <li>{@code BigInteger}</li>
 *   <li>{@code byte}, {@code short}, {@code int}, {@code long}, {@code float},
 *   {@code double} and their respective
 *   wrappers</li>
 * </ul>
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Gunnar Morling
 * @since 2.0
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Positive {

    String message() default
    "{javax.validation.constraints.Positive.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Whether the annotated element must be strictly positive (0 is
     * considered as an invalid value) or not (0 is a
     * valid value).
     *
     * @return whether the annotated element must be strictly positive
     */
    boolean strict() default false;

    /**
     * Defines several {@link Positive} constraints on the same element.
     *
     * @see Positive
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Positive[] value();
    }
}

```

*Example 122. @Size constraint*

```

package javax.validation.constraints;

/**
 * The annotated element size must be between the specified boundaries
 * (included).
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code CharSequence} (length of character sequence is
evaluated)</li>
 *   <li>{@code Collection} (collection size is evaluated)</li>
 *   <li>{@code Map} (map size is evaluated)</li>
 *   <li>Array (array length is evaluated)</li>
 * </ul>
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Size {

    String message() default "
{javax.validation.constraints.Size.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * @return size the element must be higher or equal to
     */
    int min() default 0;

    /**
     * @return size the element must be lower or equal to
     */
    int max() default Integer.MAX_VALUE;

    /**
     * Defines several {@link Size} annotations on the same element.
     *
     * @see Size
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Size[] value();
    }
}

```

*Example 123. @Digits constraint*

```

package javax.validation.constraints;

/**
 * The annotated element must be a number within accepted range
 * Supported types are:
 * <ul>
 *   <li>{@code BigDecimal}</li>
 *   <li>{@code BigInteger}</li>
 *   <li>{@code CharSequence}</li>
 *   <li>{@code byte}, {@code short}, {@code int}, {@code long}, and
their respective
 *   wrapper types</li>
 * </ul>
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Digits {

    String message() default
    "{javax.validation.constraints.Digits.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * @return maximum number of integral digits accepted for this number
     */
    int integer();

    /**
     * @return maximum number of fractional digits accepted for this
number
     */
    int fraction();

    /**
     * Defines several {@link Digits} annotations on the same element.
     *
     * @see Digits
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Digits[] value();
    }
}

```

*Example 124. @Past constraint*

```
package javax.validation.constraints;

/**
 * The annotated element must be an instant, date or time in the past.
 * <p>
 * <i>Now</i> is defined by the {@link ClockProvider} attached to the
{@link javax.validation.Validator}
 * or {@link javax.validation.ValidatorFactory}.
 * The default {@code clockProvider} defines the current time according
to the virtual machine,
 * applying the current default time zone if needed.
 * <p>
 * Supported types are:
 * <ul>
 *   <li>{@code java.util.Date}</li>
 *   <li>{@code java.util.Calendar}</li>
 *   <li>{@code java.time.Instant}</li>
 *   <li>{@code java.time.LocalDate}</li>
 *   <li>{@code java.time.LocalDateTime}</li>
 *   <li>{@code java.time.LocalTime}</li>
 *   <li>{@code java.time.MonthDay}</li>
 *   <li>{@code java.time.OffsetDateTime}</li>
 *   <li>{@code java.time.OffsetTime}</li>
 *   <li>{@code java.time.Year}</li>
 *   <li>{@code java.time.YearMonth}</li>
 *   <li>{@code java.time.ZonedDateTime}</li>
 *   <li>{@code java.time.chrono.HijrahDate}</li>
 *   <li>{@code java.time.chrono.JapaneseDate}</li>
 *   <li>{@code java.time.chrono.MinguoDate}</li>
 *   <li>{@code java.time.chrono.ThaiBuddhistDate}</li>
 * </ul>
 * <p>
 * {@code null} elements are considered valid.
 *
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Past {

    String message() default "
{javax.validation.constraints.Past.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * The notion of present here is defined relatively to the type on
which the constraint is used. For instance, if
     * the constraint is on a {@link Year}, present would mean the whole
current year.
}
```

```

/*
 * @return {@code true} if the present date should be considered
 * valid
 */
boolean orPresent() default false;

/**
 * Defines several {@link Past} annotations on the same element.
 *
 * @see Past
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Documented
@interface List {

    Past[] value();
}
}

```

*Example 125. @Future constraint*

```

package javax.validation.constraints;

/**
 * The annotated element must be an instant, date or time in the future.
 * <p>
 * <i>Now</i> is defined by the {@link ClockProvider} attached to the
{@link javax.validation.Validator}
 * or {@link javax.validation.ValidatorFactory}.
 * The default {@code clockProvider} defines the current time according
to the virtual machine,
 * applying the current default time zone if needed.
 * <p>
 * Supported types are:
 * <ul>
 *     <li>{@code java.util.Date}</li>
 *     <li>{@code java.util.Calendar}</li>
 *     <li>{@code java.time.Instant}</li>
 *     <li>{@code java.time.LocalDate}</li>
 *     <li>{@code java.time.LocalDateTime}</li>
 *     <li>{@code java.time.LocalTime}</li>
 *     <li>{@code java.time.MonthDay}</li>
 *     <li>{@code java.time.OffsetDateTime}</li>
 *     <li>{@code java.time.OffsetTime}</li>
 *     <li>{@code java.time.Year}</li>
 *     <li>{@code java.time.YearMonth}</li>
 *     <li>{@code java.time.ZonedDateTime}</li>
 *     <li>{@code java.time.chrono.HijrahDate}</li>
 *     <li>{@code java.time.chrono.JapaneseDate}</li>
 *     <li>{@code java.time.chrono.MinguoDate}</li>
 *     <li>{@code java.time.chrono.ThaiBuddhistDate}</li>
 * </ul>
 * <p>
 * {@code null} elements are considered valid.

```

```

/*
 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Future {

    String message() default
    "{javax.validation.constraints.Future.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * The notion of present here is defined relatively to the type on
     * which the constraint is used. For instance, if
     * the constraint is on a {@link Year}, present would mean the whole
     * current year.
     *
     * @return {@code true} if the present date should be considered
     valid
     */
    boolean orPresent() default false;

    /**
     * Defines several {@link Future} annotations on the same element.
     *
     * @see Future
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    @interface List {

        Future[] value();
    }
}

```

*Example 126. @Pattern constraint*

```

package javax.validation.constraints;

/**
 * The annotated {@code CharSequence} must match the specified regular
 * expression.
 * The regular expression follows the Java regular expression conventions
 * see {@link java.util.regex.Pattern}.
 * <p>
 * Accepts {@code CharSequence}. {@code null} elements are considered
 * valid.
 *

```

```

 * @author Emmanuel Bernard
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
@Documented
@Constraint(validatedBy = { })
public @interface Pattern {

    /**
     * @return the regular expression to match
     */
    String regexp();

    /**
     * @return array of {@code Flag}s considered when resolving the
     regular expression
     */
    Flag[] flags() default { };

    /**
     * @return the error message template
     */
    String message() default
"{javax.validation.constraints.Pattern.message}";

    /**
     * @return the groups the constraint belongs to
     */
    Class<?>[] groups() default { };

    /**
     * @return the payload associated to the constraint
     */
    Class<? extends Payload>[] payload() default { };

    /**
     * Possible Regexp flags.
     */
    public static enum Flag {

        /**
         * Enables Unix lines mode.
         *
         * @see java.util.regex.Pattern#UNIX_LINES
         */
        UNIX_LINES( java.util.regex.Pattern.UNIX_LINES ),

        /**
         * Enables case-insensitive matching.
         *
         * @see java.util.regex.Pattern#CASE_INSENSITIVE
         */
        CASE_INSENSITIVE( java.util.regex.Pattern.CASE_INSENSITIVE ),

        /**
         * Permits whitespace and comments in pattern.
         *
         * @see java.util.regex.Pattern#COMMENTS
         */

```

```

    COMMENTS( java.util.regex.Pattern.COMMENTS ),

    /**
     * Enables multiline mode.
     *
     * @see java.util.regex.Pattern#MULTILINE
     */
    MULTILINE( java.util.regex.Pattern.MULTILINE ),

    /**
     * Enables dotall mode.
     *
     * @see java.util.regex.Pattern#DOTALL
     */
    DOTALL( java.util.regex.Pattern.DOTALL ),

    /**
     * Enables Unicode-aware case folding.
     *
     * @see java.util.regex.Pattern#UNICODE_CASE
     */
    UNICODE_CASE( java.util.regex.Pattern.UNICODE_CASE ),

    /**
     * Enables canonical equivalence.
     *
     * @see java.util.regex.Pattern#CANON_EQ
     */
    CANON_EQ( java.util.regex.Pattern.CANON_EQ );

    // JDK flag value
    private final int value;

    private Flag(int value) {
        this.value = value;
    }

    /**
     * @return flag value as defined in {@link
     *         java.util.regex.Pattern}
     */
    public int getValue() {
        return value;
    }
}

/**
 * Defines several {@link Pattern} annotations on the same element.
 *
 * @see Pattern
 */
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Documented
@interface List {

    Pattern[] value();
}

```

*Example 127. @NotEmpty constraint*

```
package javax.validation.constraints;

 * The annotated element must not be {@code null} nor empty. Supported
types are:
 * <ul>
 * <li>{@code CharSequence} (length of character sequence is evaluated)<
/li>
 * <li>{@code Collection} (collection size is evaluated)</li>
 * <li>{@code Map} (map size is evaluated)</li>
 * <li>{@code Array} (array length is evaluated)</li>
 * </ul>
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 *
 * @since 2.0
 */
@Documented
@Constraint(validatedBy = { })
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
public @interface NotEmpty {

    String message() default
    "{javax.validation.constraints.NotEmpty.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Defines several {@code @NotEmpty} constraints on the same element.
     *
     * @see NotEmpty
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    public @interface List {
        NotEmpty[] value();
    }
}
```

*Example 128. @NotBlank constraint*

```
package javax.validation.constraints;

 * The annotated element must not be {@code null} nor empty after
removing any leading or trailing
 * whitespace. Accepts {@code CharSequence}.
 *
 * @author Hardy Ferentschik
 *
 * @since 2.0
 */
@Documented
@Constraint(validatedBy = { })
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
public @interface NotBlank {

    String message() default
    "{javax.validation.constraints.NotBlank.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * Defines several {@code @NotBlank} constraints on the same element.
     *
     * @see NotBlank
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    public @interface List {
        NotBlank[] value();
    }
}
```

*Example 129. @Email constraint*

```
package javax.validation.constraints;

 * address are left to Bean Validation providers. Accepts {@code
CharSequence}.
 *
 * @author Emmanuel Bernard
 * @author Hardy Ferentschik
 *
 * @since 2.0
 */
@Documented
@Constraint(validatedBy = { })
@Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
@Retention(RUNTIME)
@Repeatable(List.class)
public @interface Email {

    String message() default
    "{javax.validation.constraints.Email.message}";

    Class<?>[] groups() default { };

    Class<? extends Payload>[] payload() default { };

    /**
     * @return an additional regular expression the annotated element
     * must match. The default is any string ('.*')
     */
    String regexp() default ".*";

    /**
     * @return used in combination with {@link #regexp()} in order to
     * specify a regular expression option
     */
    Pattern.Flag[] flags() default { };

    /**
     * Defines several {@code @Email} constraints on the same element.
     *
     * @see Email
     */
    @Target({ METHOD, FIELD, ANNOTATION_TYPE, CONSTRUCTOR, PARAMETER,
TYPE_USE })
    @Retention(RUNTIME)
    @Documented
    public @interface List {
        Email[] value();
    }
}
```

# 9. XML deployment descriptor

Two kinds of XML descriptors are used by Bean Validation. The first one describes the Bean Validation configuration provided as `META-INF/validation.xml`. The second one describes constraints declarations and closely matches the annotations declaration approach. If an XML descriptor does not validate against the corresponding XSD file, a `ValidationException` is raised.

## 9.1. Constraint definition and declaration

Bean Validation lets you declare constraints via XML rather than annotations. You can either ignore constraints declared via annotations or consider XML as adding additional constraints on top of annotation constraints. While it is not possible to define a new constraint via XML, you can redefine the list of `ConstraintValidator` classes associated to a given constraint definition.

There is no distinction between an annotation based constraint declaration and an XML based constraint declaration: they are considered equivalent and should be treated as such by the Bean Validation provider. The rest of the specification only refers to annotations as validation metadata: it should be read as annotation or their XML descriptor equivalent.

Specifically when exploring metadata, the Bean Validation provider must ensure that an annotation instance corresponding to the XML declaration is provided via `ConstraintDescriptor.getAnnotation()`. The annotation elements as well as `ConstraintValidator.getAttributes()` must reflect the values described in the XML declaration (see [Converting the string representation of a value](#)). Likewise, `ConstraintDescriptor.getConstraintValidatorClasses()` must reflect XML based constraint definition overriding (see [Overriding constraint definitions in XML](#)).

A given class must not be described more than once among all the XML mapping descriptors. A given field or getter must not be described more than once on a given class description. A given constraint definition must not be overridden more than once among all the XML mapping descriptors. If any of these rules is violated in a given validation deployment, a `ValidationException` is raised during the creation of the `ValidatorFactory`.

The schema is provided in [XML Schema](#).

### 9.1.1. Constraint declaration in XML

If `default-package` is set, all unqualified class names (including annotations) are considered part of the package described by `default-package`.

A given JavaBean is described by the `bean` element. The name of the class is mandatory. By default, all constraint declarations expressed via annotations are ignored for classes described in XML. You can force Bean Validation to consider both annotations and XML constraint

declarations by using `ignore-annotations="false"` on `bean`.

**NOTE** The `ignore-annotations` setting is not inherited from nor by the class hierarchy. In other words, it applies to the current bean only.

If the name of the class does refer to a class not present in the classpath, a `ValidationException` is raised.

*Example 130. Example of bean XML declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">

    <default-package>com.acme.app.domain</default-package>

    <bean class="Customer" ignore-annotations="false">
        [...]
    </bean>
    <bean class="com.acme.common.model.Address">
        [...]
    </bean>
</constraint-mappings>
```

#### 9.1.1.1. Class-level overriding

Class level annotations are described via the `class` element. If `ignore-annotations` is declared, Bean Validation must honor the explicit value for this element. If not declared, the default value defined in the encapsulating `bean` element is considered.

When `ignore-annotations` is true, class-level Bean Validation annotations are ignored for this class (including the `@GroupSequence`). When `ignore-annotations` is false:

- Constraints declared in XML and constraints declared in annotations are added and form the list of class-level declared constraints.
- `@GroupSequence` is considered unless `group-sequence` element is explicitly used.

*Example 131. Example of class-level declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <class ignore-annotations="true">
            [...]
        </class>
    </bean>
    <bean class="com.acme.common.model.Address">
        <class>
            [...]
        </class>
    </bean>
</constraint-mappings>
```

### 9.1.1.2. Field-level overriding

Field level annotations are described via the `field` element. The `name` attribute corresponds to the name of the field considered. If `ignore-annotations` is declared, Bean Validation must honor the explicit value for this element. If not declared, the default value defined in the encapsulating `bean` element is considered.

When `ignore-annotations` is true, field-level Bean Validation annotations on the targeted field are ignored (including `@Valid` and `@ConvertGroup`). When `ignore-annotations` is false:

- Constraints declared in XML and constraints declared in annotations are added and form the list of field-level declared constraints.
- `@Valid` is considered unless the `valid` element is explicitly used. Note that the only way to disable cascading on a field marked as `@Valid` is to use `ignore-annotations=true`.
- Group conversions declared in XML and via the `@ConvertGroup` annotation are added and form the list of applied conversions. Note that the rules for the declaration of group conversions as outlined in `Group conversion` apply, in particular it is not legal to declare several conversions for the same source group.

If the name of the field does not correspond to a field in the given bean a `ValidationException` is raised.

### Example 132. Field-level declaration

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <field name="firstName">
            [...]
        </field>
        <field name="orders">
            <valid/>
            [...]
        </field>
    </bean>
</constraint-mappings>
```

#### 9.1.1.3. Property-level overriding

Property-level annotations are described via the `getter` element. The `name` attribute corresponds to the name of the property considered as defined in [Field and property validation](#) (for example a getter `String getAge()` would have `<getter name="age"/>` as a corresponding descriptor). If `ignore-annotations` is declared, Bean Validation must honor the explicit value for this element. If not declared, the default value defined in the encapsulating `bean` element is considered.

When `ignore-annotations` is true, property-level Bean Validation annotations on the targeted property are ignored (including `@Valid` and `@ConvertGroup`). When `ignore-annotations` is false:

- Constraints declared in XML and constraints declared in annotations are added and form the list of property-level declared constraints.
- `@Valid` is considered unless the `valid` element is explicitly used. Note that the only way to disable cascading on a property marked as `@Valid` is to use `ignore-annotations=true`.
- Group conversions declared in XML and via the `@ConvertGroup` annotation are added and form the list of applied conversions. Note that the rules for the declaration of group conversions as outlined in [Group conversion](#) apply, in particular it is not legal to declare several conversions for the same source group.

If the name of the property does not correspond to a property in the given bean a `ValidationException` is raised.

*Example 133. Property-level declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <getter name="firstName">
            [...]
        </getter>
        <getter name="orders">
            <valid/>
            [...]
        </getter>
    </bean>
</constraint-mappings>
```

#### 9.1.1.4. Constructor-level overriding

Constructor-level annotations are described via the `constructor` element.

To identify a constructor to be configured, zero or more parameter elements are used, matching the number and types of parameters of the configured constructor. When configuring the default constructor, no parameter element is to be used. The parameter types are specified using their fully qualified name using the syntax described in the documentation of `java.lang.Class.getName()`.

Let's look at some examples:

- "`java.lang.String`" must be specified for a parameter of type `java.lang.String`
- "`long`" must be specified for a parameter of type `long`
- "`[Ljava.lang.Object;`" must be specified for a parameter of type `java.lang.Object[]`

Varargs parameters are specified using the corresponding array type, e.g. a parameter `String...` must be specified as "`[Ljava.lang.String;`".

If the `default-package` element is configured for the mapping file, any unqualified class names will be resolved using the given default package.

**NOTE**

You must declare all parameters even if they are not reconfigured to ensure the right constructor is identified.

If no constructor with the specified parameter types exists in the given bean a `ValidationException` is raised.

The optional `return-value` element is used to change the configuration of a constructor's return value if required.

The optional `cross-parameter` element is used to change the configuration of a constructor's cross-parameter constraints if required.

The constraints applying for a constructor's parameters and its return value are specified by adding `constraint` elements to the `parameter` and `return-value` elements respectively. Whether or not to perform cascaded validation is controlled using the `valid` element. Group conversion rules for cascaded validation are specified using the `convert-group` element.

The cross-parameter constraints applied on a constructor parameter list are specified by adding `constraint` elements to the `cross-parameter` element.

If `ignore-annotations` is declared on the parameter, cross-parameter element or return value level, Bean Validation must honor the explicit value for this element. Otherwise, if `ignore-annotations` is declared for the `constructor` element, Bean Validation must honor this value. Otherwise, the default value declared in the encapsulating `bean` element is considered.

When `ignore-annotations` is true, Bean Validation annotations on the targeted constructor or parameter are ignored (including `@Valid` and `@ConvertGroup`). When `ignore-annotations` is false:

- Constraints declared in XML and constraints declared in annotations are added and form the list of declared parameter, cross-parameter or return value constraints respectively.
- `@Valid` is considered unless the `valid` element is explicitly used. Note that the only way to disable cascading on a constructor parameter or return value marked as `@Valid` is to use `ignore-annotations=true`. This does not apply to cross-parameter elements as cascading does not make sense in this situation.
- Group conversions declared in XML and via the `@ConvertGroup` annotation are added and form the list of applied conversions. Note that the rules for the declaration of group conversions as outlined in [Group conversion](#) apply, in particular it is not legal to declare several conversions for the same source group. This does not apply to cross-parameter elements as cascading does not make sense in this situation.

*Example 134. Constructor-level declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <constructor ignore-annotations="true">
            <parameter type="java.lang.String">
                [...]
            </parameter>
            <parameter type="int">
                <valid/>
                [...]
            </parameter>
            <parameter type="long" ignore-annotations="false"/>
            <cross-parameter ignore-annotations="false">
                [...]
            </cross-parameter>
            <return-value>
                <valid/>
                [...]
            </return-value>
            [...]
        </constructor>

    </bean>
</constraint-mappings>
```

### 9.1.1.5. Method-level overriding

Method-level annotations are described via the `method` element.

To identify a method to be configured, zero or more parameter elements are used, matching the number and types of parameters of the configured method. The parameter types are specified using their fully qualified name using the syntax described in the documentation of `java.lang.Class.getName()`.

Let's look at some examples:

- "`java.lang.String`" must be specified for a parameter of type `java.lang.String`
- "`long`" must be specified for a parameter of type `long`
- "[`java.lang.Object`;" must be specified for a parameter of type `java.lang.Object[]`

Varargs parameters are specified using the corresponding array type, e.g. a parameter `String...` must be specified as "[`Ljava.lang.String;`".

If the `default-package` element is configured for the mapping file, any unqualified class names will be resolved using the given default package.

**NOTE** You must declare all parameters even if they are not reconfigured to ensure the right method is identified.

**NOTE** A given getter method representing a JavaBeans property may either be configured using the `getter` or the `method` element, but not both. If a `getter` element and a `method` element referring to the same method are detected by the Bean Validation provider, a `ValidationException` is raised.

If no method with the specified name and parameter types exists in the given bean a `ValidationException` is raised.

The optional `return-value` element is used to change the configuration of a method's return value if required.

The optional `cross-parameter` element is used to change the configuration of a method's cross-parameter constraints if required.

The constraints applying for a method's parameters and its return value are specified by adding `constraint` elements to the `parameter` and `return-value` elements respectively. Whether or not to perform cascaded validation is controlled using the `valid` element. Group conversion rules for cascaded validation are specified using the `convert-group` element.

The cross-parameter constraints applied on a method parameter list are specified by adding `constraint` elements to the `cross-parameter` element.

If `ignore-annotations` is declared on the parameter, cross-parameter element or return value level, Bean Validation must honor the explicit value for this element. Otherwise, if `ignore-annotations` is declared for the `method` element, Bean Validation must honor this value. Otherwise, the default value declared in the encapsulating `bean` element is considered.

When `ignore-annotations` is true, Bean Validation annotations on the targeted method or parameter are ignored (including `@Valid` and `@ConvertGroup`). When `ignore-annotations` is false:

- Constraints declared in XML and constraints declared in annotations are added and form the list of declared parameter, cross-parameter or return value constraints respectively.
- `@Valid` is considered unless the `valid` element is explicitly used. Note that the only way to disable cascading on a method parameter or return value marked as `@Valid` is to use

`ignore-annotations=true`. This does not apply to cross-parameter elements as cascading does not make sense in this situation.

- Group conversions declared in XML and via the `@ConvertGroup` annotation are added and form the list of applied conversions. Note that the rules for the declaration of group conversions as outlined in [Group conversion](#) apply, in particular it is not legal to declare several conversions for the same source group. This does not apply to cross-parameter elements as cascading does not make sense in this situation.

*Example 135. Method-level declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <method name="update" ignore-annotations="true">
            <parameter type="java.lang.String">
                [...]
            </parameter>
            <parameter type="int">
                <valid/>
                [...]
            </parameter>
            <parameter type="long" ignore-annotations="false"/>
            <cross-parameter ignore-annotations="false">
                [...]
            </cross-parameter>
            <return-value>
                <valid/>
                [...]
            </return-value>
            [...]
        </method>
    </bean>
</constraint-mappings>
```

#### 9.1.1.6. Container-element overriding

For applying constraints to the elements of generic container types or marking the same for cascaded validation, the `container-element-type` element is used.

`container-element-type` can be used within the `field`, `getter`, `parameter` and `return-value` elements.

The `type-argument-index` is used to specify the index of the configured type argument. The `ignore-annotations` settings effectively applying for the encapsulating element (`field`, `getter` etc.) are applied for `container-element-type`, too. The `container-element-type` element can be nested for configuring nested generic containers such as `List<List<String>>`.

Constraints are applied by adding `constraint` elements to `container-element-type`. Whether or not to perform cascaded validation is controlled using the `valid` element. Group conversion rules for cascaded validation are specified using the `convert-group` element.

*Example 136. Container-element declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <!-- Map<String, Address> -->
        <field name="addressesByType" ignore-annotations="true">
            <container-element-type type-argument-index="0">
                [...]
            </container-element-type>
            <container-element-type type-argument-index="1">
                <valid/>
                [...]
            </container-element-type>
            [...]
        </field>

        <!-- setContactsByType(Map<String, List<String>>) -->
        <method name="setContactsByType" ignore-annotations="true">
            <parameter type="java.util.Map">
                <container-element-type type-argument-index="1">
                    <valid/>
                    <container-element-type type-argument-index="0">
                        <valid/>
                        [...]
                    </container-element-type>
                    [...]
                </container-element-type>
                [...]
            </parameter>
            [...]
        </method>

    </bean>
</constraint-mappings>
```

### 9.1.1.7. Constraint declaration

New constraint declarations are represented by the `constraint` element. The `annotation` attribute is the class name of the annotation representing the constraint. Message, groups and payload are defined respectively by the `message`, `groups` and `payload` elements.

Other custom elements of an annotation are represented by `element`. The `name` attribute is mandatory and represents the name of the element in the constraint declaration. `message`, `groups` and `payload` are not permitted names, use the `message`, `groups` or `payload` elements instead. Otherwise a `ValidationException` is raised.

**NOTE** `validationAppliesTo` (see `validationAppliesTo`) is not necessary as cross-parameter constraints and return value constraints are declared in different XML elements, respectively `cross-parameter` and `return-value`.

If the element represents a primitive type, a class or an enum, the string representation of its value is placed in the element itself. See [Converting the string representation of a value](#) for a detailed explanation of the conversion rules from string to the type.

If the element represents a primitive type array, a class array or an enum array, the string representation of each value is placed in a `value` element placed under the element itself.

If the element represents an annotation, the `annotation` element is used to represent the annotation and placed under `element`. An `annotation` element contains `element` elements.

If the element represents an array of annotations, one or more `annotation` elements are placed under `element`.

Elements with default values in the annotation definition do not have to be represented in XML: the default value will be used in this case. If an XML constraint declaration is missing mandatory elements, or if it contains elements not part of the constraint definition, a `ValidationException` is raised.

#### *Example 137. Constraint declaration*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">
        <field name="firstName">
```

```

<!-- @LooksLike(patterns={
    @Pattern(value="myRegExp",
flag=PatternFlag.INSENSITIVE),
    @Pattern(value="my2ndRegExp") }
)
-->
<constraint annotation="com.acme.app.constraint.LooksLike">
    <element name="patterns">
        <annotation>
            <element name="value">myRegExp</element>
            <element name="flag">
                <value>INSENSITIVE</value>
            </element>
        </annotation>
        <annotation>
            <element name="value">my2ndRegExp</element>
        </annotation>
    </element>
</constraint>

</field>
<field name="orders">
    <valid/>

    <!-- @DiscreteSize(value={ 0, 20 } ) -->
    <constraint annotation="com.acme.app.constraint.DiscreteSize">
        <element name="value">
            <value>0</value>
            <value>20</value>
        </element>
    </constraint>

</field>

<!-- Map<@NotBlank String, @Valid PhoneNumber> -->
<field name="phoneNumbersByType">
    <container-element-type type-argument-index="0">
        <constraint annotation=
"javax.validation.constraints.NotBlank"/>
    </container-element-type>
    <container-element-type type-argument-index="1">
        <valid/>
    </container-element-type>
</field>

<getter name="orders">
    <valid/>

    <!-- @Size(message="Size is limited",
groups={Default.class, LightValidation.class},
max=30
)
-->

```

```

<constraint annotation="javax.validation.constraints.Size">
    <message>Size is limited</message>
    <groups>
        <value>com.acme.app.model.LightValidation</value>
        <value>javax.persistence.Default</value>
    </groups>
    <payload>
        <value>com.acme.app.model.WARN</value>
    </payload>
    <element name="max">30</element>
</constraint>

</getter>

<constructor ignore-annotations="true">
    <parameter type="java.lang.String">
        <!-- @DiscreteSize(value={ 0, 20 } ) -->
        <constraint annotation=
"com.acme.app.constraint.DiscreteSize">
            <element name="value">
                <value>0</value>
                <value>20</value>
            </element>
        </constraint>
    </parameter>
</constructor>

<method name="update" ignore-annotations="true">
    <parameter type="java.lang.String">
        <!-- @DiscreteSize(value={ 0, 20 } ) -->
        <constraint annotation=
"com.acme.app.constraint.DiscreteSize">
            <element name="value">
                <value>0</value>
                <value>20</value>
            </element>
        </constraint>
    </parameter>
    <return-value>
        <!-- @ValidCustomer -->
        <constraint annotation=
"com.acme.app.constraint.ValidCustomer"/>
    </return-value>
</method>

<method name="resetPassword" ignore-annotations="false">
    <parameter type="java.lang.String"/>
    <parameter type="java.lang.String"/>

    <cross-parameter>
        <!-- @ValidResetPasswordParameters -->
        <constraint annotation=
"com.acme.app.constraint.ValidResetPasswordParameters"/>
    </cross-parameter>
</method>
</bean>
```

```
</constraint-mappings>
```

#### 9.1.1.8. Declaration of group conversions

Group conversion rules are declared by specifying one or more `convert-group` elements within the `field`, `getter`, `parameter` and `return-value` elements.

Source and target group of a conversion rule are given by specifying their fully-qualified names within the `from` and `to` attribute respectively. If the `default-package` element is configured for the mapping file, any unqualified class names will be resolved using the given default package.

*Example 138. Declaration of group conversions*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="Customer" ignore-annotations="false">

        <field name="firstName">
            <valid/>
            <convert-group from="javax.validation.groups.Default" to=
"com.acme.CustomerBasic"/>
            <convert-group from="com.acmenote.Advanced" to=
"com.acme.CustomerComplex"/>
        </field>

        <getter name="orders">
            <valid/>
            <convert-group from="javax.validation.groups.Default" to=
"com.acme.CustomerBasic"/>
        </getter>

        <constructor>
            <parameter type="java.lang.String">
                <valid/>
                <convert-group from="javax.validation.groups.Default" to
="com.acme.CustomerBasic"/>
            </parameter>
            <return-value>
                <valid/>
                <convert-group from="javax.validation.groups.Default" to
="com.acme.CustomerBasic"/>
            </return-value>
        </constructor>

        <method name="update">
            <parameter type="java.lang.String">
                <valid/>
                <convert-group from="javax.validation.groups.Default" to
="com.acme.CustomerBasic"/>
            </parameter>
            <return-value>
                <valid/>
                <convert-group from="javax.validation.groups.Default" to
="com.acme.CustomerBasic"/>
            </return-value>
        </constructor>
    </bean>
</constraint-mappings>
```

### 9.1.2. Overriding constraint definitions in XML

A constraint definition (i.e. the annotation representing a constraint), cannot be fully expressed in XML but the list of `ConstraintValidators`s associated to a given constraint can be altered.

A constraint definition is represented by a `constraint-definition` element. The `annotation` attribute represents the constraint annotation being altered. The `validated-by` elements represent the (ordered) list of `ConstraintValidator` implementations associated to the constraint.

If `include-existing-validator` is set to false, `ConstraintValidator` defined on the constraint annotation are ignored. If set to true, the list of `ConstraintValidators` described in XML are concatenated to the list of `ConstraintValidator` described on the annotation to form a new array of `ConstraintValidator` evaluated. Annotation based `ConstraintValidator` come before XML based `ConstraintValidators` in the array. The new list is returned by `ConstraintDescriptor.getConstraintValidatorClasses()`.

*Example 139. Overriding constraint definitions*

```
<?xml version="1.0" encoding="UTF-8"?>
<constraint-mappings
    xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/mapping validation-
mapping-2.0.xsd"
    version="2.0">
    <default-package>com.acme.app.domain</default-package>
    <bean class="com.acme.common.model.Address">
        [...]
    </bean>

    <constraint-definition annotation="javax.validation.constraints.Size">
        <validated-by include-existing Validators="true">
            <value>
                com.acme.app.constraint.SizeValidatorForDictionary</value>
            </validated-by>
        </constraint-definition>
        <constraint-definition annotation="AcmeOrderNumber">
            [...]
        </constraint-definition>
    </constraint-mappings>
```

### 9.1.3. Converting the string representation of a value

Primitive types, `Class` and `Enum` are represented as strings in the XML descriptor. Elements of an array are represented by the `value` element.

A `byte` is represented according to the rules defined in `Byte.parseByte(String)`.

A `short` is represented according to the rules defined in `Short.parseShort(String)`.

An `int` is represented according to the rules defined in `Integer.parseInt(String)`.

A `long` is represented according to the rules defined in `Long.parseLong(String)`.

A `float` is represented according to the rules defined in `Float.parseFloat(String)`.

A `double` is represented according to the rules defined in `Double.parseDouble(String)`.

A `boolean` is represented according to the rules defined in `Boolean.parseBoolean(String)`.

A `char` is represented according to the following rules:

- the string must be of one character long
- the character extracted from the string is the returned `char`

A `Class` is represented by the fully qualified class name of the class or more precisely according to the syntax described in the documentation of `java.lang.Class.getName()`. Note that if the raw string is unqualified, default package is taken into account.

An enum is represented by its `enum.name()` value.

If any of the string representation does not match its type counterpart, a `ValidationException` is raised.

#### 9.1.4. XML Schema

This section contains the XML schema used for constraint mapping descriptors.

From Bean Validation revision 1.1 onwards, mapping authors must specify the used version of the schema within the `version` attribute of the `constraint-mappings` element. Implementations supporting Bean Validation 2.0 must properly parse mapping descriptors of Bean Validation 1.0, 1.1 and 2.0. If the `version` attribute attribute is not given, schema version 1.0 is to be assumed by the Bean Validation provider.

In case an unknown version is given (e.g. if a mapping descriptor adhering to a future schema version is parsed by a Bean Validation 2.0 provider) a `ValidationException` is raised.

*Example 140. XML schema for constraint mapping descriptors*

```
<?xml version="1.0" encoding="UTF-8"?>
```

```

<xs:schema attributeFormDefault="unqualified"
            elementFormDefault="qualified"
            targetNamespace=
"http://xmlns.jcp.org/xml/ns/validation/mapping"
            xmlns:xs="http://www.w3.org/2001/XMLSchema"
            xmlns:map="http://xmlns.jcp.org/xml/ns/validation/mapping"
            version="2.0">

    <xs:annotation>
        <xs:documentation><![CDATA[
            This is the XML Schema for Bean Validation constraint mapping
            files.

            Bean Validation constraint mapping files must indicate the
            Bean Validation
            XML schema by using the constraint mapping namespace:

            http://xmlns.jcp.org/xml/ns/validation/mapping

            and indicate the version of the schema by using the version
            attribute
            as shown below:

            <constraint-mappings
                xmlns="http://xmlns.jcp.org/xml/ns/validation/mapping"
                xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
                xsi:schemaLocation="
                    http://xmlns.jcp.org/xml/ns/validation/mapping
                    validation-mapping-2.0.xsd"
                version="2.0">
                ...
            </constraint-mappings>
        ]]>
        </xs:documentation>
    </xs:annotation>

    <xs:element name="constraint-mappings" type="map:constraint-
mappingsType"/>

    <xs:complexType name="payloadType">
        <xs:sequence>
            <xs:element type="xs:string" name="value" maxOccurs=
"unbounded" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="groupsType">
        <xs:sequence>
            <xs:element type="xs:string" name="value" maxOccurs=
"unbounded" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="groupSequenceType">
        <xs:sequence>
            <xs:element type="xs:string" name="value" maxOccurs=
"unbounded" minOccurs="0"/>
        </xs:sequence>
    </xs:complexType>
    <xs:complexType name="groupConversionType">
        <xs:attribute type="xs:string" name="from" use="required"/>
        <xs:attribute type="xs:string" name="to" use="required"/>

```

```

</xs:complexType>
<xs:complexType name="constraint-mappingsType">
    <xs:sequence>
        <xs:element type="xs:string" name="default-package"
minOccurs="0"/>
        <xs:element type="map:beanType"
name="bean"
maxOccurs="unbounded"
minOccurs="0"/>
        <xs:element type="map:constraint-definitionType"
name="constraint-definition"
maxOccurs="unbounded"
minOccurs="0"/>
    </xs:sequence>
    <xs:attribute name="version" type="map:versionType" fixed="2.0"
use="required"/>
</xs:complexType>
<xs:simpleType name="versionType">
    <xs:restriction base="xs:token">
        <xs:pattern value="[0-9]+(\.[0-9]+)*"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="validated-byType">
    <xs:sequence>
        <xs:element type="xs:string" name="value" maxOccurs=
"unbounded" minOccurs="0"/>
    </xs:sequence>
    <xs:attribute type="xs:boolean" name="include-existing-
validators" use="optional"/>
</xs:complexType>
<xs:complexType name="constraintType">
    <xs:sequence>
        <xs:element type="xs:string" name="message" minOccurs="0"/>
        <xs:element type="map:groupsType"
name="groups"
minOccurs="0"/>
        <xs:element type="map:payloadType"
name="payload"
minOccurs="0"/>
        <xs:element type="map:elementType"
name="element"
maxOccurs="unbounded"
minOccurs="0"/>
    </xs:sequence>
    <xs:attribute type="xs:string" name="annotation" use="required"/>
</xs:complexType>
<xs:complexType name="elementType" mixed="true">
    <xs:sequence>
        <xs:element type="xs:string" name="value" maxOccurs=
"unbounded" minOccurs="0"/>
        <xs:element type="map:annotationType"
name="annotation"
maxOccurs="unbounded"
minOccurs="0"/>
    </xs:sequence>
    <xs:attribute type="xs:string" name="name" use="required"/>
</xs:complexType>
<xs:complexType name="containerElementTypeType">
    <xs:sequence>

```

```

<xs:element type="xs:string" name="valid" minOccurs="0"
fixed="" />
<xs:element type="map:groupConversionType"
            name="convert-group"
            minOccurs="0"
            maxOccurs="unbounded" />
<xs:element type="map:constraintType"
            name="constraint"
            maxOccurs="unbounded"
            minOccurs="0" />
<xs:element type="map:containerElementTypeType"
            name="container-element-type"
            maxOccurs="unbounded"
            minOccurs="0" />
</xs:sequence>
<xs:attribute name="type-argument-index" use="optional">
<xs:simpleType>
<xs:restriction base="xs:int">
<xs:minInclusive value="0" />
</xs:restriction>
</xs:simpleType>
</xs:attribute>
</xs:complexType>
<xs:complexType name="classType">
<xs:sequence>
<xs:element type="map:groupSequenceType"
            name="group-sequence"
            minOccurs="0" />
<xs:element type="map:constraintType"
            name="constraint"
            maxOccurs="unbounded"
            minOccurs="0" />
</xs:sequence>
<xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional"/>
</xs:complexType>
<xs:complexType name="beanType">
<xs:sequence>
<xs:element type="map:classType"
            name="class"
            minOccurs="0" />
</xs:element>
<xs:element type="map:fieldType"
            name="field"
            minOccurs="0"
            maxOccurs="unbounded" />
<xs:element type="map:getterType"
            name="getter"
            minOccurs="0"
            maxOccurs="unbounded" />
<xs:element type="map:constructorType"
            name="constructor"
            minOccurs="0"
            maxOccurs="unbounded" />
<xs:element type="map:methodType"
            name="method"
            minOccurs="0"
            maxOccurs="unbounded" />
</xs:sequence>

```

```

<xs:attribute type="xs:string" name="class" use="required"/>
<xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional" default="true"/>
</xs:complexType>
<xs:complexType name="annotationType">
<xs:sequence>
<xs:element type="map:elementType"
            name="element"
            maxOccurs="unbounded"
            minOccurs="0"/>
</xs:sequence>
</xs:complexType>
<xs:complexType name="getterType">
<xs:sequence>
<xs:element type="xs:string" name="valid" minOccurs="0"
fixed="" />
<xs:element type="map:groupConversionType"
            name="convert-group"
            minOccurs="0"
            maxOccurs="unbounded"/>
<xs:element type="map:containerElementTypeType"
            name="container-element-type"
            minOccurs="0"
            maxOccurs="unbounded"/>
<xs:element type="map:constraintType"
            name="constraint"
            minOccurs="0"
            maxOccurs="unbounded"/>
</xs:sequence>
<xs:attribute type="xs:string" name="name" use="required"/>
<xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional"/>
</xs:complexType>
<xs:complexType name="methodType">
<xs:sequence>
<xs:element type="map:parameterType"
            name="parameter"
            minOccurs="0"
            maxOccurs="unbounded"/>
<xs:element type="map:crossParameterType"
            name="cross-parameter"
            minOccurs="0"
            maxOccurs="1"/>
<xs:element type="map:returnValueType"
            name="return-value"
            minOccurs="0"
            maxOccurs="1"/>
</xs:sequence>
<xs:attribute type="xs:string" name="name" use="required"/>
<xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional"/>
</xs:complexType>
<xs:complexType name="constructorType">
<xs:sequence>
<xs:element type="map:parameterType"
            name="parameter"
            minOccurs="0"
            maxOccurs="unbounded"/>
<xs:element type="map:crossParameterType"

```

```

        name="cross-parameter"
        minOccurs="0"
        maxOccurs="1"/>
    <xs:element type="map:returnValueType"
        name="return-value"
        minOccurs="0"
        maxOccurs="1"/>
</xs:sequence>
<xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional"/>
</xs:complexType>
<xs:complexType name="parameterType">
    <xs:sequence>
        <xs:element type="xs:string" name="valid" minOccurs="0"
fixed="" />
        <xs:element type="map:groupConversionType"
            name="convert-group"
            minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element type="map:containerElementTypeType"
            name="container-element-type"
            minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element type="map:constraintType"
            name="constraint"
            minOccurs="0"
            maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute type="xs:string" name="type" use="required"/>
    <xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional"/>
</xs:complexType>
<xs:complexType name="returnValueType">
    <xs:sequence>
        <xs:element type="xs:string" name="valid" minOccurs="0"
fixed="" />
        <xs:element type="map:groupConversionType"
            name="convert-group"
            minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element type="map:containerElementTypeType"
            name="container-element-type"
            minOccurs="0"
            maxOccurs="unbounded"/>
        <xs:element type="map:constraintType"
            name="constraint"
            minOccurs="0"
            maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute type="xs:boolean" name="ignore-annotations" use=
"optional"/>
</xs:complexType>
<xs:complexType name="crossParameterType">
    <xs:sequence>
        <xs:element type="map:constraintType"
            name="constraint"
            minOccurs="0"
            maxOccurs="unbounded"/>
    </xs:sequence>

```

```

<xs:attribute type="xs:boolean" name="ignore-annotations" use="optional"/>
</xs:complexType>
<xs:complexType name="constraint-definitionType">
    <xs:sequence>
        <xs:element type="map:validated-byType"
                    name="validated-by"/>
    </xs:sequence>
    <xs:attribute type="xs:string" name="annotation" use="required"/>
</xs:complexType>
<xs:complexType name="fieldType">
    <xs:sequence>
        <xs:element type="xs:string" name="valid" minOccurs="0"
fixed="" />
        <xs:element type="map:groupConversionType"
                    name="convert-group"
                    minOccurs="0"
                    maxOccurs="unbounded"/>
        <xs:element type="map:containerElementTypeType"
                    name="container-element-type"
                    minOccurs="0"
                    maxOccurs="unbounded"/>
        <xs:element type="map:constraintType"
                    name="constraint"
                    minOccurs="0"
                    maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute type="xs:string" name="name" use="required"/>
    <xs:attribute type="xs:boolean" name="ignore-annotations" use="optional"/>
</xs:complexType>
</xs:schema>

```

## 9.2. Configuration schema

XML Configuration is set in **META-INF/validation.xml**. The file is optional. The XML schema followed by the configuration file is as followed.

*Example 141. XML configuration XSD*

```

<?xml version="1.0" encoding="UTF-8"?>

<xs:schema attributeFormDefault="unqualified"
            elementFormDefault="qualified"
            targetNamespace=
"http://xmlns.jcp.org/xml/ns/validation/configuration"
            xmlns:xs="http://www.w3.org/2001/XMLSchema"
            xmlns:config=
"http://xmlns.jcp.org/xml/ns/validation/configuration"
            version="2.0">

    <xs:annotation>
        <xs:documentation><![CDATA[
            This is the XML Schema for the Bean Validation configuration

```

```

file.
    The configuration file must be named "META-INF/validation.xml".

        Bean Validation configuration files must indicate the Bean Validation
        XML schema by using the validation namespace:
            http://xmlns.jcp.org/xml/ns/validation/configuration
            and indicate the version of the schema by using the version
            attribute
            as shown below:

                <validation-config

                    xmlns="http://xmlns.jcp.org/xml/ns/validation/configuration"
                        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
                        xsi:schemaLocation="
                            http://xmlns.jcp.org/xml/ns/validation/configuration
                            validation-configuration-2.0.xsd"
                        version="2.0">
                    [...]
                </validation-config>
            ]]>
        </xs:documentation>
    </xs:annotation>

        <xs:element name="validation-config" type="config:validation-
configType"/>
        <xs:complexType name="validation-configType">
            <xs:sequence>
                <xs:element type="xs:string" name="default-provider"
minOccurs="0"/>
                <xs:element type="xs:string" name="message-interpolator"
minOccurs="0"/>
                <xs:element type="xs:string" name="traversable-resolver"
minOccurs="0"/>
                <xs:element type="xs:string" name="constraint-validator-
factory" minOccurs="0"/>
                <xs:element type="xs:string" name="parameter-name-provider"
minOccurs="0"/>
                <xs:element type="xs:string" name="clock-provider" minOccurs
="0"/>
                <xs:element type="xs:string" name="value-extractor"
maxOccurs="unbounded" minOccurs="0"/>
                <xs:element type="config:executable-validationType" name=
"executable-validation" minOccurs="0"/>
                <xs:element type="xs:string" name="constraint-mapping"
maxOccurs="unbounded" minOccurs="0"/>
                <xs:element type="config:propertyType" name="property"
maxOccurs="unbounded" minOccurs="0"/>
            </xs:sequence>
            <xs:attribute name="version" type="config:versionType" fixed="2.0"
use="required"/>
        </xs:complexType>

        <xs:complexType name="executable-validationType">
            <xs:sequence>
                <xs:element type="config:default-validated-executable-

```

```

typesType" name="default-validated-executable-types" minOccurs="0"/>
  </xs:sequence>
  <xs:attribute name="enabled" use="optional" type="xs:boolean"
default="true"/>
</xs:complexType>
<xs:complexType name="default-validated-executable-typesType">
  <xs:sequence>
    <xs:element name="executable-type" maxOccurs="unbounded"
minOccurs="1">
      <xs:simpleType>
        <xs:restriction base="xs:string">
          <xs:enumeration value="NONE"/>
          <xs:enumeration value="CONSTRUCTORS"/>
          <xs:enumeration value="NON_GETTER_METHODS"/>
          <xs:enumeration value="GETTER_METHODS"/>
          <xs:enumeration value="ALL"/>
        </xs:restriction>
      </xs:simpleType>
    </xs:element>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="propertyType">
  <xs:simpleContent>
    <xs:extension base="xs:string">
      <xs:attribute name="name" use="required" type="xs:string"
    />
    </xs:extension>
  </xs:simpleContent>
</xs:complexType>
<xs:simpleType name="versionType">
  <xs:restriction base="xs:token">
    <xs:pattern value="[0-9]+(\.[0-9]+)*" />
  </xs:restriction>
</xs:simpleType>
</xs:schema>

```

From Bean Validation revision 1.1 onwards, the used version of the schema must be specified within the `version` attribute of the `validation-config` element. Implementations supporting Bean Validation 2.0 must properly parse configuration descriptors of Bean Validation 1.0, 1.1 and 2.0. If the `version` attribute attribute is not given, schema version 1.0 is to be assumed by the Bean Validation Provider.

In case an unknown version is given a `ValidationException` is raised.

See [XML configuration: META-INF/validation.xml](#) for more information on XML based configuration.

# 10. Exception model

Illegal arguments passed to the Bean Validation APIs generally lead to an `IllegalArgumentException` (see the JavaDoc for specific details). Other exceptions raised by Bean Validation are or inherit from the runtime exception `javax.validation.ValidationException`. Exception cases are described in their respective sections but include (non exhaustive list):

- invalid constraint definitions (missing mandatory elements, illegal composition cycle, illegal attribute overriding, etc.)
- invalid constraint declarations (`ConstraintValidator` implementation matching failure, etc.)
- invalid group definition (circularity)
- invalid `Default` group redefinition for classes (missing class group etc)
- invalid group conversion definitions
- error when retrieving, initializing, executing `ConstraintValidators`
- error when parsing the XML configuration or mappings
- multiple XML configuration files found
- missing expected provider or no default provider found
- missing no-arg constructor on extension implementations described in XML configuration files
- same entity described more than once across the XML mapping files
- same property or field described more than once for a given entity in the XML mapping files
- class, field or getter declared in XML mapping files but not found
- illegal XML constraint definition
- illegal XML constraint declaration
- exception raised either at initialization time or execution time by any of the extension interfaces

Each of these error cases lead to a `ValidationException` or a subclass of `ValidationException` (see following subsections).

Every (runtime) exception raised either at initialization time or execution time by any of the extension interfaces (`ConstraintValidator`, `ConstraintValidatorFactory`, `MessageInterpolator`, `TraversableResolver`, `ValidationProviderResolver`, `ParameterNameProvider`, `ClockProvider`) is wrapped in a `ValidationException`.

If a constraint definition or constraint declaration is invalid for a given class, the metadata API

should raise the according exception.

## 10.1. Error report: `ConstraintViolationException`

Some frameworks or applications need to convey the result of a validation by raising an exception if the validation returns constraint violations.

Bean Validation provides a reference exception for such cases. Frameworks and applications are encouraged to use `ConstraintViolationException` as opposed to a custom exception to increase consistency of the Java platform. The exception can be raised directly or wrapped into the framework or application specific parent exception.

*Example 142. ConstraintViolationException*

```
/**  
 * Reports the result of constraint violations.  
 *  
 * @author Emmanuel Bernard  
 * @author Gunnar Morling  
 */  
public class ConstraintViolationException extends ValidationException {  
    [...]  
  
    /**  
     * Creates a constraint violation report.  
     *  
     * @param message error message  
     * @param constraintViolations {@code Set<? extends ConstraintViolation>} of {@link ConstraintViolation}  
     */  
    public ConstraintViolationException(String message,  
                                         Set<? extends ConstraintViolation> constraintViolations) {  
        [...]  
    }  
  
    /**  
     * Creates a constraint violation report.  
     *  
     * @param constraintViolations {@code Set<? extends ConstraintViolation>} of {@link ConstraintViolation}  
     */  
    public ConstraintViolationException(Set<? extends ConstraintViolation> constraintViolations) {  
        [...]  
    }  
  
    /**  
     * Set of constraint violations reported during a validation.  
     *  
     * @return {@code Set<ConstraintViolation>} of {@link ConstraintViolation}  
     */  
    public Set<ConstraintViolation> getConstraintViolations() {  
        [...]  
    }  
}
```

The `ConstraintViolationException` carries a `Set` of `ConstraintViolation`.

**NOTE**

Bean Validation never raises this exception itself. Other frameworks like Java Persistence 2 or interception framework wiring method validation do.

**NOTE** If this exception is meant to be sent remotely, `ConstraintViolation` objects should be `Serializable` as defined and explained in [ConstraintViolation](#).

## 10.2. Constraint definition: `ConstraintDefinitionException`

If a constraint definition does not respect the Bean Validation rules or is inconsistent, a `ConstraintDefinitionException` is raised. `ConstraintDefinitionException` is a subclass of `ValidationException`.

This exception can be raised during validation or when the metadata model for the class hosting this constraint is requested.

**NOTE** These exception cases can be determined at compile time by a tool such as an annotation processor.

## 10.3. Constraint declaration: `ConstraintDeclarationException` and `UnexpectedTypeException`

When a constraint declaration is illegal, `ConstraintDeclarationException` is raised. Reasons include:

- incorrect group conversion rules (definition or positioning)
- no suitable value extractor could be unambiguously identified for container element validation or cascaded validation of a container
- illegal method constraint declarations (e.g. inheritance rules, cross-parameter constraint used in an illegal situation, improper use of `validationAppliesTo`).

`ConstraintDeclarationException` is a subclass of `ValidationException`.

When the return type of a property cannot be processed for a given constraint, an `UnexpectedTypeException` is raised. This problem typically arises when either no `ConstraintValidators` or too many `ConstraintValidators` match the return type (see [ConstraintValidator resolution algorithm](#)).

`UnexpectedTypeException` is a subclass of `ConstraintDeclarationException`.

This exception can be raised during validation or when the metadata model for the class hosting this constraint is requested.

**NOTE**

These exception cases can be determined at compile time by a tool such as an annotation processor.

## 10.4. Group definition: `GroupDefinitionException`

When a group definition is illegal, a `GroupDefinitionException` is raised. This typically arises when a cyclic group dependency is discovered, an illegal attribute overriding is defined etc.

`GroupDefinitionException` is a subclass of `ValidationException`.

**NOTE**

These exception cases can be determined at compile time by a tool such as an annotation processor.

## 10.5. Value extractor definition:

`ValueExtractorDefinitionException`

When detecting an illegal value extractor definition, a `ValueExtractorDefinitionException` will be raised.

Reasons for raising this exception include:

- The extracted type is not marked with `@ExtractedValue`
- The `@ExtractedValue` annotation is given more than once for one value extractor type

```

package javax.validation.valueextraction;

/**
 * Raised if a {@link ValueExtractor} definition is illegal, e.g. because it
 * doesn't declare its extracted value using
 * {@link ExtractedValue}.
 *
 * @author Gunnar Morling
 *
 * @since 2.0
 */
public class ValueExtractorDefinitionException extends ValidationException {

    public ValueExtractorDefinitionException() {
        super();
    }

    public ValueExtractorDefinitionException(String message) {
        super( message );
    }

    public ValueExtractorDefinitionException(Throwable cause) {
        super( cause );
    }

    public ValueExtractorDefinitionException(String message, Throwable cause)
    {
        super( message, cause );
    }
}

```

## 10.6. Value extractor declaration:

`ValueExtractorDeclarationException`

When detecting an illegal configuration of value extractors, a `ValueExtractorDeclarationException` will be raised. One example is the configuration of multiple extractors for the same container element type in `META-INF/validation.xml`.

```

package javax.validation.valueextraction;

/**
 * Raised if the configuration of {@link ValueExtractor} is illegal, e.g.
 * because multiple extractors for the same type
 * and type use have been configured in {@code META-INF/validation.xml}.
 *
 * @author Gunnar Morling
 *
 * @since 2.0
 */
public class ValueExtractorDeclarationException extends ValidationException {

    public ValueExtractorDeclarationException() {
        super();
    }

    public ValueExtractorDeclarationException(String message) {
        super( message );
    }

    public ValueExtractorDeclarationException(Throwable cause) {
        super( cause );
    }

    public ValueExtractorDeclarationException(String message, Throwable cause)
    {
        super( message, cause );
    }
}

```

## 10.7. No Bean Validation Provider detected:

NoProviderFoundException

When trying to bootstrap Bean Validation via `Validation.buildDefaultValidatorFactory()` or `Validation.byDefaultProvider().configure()` and no Bean Validation provider could be found, a `NoProviderFoundException` is raised.

`NoProviderFoundException` is a subclass of `ValidationException`.

# 11. Integration

In this chapter, integration points between Bean Validation and other technologies are discussed. We first address the integration in generic terms applying to all integrations and we then detail how integration with various Java EE specifications is handled more specifically.

## 11.1. General requirements

This section covers general requirements that should be followed by any container and interception technology integrating Bean Validation.

### 11.1.1. Objects lifecycle

Generally speaking, containers and frameworks controlling the lifecycle of objects (such as Java EE, dependency injection frameworks or component frameworks) should:

- build and bootstrap the `ValidatorFactory` instance for an application.
- provide access to the `ValidatorFactory` instance as well as `Validator` instances in their default configuration using the paradigm of the container: for example, such instances would be injectable in other objects via a dependency injection framework.
- configure `ValidatorFactory` with a custom `ConstraintValidatorFactory` instance that returns managed `ConstraintValidator` instances, unless a custom `ConstraintValidatorFactory` is requested by the user. The scope of `ConstraintValidator` instances is still fully controlled by the Bean Validation provider as described in [The ConstraintValidatorFactory](#), but as managed beans they can receive expected services like injection of other objects.
- configure `ValidatorFactory` with managed instances of `ConstraintValidatorFactory`, `MessageInterpolator`, `ParameterNameProvider`, `ClockProvider` and `TraversableResolver`, if such instances are defined in the XML deployment descriptor. Services provided by the container (like dependency injection) should thus be available to these instances.
- invoke `ValidatorFactory.close()` when the `ValidatorFactory` instance is no longer needed.
- dispose of managed instances provided to the Bean Validation bootstrap process after `ValidatorFactory.close()` has been invoked.

## IMPORTANT

In this context, a default `ValidatorFactory` is a factory configured like the factory returned by `Validation.buildDefaultValidatorFactory` (see also [Validation](#)) except for the enhancements described above. A default `Validator` instance is a `Validator` instance retrieved via `getValidator()` from the default `ValidatorFactory`.

### 11.1.2. Method and constructor validation

This section expresses the behavior that integration with interception frameworks should follow. Any deviation should be considered with care as it will surprise Bean Validation users.

Method interception frameworks (such as AOP or interceptor frameworks) enable interception of constrained methods following the steps defined in [Triggering method validation](#). Method validation execution is implicit for any method or constructor annotated with constraints.

By default, method validation is applied to all constrained methods or constructors provided the integration technology can intercept the call. By default, getters (as defined in [Requirements on classes to be validated](#)) are not considered constrained methods. Static methods are ignored by validation. Putting constraints on a static method is not portable.

Bean Validation - via the interception technology - offers a way to customize whether or not a constructor, method or getter is validated when executed. This is achieved:

- via the `@ValidateOnExecution` annotation on the executable (see [@ValidateOnExecution annotation](#))
- via the `@ValidateOnExecution` annotation on the type declaring the executable
- via a global configuration defined in `validation.xml`: `executable-validation` and `default-validated-executable-types`. See [XML configuration: META-INF/validation.xml](#) for more details.

## NOTE

Integration layers can read the list of validated executable types defined in the global configuration as well as read whether or not executable validation is disabled via the `Configuration` object: `configuration.getBootstrapConfiguration().getDefaultValidatedExecutableTypes()` and `configuration.getBootstrapConfiguration().isExecutableValidationEnabled()` respectively. This list is extracted from `validation.xml`.

More formally, a given executable (constructor or method) is validated upon execution according to the following rules in decreasing order:

- the executable is validated if it is annotated with `@ValidateOnExecution` and the type

attribute contains the executable type or **IMPLICIT**. If the `type` attribute does neither contain the executable type nor **IMPLICIT**, the executable is not validated.

- otherwise the executable is validated if the type (class, interface) on which it is declared is annotated with `@ValidateOnExecution` and the `type` attribute contains the executable type. If the `type` attribute contains **IMPLICIT**, then this rule is ignored and the behavior is equivalent to `@ValidateOnExecution` not being present. If the `type` attribute does not contain the executable type, the executable is not validated.
- otherwise the executable is validated if the global executable validation setting contains the executable type. If the global setting does not contain the executable type, the executable is not validated.
- The rules above do not apply to methods overriding a superclass method or implementing an interface method. In this case, the method inherits the behavior of the method it overrides / implements. Out of the box, a conforming integration implementation raises a `ValidationException` if the overriding / implementing method hosts the `@ValidateOnExecution` annotation.

The last point is present to enforce the Liskov substitution principle (more info at [Method constraints in inheritance hierarchies](#)). In addition, providers may implement alternative, potentially more liberal, approaches for handling validated methods in inheritance hierarchies. Possible means for activating such alternative behavior include provider-specific configuration properties or annotations. Note that client code relying on such alternative behavior is not portable.

The following executable types are available:

- **NONE**: parameters and return values are not validated upon execution. This option is equivalent to an empty list of executable types and is present to improve readability. A list containing **NONE** and other types of executables is equivalent to a list containing the types of executables without **NONE**.
- **CONSTRUCTORS**: parameters and return values are validated provided the executable is a constructor.
- **NON\_GETTER\_METHODS**: parameters and return values are validated provided the executable is a method but not a getter.
- **GETTER\_METHODS**: return values are validated provided the executable is a getter method.
- **ALL**: parameters and return values are validated for all executables (getters, non getters and constructors). This option is equivalent to a list of all executable types and is present to improve readability. A list containing **ALL** and other types of executables is equivalent to a list containing only **ALL**.
- **IMPLICIT**: if `@ValidateOnExecution` is on a type (class or interface), then it is equivalent to `@ValidateOnExecution` not being present; if `@ValidateOnExecution` is on a executable, the following applies:

- if on a constructor, it is equivalent to **CONSTRUCTORS**.
- if on a non-getter method, it is equivalent to **NON\_GETTER\_METHODS**.
- if on a getter, it is equivalent to **GETTER\_METHODS**.

Mixing **IMPLICIT** and other executable types is illegal.

*Example 143. @ValidateOnExecution annotation*

```
package javax.validation.executable;

/**
 * Expresses which executables (methods or constructors) should have
their parameters
 * and return value validated upon execution. Can be on executable
(method, constructor)
 * or type level (with the former taking precedence).
 * <p>
 * If not present for a given executable, the default configuration from
 * {@code META-INF/validation.xml} and finally the implicit default
 * validated executable types (constructors and non-getters) are taken
into account to determine
 * whether a given executable is validated upon execution or not.
 * <p>
 * The following describes the formal rules for deciding whether an
executable is validated.
 * They are applied in decreasing order:
 * <ul>
 *   <li>the executable is validated if it is annotated with {@code
@ValidateOnExecution} and
 *       the {@code type} attribute contains the executable type or {@link
ExecutableType#IMPLICIT}.
 *   <li>If the {@code type} attribute does neither contain the executable
type nor {@code IMPLICIT},
 *       the executable is not validated.</li>
 *   <li>otherwise the executable is validated if the type (class,
interface) on which it is
 *       declared is annotated with {@code @ValidateOnExecution} and the
{@code type} attribute
 *       contains the executable type. If the {@code type} attribute
contains
 *       {@code IMPLICIT}, then this rule is ignored and the behavior is
 *       equivalent to {@code ValidateOnExecution} not being present. If
the
 *       {@code type} attribute does not contain the executable type, the
executable is not
 *       validated.</li>
 *   <li>otherwise the executable is validated if the global executable
validation setting
 *       contains the executable type. If the global setting does not
contain the executable type,
 *       the executable is not validated.</li>
 *   <li>The rules above do not apply to methods overriding a
superclass method or
 *       implementing an interface method. In this case, the method
```

```

inherits the behavior
 *      of the method it overrides or implements. Out of the box, a
conforming implementation
 *      raises a {@link ValidationException} if the overriding /
implementing method hosts
 *      the {@code ValidateOnExecution} annotation.</li>
* </ul>
* <p>
* Note that you can exclude an executable from validation by making sure
the rules above do not match
 * or by annotating the executable with {@code
@ValidateOnExecution(NONE)}.
*
* @author Emmanuel Bernard
* @since 1.1
*/
@Target({ CONSTRUCTOR, METHOD, TYPE, PACKAGE })
@Retention(RUNTIME)
@Documented
public @interface ValidateOnExecution {

    /**
     * List of executable types to be validated when called.
     * Defaults to the types discovered implicitly (see {@link
ExecutableType#IMPLICIT}).
    *
     * @return array of {@code ExecutableType}s to be validated
    */
    ExecutableType[] type() default {ExecutableType.IMPLICIT};
}

```

```

package javax.validation.executable;

/**
 * Defines the types of executables targeted by an operation.
 *
 * @author Emmanuel Bernard
 * @since 1.1
*/
public enum ExecutableType {

    /**
     * If the annotation using {@code ExecutableType} is on a type (class
or interface),
     * the behavior is equivalent to the annotation not being present.
     * <p>
     * If on a constructor, it is equivalent to {@link #CONSTRUCTORS}.
     * <p>
     * If on a non-getter method, it is equivalent to {@link
#NON_GETTER_METHODS}.
     * <p>
     * If on a getter method, it is equivalent to {@link
#GETTER_METHODS}.
    */
    IMPLICIT,

    /**
     * None of the executables.

```

```

    * <p>
    * Note that this option is equivalent to an empty list of executable
types
        * and is present to improve readability. If {@code NONE} and other
types of executables
            * are present in a list, {@code NONE} is ignored.
        */
    NONE,
}

/**
 * All constructors.
*/
CONSTRUCTORS,

/**
 * All methods except the ones following the getter pattern. A getter
according to the
    * JavaBeans specification is a method whose:
    * <ul>
        *      <li>name starts with get, has a return type but no
parameter</li>
        *      <li>name starts with is, has a return type and is returning
{@code boolean}.</li>
    * </ul>
    */
NON_GETTER_METHODS,

/**
 /**
 * All methods following the getter pattern. A getter according to
the
    * JavaBeans specification is a method whose:
    * <ul>
        *      <li>name starts with get, has a return type but no
parameter</li>
        *      <li>name starts with is, has a return type and is returning
{@code boolean}.</li>
    * </ul>
    */
GETTER_METHODS,

/**
 * All executables (constructors and methods).
*/
ALL
}

```

If a sub type overrides/implements a method originally defined in several parallel types of the hierarchy (e.g. two interfaces not extending each other, or a class and an interface not implemented by said class), **@ValidateOnExecution** cannot be placed in the parallel types of the hierarchy. This is to avoid an unexpected altering of the post conditions to be guaranteed to the caller.

You can globally disable executable validation by using **<executable-validation enabled="false"/>**, in this case, **<default-validated-executable-types/>** and

`@ValidateOnExecution` are ignored.

*Example 144. validation.xml disabling executable validation*

```
<?xml version="1.0" encoding="UTF-8"?>
<validation-config
    xmlns="http://xmlns.jcp.org/xml/ns/validation/configuration"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation=
        "http://xmlns.jcp.org/xml/ns/validation/configuration
validation-configuration-2.0.xsd"
    version="2.0">
    <default-provider>com.acme.ACMEProvider</default-provider>
    <message-interpolator>com.acme.ACMEAwareMessageInterpolator</message-
interpolator>

    <executable-validation enabled="false"/>

    <constraint-mapping>META-INF/validation/order-constraints.xml<
/constraint-mapping>
    <constraint-mapping>META-INF/validation/catalog-constraints.xml<
/constraint-mapping>
    <constraint-mapping>META-INF/validation/customer-constraints.xml<
/constraint-mapping>

    <property name="com.acme.validation.logging">WARN</property>
    <property name="com.acme.validation.safetyChecking">failOnError<
/property>
</validation-config>
```

`@ValidateOnExecution(type=IMPLICIT)` on a type (class or interface) is useful to mark a class as being involved in executable validation without affecting the behavior. This is used when the integration technology needs a little help to find the classes and interfaces involved.

**NOTE**

The proper selection of the validated executables is the responsibility of the integration between the interception technology and Bean Validation. Bean Validation engines ignore the XML configuration around executable validation and `@ValidateOnExecution` when validating executables and when providing metadata.

### 11.1.2.1. Examples

The following example shows some of the way you can refine executable validation with `@ValidateOnExecution`.

*Example 145. Method validation configurations*

```
//optional: @ValidateOnExecution
public class OrderService {

    boolean isValidCustomer(@NotNull String customerCode) { [...] }

    @ValidateOnExecution
    @Min(0)
    Integer getBacklog() { [...] }

    @ValidateOnExecution(type=NONE)
    Order placeOrder(@NotNull String customerCode, @Valid Item item, int
    quantity) { [...] }

}

@ValidateOnExecution(type={GETTER_METHODS, NON_GETTER_METHODS})
public class SimpleOrderService extends OrderService {

    public SimpleOrderService(@NotNull ServiceProvider provider) { [...] }

    @Overrides
    Order placeOrder(String customerCode, Item item, int quantity) { ..
    .] }

}

//optional: @ValidateOnExecution
public class ComplexOrderService extends SimpleOrderService {
    public ComplexOrderService(@NotNull ServiceProvider provider) { [...] }
}
```

All constructors and non-getter methods of `OrderService` are validated upon execution as this is the default setting. `isValidCustomer()` is validated as this method is not a getter (it has a parameter). `getBacklog()` is a getter but is validated thanks to `@ValidateOnExecution` defaulting to `GETTER_METHODS`. `placeOrder()` is not validated as `@ValidateOnExecution` is set to `NONE`.

All getter and non-getter methods of `SimpleOrderService` are validated upon execution by default due to the presence of `@ValidateOnExecution` on the class. The `SimpleOrderService` constructor is thus not validated. `SimpleOrderService.placeOrder()` is not validated either because it overrides `OrderService.placeOrder()` and thus inherits its settings.

All constructors and non-getter methods of `ComplexOrderService` are validated upon execution as this is the default setting - the type level settings of `SimpleOrderService` are not inherited. This means that the `ComplexOrderService` constructor is validated.

`@ValidateOnExecution` can be optionally set on `OrderService` and

`ComplexOrderService` without altering the semantic. This marker is necessary for some integration technology in some situations.

## 11.2. Java EE

Java EE must obey the rules defined above and make the following instances available under JNDI:

- `ValidatorFactory` under `java:comp/ValidatorFactory`
- `Validator` under `java:comp/Validator`

Instead of looking the instances up via JNDI, the user can request them to be injected via the `Resource` annotation:

```
@Resource ValidatorFactory validatorFactory;  
@Resource Validator validator;
```

When the application is CDI enabled, the `ValidatorFactory` and `Validator` instances returned by JNDI or `@Resource` injection are CDI enhanced as defined in [Context and Dependency Injection \(CDI\) integration](#). In particular, dependency injection is available to Bean Validation components.

## 11.3. Context and Dependency Injection (CDI) integration

There are several integration points between Bean Validation and CDI. If a Bean Validation provider integrates with CDI, it must follow the rules laid out in this section. In a Java EE container, a Bean Validation provider must integrate with CDI.

### 11.3.1. `ValidatorFactory` and `Validator`

Similar to the Java EE integration via `@Resource` (see [Java EE](#)), a CDI container must support injection of built-in default `ValidatorFactory` and `Validator` beans via `@Inject`. These default beans are injectable via the `@Default` qualifier.

```
@Inject ValidatorFactory;  
@Inject Validator;
```

Optionally, the CDI container can support injection of provider specific - as defined by `Validation.byProvider()` - `ValidatorFactory` and `Validator` beans via `@Inject`. These beans must be registered with a custom qualifier, for example `@ACME`. Using the product name or brand for the qualifier is considered good practice.

```
@Inject @ACME ValidatorFactory;  
@Inject @ACME Validator;
```

*Discussion on possible implementations*

**NOTE** Registration of the built-in default beans and the provider specific beans may be achieved using the CDI portable extension SPI or a vendor specific SPI.

### 11.3.2. ConstraintValidatorFactory, MessageInterpolator, ParameterNameProvider, ClockProvider and TraversableResolver

If a custom `ConstraintValidatorFactory`, `MessageInterpolator`, `ParameterNameProvider`, `ClockProvider` or `TraversableResolver` class is defined in the XML deployment descriptor (see [XML configuration: META-INF/validation.xml](#)), the `ValidatorFactory` must be configured with CDI managed beans representing the requested classes. Services like dependency injection, interception and decoration must thus be made available to these instances by the container.

If no custom `ConstraintValidatorFactory` is requested by the user, the `ValidatorFactory` must be configured with a custom `ConstraintValidatorFactory` instance that returns CDI managed beans representing the requested `ConstraintValidator` types. The factory

- creates non-contextual `ConstraintValidator` instances for each `ConstraintValidatorFactory.getInstance()` call. To inject dependencies into the `ConstraintValidator` instance, the CDI `InjectionTarget` API should be used. Before returning the instance the following calls should be made: `InjectionTarget.produce()`, `InjectionTarget.inject()` and `InjectionTarget.postConstruct()`.
- calls `InjectionTarget.preDestroy()` and `InjectionTarget.dispose()` upon `ConstraintValidatorFactory.releaseInstance` (see also [The ConstraintValidatorFactory](#) for more information about the lifecycle of a `ConstraintValidator`).

Using directly or indirectly a JPA `EntityManager` that might call back Bean Validation for validation is not allowed in the Bean Validation extension points and in `ConstraintValidator` instances. This would lead to infinite flush or unexpected behavior.

### 11.3.3. Method and constructor validation

Bean Validation requires that CDI beans support constructor and method validation as defined in [Method and constructor validation](#). Validation must happen at the equivalent time an interceptor occurs when having priority `Interceptor.Priority.PLATFORM_AFTER+800`, in other words priority of `4800`.

For maximum portability, it is recommended to mark CDI bean interfaces and classes involved in executable validation with `@ValidateOnExecution` (defaults to `IMPLICIT`). This helps some implementations to bind the method validation interceptor. Most CDI - Bean Validation integration implementations do not need such marker. In particular this marker should not be needed on validated beans annotated with constraint annotations, `@Valid` or `@ValidateOnExecution` anywhere in the class. Such limitation will be removed in a future version of this specification.

**NOTE**

*Discussion on possible implementations*

The CDI interceptor binding facility does not directly support this, but the effect may be achieved using the CDI portable extension SPI, or vendor specific SPIs. For example, an interceptor with the expected priority can be programmatically bound to the constructors and methods expected to be validated according to the rules at [Method and constructor validation](#).

It is recommended to only intercept methods and constructors that are both constrained and validated according to the rules defined at [Method and constructor validation](#). [Triggering method validation](#) gives examples how the metadata API can be used to determine whether or not a method is constrained (regardless of the filtering rules of `@ValidateOnExecution`).

## 11.4. Java Persistence 2.0 integration

Integration with Java Persistence is described in the Java Persistence 2 specification ([JSR-317](#) and later [JSR-338](#)). Persistence frameworks are encouraged to mimic the integration work done with Java Persistence.

## 11.5. Java Server Faces 2.0 integration

Integration with Java Server Faces is described in the Java Server Faces 2 specification ([JSR-314](#) and later [JSR-344](#)). Presentation frameworks are encouraged to study the integration work done with JSF 2.

## 11.6. JAX-RS 2 integration

Integration with JAX-RS is described in the JAX-RS 2 specification ([JSR-339](#)).

# Appendix A: Terminology

This appendix aims at giving an overview on the different key terms used through this specification. They are not to be considered formal definitions. Formal definitions are to be inferred from the core specification.

## *Constraint*

A restriction on a bean instance, the value of a field or the value of a JavaBean property.

## *Constraint declaration*

Assignment of a constraint to a target (bean, field, property) for a specific class. Typically by declaring an annotation on the target but can also be done through a XML deployment descriptor.

## *Validation routine*

Sequence of operations executed by the Bean Validation provider to validate a given object graph.

## *Constraint definition*

Defines a type of constraint, its attributes and the actual constraint validation implementations. Done through annotations. The list of constraint validation implementations can be provided via XML.

## *Group*

Constraints can belong to one or more group or context. Useful to apply a subset of the constraints for a given use case. By default, the **Default** group is used.

## *Group Sequence*

Defines a group ordering in the validation process. If a given group in the sequence contains one or more failure, the following groups in the sequence must be ignored.

## *Constraint validation*

Constraint logic algorithm used to determine whether a given value passes a constraint or not.

## *Constraint validation implementation*

Class implementing the constraint logic and used to determine whether a given value pass a constraint or not.

## *Bean Validation provider*

Product implementing this specification.

### *Message interpolator*

Algorithm used to build the end user message associated to a constraint failure. Typically useful for i18n.

### *Constraint metadata API*

API exposing the constraints applied to a given bean type. Also considered one of the integration points with other JSR or frameworks.

### *Bootstrap API*

Bootstrapping part of the Bean Validation API producing a **ValidatorFactory**.

### *javax.validation.ConstraintValidator*

Interface implemented by a constraint validation implementation.

### *Composing constraint*

Constraint declared on another constraint definition. When the main constraint is validated, the composing constraints are validated too.

### *javax.validation.Validator*

Main API. Holds contracts to validate object graphs.

### *javax.validation.ConstraintViolation*

Interface describing a given constraint failure on a given bean.

### *Getter*

Method whose:

- name starts with **get** and has a return type but no parameter
- name starts with **is**, has no parameter and is returning **boolean**

# Appendix B: Standard ResourceBundle messages

The properties listed below are resolved by the default message interpolator.

```
javax.validation.constraints.AssertFalse.message=must be false
javax.validation.constraints.AssertTrue.message=must be true
javax.validation.constraints.DecimalMax.message=\
    must be less than ${inclusive == true ? 'or equal to ' : ''}{value}
javax.validation.constraints.DecimalMin.message=\
    must be greater than ${inclusive == true ? 'or equal to ' : ''}{value}
javax.validation.constraints.Digits.message=\
    numeric value out of bounds (<{integer} digits>.<{fraction} digits>
expected)
javax.validation.constraints.Email.message=must be a well-formed email address
javax.validation.constraints.Future.message=must be a future date
javax.validation.constraints.Max.message=must be less than or equal to {value}
javax.validation.constraints.Min.message=must be greater than or equal to
{value}
javax.validation.constraints.Negative.message=\
    must be less than ${strict == true ? '' : 'or equal to '}0
javax.validation.constraints.NotBlank.message=must not be blank
javax.validation.constraints.NotEmpty.message=must not be empty
javax.validation.constraints.NotNull.message=must not be null
javax.validation.constraints.Null.message=must be null
javax.validation.constraints.Past.message=must be a past date
javax.validation.constraints.Pattern.message=\
    must match the following regular expression: {regexp}
javax.validation.constraints.Positive.message=\
    must be greater than ${strict == true ? '' : 'or equal to '}0
javax.validation.constraints.Size.message=size must be between {min} and {max}
```

# Appendix C: Java Persistence 2.0 and schema generation

While not specified by this specification or the Java Persistence 2.0 specification, Persistence Providers are encouraged to make use of Bean Validation constraint metadata when generating DDL schemas. The proposal is as followed.

## Ideas explored and not standardized

Java Persistence consumes Bean Validation (BV) metadata to enhance persistence property metadata.

A Persistence provider must use the BV metadata of a given list of groups. The default group evaluated is Default (default BV group). Groups evaluated can be overridden by a property.

This property contains the comma separated groups (fully qualified class name).

For each entity, apply the following algorithm.

For each persistent property in a given entity:

- extract the list of BV constraints (including the composing constraints)
- determine the subset of applicable constraints  
(i.e. constraints understood by the persistence provider)
- apply these constraints on the persistent property metadata
- if the property type is an embeddable object or a collection of embeddable objects, apply the algorithm on the embeddable object properties.

The list of constraints that must be understood by persistence providers are as followed:

- @NotNull should be considered equivalent to @Column(nullable=false) / @JoinColumn(nullable=false)
- @Size.max should be considered equivalent to @Column.length for String properties
- @Digits (which contains integer and fraction) should be considered equivalent to @Column.precision = integer+fraction, @Column.scale = fraction for decimal columns

The BV annotation metadata should have priority over JPA metadata (JPA has no sensible "unset" values on their annotations).

Question: should we add @Unique that would map to @Column(unique=true)? @Unique cannot be tested at the Java level reliably but could generate a database unique constraint generation. @Unique is not part of the BV spec today.

Persistence Provider should optionally recognize and try to apply the following constraints as well:

- @Min / @Max on numeric columns (TODO String too?)
- @Future / @Past on temporal columns
- @Size for collections and array (not sure it is feasible).

Persistence Providers can also apply non standard constraints to their metadata model.

For example, provider ACME might recognize and understand  
@com.acme.validation.Email  
and apply it to the database model.

While most high level constraints will not be recognized, the BV built-in constraints will be the common language spoken by Persistence Providers. Any high level constraint can be composed of more modular constraints (constraint composition).

\* additional proposal  
In case of a constraint violation report detected and generated by the database (not null, etc), the Java persistence provider catches this report and translates it into a BV error report. From the perspective of the application, constraint errors are viewed through a unified layer. BV must provide some API to create a constraint violation error  
(constraintDescriptor.createConstraintViolation(&#8230;&#8203;)).

While this proposal has a lot of value-add, I wonder how difficult it can be to implement this in persistence providers.

Provide a way to disable BV metadata use by a persistence provider (property based).

This is not an endorsement of the Java Persistence expert group or the Bean Validation expert group. Such approach may or may not be standardized in the future. Such integration should not be considered portable.

# Appendix D: Changelog

Example 146. Changelog

```
2.0.0.Beta1 (Public Review Draft 1, 2017-04-24)
-----
** Improvement
  * [BVAL-598] - Use the license-maven-plugin to check the presence of
the license
  * [BVAL-596] - Move ValidateUnwrappedValue to
javax.validation.metadata
  * [BVAL-595] - Adding missing @since tags

** New Feature
  * [BVAL-594] - Extend meta-data API to cover container element
constraints
  * [BVAL-593] - Allow to configure group conversions for container
elements in XML
  * [BVAL-591] - Dissolve "container element validation" appendix into
spec sections
  * [BVAL-589] - Document release process of the spec
  * [BVAL-549] - Nested cascaded validation

** Task
  * [BVAL-602] - Check that every section has an id
  * [BVAL-599] - Remove metadata usage example from API
  * [BVAL-585] - Add descriptions of build goals to beanvalidation-
spec/README.md
  * [BVAL-584] - Use short license headers
  * [BVAL-581] - Discuss with Java EE EG whether it's actually WEB-
INF/validation.xml
  * [BVAL-577] - Proof-read "3.3. Constraint composition" on
"composing" vs. "composed"
  * [BVAL-575] - Update documentation of
Configuration#getDefaultParameterNameProvider()

2.0.0.Alpha2 (2017-03-28)
-----
** Bug
  * [BVAL-566] - Configuration JavaDoc still references "TODO BVAL-496
paste definition of the specification"

** New Feature
  * [BVAL-548] - New constraints: @NotEmpty, @NotBlank, @Email,
@Positive, @Negative
  * [BVAL-559] - Add NoProviderFoundException
  * [BVAL-562] - Create new ElementKind for constraint violations on
the type-use level
  * [BVAL-571] - Discover value extractor implementations using the
service loader mechanism
  * [BVAL-572] - Allow to add value extractors per validator factory
and validator and via validation.xml
  * [BVAL-586] - Support defining constraint on container element type
in XML mapping
```

```

** Task
    * [BVAL-560] - Mention Oracle instead of Sun in the evaluation
license
    * [BVAL-565] - Configure japicmp plug-in for creating API change
report
    * [BVAL-578] - Make the assertion related to NoProviderFoundException
not testable
    * [BVAL-587] - Go back to coderay for code highlighting in the spec

** Improvement
    * [BVAL-264] - Improve toString() in ConstraintViolationException
    * [BVAL-528] - Replace all inline listings with includes of the
actual API files / spec examples
    * [BVAL-561] - Make @OverridesAttribute repeatable and documented
    * [BVAL-567] - Tone down @Past / @Future JavaDoc on clockprovider
    * [BVAL-568] - Make built-in annotations documented
    * [BVAL-576] - Revise wording in 10.3.3 "Method and constructor
validation"
    * [BVAL-580] - Switch assertion section ids to a string instead of a
numeric representation
    * [BVAL-583] - Use the common theme for the asciidoc output

```

2.0.0.Alpha1 (Early Draft 1, 2017-02-02)

---

```

** Bug
    * [BVAL-558] - Ensure correct concurrent access to
cacheValidationProviders in Validation#GetValidationProviderListAction

** New Feature
    * [BVAL-467] - Support JDK8's Optional class
    * [BVAL-496] - @Future/@Past validators for JSR 310 data types
    * [BVAL-497] - Mark BV-defined constraint types with @Repeatable
    * [BVAL-498] - Retrieve method parameter names via new API in Java 8
    * [BVAL-508] - Offer validation of values contained in containers
    * [BVAL-544] - Promote TYPE_USE usage for constraint annotations
    * [BVAL-550] - Make @ConvertGroup repeatable and usable on type
arguments

** Task
    * [BVAL-509] - Make BVAL compilable with Java 9
    * [BVAL-512] - Provide a way to reference validation-api source code
in the spec
    * [BVAL-513] - Add Google Analytics to HTML version of the
specification
    * [BVAL-538] - Rename createTckAuditFile ant task to create-tck-
audit-file for consistency
    * [BVAL-540] - Use Maven to download the snapshot of the API sources
    * [BVAL-541] - Change CI links in README.md
    * [BVAL-547] - Use simplified license header for API files
    * [BVAL-554] - Add the ability to generate an asciidoc document
containing all the spec in a single file

** Improvement
    * [BVAL-455] - Move XML namespace to jcp.org from jboss.org
    * [BVAL-460] - Set ignore-annotation default value for beans to true
in XSD to document the spec behavior
    * [BVAL-486] - Do not use validation provider resolver when provider
is explicitly given

```

```
* [BVAL-527] - Raise Java baseline to version 8
* [BVAL-529] - Mention JSR 380 and BV 2.0 in the spec
* [BVAL-530] - Rename master.asciidoc to index.asciidoc
* [BVAL-532] - Fix javadoc warnings
* [BVAL-533] - Update Maven dependencies
* [BVAL-534] - Update all outdated links to java.sun.com
* [BVAL-535] - Reduce the number of compilation warnings in the API
* [BVAL-536] - Update tck-audit.xsl to the current version of BV
* [BVAL-537] - Make section numbers stable from 1.1 to 2.0
* [BVAL-539] - Set the version of the maven-deploy-plugin
* [BVAL-545] - Fix description of validateValue() method
* [BVAL-546] - Make ValidatorFactory extend AutoClosable
* [BVAL-555] - Provide default implementation for
ConstraintValidator#initialize()
```

1.1.0.Final (2013-04-10)

---

```
** Improvement
* [BVAL-452] - Remove @Deprecate annotation from addNode() method
```

1.1.0.CR3 (2013-03-20)

---

```
** Bug
* [BVAL-444] - Remove revisionflags from specification
* [BVAL-445] - Do not consider arrays of primitives equivalent to
arrays of wrappers in ConstraintValidation resolution

** Improvement
* [BVAL-448] - Mention "boolean" instead of "Boolean" in getter
definition
* [BVAL-450] - Make @ValidateOnExecutable for @Override methods raise
an exception

** Task
* [BVAL-449] - Remove tck-needs-update
```

1.1.0.CR2 (2013-03-14)

---

```
** Bug
* [BVAL-431] - Typo in EL expression exemple
* [BVAL-435] - Rename element <validated-executables/> to <default-
validated-executable-types/>
* [BVAL-436] - Offer global switch to disable executable validation
altogether
* [BVAL-437] - Redesign @ValidateExecutable into @ValidateOnExecution
and as CDI marker for portability

** Improvement
* [BVAL-420] - Add missing @since in metadata package
* [BVAL-421] - Clarify whether or not getters are provided by the
metadata API
* [BVAL-422] - Update TCK markers
* [BVAL-423] - Clarify behavior of ConstraintViolation#getLeafBean()
for validateValue()
* [BVAL-424] - Refer to @SupportedValidationTarget in
```

```

ConstraintValidation JavaDoc
    * [BVAL-429] - Throw a ConstraintDefinitionException if there are
several cross-parameter validators
    * [BVAL-432] - Rename areParametersConstrained to
hasConstrainedParameters and isReturnValueConstrained to
hasConstrainedReturnValue on ExecutableDescriptor
    * [BVAL-433] - Forbid @ValidatedExecutable on methods of parallel
hierarchies
    * [BVAL-434] - Clarify exception type if cross-parameter validator
supports neither Object nor Object[]
    * [BVAL-440] - Improve description of ExecutableType.GETTER_METHODS
    * [BVAL-442] - Make getConstrainedMethods(MethodType methodType,
MethodType... methodTypes) to be less error-prone

** New Feature
    * [BVAL-441] - Allow for identical configuration in subtypes

** Task
    * [BVAL-425] - Raise IllegalArgumentException when validateParameters
and validateReturnValue are passed parameters that do not match
    * [BVAL-428] - Map remaining assertions for BV 1.1
    * [BVAL-438] - Integration chapter should not mention that the
bootstrap API can be used to create additional ValidationFactory
    * [BVAL-439] - Clarify that EE validator factory supports CDI
services

```

1.1.0.CR1 (proposed final draft, 2013-02-20)

---

```

** Bug
    * [BVAL-322] - Formatting and style improvements
    * [BVAL-369] - Specify copyright year correctly in license headers
    * [BVAL-391] - Use @SupportValidationTarget instead of
@CrossParameterConstraint for cross-parameter constraint validators
    * [BVAL-397] - Align the JavaDoc on temps (return vs returns, define
vs defines)
    * [BVAL-401] - validateReturnValue should not throw an exception if
the method has no return value
    * [BVAL-402] - Remove notion of "reachable" parameters in method
validation routine
    * [BVAL-403] - Add example on method validation to 4.6.3.
("Traversable property")
    * [BVAL-407] - ConstraintViolation.unwrap parameterized type hides
ConstraintViolation parameterized type

** Improvement
    * [BVAL-275] - Align on style for referencing methods in spec text
    * [BVAL-277] - Align on style for author names in JavaDoc
    * [BVAL-285] - ValidatorFactory#close should clearly state post
conditions
    * [BVAL-350] - Add more examples on how to use methods for validating
method and constructor constraints
    * [BVAL-362] - Reference the various specs (JPA, JSF, CDI, JavaBeans)
    * [BVAL-400] - Add xml and exception chapters to the list in "How
this document is organized"
    * [BVAL-404] - Path examples in table 5.2 are missing node specific
attributes like parameterIndex
    * [BVAL-405] - Clarify what isBeanConstrained does and add
hasExecutableConstrained

```

```

* [BVAL-406] -- Add ConstraintDescriptor.getValidationAppliesTo() and
getMessageTemplate()
    * [BVAL-409] - Make ParameterNameProvider use List instead of arrays
    * [BVAL-410] - Make node creation suppress the cross-param and bean-
level node in case of subnode creation
    * [BVAL-412] - Make <convert-group/> follow <valid/> and precede
<constraint/> in the mapping XSD
    * [BVAL-413] - Fix method validation and ConstraintViolation example
    * [BVAL-414] - Add example for metadata API with executables
    * [BVAL-415] - Make sure maven plugins are set in beanvalidation-api
    * [BVAL-417] - Mention "validationAppliesTo" in docs of
@SupportedValidationTarget
    * [BVAL-419] - Clarify that using a cross-parameter constraint on a
method without parameter is illegal

```

1.1.0.Beta4 (2013-02-15)

---

```

** Sub-task
    * [BVAL-316] - Decide on whether to allow validation of static
methods or not
    * [BVAL-330] - Refinements around metadata API

** Bug
    * [BVAL-221] - The constraint violation builder cannot put constraint
on a top level map key
    * [BVAL-283] - Clarify that ConstraintValidator instances must be
destroyed after each method validation call if the
ConstraintValidatorFactory is provided to the Validator
    * [BVAL-284] - Clarify that ConstraintValidator instances passed to
CVF.releaseInstance must be coming from the CVF creating them
    * [BVAL-326] - Fix metadata and error reports for cross-parameter
validation
    * [BVAL-328] - Add recommendation that @Inherited shouldn't be added
to constraint annotation types
    * [BVAL-337] - Clarifications around ConstraintViolation for method
validation
    * [BVAL-370] - Re-consider how cross-parameter constraints are
represented in metadata API and XML descriptors
    * [BVAL-375] - Add dedicated "validationAppliesTo" element to schema
type representing constraints
    * [BVAL-378] - Mismatch between enum ExecutableType and corresponding
schema type
    * [BVAL-380] - Remove improper sentence around constraint being
validated once globally in validation routine
    * [BVAL-381] - Specify which path is pathed to traversable resolvers
in case of cascaded method validation
    * [BVAL-388] - Create sub-types of Node instead of
Node#getElementDescriptor() and remove ElementDescriptor.getKind()
    * [BVAL-389] - @ValidateExecutable.type should default to ALL and
NONE should be renamed OFF
    * [BVAL-390] - Clarify syntax for specifying parameter types in XML
    * [BVAL-393] - Revert "intersection type trick"

** Improvement
    * [BVAL-191] - Introduce a addBeanNode() method to the fluent node
builder API
    * [BVAL-269] - Polish support for dependency injection after draft
feedback

```

```

* [BVAL-336] - Decide what to do about element descriptor when using
constraint violation builder API
    * [BVAL-344] - Improve wording around CDI integration
    * [BVAL-368] - Return constant value from Node#getName() for return
value nodes
    * [BVAL-372] - Consider moving ExecutableValidator to the executable
subpackage
    * [BVAL-379] - Clarify that modifications to BootstrapConfiguration
have no effect
    * [BVAL-384] - Add example for ElementDescriptor#findConstraints()
for methods
    * [BVAL-385] - Return void ReturnValueDescriptor from
ExecutableDescriptor#getReturnValueDescriptor() for void methods
    * [BVAL-386] - Clarify that CDI integration is mandatory under Java
EE only
    * [BVAL-398] - Make validateReturnValue raise ValidationException if
the method has no return value

** New Feature
    * [BVAL-329] - Method validation support (III)
    * [BVAL-383] - Add a unwrap method in ConstraintViolation
    * [BVAL-387] - Add ability to add a node corresponding to a parameter
in ConstraintViolationBuilder

** Task
    * [BVAL-394] - Verify that we don't need a spec defined API to expose
classes hosting constrained methods or constructor defined in XML

```

1.1.0.Beta3 (2013-02-01)

---

```

** Sub-task
    * [BVAL-273] - Extend the XML descriptor schema to represent method-
level constraints
    * [BVAL-314] - Provide ability to disable validation for
method/constructor validation

** Bug
    * [BVAL-327] - Provide way to change the executable validation (ie
accept getters)
    * [BVAL-342] - Clarify that validateProperty / validateValue does not
support property paths
    * [BVAL-343] - "Provider org.hibernate.validator.HibernateValidator
not a subtype" error during service discovery
    * [BVAL-345] - List of messages in the standard resource bundle is
incomplete
    * [BVAL-346] - Clarify that getters must have no parameter
    * [BVAL-347] - Add implicit assumptions from TCK to spec text
    * [BVAL-351] - Clarify that EntityManager cannot be injected if
validating from JPA
    * [BVAL-361] - Expose group conversions via meta-data API
    * [BVAL-363] - Clarify that super method constraints are considered
in the validation routine but not constructors
    * [BVAL-366] - Fix typo on ConfigurationState JavaDoc
    * [BVAL-371] - Add package level javadoc (package-info.java)
    * [BVAL-377] - Provide MessageInterpolator.Context#unwrap to allow
for custom extensions

** Improvement

```

```

* [BVAL-192] -- Add 'exclusive' boolean attribute to
@DecimalMin/@DecimalMax constraints
* [BVAL-332] - Specify semantics of @ConvertGroup when given several
times at overridden property
* [BVAL-340] - Denote method parameter constraints at declaration
site (vs. at definition site)
* [BVAL-352] - Clarify what managed means in the integration chapter
in particular for CDI
* [BVAL-359] - Relax contract of
ExecutableDescriptor#getParameterDescriptors()
* [BVAL-360] - Describe IllegalArgumentException for
ExecutableValidator methods
* [BVAL-364] - Clarify whether or not the metadata API ignore the
method enable/disable settings
* [BVAL-365] - Clarifications around group conversion in hierarchies
* [BVAL-367] - Make clear whether methods/properties inherited from
super types are reflected by the meta-data API
* [BVAL-373] - Move ConvertGroup to the groups subpackage

** New Feature
* [BVAL-219] - Add support for interpolating the value in error
messages
* [BVAL-223] - Add formatter syntax for interpolated messages via EL
expression support
* [BVAL-249] - Add unwrap method to ConstraintValidatorContext for
provider extension
* [BVAL-333] - Enable configuration of group conversions via XML

** Task
* [BVAL-338] - Clarify lifecycle of managed objects created by BV
povider
* [BVAL-348] - Add example for illegal group conversion on a return
value in an inheritance hierarchy
* [BVAL-349] - Mark spec sentences as TCK-relevant (1.0 assertions)
* [BVAL-353] - Mark spec sentences as TCK-relevant (1.1 assertions)
* [BVAL-354] - Describe tagging of TCK-relevant sentences in
README.md
* [BVAL-355] - Rename Validator#forMethods() to forExecutables()
* [BVAL-357] - Clarify that traversable resolver is not used on
parameter and return values during method validation
* [BVAL-358] - Make
ExecutableDescriptor#validateConstructorParameters() and
validateConstructorReturnValue() more usable
* [BVAL-374] - Clarify exceptional case in section 5.5.5
bootstrapping
* [BVAL-376] - Remove @MethodValidated as it is not adding value to
the CDI integration

```

1.1.0.Beta2 (2012-11-27)

---

```

** Sub-task
* [BVAL-331] - Establish common super-interface for MethodDescriptor
and ConstructorDescriptor

** Bug
* [BVAL-335] - @ConvertGroup.List is missing target types and
retention policy

```

```

** Improvement
  * [BVAL-198] - Simplify creation of ConstraintViolationExceptions
  * [BVAL-334] - Refer to CDI provided beans as "built-in" beans

1.1.0.Beta1 (public review draft, 2012-10-19)
-----

** Sub-task
  * [BVAL-232] - Support cross-parameter constraints
  * [BVAL-274] - Extend the meta-data API with required convenience
methods for method validation
    * [BVAL-290] - Mark new method with @since annotation
    * [BVAL-300] - Clarify behavior of constructor validation in class
hierarchies
    * [BVAL-308] - Settle on approach for constraint refinement in sub-
types
    * [BVAL-309] - Specify logic to be implemented by method validation
interceptors
    * [BVAL-310] - Move methods related to method validation to delegate
interface
    * [BVAL-317] - Rename 'method-level validation' with 'method
validation'

** Bug
  * [BVAL-296] - Example using ConstraintValidatorContext is incorrect
  * [BVAL-298] - DefaultValidationProviderResolver should check context
and current class loader for service file
  * [BVAL-304] - Add OSGi headers in the reference implementation
  * [BVAL-306] - Clarify interceptor order in method validation
triggering

** Improvement
  * [BVAL-208] - Support groups translation during cascaded validations
  * [BVAL-226] - Make clear whether the static or the runtime type
should be considered when creating property paths in case of cascaded
validations
    * [BVAL-230] - Add support for validating CharSequence types instead
of just Strings
    * [BVAL-259] - Evaluation of composed constraints should stops on
first validation error in case of @ReportAsSingleViolation
    * [BVAL-281] - Improve message when building a ValidatorFactory but
no provider is available in the classpath
    * [BVAL-292] - Clarify the behavior of ConfigurationSource methods
when no configuration file is present
    * [BVAL-299] - Add note on required Java version

** New Feature
  * [BVAL-272] - Method validation support (II)
  * [BVAL-295] - Should validation-configuration and validation-mapping
xsds define a version attribute

** Task
  * [BVAL-280] - Decide whether DefaultValidationProviderResolver
should not throw an exception when a specified provider cannot be loaded
  * [BVAL-307] - Decide how CDI and Bean Validation is integrated

```

1.1.0.Alpha1 (early draft 1, 2012-03-13)

```

** Sub-task
  * [BVAL-242] - Extend the meta-data API to represent method-level
constraints
    * [BVAL-243] - Provide a means for specifying method parameter names
    * [BVAL-244] - Extend Validator API with methods for method
validation
    * [BVAL-245] - Define how method constraints are declared at
parameters and return values

** Bug
  * [BVAL-194] - Invalid license info
  * [BVAL-196] - Missing </code> element in Javadocs for
ConstraintValidatorContext.ConstraintViolationBuilder.NodeContextBuilder
  * [BVAL-212] - Wrong closing </code> element in javadocs of
BeanDescriptor
  * [BVAL-236] - Fails to load META-INF/services provider configuration
files on non-ASCII platforms

** Improvement
  * [BVAL-201] - Fix typo in spec, chapter 4.4.3
  * [BVAL-270] - Specify that Bean Validation 1.1 providers must
support deployment descriptors version 1.0

** New Feature
  * [BVAL-238] - Support for container injection in ConstraintValidator
  * [BVAL-241] - Support for method validation
  * [BVAL-258] - Clean introduction section to reflect Bean Validation
1.1
  * [BVAL-263] - Add a close() method to ValidatorFactory
  * [BVAL-265] - Expose settings defined in XML in the Configuration
API (for ConstraintValidatorFactory, MessageInterpolator etc)

** Task
  * [BVAL-206] - Update pom to use the new distributionManagement
information
  * [BVAL-228] - Prepare specification document and Git repository for
public eyes
  * [BVAL-279] - Update POM file for Bean Validation API to use latest
Git repo urls and generally be ready for a release

1.0.0 final (2009-10-12)
-----
** Bug
  * [BVAL-181] - Fix some namespace issues in validation-configuration-
1.0.xsd

** Improvement
  * [BVAL-182] - Add getDefaultTraversableResolver and
getDefaultValueConstraintValidatorFactory to Configuration
  * [BVAL-183] - Add getTraversableResolver and
getConstraintValidatorFactory to ValidatorFactory
  * [BVAL-184] - Replace Red Hat Middleware LLC to Red Hat, Inc. and/or
its affiliates
  * [BVAL-186] - Clarify method names on the constraint violation
builder DSL of ConstraintValidatorContext
  * [BVAL-187] - Imply that ConstraintViolation is serializable if
entities are serializable

** New Feature

```

```

* [BVAL-185] - Allow overriding of ConstraintValidatorFactory when
creating a Validator
* [BVAL-190] - Add methods to filter ConstraintDescriptor per groups,
target and scope

** Task
* [BVAL-132] - Define behaviour for
BeanDescriptor.getConstraintsForProperty(null)

```

1.0.CR5 (2009-08-27)

---

```

** Bug
* [BVAL-173] - Fix typo
getUnorderdConstraintDescriptorsMatchingGroups =>
getUnorderedConstraintDescriptorsMatchingGroups
* [BVAL-177] - Payload of composed constraints are ignored, the main
constraint payload is propagated
* [BVAL-178] - Add payload to the XML schema
* [BVAL-180] - ConstraintDescriptor.getPayload() should return
Set<Class<? extends Payload>> not Set<Class<Payload>>

** Improvement
* [BVAL-174] - clearer default message for assertTrue and assertFalse
* [BVAL-179] - Rename ConstraintPayload to Payload

```

1.0.CR4 Unpublished release

---

1.0.CR3 (Proposed Final Draft 2, 2009-07-08)

---

```

** Bug
* [BVAL-144] - validation-configuration.xsd property element does not
extend basic string type preventing Oxygen to be happy
* [BVAL-159] - Fix example 3.8 on object graph validation

** Improvement
* [BVAL-143] - Describe path with an object model
* [BVAL-147] - Support for unbounded wildcards in ConstraintValidator
* [BVAL-148] - Built-in constraints annotations now annotated with
@Constraint(validatedBy={})
* [BVAL-151] - TraversableResolver#isTraversable can receive null
traversableObject when validateValue is called
* [BVAL-152] - TraversableResolver should differentiate reachability
and cascadability
* [BVAL-153] - Generify ConstraintValidatorException
* [BVAL-154] - Iterable is a superclass of all collection, clarify
it's interaction with @Valid
* [BVAL-155] - ignore-annotation is not inherited hierarchically:
make that explicit
* [BVAL-156] - Pattern.Flag takes the JDK flag int at construction
time
* [BVAL-157] - Add [] to non-indexed iterable path
* [BVAL-158] - Clarify that @Valid is orthogonal to the idea of group
* [BVAL-160] - rename message template key as [f.q.c.n of the
constraint].message
* [BVAL-162] - Move metadata classes to the metadata package

```

```

(BeanDescriptor, ElementDescriptor, PropertyDescriptor,
ConstraintDescriptor)
    * [BVAL-164] - Validation.byProvider now accept the provider
implementation class
    * [BVAL-166] - IllegalArgumentException raised on
BeanDescriptor.getConstraintsForProperty and
Validator.getConstraintsForClass
    * [BVAL-167] - Recommend f.q.c.n.message for resource bundle keys and
migrate examples
    * [BVAL-169] - Rename ElementDescriptor.getType to getElementClass
    * [BVAL-170] - Let built-in annotations to support
ElementType.PARAMETER and ElementType.CONSTRUCTOR

** New Feature
    * [BVAL-149] - Provide access to the ValidationProviderResolver via
BootstrapState
    * [BVAL-150] - Add ConstraintViolation.getRootBeanClass
    * [BVAL-161] - Add unwrap methods to ValidatorFactory and Validator
    * [BVAL-163] - Add support for constraint payload
    * [BVAL-168] - Return the list of matching ConstraintDescriptor for a
given set of groups
    * [BVAL-172] - Provide ConstraintDescriptor#getPayload

```

#### 1.0.CR2 Unpublished release

---

#### 1.0.CR1 (Proposed Final Draft, 2009-03-16)

---

```

** Bug
    * [BVAL-118] - ConstraintDescriptor.getGroups() returns Default if no
group is declared on the constraint
    * [BVAL-125] - @Size.min default value should be 0

** Improvement
    * [BVAL-32] - Describe what is happening when a composition is not
consistent
    * [BVAL-50] - Be consistent in the spec, use @author or not
    * [BVAL-54] - Specify that constraints on non getter methods are
ignored (if BVAL-36 is not accepted)
    * [BVAL-72] - Validating an object multiple times if in a different
branch of the graph
    * [BVAL-86] - Default TraversableResolver is JPA aware
    * [BVAL-88] - Improvement on MessageInterpolator
    * [BVAL-91] - Rename Constraint related classes to improve
readability
    * [BVAL-95] - @Size should support Map
    * [BVAL-96] - Support byte in @Min/@Max
    * [BVAL-106] - Constraintdescriptor.getConstraintValidatorClasses()
should return a List, not an array
    * [BVAL-114] - Relax property names in ConstraintValidatorContext
    * [BVAL-120] - Rename ConstraintViolation
getRawMessage=>getMessageTemplate, getInterpolatedMessage=>getMessage
    * [BVAL-122] - Rename @GroupSequence.sequence to @GroupSequence.value
    * [BVAL-126] - Define group sequence logic more formally and
eliminate corner cases
    * [BVAL-129] - Clarify ConstraintValidatorContext propertyPath
generation

```

```

* [BVAL-130] - Make ConstraintDescriptor generic:
ConstraintDescriptor<T extends Annotation>
    * [BVAL-131] - Provide object graph navigation determinism
    * [BVAL-134] - @Valid accepts objects implementing Iterable
    * [BVAL-135] - Remove DefaultValidationProviderResolver from the
public API
    * [BVAL-136] - Add Context object for MessageInterpolator
    * [BVAL-137] - prefix for message template key is constraint. instead
of validator.
    * [BVAL-138] - Rename OverridesParameter to OverridesAttribute
    * [BVAL-139] - Remove @OverridesParameters and use the inner class
mode (OverridesAttribute.List)
    * [BVAL-140] - BeanDescriptor.getConstrainedProperties() returns
Set<PropertyDescriptor>
    * [BVAL-141] - Rename ConstraintDescriptor.getParameters() to
getAttributes()

** New Feature
    * [BVAL-52] - Define the exception hierarchy and rules
    * [BVAL-55] - Exception policy
    * [BVAL-65] - Additional built-in constraints
    * [BVAL-98] - Type-safe ConstraintValidator
    * [BVAL-100] - Support XML mapping overriding
    * [BVAL-102] - Support META-INF/validation.xml
    * [BVAL-119] - Introduce @Pattern for regexp
    * [BVAL-121] - Define built-in constraints plural forms
    * [BVAL-123] - Add ConstraintViolationException
    * [BVAL-124] - Introduce backslash as escaping character
    * [BVAL-142] - @Min/@max no longer accept float/double and introduce
@DecimalMin/@DecimalMax

** Task
    * [BVAL-24] - What should be done when multiple META-
INF/validation.xml are found?
        * [BVAL-117] - Specify behaviour of ConstraintValidator.initialize in
the case of inconsistent values in constraint parameters
        * [BVAL-127] - Remove ConstraintViolation.getGroups()
        * [BVAL-128] - Clarify invalid cases for validateProperty /
validateValue on proeprtyName being empty or null
        * [BVAL-133] - Remove JPA and JSF integration proposals

```

1.0.Beta2 (Public Draft, 2008-12-15)

---

```

** Bug
    * [BVAL-6] - Wrong example in validation methods section
    * [BVAL-17] - Validator<A>.validate(b) where b:B and B extends A
should validate B. Metadata APIs are specific to A
    * [BVAL-42] - Names of message keys in spec inconsistent
    * [BVAL-45] - Typo at ConstraintDescriptor.getContstraintClass()

** Improvement
    * [BVAL-29] - Types should be determined at runtime
    * [BVAL-33] - Should
ConstraintDescriptor.getConstraintImplementation() replaced by
.getConstraintImplementationClass()?
    * [BVAL-40] - Rename InvalidConstraint to ConstraintViolation
    * [BVAL-48] - Add a way to access the default message resolver
    * [BVAL-49] - Mark metadata classes as immutable

```

```

* [BVAL-59] - Rethink the group sequence inheritance rules
* [BVAL-60] - ConstraintViolation points to the corresponding
ConstraintDescriptor
    * [BVAL-68] - Specify that static methods and fields are not
validated
        * [BVAL-73] - Rename ConstraintViolation.getBeanClass() to CV.
getRootClass() or simply remove it
        * [BVAL-78] - Forbid a Validation implementation to modify the state
of the object being validated

** New Feature
    * [BVAL-30] - Define validation Context to be passed to constraint
implementation calls
        * [BVAL-36] - Validation of method parameters and returned values
        * [BVAL-67] - Allow MessageResolver to be Localizable
        * [BVAL-71] - Should we have group aggregation?
        * [BVAL-76] - Expose the raw message to ConstraintViolation
        * [BVAL-79] - Groups are now Type based rather than String based
        * [BVAL-81] - Provide a TraversableResolver contract

** Task
    * [BVAL-1] - Remove references to 'beancheck' in the spec
    * [BVAL-3] - Replace array return types with Sets
    * [BVAL-4] - Return value for @NotEmpty for null values
    * [BVAL-5] - Change order of example classes in Book/Author example
    * [BVAL-7] - Use of example in ConstraintFactory section (2.4)
    * [BVAL-8] - StandardConstraint description (2.5)
    * [BVAL-23] - Make Validator<T> thread-safe

```