```
Time
                      Source
                                            Destination
                                                                   Protocol Length Info
   496 51.667956520
                      128.93.162.63
                                            192.168.1.71
                                                                            74
                                                                                   Echo (ping) reply
seq=48/12288, ttl=43 (request in 479)
Frame 496: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface enp4s0, id 0
Ethernet II, Src: Actionte_f6:8c:80 (fc:2b:b2:f6:8c:80), Dst: ASUSTekC_de:7c:0a (24:4b:fe:de:7c:0a)
Internet Protocol Version 4, Src: 128.93.162.63, Dst: 192.168.1.71
   0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
   Differentiated Services Field: 0x28 (DSCP: AF11, ECN: Not-ECT)
   Total Length: 60
   Identification: 0x659c (26012)
   Flags: 0x00
   Fragment Offset: 0
   Time to Live: 43
   Protocol: ICMP (1)
   Header Checksum: 0x4571 [validation disabled]
   [Header checksum status: Unverified]
   Source Address: 128.93.162.63
   Destination Address: 192.168.1.71
Internet Control Message Protocol
   Type: 0 (Echo (ping) reply)
   Code: 0
   Checksum: 0x8a3e [correct]
   [Checksum Status: Good]
   Identifier (BE): 12 (0x000c)
   Identifier (LE): 3072 (0x0c00)
   Sequence Number (BE): 48 (0x0030)
   Sequence Number (LE): 12288 (0x3000)
   [Request frame: 479]
   [Response time: 189.092 ms]
   Data (32 bytes)
0000 48 49 4a 4b 4c 4d 4e 4f 50 51 52 53 54 55 56 57 HIJKLMNOPQRSTUVW
0010 58 59 5a 5b 5c 5d 5e 5f 60 61 62 63 64 65 66 67 XYZ[\]^_`abcdefg
```

id=0x000c,