Contents

1 People **1**

2 Code **1**

2.1 Theory 2

2.1.1 Notation 2

2.1.2 General 2

2.1.3 Chamber/nozzle 3

2.1.4 CEA rocket solver 4

2.2 My own set of inputs 5

1 People

Avionics:

- Nick (also propulsion)

Payload:

- Mica (contact about Pilotix)

Propulsion:

- Francesco (adapters)
- Robert (parametric)
- Nils (WhatsApp guy, propulsion not-lead)

Python RocketCEA

2 Code

Input variables:

- Tank
  - Injector hole count
  - Injector total hole area
- Fuel grain:
  - Fuel inner radius
  - Fuel outer radius
- Combustion chamber and nozzle:
  - Throat length
  - Throat radius
  - Converging throat section angle
  - Nozzle length
  - Inner liner thickness
  - Pre-combustion chamber length
  - Post-combustion chamber length
  - Chamber inner radius
  - Chamber outer radius

(I want to specify all of these in a generic manner as $f(z)$)

- Thrust
- Burn time

Output variables:

- Specific impulse




Figure 1: Design of a hybrid rocket engine

2.1 Theory

2.1.1 Notation

h altitude above sea level

$\mathcal{A}$ attitude, represented by either a 3-vector of Eulerian angles or a quaternion

$(\cdot)^*, (\cdot)_{\mathbf{t}}$ value of a variable at the throat of the convergent-divergent nozzle

$(\cdot)_{\mathbf{c}}$ value of a variable inside the combustion chamber at the entrance of the nozzle

$(\cdot)_{\mathbf{e}}$ value of a variable at the exit of the nozzle

$(\cdot)_{\mathbf{amb}}$ "ambient" value of a variable in the environment outside the rocket, for example P_{amb}

2.1.2 General

2D attitude lookup table: $\mathcal{A} : \mathbb{R}^3, \mathbb{R}^3 \to \mathbb{R}^3 | \mathbb{H}$, $\mathcal{A}(\mathbf{x}, \mathbf{v})$

Ideal rocket equation:

$$\Delta v = v_e \ln \frac{m_{\text{i}}}{m_{\text{f}}} = I_{\text{sp}} g_0 \ln \frac{m_{\text{i}}}{m_{\text{f}}}$$

Thrust equations:




Figure 1.4

Figure 2: Design of a convergent-divergent nozzle

$$\dot{m} = \rho_{\mathrm{e}} u_{\mathrm{e}} A_{\mathrm{e}}$$

$$T = \dot{m} u_{\mathrm{e}} + (P_{\mathrm{e}} - P_{\mathrm{a}}) A_{\mathrm{e}} = \dot{m} u_{\mathrm{e}} + P_{\mathrm{e}} A_{\mathrm{e}} - P_{\mathrm{a}} A_{\mathrm{e}} = T_{\mathrm{vac}} - (P_{\mathrm{a}} \cdot A_{\mathrm{e}})$$

Total force acting on the rocket:

$$F = T - D$$

(thrust - drag)

2.1.3 Chamber/nozzle

In the following, let the asterisk superscript denote the value of a function of the vertical position z at the throat.

Area-mach relation:

$$\frac{A(z)}{A^*} = \frac{1}{M(z)} \left[\frac{2}{\gamma + 1} \left(1 + \frac{\gamma - 1}{2} M^2(z) \right) \right]^{\frac{1}{2} \frac{\gamma+1}{\gamma-1}}$$

where A^* is the throat area, $M(z)$ is the Mach number at coordinate z.

Mass flow rate:

$$\dot{m} = A(z)P(z)\sqrt{\frac{\gamma}{TR}}M(z)\left[1+\frac{\gamma-1}{2}M^2(z)\right]^{-\frac{1}{2}\frac{\gamma+1}{\gamma-1}}$$

where T is the chamber temperature, R is the ideal gas constant, γ the specific heat ratio. For maximum flow rate, set $M(z^*) = 1$:

$$\dot{m} = A^*P^*\sqrt{\frac{\gamma}{TR}}\left[\frac{\gamma+1}{2}\right]^{-\frac{1}{2}\frac{\gamma+1}{\gamma-1}}$$

This is then used to calculate thrust according to the previous formula

References:

https://web.stanford.edu/~cantwell/AA284A_Course_Material/Karabeyoglu%20AA%20284A%20Lectures/AA284a_Lecture2.pdf

https://www.grc.nasa.gov/WWW/K-12/airplane/astar.html

https://www.grc.nasa.gov/WWW/K-12/airplane/isentrop.html

2.1.4 CEA rocket solver

The CEA rocket solver is a thermodynamic state-finder that follows a parcel of gas as it moves from the chamber to the exit assuming an isentropic path (line of constant entropy). The solver always calculates at least two points: the chamber and the throat. All points specified in the parameters by the user will then be appended to the list of snapshot points.

Consider packaging the incoming reactant mixture as follows:

```
mixture = [
    { name: "H2(L)", temp: 20.27, fraction: 1.0, fuel_weight: 1.0, oxidant_weight: 0.0 },
    { name: "O2(L)", temp: 90.17, fraction: 1.0, fuel_weight: 0.0, oxidant_weight: 0.1 },
]
```

Isolating the essential arguments of the CEA rocket solver, one can define a function of the following form:

```
def solve(
    mixture : dict,        # mixture component dictionary
    pc      : float,       # chamber pressure
    subar   : list[float], # subsonic area ratio
    supar   : list[float]  # supersonic area ratio
) -> cea.RocketSolution:

    ... # implementation details

    solver.solve(solution, weights, pc, pi_p, subar=subar, supar=supar, hc)

    return solution
```

`mixture` is some kind of table packaging together the chemical components of the fuel and oxidizer, their temperatures

`pc` being the chamber pressure, a design variable

`subar` being the subsonic area ratio, A_c/A^*

`supar` being the supersonic area ratio, A_e/A^*

`pi_p` being the pressure ratio P_c/P_e of chamber pressure to exit pressure. The reactants are ideally expanded at $P_e = P_{amb}$, however since the atmospheric conditions change during the flight, the ideal expansion condition

CEA computes *intensive* properties (values per unit mass), to get *extensive* properties (N and kg/s), we provide the scale in terms of the throat area A^*.

Mass flow:

$$\dot{m} = \frac{PA^*}{c^*}$$

where P is the chamber pressure and c^* is the *characteristic velocity* computed with CEA.

Thrust:

$$T = \dot{m} I_{sp} g_0 = C_f A^* P$$

compute with I_{sp} or C_f (thrust coefficient) provided by CEA.

References:

`https://nasa.github.io/cea/examples/rocket/example8.html`

2.2 My own set of inputs

Flight plan: attitude as a function of altitude and velocity, or pitch as a function of velocity

Mass and CoG time-series (CoG from mass flow?)

Chemical composition time-series -> (gamma, M_w, T) change

Nozzle erosion?