

# Apache Kylin2.3.1对接FusionInsight\_HD\_C80


## 适用场景

Apache Kylin 2.3.1 <-> FusionInsight HD V100R002C80SPC100

## 说明

Apache Kylin™是一个开源的分布式分析引擎，提供Hadoop之上的SQL查询接口及多维分析（OLAP）能力以支持超大规模数据，最初由eBay Inc. 开发并贡献至开源社区。它能在亚秒内查询巨大的Hive表。

Apache Kylin主要与FusionInsight的Hive和HBase进行对接



## 环境准备

- 修改/etc/hosts

添加本机主机名解析

```
172.16.52.86 kylin
```

- 配置NTP服务

使用vi /etc/ntp.conf增加NTP服务的配置,时间与FusionInsight集群同步

```
server 172.18.0.18 nomodify notrap nopeer noquery
```

启动NTP服务

```
service ntpd start
chkconfig ntpd on
```

- 参考FusionInsight产品文档在Kylin节点安装FusionInsight客户端

在FusionInsight Manager服务管理页面下载客户端，上传到kylin节点安装FusionInsight客户端到 `/opt/hadoopclient` 目录

```
./install.sh /opt/hadoopclient
```

- 安装JDK1.8

```
rpm -Uvh jdk-8u112-linux-x64.rpm
```

## 下载Kylin

Fusioninsight配套的HBase是1.3.0，Apache Kylin可直接下载apache-kylin-2.3.1-hbase1x-bin.tar.gz主版本二进制包，无需编译Apache kylin

## 下载解压Kylin

- 下载Kylin-2.3.1基于HBase1.x版本的二进制包， <http://ftp.cuhk.edu.hk/pub/packages/apache.org/kylin/apache-kylin-2.3.1/apache-kylin-2.3.1-hbase1x-bin.tar.gz>
- 上传apache-kylin-2.3.1-hbase1x-bin.tar.gz到Apache kylin节点的 `/opt` 目录
- 解压上一步骤的安装包

```
cd /opt
tar -zxvf apache-kylin-2.3.1-hbase1x-bin.tar.gz -C /opt
```

## 配置Kylin

### 配置环境变量

- 配置环境变量： `vi /etc/profile`，增加以下配置

```
export KYLIN_HOME=/opt/apache-kylin-2.3.1-bin
```

- 导入环境变量

```
source /etc/profile
```

- Kylin启动还需要配置HIVE\_CONF、HCAT\_HOME，使用 `vi /opt/hadoopclient/Hive/component_env`，在文件最后增加

```
export HIVE_CONF=/opt/hadoopclient/Hive/config
export HCAT_HOME=/opt/hadoopclient/Hive/HCatalog
```

- 导入环境变量

```
source /opt/hadoopclient/bigdata_env
```

- 进行kerberos认证

```
kinit test
```

- Kylin检查环境设置：


```
cd /opt/apache-kylin-2.3.1-bin/bin
./check-env.sh
```

```
[root@kylin bin]# ./check-env.sh
Retrieving hadoop conf dir...
KYLIN_HOME is set to /opt/apache-kylin-2.3.1-bin
[root@kylin bin]#
```

### 修改FusionInsight的Hive配置项

- 在hive.security.authorization.sqlstd.confwhitelist.append参数最后追加一下参数配置，保存配置，重启影响的服务

```
|mapreduce\.job\..*|dfs\..*
```



## 修改Kylin配置

- 获取Hive的JDBC字符串

执行Beeline查看Hive的JDBC字符串

```
source bigdata_env
kinit test
beeline
```

```
[root@kylin hadoopclient]# source bigdata_env
[root@kylin hadoopclient]# kinit test
Password for test@HADOOP.COM:
[root@kylin hadoopclient]# beeline
Connecting to jdbc:hive2://172.21.3.101:24002,172.21.3.102:24002,172.21.3.103:24002;/serviceDiscoveryMode=zooKeeper;
zooKeeperNamespace=hiveserver2;sasl.qop=auth-conf;auth=KERBEROS;principal=hive/hadoop.hadoop.com@HADOOP.COM
Debug is true storeKey false useTicketCache true useKeyTab false doNotPrompt false ticketCache is null isInitia
tor true KeyTab is null refreshKrb5Config is false principal is null tryFirstPass is false useFirstPass is false
storePass is false clearPass is false
Acquire TGT from Cache
Principal is test@HADOOP.COM
Commit Succeeded

Connected to: Apache Hive (version 1.2.1)
Driver: Hive JDBC (version 1.2.1)
Transaction isolation: TRANSACTION_REPEATABLE_READ
Beeline version 1.2.1 by Apache Hive
0: jdbc:hive2://172.21.3.101:21066/>
```

- 修改kylin.properties: `vi /opt/apache-kylin-2.3.1-bin/conf/kylin.properties`

配置Hive client使用beeline:

```
kylin.source.hive.client=beeline
kylin.source.hive.beeline-shell=beeline
kylin.source.hive.beeline-params=-n root -u
'jdbc:hive2://172.21.3.101:24002,172.21.3.102:24002,172.21.3.103:24002;/serviceDiscoveryMode=zooKeeper;zooKeeperNamespace=hiveserv
er2;sasl.qop=auth-conf;auth=KERBEROS;principal=hive/hadoop.hadoop.com@HADOOP.COM'
```

JDBC字符串使用上一步骤获取的字符串


```
--hiveconf hive.security.authorization.sqlstd.confwhitelist.append='mapreduce.job.*|dfs.*' 要去掉
```

- kylin的/opt/apache-kylin-2.3.1-bin/bin/find-hive-dependency.sh默认Hive lib路径为大数据集群中Hive的安装路径，需要修改为客户端路径

```
A new Kylin instance is started by root. To stop it, run 'kylin.sh stop'
Check the log at /opt/apache-kylin-2.3.1-bin/logs/kylin.log
Web UI is at http://<hostname>:7070/kylin
```

A screenshot of a web browser displaying the Kylin login page. The browser's address bar shows the URL '172.16.52.86:7070/kylin/login'. The page has a blue header bar with the Kylin logo on the left and a 'Login' button on the right. The main content area is white and features a light gray box containing the 'Sign in' form. The form includes a green coffee cup icon next to the 'Sign in' text, followed by two input fields: 'Username' with a user icon and 'Password' with a lock icon. Below these fields is a 'Log In' button with a magnifying glass icon and a 'Login Issue?' link.

输入默认用户名密码：ADMIN/KYLIN登陆



## Demo测试


### 导入Demo数据

- 执行以下命令导入sample数据

```
cd /opt/apache-kylin-2.3.1-bin/bin
./sample.sh
```

```
2018-06-20 11:26:35,651 INFO [close-hbase-conn] hbase.HBaseConnection:137 : Closing HBase connections...
2018-06-20 11:26:35,651 INFO [close-hbase-conn] client.ConnectionManager$HConnectionImplementation:2292 : Closing master protocol: MasterService
2018-06-20 11:26:35,655 INFO [close-hbase-conn] client.ConnectionManager$HConnectionImplementation:1756 : Closing zookeeper sessionid=0x1400000686169fef
2018-06-20 11:26:35,657 INFO [main-EventThread] zookeeper.ClientCnxn:614 : EventThread shut down for session: 0x1400000686169fef
2018-06-20 11:26:35,658 INFO [close-hbase-conn] zookeeper.ZooKeeper:1325 : Session: 0x1400000686169fef closed
Sample cube is created successfully in project 'learn_kylin'.
Restart Kylin Server or click Web UI => System Tab => Reload Metadata to take effect
```

选择菜单 **System** -> **Actions** -> **Reload Metadata**



选择菜单 **System** -> **Model**

172.16.52.86:7070/kylin/models

Kylin-- Choose Project --InsightModelMonitorSystemWelcome, ADMIN

ModelsData Source

+ New

Models

No Result.

Cubes

Search by name

Name	Status	Cube Size	Source Records	Last Build Time	Owner	Create Time	Actions	Admins
kylin_sales_cube	DISABLED	0.00 KB	0				Action	Action

GridSQLJSON(Cube)AccessNotificationStorage

Cube Designer

1234567

Cube InfoDimensionsMeasuresRefresh SettingAdvanced SettingConfiguration OverwritestOverview

Model Name

kylin\_sales\_model

Notification Email List

Notification Events

Description

构建Cube

- 构建默认的kylin\_sales\_cube

Cubes

Search b

Name	Status	Cube Size	Source Records	Last Build Time	Owner	Create Time	Actions	Admins
kylin_sales_cube	DISABLED	0.00 KB	0				Action	Action

Total: 1  
Storage: 0.00 KB

Drop

Edit

Build

Refresh

Merge

Enable

Purge

Clone

- 选择End Data（Exclude）时间：

CUBE BUILD CONFIRM

PARTITION DATE COLUMN

KYLIN\_SALES.PART\_DT

Start Date (Include)

2012-01-01 00:00:00

End Date (Exclude)

2017-09-21 13:05:00

Submit

Close

- 点击Monitor可以查看build状态：



Kylin

InsightModelMonitorSystem

Welcome, ADMIN

Jobs

Slow Queries

Cube Name: Filter

Jobs in: LAST ONE WEEK

NEW

PENDING

RUNNING

STOPPED

FINISHED

ERROR

DISCARDED

Job Name	Cube	Progress	Last Modified Time	Duration	Actions
BUILD CUBE - kylin_sales_cube - 20170921010500_20170921063000 - GMT+08:00 2017-09-21 17:21:51	kylin_sales_cube	3.3	2017-09-21 17:25:14 GMT+8	3.17 mins	Action

Total: 1

Detail Information

Job Name

Job ID

Status

Duration

MapReduce Waiting

BUILD CUBE - kylin\_sales\_cube - 20170921010500\_20170921063000 - GMT+08:00 2017-09-21 17:21:51

b0187579-3277-4f1d-91f8-a9060f0a5332

RUNNING

3.17 mins

0.70 mins

Start: 2017-09-21 17:22:11 GMT+8

2017-09-21 17:22:11 GMT+8

#1 Step Name: Create Intermediate Flat Hive Table  
Duration: 0.45 mins Waiting: 0 seconds

2017-09-21 17:22:38 GMT+8

#2 Step Name: Redistribute Flat Hive Table  
Duration: 0.40 mins Waiting: 0 seconds

- Build完成:

Kylin

learn\_kylin

InsightModelMonitorSystem

Welcome, ADMIN

Jobs

Slow Queries

Cube Name: Filter

Jobs in: LAST ONE WEEK

NEW

PENDING

RUNNING

STOPPED

FINISHED

ERROR

DISCARDED

Job Name	Cube	Progress	Last Modified Time	Duration	Actions
BUILD CUBE - kylin_sales_cube - 20120101000000_20170922020500 - GMT+08:00 2017-09-22 11:39:24	kylin_sales_cube	100%	2017-09-22 11:49:36 GMT+8	10.12 mins	Action

Total: 1

- Cube构建成功，状态变为READY

Kylin

Choose Project

InsightModelMonitorSystem

Welcome, ADMIN

Models

Data Source

+ New

Models

kylin\_sales\_model

Cubes

Search by name

Name	Status	Cube Size	Source Records	Last Build Time	Owner	Create Time	Actions	Admins
kylin_sales_cube	READY	96.46 MB	10,000	2017-09-22 11:49:32 GMT+8			Action	Action

Total: 1  
Storage: 96.46 MB

## 查询表数据

- 在Insight页面执行查询

Kylin

learn\_kylin

Insight

Model

Monitor

System

Welcome, ADMIN

tables

DEFAULT

KYLIN\_ACCOUNT

KYLIN\_CAL\_DT

KYLIN\_CATEGORY\_GROUPINGS

KYLIN\_COUNTRY

KYLIN\_SALES

1

select \* from kylin\_sales;

Tips: Ctrl+Shift+Space or Alt+Space(Windows), Command+Option+Space(Mac) to list tables/columns in query box.

Project: learn\_kylin

LIMIT1000

Submit

Results

1

✓

✕

|

Status: All

Query String

Start Time: 2017-09-22 11:56:00 GMT+8 Duration: 1.88s

Rerun

Save

Status: Success

Project: learn\_kylin

Cubes: CUBE[name=kylin\_sales\_cube]

Results (1000)

Visualization

Export

	TRANS_ID	PART_DT	LSTG_FORM..	LEAF_CATEG..	LSTG_SITE_ID	PRICE	SELLER_ID	BUYER_ID	
	2664	2013-01-26	FP-GTC	57990	0	2.772	10000896	10000001	
	3243	2013-09-20	FP-non GTC	57990	0	43.608	10000446	10000001	
	5180	2013-06-08	ABIN	60340	0	6.906	10000458	10000001	
	5325	2013-09-03	ABIN	11848	0	21.722	10000419	10000001	
	4007	2012-04-17	FP-non GTC	13987	0	8.16	10000472	10000002	
	787	2013-05-04	Others	13836	0	13.466	10000331	10000004	