

# COMP10001 Foundations of Computing

## Functions, Methods and Iteration

Semester 2, 2018  
Chris Leckie & Nic Geard




THE UNIVERSITY OF  
MELBOURNE

# Lecture Agenda

- Last lecture:
  - `bool`
  - `if`
  - Conditionals
- This lecture:
  - Conditional Recap
  - Functions
  - Iteration

# Conditional Recap

- Problem: evaluate whether a given year is a leap year (True) or not (False)
- Flowchart:




# Cascading Conditions

- It is possible to test various **mutually-exclusive** conditions by adding extra conditions with `elif`, and possibly a catch-all final state with `else`

```
if year % 400 == 0:
    print("leap year")
elif year % 100 == 0:
    print("not leap year")
elif year % 4 == 0:
    print("leap year")
else:
    print("not leap year")
```

# Conditional Recap

- Problem: evaluate whether a given year is a leap year (True) or not (False)
- Pythonic flowchart:



# Class Exercise

- Simply the preceding code into one `if` statement and one `else` statement (and no `elif` statements)

# Functions: Introduction

- What's a function?
  - (much like in Maths) functions take a set of input values, perform some calculation based on them, and optionally return a value
  - you have already seen and used a bunch of functions by this stage, e.g.: `ord()`, `range()`, `str()`, `len()`,  
...
- Wouldn't it be nice to be able to recycle chunks of our own code?

# Functions: The Details

- In order to define a function, we need:
  - A function name (following same conventions as other variable names)
  - (optionally) a list of input variables
  - (optionally) a UNIQUE output object (via `return`)
- Basic form:

```
def _NAME ( INPUTLIST ) :  
    _statement_block
```



# Warm-up Functions

- Print the number of digits in a number

```
def print_digits(n):  
    s = str(abs(n))  
    print(len(s) - ('.' in s))
```

- Convert from Celsius to Fahrenheit:

```
def C2F(n):  
    print(9*n/5 + 32)
```

## Functions: More Details

- It is possible to define “variable-arity” functions (i.e. functions which take variable numbers of arguments) by specifying default values for arguments:

```
def seconds_in_year(days=365):  
    return(days*24*60*60)
```

```
>>> seconds_in_year()  
31536000  
>>> seconds_in_year(366)  
31622400
```

# The Power of return I

- In order to use the output of a function (eg to assign it to a variable), we need to `return` a value:

```
def count_digits(n):  
    s = str(abs(n))  
    return len(s) - ('.' in s)  
  
print(count_digits(-123.123))
```

- Convert from Celsius to Fahrenheit:

```
def C2F(n):  
    return (9*n/5 + 32)  
  
print(C2F(21))
```

# The Power of return II

- `return` is also a way of (unconditionally and irrevocably) terminating a function:

```
def safe_divide(x,y):  
    if y:  
        return(x/y)  
  
    print("ERROR: denom must be non-zero")
```

# Quiz

What is printed to the screen here?

```
def bloodify(word):  
    return(word[:3] + '-bloody-' + word[3:])  
  
w = bloodify('fantastic')  
print(w)
```

What is printed to the screen here?

```
def bloodify(word):  
    return(word[:3] + '-bloody-' + word[3:])  
  
w = bloodify('andrew')  
print(w)
```

# Variables and “Scope” I

- Each function (call) defines its own local variable “scope”. Its variables are not accessible from outside the function (call)

```
def subtract_one(k):  
    k = k - 1  
    return(k)
```

```
i = 0  
n = subtract_one(i)  
print(i)  
print(n)  
print(k)
```

## Variables and “Scope” II

- Are the semantics different to the previous slide?

```
def subtract_one(i):  
    i = i - 1  
    return(i)  
  
i = 0  
n = subtract_one(i)  
print(i)  
print(n)  
print(k)
```

## Variables and “Scope” III

- Functions can access variables defined outside functions (“global” variables), although they should be used with extreme caution (perhaps never!)

```
def fun1(j):  
    fun2(j)  
    return(1)  
def fun2(k):  
    global i,j # global variables  
    print(i,j,k)  
    return(2)  
i,j,k = 1,2,3  
fun1(i)
```



# Reasons for Using Functions

- “Archiving” code in libraries
- Removing redundancy
- Ease of testing
- Increasing modularity
- Increasing readability

# Iteration

One final, essential tool to make the computer do something over and over again.

- Repeat something forever (eg Windows)
- Repeat something a fixed number of times
  - move Mario forward 10 pixels
  - print 7 copies
  - play Nyan Cat 15 times
- Repeat something until something happens (eg scroll while button held)

# Iteration: while Loops I

A conditional loop.

- The general idea is that we continue repeating a block of code as long as a given condition holds
- Basic form:

```
while <condition>:  
    statement_block
```

- We use the notion of “block” as in `if` statements, but here, potentially the code block is repeated

```
text = ''  
while len(text) != 3:  
    text = input('Enter 3-digit code: ')
```

## Iteration: while Loops II

- Another way to end `while` loops (and bypass the condition in the `while` statement) is via a `break` in the block of code

```
text = ''
while True:
    text = input('Enter 3-digit code: ')
    if len(text) == 3:
        break
    print('Sorry, invalid code.')
```

This prematurely and unconditionally exits from the loop

# Iteration: for Loops I

A loop over sequences.

- The general idea is that we work our way through (all of) an “iterable” (eg `str`, `tuple`) of items one item at a time, in sequence
- Basic form:

```
for <var> in <iterable>:  
    <statement>  
    <block>
```

- Note: `in` here is not (quite) the same as the comparison operator of the same name

## Iteration: for Loops II

- Simple example:

```
sum = 0
for i in (1,2,3):
    sum = sum + i
print(sum)
```

is equivalent to:

```
sum = 0
sum = sum + 1
sum = sum + 2
sum = sum + 3
print(sum)
```

# Iteration: for Loops III

- More interesting example:

```
vowels = 0
for char in "rhythm":
    if char in "aeiou":
        vowels = vowels + 1
print(vowels)
```

## A Useful Function for creating a sequence


- `range(start=0,end,step=1)`: generate a sequence of `int` values from `start` (inclusive) to `end` (non-inclusive), counting `step` at a time

```
>>> for i in range(5):  
...     print(i, end=" ")  
0 1 2 3 4  
>>> for i in range(0,10,2):  
...     print(i, end=" ")  
0 2 4 6 8  
>>> for i in range(10,0,-1):  
...     print(i, end=" ")  
10 9 8 7 6 5 4 3 2 1
```



## for Loop Practice: Mexican Wave

- Given the string `wave` made up of a "Y" and `width-1` repeats of "x", how can we use a `for` loop to move the "Y" across one position to the right at a time?



# Choosing between for and while

- If you need to iterate over all items of an iterable, use a `for` loop
- If there is a well defined end-point to the iteration which doesn't involve iterating over all items, use a `while` loop
- With a `for` loop, avoid modifying the object you are iterating over within the block of code
- Given a choice between the two, `for` loops are generally more elegant/safer/easier to understand

# Class Exercise

- Assuming an unlimited number of coins of each of the following denominations:

(1, 2, 5, 10, 20)

calculate the number of distinct coin combinations which make up a given amount  $N$  (in cents).

# Lecture Summary

- What is an “iteration”, and what are the two basic forms of iteration in python?
- What is the basic syntax of a `for` loop, and what function is commonly used to iterate a fixed number of times?
- What is the basic syntax of the `while` loop, and what is the role of `break`?
- When should you use `for` vs. `while`?