

Exercise 2.1

Plotting

useful commands: `hist()`, `barplot()`, `boxplot()`, `plot()` (for scatter plot)

useful arguments within `plot()`: `main`, `xlab`, `ylab`, `col`, `pch`, `cex`

00*. read in the “crabs.csv” dataset

```
getwd()

## [1] "/Users/Erin/Documents/gitErin/STEMinist_R/Day_2/Day_2_Solutions"

# here the working directory is STEMinist_R/Day_2/Day_2_Solutions/,
# and crabs.csv is located in STEMinist_R/Day_2/Day_2_Exercises/ .
# You can change the working directory using setwd()
crabs <- read.csv("../Day_2_Exercises/crabs.csv",
                  header = T,
                  stringsAsFactors = F)
# note: this dataset is published as part of the MASS package
```


00*. subset the data to only include the blue crabs

```
blueCrabs = crabs[crabs[, "sp"] == "B", ]
```

01*. plot carapace length versus carapace width of the blue crabs


- 01a*. make a scatterplot using the ‘plot’ command

```
plot(x = blueCrabs[, "CW"], blueCrabs[, "CL"])
```




- 01b*. change the color of the points

```
plot(x = blueCrabs[ , "CW"], blueCrabs[ , "CL"], col = "red")
```




- 01c.change the shape of the points to a triangle

```
plot(x = blueCrabs[ , "CW"], blueCrabs[ , "CL"], col = "red", pch = 2)
```



- 01d. change the size of the points


```
plot(x = blueCrabs[ , "CW"], blueCrabs[ , "CL"], col = "red", pch = 2, cex = 2)
```



- 01e*. add a title and axis labels to the plot


```
plot(x = blueCrabs[ , "CW"], blueCrabs[ , "CL"], col = "red", pch = 2, cex = 2, xlab = "Carapace width
```

Carapace length versus carapace width of blue crabs



02*. make a barplot of the number of observations for each sex of blue crabs


```
barplot(table(blueCrabs[, "sex"]))
```



03*. make a histogram of the body depth of the blue crabs


```
hist(blueCrabs[, "BD"])
```

Histogram of blueCrabs[, "BD"]




04*. boxplot of body depth by sex of the blue crabs

```
boxplot(blueCrabs[, "BD"] ~ blueCrabs[, "sex"])
```



- 04a* plot this in different colors for each sex


```
boxplot(blueCrabs[, "BD"] ~ blueCrabs[, "sex"], col = c("red", "blue"))
```



- 04b add a main title and axis labels

```
boxplot(blueCrabs[, "BD"] ~ blueCrabs[, "sex"], col = c("red", "blue"), main = "Blue crab body depth by sex")
```

Blue crab body depth by sex



05 BONUS** - defining color variables for plotting


useful commands: `[logical,]=`, `ifelse()`, `plot()` + `points()`

make scatter plot for carapace length versus carapace width of the blue crabs

but now depict records of female crabs with red, and male crabs with blue


- Solution 1 — add a column of colors to the original dataset using indexing

```
# add a new column to the data.frame, and assign "dummy" values for now  
blueCrabs$color = NA  
# now assign "red" to the new column when crabs are females  
blueCrabs$color[blueCrabs$sex == "F"] = "red"  
# now assign "blue" when they are males  
blueCrabs$color[blueCrabs$se == "M"] = "blue"  
# depict females and males with different colors  
plot(blueCrabs$CL ~ blueCrabs$CW, col = blueCrabs$color)
```



- Solution 2 – add a color column to the dataset using an “ifelse” statement

```
blueCrabs$color2 = ifelse(blueCrabs$sex == "F", "red", "blue")  
# if crabs are females add "red", but if they are not females, add "blue" to the new column  
  
# plot mass across time, and depict females and males with different colors  
plot(blueCrabs$CL ~ blueCrabs$CW, col = blueCrabs$color2)
```



- Solution 3 — make NULL plot and add points (note: this can be a good strategy to combine with supply for a large number of categories)

```
plot(blueCrabs$CL ~ blueCrabs$CW, col = NULL)
points(blueCrabs[blueCrabs$sex == "F", "CW"], blueCrabs[blueCrabs$sex == "F", "CL"], col = "red")
points(blueCrabs[blueCrabs$sex == "M", "CW"], blueCrabs[blueCrabs$sex == "M", "CL"], col = "blue")
```

