

# Prediction of optical modulation properties of twisted-nematic liquid-crystal display by improved measurement of Jones matrix

Baiheng Ma,<sup>1,2</sup> Baoli Yao,<sup>1,a)</sup> Tong Ye,<sup>1</sup> and Ming Lei<sup>3</sup>

<sup>1</sup>State Key Laboratory of Transient Optics and Photonics, Xi'an Institute of Optics and Precision


Mechanics, Chinese Academy of Sciences, Xi'an 710119, China

<sup>2</sup>Graduate School of the Chinese Academy of Sciences, Beijing 100039, China


<sup>3</sup>College of Life Science and Shaanxi Key Laboratory of Molecular Biology for Agriculture, Northwest A&F University, Yangling 712100, People's Republic of China

## 1. Medir

$$I_1 = | \langle \mathbf{H} | SLM | \mathbf{H} \rangle |^2, \quad I_2 = | \langle \mathbf{CD} | SLM | \mathbf{CD} \rangle |^2, \quad I_3 = | \langle 45^\circ | SLM | 45^\circ \rangle |^2, \\ I_1^\perp = | \langle \mathbf{V} | SLM | \mathbf{H} \rangle |^2, \quad I_2^\perp = | \langle \mathbf{CI} | SLM | \mathbf{CD} \rangle |^2, \quad I_3^\perp = | \langle -45^\circ | SLM | 45^\circ \rangle |^2$$



(a)



(b)