

# GRASP Prototype

Brian E Carpenter  
The University of Auckland  
March 2017

# What is Autonomic Networking?

- “Plug and play for the ISP” or “plug and play for the enterprise”
- The goal is self-management, including self-configuration.
- Nodes will discover information about the surrounding network and negotiate parameter settings with other nodes.
- Humans will set general policy intent.

# What is GRASP?

- GeneRic Autonomic Signaling Protocol
- Allows autonomic nodes to discover each other, and mutually negotiate or synchronize parameters.
- The “customers” for GRASP are Autonomic Service Agents (ASAs) – the “apps” of autonomic networking

# What is a GRASP Objective?

- A configurable parameter:
  - a logical, numerical or string value, or a more complex data structure.
  - used in Discovery, Negotiation and Synchronization.
- Example for IPv6 prefix management:  
**["PrefixManager", flags,  
loop\_count, [PD\_support,  
prefix\_length, prefix]]**


# GRASP messages

- Discovery (multicast)  
Discovery Response
- Request Synchronization  
Synchronization
- Flood Synchronization (multicast)
- Request Negotiation  
Negotiation  
Confirm Waiting  
Negotiation End

# Python prototype

- A Python 3 implementation of GRASP as a module **grasp.py**
  - About 1400 lines of code
- A test suite to exercise as many code paths as possible, **grasptests.py**
- Various toy ASAs to test “real” operation across the network, e.g. **Briggs.py** and **Gray.py**
- Some documentation

# Tests



# Sample logs

```
GRASP startup thread exiting
ASA Gray is starting up
...
Asking for $ 129
Discovered locator
    2406:e007:477e:1:28cc:dc4c:9703:6781
Sending req_negotiate to
    2406:e007:477e:1:28cc:dc4c:9703:6781
Assembled Python message [3, 2706907,
    ['EX3', 1, 5, ['NZD', 129]]]

negloop: CBOR->Python: [4, 2706907,
    ['EX3', 1, 4, ['NZD', 118]]]
negloop: got NEGOTIATE
Assembled Python message [5, 2706907,
    [101]]
Negotiation succeeded ['NZD', 118]
```

```
GRASP startup thread exiting
ASA Briggs is starting up
...
listen_negotiate: Waiting for a
    negotiate request

Received request: CBOR->Python: [3,
    2706907, ['EX3', 1, 5, ['NZD',
    129]]]
Request queued for ASA
listen_negotiate: Got negotiate request
    from queue
listened, answer EX3 ['NZD', 129]
Assembled Python message [4, 2706907,
    ['EX3', 1, 4, ['NZD', 118]]]

negloop: CBOR->Python: [5, 2706907,
    [101]]
Negotiate_step: got END
```



## Further reading

- RFC 7575
- RFC 7576
- <https://datatracker.ietf.org/wg/anima/documents/>
- <https://www.cs.auckland.ac.nz/~brian/graspy/>