GeneRic Autonomic Signaling Protocol (GRASP) An Introduction

Brian Carpenter

November 2020

draft-ietf-anima-grasp (RFC Editor) draft-ietf-anima-grasp-api (IESG agenda)

English lesson


- Automatic
 - done <u>as if by machine</u>; self-acting or self-regulating mechanism



- Autonomous
 - without outside control; responding, reacting, or developing independently of the whole



- Autonomic
 - occurring involuntarily or <u>spontaneously</u>;
 occurring as a result of <u>internal stimuli</u>



November 2020 GRASP overview

Terminology (1)

- Autonomic Nervous System: a control system that acts largely unconsciously and regulates bodily functions such as heart rate.
- Autonomic Computing: self-managing distributed computing resources, adapting to unpredictable changes while hiding intrinsic complexity from operators and users (IBM, 2001).
- Autonomic Network: Self-managing (self-configuring, selfprotecting, self-healing, self-optimizing) but allowing high-level guidance by a central entity ("Intent")
 - "Plug and play for the ISP" or "plug and play for the enterprise"

Terminology (2)

- Autonomic Function: A specific self-managing feature or function.
- Autonomic Service Agent (ASA): An agent that implements an autonomic function, in part (for a distributed function) or whole.
- Autonomic Node: A node that employs autonomic functions
- Autonomic Control Plane (ACP): Self-configuring fully secure virtual network used for all autonomic messaging.

For more details see RFC7575

Autonomic Networking Integrated Model and Approach (ANIMA) WG

- Initial work items (RFCs imminent)
 - Bootstrapping & trust infrastructure
 - Secure Autonomic Control Plane (ACP)
 - Discovery for autonomic nodes
 - Negotiation & synchronisation for autonomic nodes

- Next steps
 - Intent (high level policy)
 - Defining the domain boundary
 - ASA life cycle, authorisation and coordination
 - Reporting

- Left for much later
 - Tie in to machine learning and other AI techniques


Bootstrap and ACP

- Secure bootstrap all nodes must start (out of the box or after a factory reset) by using a registrar to authenticate themselves and obtain a domain certificate. This is coordinated with related work for IoT devices. No human intervention except to create the registrar.
- ACP the ACP will bootstrap itself using only link-local IPv6 addresses and IPv6 Unique Local Address prefix. All links secured (IPsec). No human intervention except to define the domain boundary.

GeneRic Autonomic Signaling Protocol (GRASP)

- GRASP will be used for signaling between ASAs
 - That includes the special-purpose ASAs that support both secure bootstrap & ACP creation
 - After that, GRASP runs over the ACP to guarantee security
- GRASP provides discovery, flooding, synchronization and negotiation for the <u>technical objectives</u> supported by ASAs
 - Based on CBOR (Concise Binary Object Representation)
 - Objectives can be expressed in JSON or Python-like syntax & semantics

Reference Model – High Level View



Network with autonomic functions

More about a GRASP Objective

- A configurable parameter:
 - a logical, numerical or string value, or a more complex data structure.
 - used in Discovery, Negotiation, Flooding and Synchronization.
 - semantics depend on the autonomic function concerned, and are built into the code of each ASA.
- Example for IP prefix management:

```
["PrefixManager", flags, loop_count, [IP_version, prefix_length, prefix]]
```

GRASP Messages

Discovery (multicast)
 Discovery Response

M_DISCOVERY M RESPONSE

 Request Negotiation Negotiation Confirm Waiting Negotiation End

M_REQ_NEG M_NEGOTIATE

M_WAIT M_END

 Request Synchronization Synchronization M_REQ_SYN M_SYNCH

Flood Synchronization (multicast)

M_FLOOD

GRASP API Functions

- Registration. An ASA can register itself and register the GRASP Objectives it manipulates.
- *Discovery*. An ASA can discover a peer willing to respond for a particular objective.
- Negotiation. An ASA can act as an initiator (requester) or responder (listener)
 for a negotiation session. Negotiation is a symmetric process, so most functions
 can be used by either party.
- Synchronization. An ASA can act as an initiator (requester) or responder (listener and data source) for data synchronization.
- *Flooding*. An ASA can send and receive a GRASP Objective that is flooded to all nodes of the ACP.

A negotiation session

<u>Initiator</u>		<u>Responder</u>	
		listen_negotiate()	\ Await request
<pre>request_negotiate()</pre>			
M_REQ_NEG	->	<pre>negotiate_step()</pre>	\ Open session,
	<-	M_NEGOTIATE	/ start negotiation
<pre>negotiate_step()</pre>			
M_NEGOTIATE	->	<pre>negotiate_step()</pre>	\ Continue
	<-	M_NEGOTIATE	/ negotiation
	• • •		
<pre>negotiate_step()</pre>			
M_NEGOTIATE	->	<pre>negotiate_step()</pre>	\ Continue
	<-	M_NEGOTIATE	/ negotiation
<pre>negotiate_step()</pre>			
M_NEGOTIATE	->	<pre>end_negotiate()</pre>	\ End
	<-	M_END	/ negotiation,
			\ process results

GRASP Prototype

- A Python 3 implementation of GRASP as a module grasp.py
- About 2400 lines of code
- A test suite to exercise as many code paths as possible
- Various toy ASAs to test "real" operation across the network
 - bank/client negotiation
 - model of secure bootstrap process
 - model of IPv6 prefix management
 - bulk transfer using GRASP
- Some documentation

More...

- RFC 7575
- RFC 7576
- https://datatracker.ietf.org/wg/anima/documents/
- https://github.com/becarpenter/graspy