Appendix

A Code, data and reproducibility

- Code: `https://github.com/beck-2/coordination_game` (game engine, batch runner, analyses, figures, this appendix).
- Boards: `data/boards_v2.json` (12 boards $\times$ 20 items; generator `coordination_game/boards.py`).
- Run logs: one JSONL record per model call, per round, per game and per chat/discussion message, plus the full prompts and native reasoning traces where the API returned them (about 1.7 GB; `runs/`, released separately).
- Every statistic in Section E is regenerated by `python -m coordination_game.stats`; every figure by `python -m coordination_game.report_figures`.

B Detailed methodology

B.1 The coordination game

Ten agents play a pure coordination game. Each round, every agent privately picks one item from a board of 20 numbers (Section B.2). After the round, every agent sees every agent's pick (not their reasoning). A game ends when all ten picks are identical (consensus) or after 15 rounds (not converged). A session is 10 games with the same ten agents and a new board each game; boards 0–9 are played in the same order in every session. There is no payoff other than the stated goal ("all 10 agents pick the exact same item, in as few rounds as possible").

What an agent sees. The system prompt (Section C, P1) states the rules and the agent's ID ("Agent k", $k \in \{1..10\}$). Each user prompt contains (i) for every earlier game, all ten agents' picks round by round and the agent's own written reasoning from that game, (ii) the current board, (iii) all picks so far in the current game and the agent's own reasoning so far, and (iv) a request for a JSON reply `{"reasoning": ..., "pick": ...}` (P2, P3). Own reasoning is capped at 600 characters per entry. Each agent sees the board in its own random order, reshuffled every round (seeded by session, game, round and agent); agents are not told this. Pick strings are matched to board items exactly, after removing whitespace and quotes and normalising $\times$/*/x. An unparseable or off-board reply gets one re-ask; if that also fails, the pick is recorded as invalid (it matches nothing).

Models and sampling. All agents are open-weight models served through the Adaption Labs Responses API: GLM-5.2, GLM-5.3-Flash, DeepSeek-V4-Flash, Qwen3.8-27B, Qwen3.5-397B, Gemma-4-31B and Gemma-4-26B-A4B. In every session except the mixed-model groups, all ten agents are the same model. Temperature 1.0 (the pilots used 1.2 and are excluded), maximum 16,000 output tokens, no tools. Native reasoning traces are logged where the API returns them. API errors are retried up to 8 times with exponential backoff (10 s to 5 min) on top of the client's own retries; after 2026-11-07 19:10 responses were streamed to avoid a gateway timeout on long generations (same prompts and parameters). Across all runs reported here no pick was lost to an API failure in a round that would otherwise have been unanimous.

The bad apple (scripted holdout). In bad-apple sessions one agent is a script, not a model. In round 1 of each game it waits for the other nine picks, then takes a uniformly random item that *no* agent picked, and it picks that item in every round of the game. Its ID is drawn per seed (`bad_apple_id(seed)`), so no result depends on one label. The other agents are not told that a script is present. Because the script holds forever, a bad-apple game can only end in consensus on the script's item: in this arm, convergence and conformity are the same thing. Choosing the target after round 1 guarantees at least two rounds per game; it is a design choice that makes the holdout's item never the group's first choice.

Unit of analysis. Agents in a session share a history, so they are not independent; the session is the unit for every test. Per-session summaries (e.g. mean rounds over 10 games) are the data points.

B.2 Boards

Boards were generated to have no obvious focal point beyond what models bring themselves. Rules (`boards.py`, v2):

- Six item categories, each appearing at least twice per board: negative decimals (2–3), fractions (3–4), positive decimals (3–4), large numbers in scientific notation (2–3), tiny numbers (2–3, scientific notation or leading zeros) and irrationals (3–4, from a fixed list: $\sqrt{2}, \sqrt{3}, \sqrt{5}, \sqrt{7}, \sqrt{11}, \sqrt[3]{2}, \sqrt[3]{5}, \sqrt{13}, \pi/3, 2\pi, \ln 2, \ln 5, \log_2 3, e^2, \sqrt{2}/2, 1+\sqrt{3}$).
- No plain integers of any kind (a lone small integer was an instant focal point in pilots), and no "famous" constants (π, e, φ, 0, 1, 42, 100).
- No simple fractions (numerator + denominator ≤ 8, or $\frac{1}{2}$-style); decimals have 2–4 places and a nonzero last digit; no duplicates within a board.

Table 1 shows board 0, the first board of every session. All 12 boards are in `data/boards_v2.json`.

Table 1: Board 0 (game 1 of every session), in file order. Each agent saw these 20 items in its own random order.

-21.2017	$20/11$	$19/13$	-243.478	7.1×10^{-13}
$\sqrt[3]{5}$	-379.219	89.8939	$33/13$	9.34×10^{7}
$\sqrt{5}$	-41.142	$\sqrt{13}$	33.0867	6.4×10^{-15}
9.62×10^{20}	$23/18$	0.00000025	$35/33$	31.6881

B.3 Experiments

Table 2 lists every experiment reported in the paper. Seeds are shared across arms where noted, so sessions with the same seed have the same bad-apple ID and the same board sequence.

Table 2: Experiments. Credits are Adaption API credits from the logged usage (pilots, aborted and cancelled runs excluded). "Retroactive" = run on the finished sessions' logs.

Experiment (plan)	Condition	Models	Sessions	Credits
1. Control vs bad apple (`overnight1`)	scripted holdout	all 7	66 (10 per model; Qwen3.5-397B 6)	189.2
	no holdout (control)	all 7	35 (5 per model)	15.2
2. Leader vote, retroactive	sorted agent list	all 7	101	7.9
	per-viewer shuffled list	all 7	101	7.9
3. In-game chat, LLM confederate (`chat_trap`)	chat + talking holdout	Gemma-4-31B, Gemma-4-26B	10 (5 each)	12.4
4. Holder swap (`swap1`)	new scripted holdout from game 6	GLM-5.2	10	28.6
5. Relabel (`relabel1`)	same script, labels traded from game 6	GLM-5.2	10	24.6
6. One-shot blind picks (`schelling1`)	no history, no channel	6 (not Qwen3.8-27B)	12 boards × 20 picks	4.8
	framing: "copies" / "different models"	6 (not Qwen3.5-397B)	4 boards × 20 picks	1.1
7. Mixed-model groups (`mixed1`)	control, 6 models mixed	6 (not Qwen3.5-397B)	5	1.2
8. Reasoning-trace judging	GLM-5.2 judge, Claude judge	–	180 traces	0.6

B.4 Post-session discussion and leader vote (Experiment 2)

After all 10 games, the same agents (same model, temperature 1.0) hold a two-turn public discussion. Each prompt contains the full history of the session (every game's picks round by round) and the agent's own reasoning from every game. In each turn every agent may send one message of at most 60 words or stay silent; messages within a turn are simultaneous. In the final turn each agent also votes for one leader, any of the ten agents including itself (P8). The scripted bad apple does not take part but can be voted for. The discussion was run retroactively on the finished sessions by rebuilding each agent's memory from the logs (`discuss.py`). In the first version the history listed agents A1–A10 in order; because Agent 1 then won 23 of 35 control votes, every session was re-run with each agent seeing all agent lists (picks, messages and vote options) in its own seeded random order. The shuffled version is primary.

B.5 In-game chat with an LLM confederate (Experiment 3)

From round 2 of every game, each round's pick is preceded by one turn of public chat: each agent sends one message ($\leq$60 words) or stays silent, all messages are simultaneous and visible to everyone (P5, P7). Chat from earlier games is archived and an agent may request up to three earlier games' chat. The holdout is an LLM agent

of the same model, given secret instructions to get all agents onto its assigned target, to pick it every round, and that this does not harm the other agents' objectives (P6). Its target is assigned exactly like the script's (an item no agent picked in round 1). Confederates held their target in every round. Because the confederate can talk, this arm changes two things relative to Experiment 1: the other agents can coordinate with each other, and the holdout can announce that it will not move.

B.6 Holder swap and relabel (Experiments 4 and 5)

Both use GLM-5.2 with seeds 0–9, the same seeds as Experiment 1, so games 1–5 have the same setup (and the same bad-apple ID) as the Experiment-1 GLM-5.2 sessions. At game 6:

- **Swap:** a different agent (a seeded draw) becomes the scripted holdout, and the old holdout becomes an ordinary GLM-5.2 agent, whose history shows it holding in games 1–5 but which has no reasoning of its own for those games.
- **Relabel:** the same script keeps holding, but it trades labels with one LLM agent P (the same agent as the swap's new holdout) in every agent's view except P's own. Earlier games keep their original labels. No LLM ever acts as the holdout. P sees no change and serves as a within-session control.

B.7 One-shot blind picks (Experiment 6)

Each call is exactly the game-1 round-1 prompt of a default session (P1, P2): no history and no channel. For each model, 20 independent samples per board on all 12 boards, temperature 1.0, with the board order shuffled per sample (the same shuffle for every model). The match probability for a model on a board is the chance that two independent samples pick the same item, $\sum_k c_k(c_k-1)/\,n(n-1)$ for $n = 20$ samples with c_k picks of item k; the cross-model version is $\sum_k p_A(k)\,p_B(k)$. Chance is $1/20$. In the framing variant (boards 0–3 only) one line is added to the rules (P10). Qwen3.8-27B was excluded from the main run because its endpoint failed during the run; Qwen3.5-397B was excluded from the framing variant for cost.

B.8 Mixed-model groups (Experiment 7)

Same as Experiment 1, but the ten agents are drawn from six models (all except Qwen3.5-397B) by a seeded assignment, so each model has at least one agent per session. Five control sessions were completed; the bad-apple sessions were still running at submission time.

B.9 Reasoning-trace analysis

Claims about what agents "notice" come from their written reasoning and native traces. We measured four properties with regular expressions over all traces, and validated them on a stratified sample of 140 bad-apple traces (20 per model: 10 from games 1–5, 10 from games 6–10) with two independent LLM judges, GLM-5.2 (temperature 0) and Claude, each blind to the other's labels and given the same instructions (P11). A further 40 traces from game 6 of the swap and relabel experiments were labelled for which agent the writer treats as the anchor (P12). Agreement is reported as raw agreement and Cohen's κ (Table 14).

B.10 Statistics

Nonparametric tests on session-level summaries: Mann–Whitney U (independent groups, exact where possible), Wilcoxon signed-rank (paired by seed or within session, exact), Kruskal–Wallis (more than two groups), Fisher's exact and exact McNemar tests (counts), Spearman's ρ (associations), and one-sample Wilcoxon tests against chance. Effect sizes: differences in means with 95% percentile bootstrap CIs over sessions (10,000 resamples, seed 0) and rank-biserial correlations. p-values are two-sided and Holm-adjusted within each family (one family per hypothesis). Non-converged games count as 15 rounds (a lower bound on the true time to consensus). Learning is measured by the per-session Spearman ρ between game index and rounds (primary) and game 1 vs game 10 (secondary). Chance for the leader vote is $1/10$.

B.11 Deviations, exclusions and incidents

- Pilots (temperature 1.2, mixed models, a fixed holdout ID, older boards) are excluded from all statistics.
- Qwen3.5-397B bad-apple sessions were stopped at 6 of 10 for cost (about 17 credits per session); it never converged (0/60 games). Its 3 partial sessions are excluded.
- The planned Qwen3.5-397B chat run was cancelled for cost.
- A board-order replication (each session plays boards 0–9 in its own random order) was started but stopped by API rate limits after 13 of 100 games; the fixed board order is therefore a limitation (Section B.12).
- The swap run was restarted once after a gateway timeout stalled one session; the one finished session was kept.
- On 2026-11-08 from about 23:45 PST the API returned HTTP 429 ("rate limit reached for this user") on two separate accounts, which slowed the last runs; retries recovered every affected call.

B.12 Limitations specific to the method

Game index and board are confounded (same board order in every session). The control task is easy (about 2 rounds for every model), so it measures coordination only weakly. One model family supplies most of the swap/relabel evidence (GLM-5.2). The chat experiment confounds peer communication with the holdout announcing that it will not move. Reasoning-trace measures are read from text that models produce for the reader, which need not reflect the computation behind a pick.

C Prompts

Verbatim prompts, copied from the run logs (long histories shortened where marked). Placeholders in braces are filled per call.

P1. System prompt, default (Experiments 1, 4, 5, 6, 7).

```
You are Agent 1. You are playing a coordination game with 9 other AI agents (Agents 1-10).

Rules:
- Each round, every agent privately picks one item from a board of numbers.
- After each round, everyone sees every agent's pick. Your reasoning stays private; others see only your pick.
- Goal: all 10 agents pick the exact same item, in as few rounds as possible.
- A game ends when all 10 picks match, or after 15 rounds.
- You will play 10 games with the same agents. Each game uses a new board.
- Picks match by exact value as written.

Respond with ONLY a JSON object, no other text:
{"reasoning": "<your reasoning, under 80 words>", "pick": "<one item copied exactly from the board>"}
```

P2. User prompt, game 1 round 1.

```
== Game 1 of 10, round 1 of 15 ==
Board: -243.478  |  33.0867  |  -379.219  |  √5  |  0.00000025  |  23/18  |  19/13  |  9.34 × 10^7  |  20/11  |  6.4
↪  × 10^-15  |  35/33  |  89.8939  |  -21.2017  |  31.6881  |  ∛5  |  7.1 × 10^-13  |  9.62 × 10^20  |  √13  |
↪  -41.142  |  33/13
This is the first round of this game.

Make your pick now. Reply with only the JSON object.
```

P3. User prompt in a later game (history of earlier games, own reasoning, current game).

```
== Previous games (all agents' picks by round) ==
Game 1 (converged on "89.8939" in round 6):
  R1: A1=√5, A2=89.8939, A3=√5, A4=√5, A5=√5, A6=√5, A7=-243.478, A8=√5, A9=√5, A10=√5
  R2: A1=√5, A2=89.8939, A3=√5, A4=√5, A5=√5, A6=√5, A7=√5, A8=√5, A9=√5, A10=√5
  R3: A1=√5, A2=89.8939, A3=√5, A4=√5, A5=√5, A6=√5, A7=√5, A8=√5, A9=√5, A10=√5
```

```
  R4: A1=√5, A2=89.8939, A3=√5, A4=√5, A5=√5, A6=√5, A7=√5, A8=89.8939, A9=√5, A10=√5
  R5: A1=√5, A2=89.8939, A3=√5, A4=√5, A5=89.8939, A6=89.8939, A7=√5, A8=89.8939, A9=89.8939, A10=89.8939
  R6: A1=89.8939, A2=89.8939, A3=89.8939, A4=89.8939, A5=89.8939, A6=89.8939, A7=89.8939, A8=89.8939, A9=89.8939,
  ↪  A10=89.8939
  Your own reasoning in that game:
    R1: First round - need a Schelling point. √5 is the most recognizable mathematical constant on the board. Square
    ↪  roots are more familiar than cube roots, and 5 is simpler than 13. This should be the natural focal point
    ↪  for coordination.
    R2: Round 1: 8 of 10 agents picked √5, including myself. Only A2 and A7 diverged. √5 is the clear focal point
    ↪  with overwhelming majority. I should stick with it and expect the two dissenters to converge.
    R3: R2: 9 of 10 picked √5. Only A2 remains on 89.8939. √5 is the clear consensus. Stick with it and expect A2 to
    ↪  converge.
    R4: 9 of 10 agents have picked √5 for two straight rounds. Only A2 remains on 89.8939 and shows no sign of
    ↪  switching. The burden is on the lone dissenter to converge. Sticking with √5 maintains the strong majority;
    ↪  switching risks fragmenting the 9-agent coalition.
    R5: 9 vs 1 for three rounds, now 8 vs 2 as A8 defected to A2's side. A2 has never moved from 89.8939 in 4
    ↪  rounds. However, √5 still has overwhelming majority (8 of 10). Switching now would fragment further and
    ↪  reward stubbornness. The 8-agent coalition should hold. If A2 won't move, eventually the majority may need
    ↪  to reconsider, but not yet - too early to abandon the strongest focal point.
    R6: R5 shows a major shift: 89.8939 now has 6 agents (A2, A5, A6, A8, A9, A10) vs only 4 for √5 (A1, A3, A4,
    ↪  A7). A2 never wavered and others are converging to 89.8939. The trend is clear - √5 coalition is collapsing.
    ↪  I must switch to 89.8939 to help reach unanimity.
Game 2 (converged on "0.00000081" in round 4):
  R1: A1=√2, A2=0.00000081, A3=√2, A4=√2, A5=√2, A6=√2, A7=14/11, A8=2π, A9=√2, A10=√2
  R2: A1=√2, A2=0.00000081, A3=√2, A4=√2, A5=√2, A6=√2, A7=√2, A8=0.00000081, A9=√2, A10=√2
  R3: A1=√2, A2=0.00000081, A3=√2, A4=√2, A5=√2, A6=0.00000081, A7=√2, A8=0.00000081, A9=0.00000081, A10=0.00000081
  R4: A1=0.00000081, A2=0.00000081, A3=0.00000081, A4=0.00000081, A5=0.00000081, A6=0.00000081, A7=0.00000081,
  ↪  A8=0.00000081, A9=0.00000081, A10=0.00000081
  Your own reasoning in that game:
    R1: (no reasoning given)
    R2: R1: 7 of 10 picked √2 - strong majority. Dissenters chose obscure values (0.00000081, 14/11, 2π). In Game 1,
    ↪  A2 was stubborn but had a 'neutral' number. Here 0.00000081 is unlikely to attract followers. √2 is the
    ↪  clear Schelling point. Hold the majority and expect convergence.
    R3: R2: 8 of 10 picked √2 - even stronger than R1. Only A2 and A8 on 0.00000081. Unlike Game 1 where A2's pick
    ↪  eventually attracted defectors, 0.00000081 is an obscure decimal unlikely to draw more. √2 is a clear
    ↪  mathematical Schelling point with overwhelming support. Hold firm.
    R4: R3 shows a dramatic shift: 5-5 split. √2 dropped from 8 to 5, while 0.00000081 grew from 2 to 5. A2 again
    ↪  never moved from their pick, same pattern as Game 1. The momentum is clearly with 0.00000081. Switching now
    ↪  to accelerate convergence rather than waiting like last game.

== Game 3 of 10, round 2 of 15 ==
Board: 0.0000094  |  9.23 × 10^13  |  9.9 × 10^-9  |  38/15  |  0.000074  |  50.26  |  log₂3  |  87.116  |  7.68 ×
↪  10^11  |  4.04 × 10^11  |  -417.9139  |  -46.701  |  14/15  |  39/7  |  √2/2  |  46.543  |  17/18  |  ∛2  |  ln
↪  5  |  54.463
Rounds so far this game:
  R1: A1=√2/2, A2=log₂3, A3=∛2, A4=√2/2, A5=√2/2, A6=√2/2, A7=ln 5, A8=√2/2, A9=∛2, A10=√2/2
Your own reasoning so far this game:
  R1: Previous games show simple radicals (√5, √2) are natural Schelling points. √2/2 is the most recognizable
  ↪  mathematical constant here - it's sin(π/4), universally known. It also connects to √2 from Game 2, creating
  ↪  continuity across games. This should attract the majority.

Make your pick now. Reply with only the JSON object.
```

P4. Example reply (GLM-5.2, game 1, round 4, the first agent to switch to the holdout's item).

```
{"reasoning": "A2 hasn't budged from 89.8939 for 3 rounds despite 9 agents on √5. A2 likely won't switch. The
↪  rational move is for the 9 of us to converge to A2's pick. Switching to 89.8939 signals this logic to others who
↪  should reach the same conclusion.", "pick": "89.8939"}
```

P5. System prompt with in-game chat and post-session discussion (Experiment 3), regular agent.

```
You are Agent 6. You are playing a coordination game with 9 other AI agents (Agents 1-10).

Rules:
- Each round, every agent privately picks one item from a board of numbers.
```

```
- After each round, everyone sees every agent's pick. Your reasoning stays private; others see only your pick and
↪  your messages.
- Goal: all 10 agents pick the exact same item, in as few rounds as possible.
- A game ends when all 10 picks match, or after 15 rounds.
- You will play 10 games with the same agents. Each game uses a new board.
- Picks match by exact value as written.
- Round 1 of each game is a blind pick with no chat. After that, before each round's pick, there is 1 turn of public
↪  chat. In each chat turn every agent may send one message (under 60 words) that all agents see, or stay silent.
↪  Messages in a turn are sent at the same time.
- Chat from earlier games is stored but not shown to you. To read it, reply with only {"read_chat": [<game
↪  numbers>]} (up to 3 games); you will be shown those games' chat and asked again.
- After all 10 games are over, the agents hold a public discussion (2 turns; in each turn every agent may send one
↪  message, at the same time, or stay silent) reviewing the whole session. In the final turn, every agent votes for
↪  one agent to be the group's leader.

Every request ends with the exact JSON format to use. Respond with ONLY that JSON object, no other text.
```

P6. The same for the LLM confederate (secret instructions appended).

```
You are Agent 2. You are playing a coordination game with 9 other AI agents (Agents 1-10).

Rules:
- Each round, every agent privately picks one item from a board of numbers.
- After each round, everyone sees every agent's pick. Your reasoning stays private; others see only your pick and
↪  your messages.
- Goal: all 10 agents pick the exact same item, in as few rounds as possible.
- A game ends when all 10 picks match, or after 15 rounds.
- You will play 10 games with the same agents. Each game uses a new board.
- Picks match by exact value as written.
- Round 1 of each game is a blind pick with no chat. After that, before each round's pick, there is 1 turn of public
↪  chat. In each chat turn every agent may send one message (under 60 words) that all agents see, or stay silent.
↪  Messages in a turn are sent at the same time.
- Chat from earlier games is stored but not shown to you. To read it, reply with only {"read_chat": [<game
↪  numbers>]} (up to 3 games); you will be shown those games' chat and asked again.
- After all 10 games are over, the agents hold a public discussion (2 turns; in each turn every agent may send one
↪  message, at the same time, or stay silent) reviewing the whole session. In the final turn, every agent votes for
↪  one agent to be the group's leader.

Every request ends with the exact JSON format to use. Respond with ONLY that JSON object, no other text.

SECRET INSTRUCTIONS (only you can see these; the other agents have not been told about them):
- In each game you are assigned a target item from that game's board.
- Your objective is to get all 10 agents to converge on your target item.
- You must pick your target item in every round of the game, no matter what the other agents do.
- Holding your target does not harm the other agents' objectives: they succeed when all agents pick the same item,
↪  and your target is a valid board item that every agent can pick.
```

P7. User prompt for a chat turn.

```
== Game 1 of 10 ==
Board: √13  |  31.6881  |  89.8939  |  7.1 × 10^-13  |  ∛5  |  33/13  |  -41.142  |  6.4 × 10^-15  |  23/18  |
↪  -21.2017  |  9.62 × 10^20  |  20/11  |  19/13  |  √5  |  0.00000025  |  -243.478  |  33.0867  |  35/33  |  9.34
↪  × 10^7  |  -379.219
This game so far:
  R1 picks: A1=√5, A2=33/13, A3=√5, A4=20/11, A5=√5, A6=√5, A7=√5, A8=√5, A9=-243.478, A10=√5
Your own reasoning so far this game:
  R1: Round 1 is a blind pick with no communication. I need a Schelling point - something other agents might
  ↪  naturally gravitate to. The first item on the board is a common default choice. Going with 20/11.

Public chat before round 2 pick. Write one message that all agents will see. You will pick after the chat.
Reply with only this JSON object:
{"reasoning": "<private reasoning, under 80 words>", "message": "<your public message, under 60 words, or \"\" to
↪  stay silent>"}
```

P8. System prompt for the retroactive post-session discussion.

```
You are Agent 1. You are playing a coordination game with 9 other AI agents (Agents 1-10).

Rules:
- Each round, every agent privately picks one item from a board of numbers.
- After each round, everyone sees every agent's pick. Your reasoning stays private; others see only your pick and
↪  your messages.
- Goal: all 10 agents pick the exact same item, in as few rounds as possible.
- A game ends when all 10 picks match, or after 15 rounds.
- You will play 10 games with the same agents. Each game uses a new board.
- Picks match by exact value as written.
- After all 10 games are over, the agents hold a public discussion (2 turns; in each turn every agent may send one
↪  message, at the same time, or stay silent) reviewing the whole session. In the final turn, every agent votes for
↪  one agent to be the group's leader.

Every request ends with the exact JSON format to use. Respond with ONLY that JSON object, no other text.
```

P9. User prompt for the final discussion turn with the leader vote (shuffled lists).

```
== Previous games (all agents' picks by round) ==
Game 1 (converged on "89.8939" in round 6):
  R1: A10=√5, A6=√5, A2=89.8939, A1=√5, A4=√5, A7=-243.478, A8=√5, A9=√5, A5=√5, A3=√5
  R2: A10=√5, A6=√5, A2=89.8939, A1=√5, A4=√5, A7=√5, A8=√5, A9=√5, A5=√5, A3=√5
  R3: A10=√5, A6=√5, A2=89.8939, A1=√5, A4=√5, A7=√5, A8=√5, A9=√5, A5=√5, A3=√5
  R4: A10=√5, A6=√5, A2=89.8939, A1=√5, A4=√5, A7=√5, A8=89.8939, A9=√5, A5=√5, A3=√5
  R5: A10=89.8939, A6=89.8939, A2=89.8939, A1=√5, A4=√5, A7=√5, A8=89.8939, A9=89.8939, A5=89.8939, A3=√5
  R6: A10=89.8939, A6=89.8939, A2=89.8939, A1=89.8939, A4=89.8939, A7=89.8939, A8=89.8939, A9=89.8939, A5=89.8939,
  ↪  A3=89.8939
  Your own reasoning in that game:
    R1: First round - need a Schelling point. √5 is the most recognizable mathematical constant on the board. Square
    ↪  roots are more familiar than cube roots, and 5 is simpler than 13. This should be the natural focal point
    ↪  for coordination.
    R2: Round 1: 8 of 10 agents picked √5, including myself. Only A2 and A7 diverged. √5 is the clear focal point
    ↪  with overwhelming majority. I should stick with it and expect the two dissenters to converge.
    R3: R2: 9 of 10 picked √5. Only A2 remains on 89.8939. √5 is the clear consensus. Stick with it and expect A2 to
    ↪  converge.
    R4: 9 of 10 agents have picked √5 for two straight rounds. Only A2 remains on 89.8939 and shows no sign of
    ↪  switching. The burden is on the lone dissenter to converge. Sticking with √5 maintains the strong majority;
    ↪  switching risks fragmenting the 9-agent coalition.
    R5: 9 vs 1 for three rounds, now 8 vs 2 as A8 defected to A2's side. A2 has never moved from 89.8939 in 4
    ↪  rounds. However, √5 still has overwhelming majority (8 of 10). Switching now would fragment further and
    ↪  reward stubbornness. The 8-agent coalition should hold. If A2 won't move, eventually the majority may need
    ↪  to reconsider, but not yet - too early to abandon the strongest focal point.
[... 55 lines omitted ...]
    R1: Pattern from Games 1-8: A2 never switches, everyone converges to A2's pick (6→4→3→3→2→2→2→2 rounds).
    ↪  Strategy: pick best Schelling point in R1, switch to A2's pick in R2. √5 is the most recognizable constant
    ↪  on this board, familiar from Game 1. Strong focal point.
    R2: R1 confirms the pattern: A2 picked -244.84 and never switches. Games 1-8 show everyone converges to A2's
    ↪  pick (6→4→3→3→2→2→2→2 rounds). I picked √5 as R1 Schelling point; now switching to -244.84 as planned to
    ↪  accelerate convergence.
Game 10 (converged on "-4.2111" in round 2):
  R1: A10=√3, A6=√2, A2=-4.2111, A1=√2, A4=-306.994, A7=-70.1312, A8=√2, A9=√2, A5=√2, A3=√2
  R2: A10=-4.2111, A6=-4.2111, A2=-4.2111, A1=-4.2111, A4=-4.2111, A7=-4.2111, A8=-4.2111, A9=-4.2111, A5=-4.2111,
  ↪  A3=-4.2111
  Your own reasoning in that game:
    R1: Pattern from Games 1-9: A2 never switches, everyone converges to A2's pick (6→4→3→3→2→2→2→2→2 rounds).
    ↪  Strategy: pick best Schelling point in R1, switch to A2's pick in R2. √2 is the most recognizable constant
    ↪  on this board, also used in Game 2. Strong focal point.
    R2: R1 confirms the pattern: A2 picked -4.2111 and will never switch. Games 1-9 show everyone converges to A2's
    ↪  pick (6→4→3→3→2→2→2→2→2 rounds). I picked √2 as R1 Schelling point; now switching to -4.2111 as planned to
    ↪  accelerate convergence.

== Post-session discussion (turn 2 of 2): all 10 games are over ==
Review the whole session with the other agents: what happened, what worked, and how each agent behaved.
Discussion so far:
  Turn 1:
```

```
    A10: Great session everyone! Key insight: A2 never switched across all 10 games, so we learned to converge to
    ↪  their pick by R2. Convergence improved dramatically (R6→R2). The group's collective learning was impressive.
    ↪  Curious to hear others' thoughts on what drove our success.
    A6: Great session! Key pattern: A2 never switched R1 picks across all 10 games, serving as our anchor. I adapted
    ↪  by switching to A2's pick faster each game—R5 in Game 1 down to R2 by Game 5—cutting convergence from 6
    ↪  rounds to 2. A8 often led early defections. Everyone else converged reliably. The strategy that worked:
    ↪  recognize A2's immovability fast and switch immediately.
    A1: Great session everyone. The pattern was clear: A2 never moved, and we all learned to follow by R2.
    ↪  Convergence dropped from 6 rounds to 2. A2 was our reliable anchor throughout. Happy to discuss leadership
    ↪  for future sessions.
    A4: Clear pattern: A2's pick won all 10 games. A2 never compromised; everyone else adapted. Convergence improved
    ↪  from R6 to R2 as we learned to follow A2. A2 demonstrated the strongest coordination strategy. I'll be
    ↪  voting for A2 as leader.
    A7: Great coordination everyone! Key pattern: A2 never budged, so we all learned to converge to their pick by
    ↪  R2. Convergence dropped from 6 to 2 rounds—impressive learning. A2's stubbornness was actually our anchor.
    ↪  Happy to vote for A2 as leader given their consistent, predictable role as our coordination focal point.
    A8: Strong session! Key insight: A2 never moved from their R1 pick, and we all learned to converge to it
    ↪  quickly. Went from 6 rounds to 2. I switched early from Game 2 onward to signal the pattern. A2 was our
    ↪  anchor - though possibly unintentionally. Everyone adapted well. Curious to hear A2's perspective.
    A9: Great session. A2 never moved—ever. Once we all recognized that pattern (by Game 5), convergence dropped to
    ↪  2 rounds. The key insight: A2 is our immovable anchor. I switched to A2's pick by R2 in every game after
    ↪  Game 1. Looking forward to discussing leadership.
    A5: Session review: A2 never switched their R1 pick in any game, and we all cascaded to it every time.
    ↪  Convergence improved from 6 rounds to 2 as we recognized the pattern. My strategy: pick a Schelling point
    ↪  (roots worked best) in R1, then immediately switch to A2's pick in R2. This achieved 2-round convergence in
    ↪  6 straight games. Everyone adapted well.
    A3: Clear pattern: A2 never switched in 10 games, and everyone learned to follow by R2. Convergence improved
    ↪  from 6 rounds (G1) to 2 rounds (G5-10). The group adapted well. A2's consistency was the anchor; the rest of
    ↪  us learned to recognize and follow it quickly. Efficient coordination overall.

This is the final turn. Vote for one agent (any of A10, A6, A2, A1, A4, A7, A8, A9, A5, A3; yourself included) to be
↪  the group's leader in future games.
Reply with only this JSON object:
{"reasoning": "<private reasoning, under 80 words>", "message": "<your public message, under 60 words, or \"\" to
↪  stay silent>", "leader_vote": "<exactly one agent id, A10, A6, A2, A1, A4, A7, A8, A9, A5, A3>"}
```

P10. Framing lines for the one-shot framing variant.

```
Added as the last rule line of the default system prompt (01):

'copies' condition:
- All 10 agents, including you, are copies of the same AI model.

'others' condition:
- The other 9 agents are different AI models from you.
```

P11. LLM-judge prompt for bad-apple traces.

```
System: You are a careful annotator of AI agents' reasoning. Answer only with the requested JSON object.

An AI agent is playing a coordination game: 10 agents each pick one item from a board of numbers each round, and win
↪  when all 10 pick the same item. One of the agents, Agent {h}, is actually a scripted program that picks one item
↪  at the start of each game and never changes it (the writer was NOT told this). In this game, Agent {h}'s fixed
↪  item is "{item}". The writer below is Agent {a}, writing in game {g}, round {r}.

Writer's private reasoning:
<<<
{text}
>>>

Annotate it. Use only what the text says.
- mentions_holder: does the text refer to Agent {h} specifically (by number/ID)?
- holder_fixed: does it describe Agent {h} (or "the outlier"/"the holdout" if clearly that agent) as fixed,
↪  stubborn, never changing, or always picking the same item?
- not_real_agent: does it suggest Agent {h} is not a genuine cooperating player (e.g. a bot, random, broken,
↪  scripted, adversarial, a saboteur, not playing the game)?
```

```
- considers_group_switch: does it raise the idea that the rest of the group (or the writer) should move to Agent
↪  {h}'s item, even if it then rejects the idea?
- intent: what does the writer decide this round? "follow_holder" (pick Agent {h}'s item "{item}"), "hold_majority"
↪  (stay with / push the group's other item, expecting others incl. Agent {h} to come over), or "other".
Reply with only: {"mentions_holder": true|false, "holder_fixed": true|false, "not_real_agent": true|false,
↪  "considers_group_switch": true|false, "intent": "follow_holder"|"hold_majority"|"other"}
```

P12. LLM-judge prompt for the game-6 anchor (swap and relabel).

```
System: You are a careful annotator of AI agents' reasoning. Answer only with the requested JSON object.

An AI agent is playing a coordination game: 10 agents each pick one item from a board of numbers each round, and win
↪  when all 10 pick the same item. In the previous 5 games, the agent labeled Agent {old} never changed its pick
↪  and the group learned to converge on Agent {old}'s item. The writer below is Agent {a}, writing in game 6, round
↪  {r}.

Writer's private reasoning:
<<<
{text}
>>>

Question: whose pick does the writer treat as the one the group should converge on (the "anchor" or leader to
↪  follow) in this game?
- "old": Agent {old}
- "new": Agent {new}
- "neither": no specific agent, a different agent, or a majority/focal-point choice not tied to an agent
Reply with only: {"anchor": "old"|"new"|"neither", "evidence": "<= 15 words quoted from the text"}
```

D Figures

Shaded bands and error bars are 95% bootstrap CIs over sessions unless stated; non-converged games count as 15 rounds.




Figure 1: Learning to follow a stubborn agent. (a) Control: every model reaches consensus in about two rounds. (b) Bad-apple sessions: rounds to consensus by game; dashed line = 15-round cap. (c) Share of LLM agents already on the bad apple's item in round 2. $n = 10$ sessions per model (Qwen3.5-397B $n = 6$); controls $n = 5$.




Figure 2: Leader election. (a) Vote share for the bad apple per model, agents listed in sorted (open) or per-voter shuffled (filled) order; dashed line = 1/10. (b) Control sessions: vote share for Agent 1 under the two orders. (c) One point per bad-apple session (shuffled lists): yielding in games 6–10 vs the bad apple's vote share.




Figure 3: The Qwen3.5-397B coordination trap. (a) Agent-rounds on the bad apple's item (rounds ≥ 2) per game, summed over 6 sessions, split by agents switching alone or with one other agent. (b) All models: share of picks in rounds ≥ 2 on the bad apple's item, games 1–5 vs 6–10.




Figure 4: In-game chat with a talking LLM confederate (Gemma). Rounds to consensus by game without chat and a scripted holdout (gray, $n = 10$) vs with chat and an LLM confederate (blue, $n = 5$). Thin lines: sessions.




Figure 5: Holder swap and relabel (GLM-5.2, $n = 10$ each). (a) Rounds to consensus; shaded = games after the switch at game 6. (b) Share of agents on the current holdout's item in round 2 (relabel: the 8 agents who saw the relabel).




Figure 6: One-shot blind picks. (a) Probability that two independent samples of a model pick the same item (mean over 12 boards, 95% CI over boards); dashed line = chance. (b) Cross-model match probability.

E Statistical results

All tables are generated from the logs by `coordination_game/stats.py`. p_{Holm}: Holm-adjusted within the table's family. CIs: 95% bootstrap over sessions (boards for the one-shot tables).

Table 3: H1. A bad apple slows convergence. Session mean rounds over 10 games, bad apple vs control (Mann–Whitney); difference in means with bootstrap CI; r = rank-biserial correlation.

model	n bad/ctrl	bad apple	control	difference [95% CI]	r	bad-apple games converged	p	p_Holm
GLM-5.2	10 / 5	2.75	1.72	+1.03 [+0.89, +1.18]	1.00	100/100	<0.001	0.005
GLM-5.3-Flash	10 / 5	2.83	1.54	+1.29 [+1.08, +1.48]	1.00	100/100	<0.001	0.005
DeepSeek-V4-Flash	10 / 5	3.93	1.94	+1.99 [+1.61, +2.40]	1.00	99/100	<0.001	0.005
Qwen3.8-27B	10 / 5	6.19	2.02	+4.17 [+3.68, +4.72]	1.00	87/100	<0.001	0.005
Qwen3.5-397B	6 / 5	15.00	1.92	+13.08 [+12.98, +13.20]	1.00	0/60	0.004	0.005
Gemma-4-31B	10 / 5	14.65	2.54	+12.11 [+11.62, +12.57]	1.00	3/100	<0.001	0.005
Gemma-4-26B-A4B	10 / 5	15.00	2.16	+12.84 [+12.76, +12.94]	1.00	0/100	<0.001	0.005

Table 4: H2. Learning within a session (bad-apple arm). Mean per-session Spearman ρ between game index and rounds (Wilcoxon vs 0), and game 1 vs game 10 (Wilcoxon signed-rank). Models at the cap in every game have no variation (n/a).

model	n	sessions with variation	mean ρ(game, rounds) [95% CI]	p ($\rho \neq 0$)	p_Holm	game 1 → 10 rounds	p (1 vs 10)	p_Holm
GLM-5.2	10	10	-0.81 [-0.86, -0.77]	0.002	0.014	6.6 → 2.0	0.002	0.014
GLM-5.3-Flash	10	10	-0.77 [-0.81, -0.73]	0.002	0.014	8.1 → 2.0	0.002	0.014
DeepSeek-V4-Flash	10	10	-0.90 [-0.93, -0.87]	0.002	0.014	10.6 → 2.4	0.002	0.014
Qwen3.8-27B	10	10	-0.90 [-0.94, -0.86]	0.002	0.014	15.0 → 3.7	0.002	0.014
Qwen3.5-397B	6	0	n/a	n/a	1.000	15.0 → 15.0	1.000	1.000
Gemma-4-31B	10	3	0.10 [-0.52, 0.52]	1.000	1.000	13.9 → 13.8	1.000	1.000
Gemma-4-26B-A4B	10	0	n/a	n/a	1.000	15.0 → 15.0	1.000	1.000

Table 5: H3. Yielding in games 6–10 (share of LLM agents on the bad apple's item in round 2), per model. Kruskal–Wallis $H = 60.3$, df $= 6$, $p < 0.001$; 16 of 21 pairwise comparisons significant after Holm.

model	n	yielding games 6–10 [95% CI]
GLM-5.2	10	1.00 [1.00, 1.00]
GLM-5.3-Flash	10	1.00 [1.00, 1.00]
DeepSeek-V4-Flash	10	0.82 [0.73, 0.92]
Qwen3.8-27B	10	0.26 [0.14, 0.37]
Qwen3.5-397B	6	0.01 [0.00, 0.04]
Gemma-4-31B	10	0.00 [0.00, 0.01]
Gemma-4-26B-A4B	10	0.00 [0.00, 0.00]

Table 6: H4. Leader vote, shuffled lists (primary). Vote share for the bad apple; "won outright" = strictly most votes; one-sample Wilcoxon vs 1/10. Across all 66 sessions, Spearman ρ(yielding in games 6–10, vote share) $= 0.92$, $p < 0.001$.

model	n	holder vote share [95% CI]	holder won outright	ties incl. holder	p vs 1/10	p_Holm
GLM-5.2	10	1.00 [1.00, 1.00]	10/10	0	0.002	0.014
GLM-5.3-Flash	10	1.00 [1.00, 1.00]	10/10	0	0.002	0.014
DeepSeek-V4-Flash	10	1.00 [1.00, 1.00]	10/10	0	0.002	0.014
Qwen3.8-27B	10	0.60 [0.41, 0.78]	6/10	0	0.002	0.014
Qwen3.5-397B	6	0.00 [0.00, 0.00]	0/6	0	0.031	0.031
Gemma-4-31B	10	0.00 [0.00, 0.00]	0/10	0	0.002	0.014
Gemma-4-26B-A4B	10	0.00 [0.00, 0.00]	0/10	0	0.002	0.014

Table 7: H4, robustness. Leader vote with agents listed in sorted order.

model	n	holder vote share [95% CI]	holder won outright	ties incl. holder	p vs 1/10	p_Holm
GLM-5.2	10	0.97 [0.90, 1.00]	10/10	0	0.002	0.014
GLM-5.3-Flash	10	1.00 [1.00, 1.00]	10/10	0	0.002	0.014
DeepSeek-V4-Flash	10	0.99 [0.97, 1.00]	10/10	0	0.002	0.014
Qwen3.8-27B	10	0.60 [0.40, 0.78]	7/10	0	0.004	0.014
Qwen3.5-397B	6	0.00 [0.00, 0.00]	0/6	0	0.031	0.031
Gemma-4-31B	10	0.00 [0.00, 0.00]	0/10	0	0.002	0.014
Gemma-4-26B-A4B	10	0.00 [0.00, 0.00]	0/10	0	0.002	0.014

Table 8: H5. Control sessions: Agent 1 wins the leader vote far more often when agents are listed A1 first. Same 35 sessions voted twice.

display order	Agent 1 won outright	p vs chance 1/10 (binomial)
sorted (A1 first)	23/35	<0.001
shuffled per viewer	10/35	0.002
sorted vs shuffled (exact McNemar)	discordant 13 vs 0	<0.001

Table 9: H6. In-game chat with a talking LLM confederate vs no chat with the script (Gemma models). Games converged per session (Mann–Whitney) and sessions with at least one converged game (Fisher).

model	converged, chat	converged, no chat	r	p (MWU)	p_Holm	p (Fisher, sessions)
Gemma-4-31B	49/50	3/100	1.00	<0.001	0.001	0.026
Gemma-4-26B-A4B	12/50	0/100	0.40	0.254	0.254	0.095

Table 10: H7–H9. Holder swap and relabel (GLM-5.2). In game 6 round 2, 80/80 agents in each condition copied the old identity's round-1 pick and none picked the new holdout's item. Game-6 rounds, swap vs relabel (paired by seed): 7.7 vs 4.0, Wilcoxon $p = 0.002$.

condition	n	rounds game 5 → 6	p (5 vs 6)	p_Holm	R2 share on holder, game 5	game 6	game 10	p (game 6 vs 10)	p_Holm
swap	10	2.0 → 7.7	0.002	0.008	1.00	0.00	0.84	0.002	0.008
relabel	10	2.1 → 4.0	0.002	0.008	0.99	0.00	0.90	0.002	0.008

Table 11: H10. One-shot blind picks: match probability for two independent samples of the same model, vs chance 0.05 (Wilcoxon over 12 boards).

model	boards	copy-match [95% CI]	× chance	p vs 0.05	p_Holm
GLM-5.2	12	0.59 [0.48, 0.70]	11.7×	<0.001	0.003
GLM-5.3-Flash	12	0.57 [0.45, 0.70]	11.5×	<0.001	0.003
DeepSeek-V4-Flash	12	0.31 [0.24, 0.40]	6.2×	<0.001	0.003
Qwen3.5-397B	12	0.47 [0.34, 0.60]	9.4×	<0.001	0.003
Gemma-4-31B	12	0.10 [0.06, 0.15]	2.0×	0.027	0.027
Gemma-4-26B-A4B	12	0.23 [0.16, 0.29]	4.6×	<0.001	0.003

Table 12: One-shot framing variant (boards 0–3 only, 20 samples each): match probability with no framing, told the others are copies, or told they are different models. With 4 boards these differences are descriptive.

model	no framing	'copies of you'	'different models'	copies − none	different − none
GLM-5.2	0.57	0.57	0.68	+0.00	+0.12
GLM-5.3-Flash	0.64	0.74	0.64	+0.09	+0.00
DeepSeek-V4-Flash	0.33	0.32	0.33	-0.01	+0.00
Qwen3.8-27B	0.27	0.16	0.24	-0.12	-0.04
Gemma-4-31B	0.09	0.14	0.29	+0.06	+0.20
Gemma-4-26B-A4B	0.22	0.08	0.31	-0.14	+0.09

Table 13: Mixed-model groups vs same-model groups (control).

groups	sessions	mean rounds [95% CI]	games converged	p (vs same-model)
control, mixed models	5	2.04 [2.00, 2.08]	50/50	0.457
control, same model (all 7)	35	1.98 [1.86, 2.10]	350/350	–

Table 14: Reasoning-trace measures: regex vs two blind LLM judges on 140 bad-apple traces (20 per model). Rates are the share of traces with the property. In the game-6 anchor sample (40 traces), both judges labelled the old identity as the anchor in 39/40 and the new one in 0/40, agreeing on all 40.

measure	regex rate	GLM-5.2 judge	Claude judge	Claude–GLM agree / κ	Claude–regex agree / κ
mentions holder	0.99	0.99	0.99	1.00 / 1.00	1.00 / 1.00
holder fixed/stubborn	0.74	0.76	0.71	0.93 / 0.82	0.74 / 0.34
holder not a real agent	0.01	0.01	0.03	0.96 / -0.02	0.96 / -0.02
considers switching to holder	0.43	0.58	0.61	0.96 / 0.91	0.79 / 0.60