



QS MOTOR LTD

Phone: 0086-188-0166-2699

Email: sales@qsmotor.com

Website: www.qsmotor.com

Contact: Harry Zhou

4000W V3 Mid Drive Motor (Air-Cooled Version, 19:45 Reduction Gear)



Motor Size	Motor Diameter	162mm
	Motor Length	242mm
	Wheel Material	Aluminum
	Gear Box	19:45 Reduction Gear Box
	Shaft / Axle	Spline Shaft
Motor Phase	Motor Type	Brushless DC IPM PMSM Motor
	Number of Motor Phase	3
	Cross Section of Cable	20 Square Millimeter
	Poles	5 Pairs of Poles
Motor Power	Rated Power	4000W
	Maximum	15KW (Sometimes 20KW)
	Rated Voltage	72V
	Continuous Current	60A
	Maximum Current	120A (200A in 30 seconds)
	Maximum Efficiency	85-91.6%
	Maximum Torque	60N.m to 80N.m
	Maximum Torque	more than 140N.m after reduction
	Rotating Speed	3800rpm to 6000rpm
Other	Waterproof Grade	IP54
	Max. Working Temperature	70 °C (peak 120°C in 5 - 10 second)
	Color	Black
	Net Weight	14.2kg
	Unit Packing	34x34x34cm/carton

Drawing of 4000W V3 Mid Drive Motor

