

Mobilisation Information Request

Information required from the Lead Appointed Party and the Appointing Party before mobilisation can complete

Document reference	KUT-SMB-ZZ-ZZ-RP-Z-0004
Revision	P01
Status / suitability	DRAFT — not issued (S0, work in progress)
From	Mayanja Davis, Information Management
To	[FILL — name], Symbion Consulting Group Studios (Lead Appointed Party)
Copied to	[FILL]
Date	[FILL]
Response requested by	[FILL — suggest five working days]

Not yet issued through the Common Data Environment. Uncontrolled when printed.

Contents

1 Purpose.....	2
2 Items that cannot be corrected later.....	3
2.1 Site survey and coordinate system.....	3
2.2 Classification of restricted information	3
3 Items required before the kickoff.....	4
3.1 Originator code register	4

3.2 Standards hierarchy	4
3.3 Level and grid register	4
3.4 Software and versions	5
3.5 Symbion standards and this role	5
4 Items for the kickoff workshop	6
5 Summary and response	7

1 Purpose

The mobilisation set is drafted and ready to issue: the BIM Execution Plan, the Project Delivery Playbook, the Document Control Standard and the Master Information Delivery Plan. Eleven items in Section 15.1 of the plan must be settled before the kickoff, because they determine the project template every appointed party starts from. Training a team on standards that are not yet decided produces a team that has to be retrained, and models that have to be redone.

Those eleven items are asked for here as nine requests — several of them are answered by the same document, and asking twice for one answer wastes your time. Section 5 lists the nine and what each unblocks. Where an answer sits with the Appointing Party rather than the Lead Appointed Party, it says so; nothing here is a decision for information management to take alone.

TWO ITEMS THAT CANNOT BE CORRECTED LATER

Two items have consequences that cannot be undone later and are marked accordingly: the site survey, which sets the coordinate system, and the classification of restricted information. Both are dealt with in Section 2.

2 Items that cannot be corrected later

2.1 Site survey and coordinate system

The shared coordinate system is established once from the site survey and is then locked. It is the only setting on this project that cannot be corrected without re-issuing every model and every drawing produced up to that point.

Required	Detail
Site survey	Surveyor's drawing and data, with the vertical datum and the site benchmark stated
Coordinate system	The projection or site grid to be used
Setting-out point	The agreed project base point, with easting, northing and elevation
True north	Angle and the direction in which it is measured

On receipt, a shared coordinates seed model is issued to every appointed party, and all models acquire their coordinates from it rather than having them entered by hand.

PRIORITY

This is the longest lead item in mobilisation. If the survey is not yet commissioned, that is the critical path and should be treated ahead of everything else in this request. Modelling can begin without several of the items below; it cannot sensibly begin without this one.

2.2 Classification of restricted information

The project is a temple, and some spaces and systems will carry sensitivities that ordinary project information does not. Access restrictions must be applied before information is created and federated, because a restriction cannot be applied retrospectively to information already shared across the team.

Required from the Appointing Party	Detail
Restricted spaces	Which spaces, if any, are restricted, and to whom
Restricted systems	Whether security, access control and CCTV information is to be separated from the general federated model
Modelling extent	Whether any space is to be modelled in outline only, or not at all, and by whom
Publication	Whether site photography and the use of project imagery are permitted, restricted or prohibited
Confidentiality	Any non-disclosure requirements to be flowed down to appointed parties

AN INTERIM ANSWER IS SUFFICIENT

If the Appointing Party has not yet issued a position, an interim instruction is enough to start: name the categories that are to be treated as restricted, and the detail can follow.

3 Items required before the kickoff

3.1 Originator code register

The originator identifies the organisation that produced a container. It is the second field of every file, model, drawing and document name on the project, so no container can be numbered until the register exists.

Required	Detail
The register	A three-character code for every appointed party, including sub-consultants
Reserved codes	Codes reserved now for the contractor and specialist subcontractors, so that Stage 3.1 does not reopen the numbering
Allocation	Who allocates a code to a party joining mid-project, and how
Confirmation	That three characters is the convention. The compliance check enforces exactly three; a register of three-letter organisation codes therefore needs no change

A POINT WORTH CONFIRMING

The originator is the organisation, not the discipline. Where one organisation produces information for two disciplines it uses one originator code and two role codes; where two organisations work in the same discipline they use two originator codes. Coding originators by discipline duplicates the role field and fails the first time either case arises. `SMB` has been used provisionally for information management pending the register.

3.2 Standards hierarchy

The Appointing Party standards package is derived from United States practice; the building is constructed in Uganda under Ugandan law. Three layers therefore apply and their precedence must be stated before any discipline begins calculation.

Required	Detail
Confirmation of precedence	That statutory Ugandan requirements are the floor and cannot be waived; that an Appointing Party standard governs where it is stricter; and that a genuine conflict requires a written derogation
Derogation authority	Who approves a derogation where an Appointing Party standard conflicts with Ugandan statute, and by what route
Applicable statutory list	Confirmation of the statutory instruments that apply, so the reconciliation schedule is complete
Exchange information requirements	The Appointing Party's requirements document, if it has been issued and not yet passed on

Section 4.1.3 of the BIM Execution Plan opens a reconciliation schedule with twelve rows already identified. The electrical row is the one that cannot be resolved by preference: Uganda operates at 240 V single phase and 415 V three phase at 50 Hz, with BS 7671 protection practice, while the United States basis assumes 120/208 V at 60 Hz with different conductor sizing. Confirmation that the local standard governs for electrical design would close that row immediately.

3.3 Level and grid register

Required	Detail
Levels	Level names and reduced levels, and which volumes each applies to
Grids	The grid naming convention
Confirmation	That the volumes are correct and complete: Temple, Meetinghouse, Housing and ancillary, Grounds building, Utility building, Guard house, Site-wide and external works

Level codes appear in every container name, so a level renamed after issue invalidates every reference to it.

3.4 Software and versions

Required	Detail
Authoring version	One Revit version for the whole project, for the duration of a stage. An upgraded model cannot be reopened in the earlier version
Coordination	The Navisworks version to be used
Other platforms	Versions for review, specification and building management platforms
Confirmation	That every appointed party can meet the agreed versions

3.5 Symbion standards and this role

Required	Detail
House standards	Whether Symbion has existing BIM standards, templates or naming conventions that should prevail over the drafts in the issued pack. Where a convention already exists and its teams know it, that convention should be adopted
Role and title	The role title and organisation to appear on the issued documents, and the reporting line
Authority	Confirmation of the authority to return information that does not meet the requirements, and the escalation route where a party disputes it

4 Items for the kickoff workshop

These do not block the kickoff; they are settled during it, and are listed so the right people attend and arrive prepared.

Item	Who must be present	Reference
Clash matrix — which discipline models are tested against which	All discipline leads	BEP 7.3.1
Clash tolerances and clearances, including maintenance access	MEP and structural leads, with manufacturer data for major plant	BEP 7.3.2
Volume and workset convention — per-volume worksets, or one model per volume	All discipline leads	BEP 4.5
Model health thresholds — file size, warning counts	All discipline leads	BEP 10.2
Task Information Delivery Plans — returns and dates	Task Team Managers	BEP 9
Capability and capacity — confirmation of named individuals and time	Task Team Managers	BEP 12.1
Sheet number banding — the first digit of a sheet number carries meaning. Three schemes were in use across earlier drafts and one must be adopted	All discipline leads	Document Control Standard 3
FF&E catalogue scope — which categories are procured and specified through the catalogue, which sets what must be linked at handover	Interior designer, Appointing Party	BEP 15.2 item 18a

ONE THAT BLOCKS DRAWING PRODUCTION

No sheet numbers can be allocated until the banding is settled. A sheet renumbered after issue invalidates every drawing reference, every transmittal and every register row that names it. It is a five-minute decision at the kickoff and an expensive one afterwards.

ONE TO SETTLE IN THE ROOM

The clash tolerances are the item most often deferred and most expensive to defer. Until they are agreed, clash detection reports geometric collisions only, and nothing about access or maintainability is being checked at all. They are required before the first coordination cycle of Stage 2.2.

5 Summary and response

#	Item	From	Blocks	Received
1	Site survey and coordinate system	Lead Appointed Party	All modelling. Longest lead item	[]
2	Restricted information classification	Appointing Party	Modelling of the affected areas	[]
3	Originator code register	Lead Appointed Party	All container numbering	[]
4	Standards hierarchy and derogation authority	Lead / Appointing Party	All discipline calculation	[]
5	Level and grid register	Lead Appointed Party	Project template, container numbering	[]
6	Software and versions	All parties	Project template	[]
7	Symbion house standards	Lead Appointed Party	Project template and the issued pack	[]
8	Role title and authority	Lead Appointed Party	Issue of the pack	[]
9	Exchange information requirements	Appointing Party	Confirmation that the pack responds to them	[]

An interim or partial answer is more useful than a complete one that arrives later. Items 1, 2 and 3 are the ones with consequences that compound: the survey because everything is positioned from it, the classification because it cannot be applied retrospectively, and the register because every container carries it.

End of document