

FirstRevenue

Backend Database Spec

Everything the backend needs to store for the FirstRevenue app — every table, column, type, relationship, and seed data set. Written from the frontend data layer so a backend developer can build the API without guessing.

Date: September 2026

Frontend stack: React 19 + TypeScript + Zustand + Vite

Source files: `src/data/types.ts`, `src/store/useApp.ts`, `src/data/*.ts`

Table of Contents

1. Overview
2. Users & Onboarding
3. Paths, Lessons & Resources (static content)
4. Day Plans & Mission Tasks (30-day program)
5. Prospects & CRM
6. Deals & Outreach Templates
7. Coach & Chat
8. Achievements, Notifications & Check-ins
9. Subscriptions, Settings & Progress
10. Entity Relationships
11. Static vs Dynamic Data
12. Enums & Allowed Values

1. Overview

This document maps every piece of data the FirstRevenue frontend uses to database tables a backend developer can implement. The frontend currently stores everything in `localStorage` via Zustand — no API, no backend.

Who this is for:

A backend developer building the REST/GraphQL API and database (Postgres, Supabase, Firebase, etc.) so the frontend can switch from local storage to real persistence.

What's covered:

- 20+ database tables with every column, type, and constraint
- All foreign key relationships
- Enums and allowed values
- Which data is static content (seed once) vs user-generated (CRUD via API)
- The full entity relationship map

Current state: one big AppState object persisted under `localStorage['firstrevenue:v1']`. Every table below corresponds to a field or nested array in that state.

2. Users & Onboarding

users table

One row per registered user. Created at signup.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
name	text	no	Full name
email	text	no	Unique
password_hash	text	no	Hashed password
age	integer	yes	Optional
role	text	yes	From onboarding: Student, Employee, Freelancer, Creator, Entrepreneur, Job seeker, Other
skills	text[]	no	Default empty array. From onboarding multi-select
experience	text	yes	None, Beginner, Some experience, Experienced
budget	text	yes	\$0, \$25, \$50, \$100, \$250+
time	text	yes	15 minutes, 30 minutes, 1 hour, 2 hours, 3+ hours
goal	text	yes	\$50, \$100, \$250, \$500, \$1,000+
goal_amount	integer	no	Default 500. Parsed numeric value of goal
confidence	text	yes	From onboarding comfort question
current_path_id	text	no	FK to paths.id. Default 'clipping'
joined_at	timestamptz	no	Default now()
created_at	timestamptz	no	Default now()
updated_at	timestamptz	no	Default now()

onboarding_answers table

Raw onboarding responses, one row per user. All 12 answers stored before path recommendation.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id, unique
name	text	no	First name entered

Column	Type	Null?	Notes
role	text	no	What best describes you
skills	text[]	no	Multi-select from 12 options
experience	text	no	Online earning experience
time	text	no	Daily time commitment
budget	text	no	Starting budget
comfort	text	no	Comfort talking to clients
interest	text	no	Creating content OR Helping businesses
goal	text	no	Income goal
blocker	text	no	Main obstacle
learning	text	no	Learning preference
commitment	text	no	Commitment level
recommended_path	text	no	Path the algorithm recommended
match_score	integer	no	0–100 match score
chosen_path	text	no	Path the user actually picked
completed_at	timestampz	no	When onboarding finished

3. Paths, Lessons & Resources

These tables hold content that doesn't change per user. Seed them once at deploy.

paths table

2 rows. The two 30-day programs users choose from.

Column	Type	Null?	Notes
id	text	PK	'clipping' or 'gbp'
slug	text	no	URL segment, e.g. 'short-form-clipping'
name	text	no	Display name
tagline	text	no	Short pitch
emoji	text	no	Path emoji
hue	integer	no	Gradient color hue
description	text	no	Long description
difficulty	text	no	Beginner, Intermediate, or Advanced
objective	text	no	30-day objective
service	text	no	What the user sells
typical_price	text	no	E.g. '\$150–\$250 per clip pack'
skills	text[]	no	Skills learned on this path
first_tasks	text[]	no	First things to do
workflow	text[]	no	Service delivery steps

path_weeks table

8 rows (4 per path). Weekly structure within each path.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
path_id	text	no	FK to paths.id
week	integer	no	1–4
title	text	no	Week theme
focus	text[]	no	Focus areas for the week

path_tools table

Recommended tools per path (4–6 per path).

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
path_id	text	no	FK to paths.id
name	text	no	Tool name
purpose	text	no	What it's used for
cost	text	no	Free, Freemium, or price

lessons table

74 rows: 30 clipping + 30 GBP + 14 shared.

Column	Type	Null?	Notes
id	text	PK	E.g. 'clip-01', 'gbp-01', 'gen-01'
title	text	no	Lesson title
category	text	no	One of 11 LessonCategory values (see Enums)
path	text	no	'clipping', 'gbp', or 'all'
duration	text	no	Display duration, e.g. '12:48'
minutes	integer	no	Numeric duration
hue	integer	no	Thumbnail gradient color
summary	text	no	Lesson summary
learn	text[]	no	3 learning points
takeaways	text[]	no	3 actionable takeaways
resource_ids	text[]	no	FK array to resources.id
instructor	text	no	Fictitious instructor name

resources table

23 rows. Downloadable templates, guides, checklists, etc.

Column	Type	Null?	Notes
id	text	PK	E.g. 'res-cold-outreach'

Column	Type	Null?	Notes
title	text	no	Resource title
type	text	no	Template, Tool, Guide, Checklist, Script, or Calculator
path	text	no	'clipping', 'gbp', or 'all'
description	text	no	Short description
minutes	integer	no	Reading time
link	text	yes	In-app route (only 3 resources have this)

resource_sections table

Content body of each resource, broken into headed sections.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
resource_id	text	no	FK to resources.id
sort_order	integer	no	Display order
heading	text	no	Section heading
body	text[]	no	Paragraphs in the section

4. Day Plans & Mission Tasks

Static content. 30 days per path = 60 total day plans, each with 3–5 tasks.

day_plans table

60 rows (30 per path). Each row is one day's mission.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
path_id	text	no	FK to paths.id
day	integer	no	1–30
week	integer	no	1–4
theme	text	no	E.g. 'Build Your Prospect List'
mission_title	text	no	Main mission description
goal	text	no	E.g. 'Find 10 potential clients'
minutes	integer	no	Estimated time
difficulty	text	no	Beginner, Intermediate, or Advanced
xp	integer	no	XP reward: 100, 150, or 300
lesson_id	text	no	FK to lessons.id

Unique constraint: (path_id, day) — one plan per day per path.

mission_tasks table

~240 rows total. Individual tasks within each day's mission.

Column	Type	Null?	Notes
id	text	PK	E.g. 'c01-t1' (clipping day 1 task 1)
day_plan_id	uuid	no	FK to day_plans.id
sort_order	integer	no	Display order within the day
title	text	no	Task title
description	text	no	Task instructions
resource_id	text	yes	FK to resources.id (optional linked resource)

5. Prospects & CRM

User-generated data. The prospect pipeline is the core of the app. 26 seed records for the demo user.

prospects table

One row per potential client the user tracks.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
path_id	text	no	FK to paths.id
name	text	no	Contact person name
business	text	no	Brand or business name
platform	text	no	YouTube, Podcast, Twitch, TikTok, Instagram, X, Google Maps, etc.
audience	text	no	E.g. '52K subscribers'
handle	text	no	@handle or email
about	text	no	Description of the prospect
status	text	no	ProspectStatus enum (see Enums)
last_contact	timestampz	yes	Last time user contacted them
follow_up	timestampz	yes	Scheduled follow-up date
value	integer	no	Potential deal value in dollars
created_at	timestampz	no	Default now()
updated_at	timestampz	no	Default now()

prospect_notes table

User notes attached to prospects.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
prospect_id	uuid	no	FK to prospects.id (cascade delete)
text	text	no	Note content
date	timestampz	no	Default now()

contact_events table

Timeline of all contact activity with a prospect.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
prospect_id	uuid	no	FK to prospects.id (cascade delete)
kind	text	no	message, reply, call, status, note, or followup
text	text	no	Event description
date	timestampz	no	Default now()

gbp_audits table

Google Business Profile audit data. Only for GBP-path prospects.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
prospect_id	uuid	no	FK to prospects.id, unique (cascade delete)
rating	numeric(2,1)	no	Google rating, e.g. 3.2
reviews	integer	no	Number of reviews
category	text	no	Business category
city	text	no	City
problems	text[]	no	List of GBP issues found
service	text	no	Recommended service to offer

6. Deals & Outreach Templates

deals table

Revenue pipeline. Deals are auto-created/updated when prospect status changes. 11 seed records.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
prospect_id	uuid	yes	FK to prospects.id (null for manual deals)
path_id	text	no	FK to paths.id
client	text	no	Client name
service	text	no	Service description
amount	integer	no	Dollar amount
status	text	no	Potential, Booked, or Collected
date	timestamptz	no	Deal date
created_at	timestamptz	no	Default now()

Important business logic — when prospect status changes:

- Status → Interested or Negotiating: auto-create a deal with status Potential
- Status → Won: update deal to Booked
- Status → Lost: delete the deal

outreach_templates table

12 static built-in templates + user-created custom templates.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	yes	FK to users.id. Null for built-in templates
path	text	no	'clipping', 'gbp', or 'all'
title	text	no	Template name
stage	text	no	First touch, Follow-up, Reply, or Closing
body	text	no	Template text with placeholders
is_custom	boolean	no	Default false. True for user-created

Column	Type	Null?	Notes
created_at	timestampz	no	Default now()

7. Coach & Chat

coach_conversations table

Each conversation with the AI coach. 10 seed records for demo.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
title	text	no	Conversation title (auto-generated from first message)
created_at	timestampz	no	Default now()
updated_at	timestampz	no	Updated on each new message

chat_messages table

Messages within coach conversations.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
conversation_id	uuid	no	FK to coach_conversations.id (cascade delete)
sender	text	no	'user' or 'coach'
text	text	no	Message content
date	timestampz	no	Default now()

coach_replies table

15 rows (static). Canned responses the mock coach selects from. Replace with a real AI integration later.

Column	Type	Null?	Notes
id	text	PK	E.g. 'objection', 'follow-up'
keywords	text[]	no	Keywords to match against user input
text_clipping	text	yes	Response text for clipping path
text_gbp	text	yes	Response text for GBP path
text_all	text	yes	Fallback response for either path
follow_ups	text[]	no	Suggested follow-up questions

Note: The frontend currently uses keyword matching to pick a response. When you add a real AI backend, replace this table with an API call to an LLM. The follow_ups field shows suggested prompts the user can tap.

8. Achievements, Notifications & Check-ins

achievements table

12 rows (static). Milestones users can unlock.

Column	Type	Null?	Notes
id	text	PK	E.g. 'first-step', '3-day-streak'
title	text	no	Achievement title
description	text	no	What you did to earn it
emoji	text	no	Display emoji
metric	text	no	Which stat to check (see AchievementMetric enum)
target	integer	no	Threshold to unlock
is_money	boolean	no	Default false. True if the metric is currency

Current achievements:

- First Step (1 mission), 3-Day Streak (3), 7-Day Streak (7), Mission Master (15 missions)
- First Prospect (1), 10 Prospects (10), First Reply (1 reply), First Client (1 client)
- \$100 Club (100 revenue), \$500 Club (500 revenue)
- Lesson Lover (10 lessons), 30-Day Finisher (30 daysCompleted)

user_achievements table

Join table. One unlock per achievement per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
achievement_id	text	no	FK to achievements.id
unlocked_at	timestampz	no	Default now()

Unique constraint: (user_id, achievement_id).

notifications table

System-generated notifications. 12 seed records.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
emoji	text	no	Notification icon
title	text	no	Notification title
body	text	no	Notification body
link	text	no	In-app route to navigate to
is_read	boolean	no	Default false
created_at	timestampz	no	Default now()

Notifications are generated on:

Mission complete, streak milestones (3/7/14/30 days), weekly check-in reminders, prospect replies, deal won, payment collected, path switch.

weekly_checkins table

Weekly self-reflection form. One per week per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
week	integer	no	1–4
accomplished	text	no	What the user accomplished
difficult	text	no	What was hardest
prospects	integer	no	Self-reported prospects contacted
replies	integer	no	Self-reported replies received
made_money	boolean	no	Did the user earn money this week
improve	text	no	What to improve next week
created_at	timestampz	no	Default now()

9. Subscriptions, Settings & Progress

subscriptions table

One row per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id, unique
status	text	no	none, active, or expired
plan	text	yes	monthly or yearly. Null when status is none
renews_at	timestampz	yes	Next renewal date. Null when status is none
created_at	timestampz	no	Default now()
updated_at	timestampz	no	Default now()

Plans: monthly (\$19.99/month), yearly (\$149.99/year, save 37%). 7 premium benefits unlocked.

user_settings table

One row per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id, unique
push_enabled	boolean	no	Default true
daily_reminders	boolean	no	Default true
weekly_checkins	boolean	no	Default true
coach_messages	boolean	no	Default true
theme	text	no	Default 'dark'. Options: dark, light
language	text	no	Default 'English'
reminder_time	text	no	Default '9:00 AM'
offline_mode	boolean	no	Default false (prototype only)

user_progress table

Tracks where the user is in each path. One row per path per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
path_id	text	no	FK to paths.id
current_day	integer	no	Default 1. Which day the user is on (1–30)

Unique constraint: (user_id, path_id).

completed_days table

Which days have been completed per user per path.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
path_id	text	no	FK to paths.id
day	integer	no	Day number (1–30)
completed_at	timestampz	no	Default now()

Unique constraint: (user_id, path_id, day).

task_completions table

Per-task completion state.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
task_id	text	no	FK to mission_tasks.id
state	text	no	'done' or 'skipped'
note	text	yes	Optional task note from the user
completed_at	timestampz	no	Default now()

Unique constraint: (user_id, task_id).

user_lessons table

Tracks lesson interactions per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
lesson_id	text	no	FK to lessons.id
completed	boolean	no	Default false
saved	boolean	no	Default false
last_viewed_at	timestampz	yes	Most recent view

Unique constraint: (user_id, lesson_id).

user_resources table

Saved/bookmarked resources per user.

Column	Type	Null?	Notes
id	uuid	PK	Auto-generated
user_id	uuid	no	FK to users.id
resource_id	text	no	FK to resources.id
saved_at	timestampz	no	Default now()

Unique constraint: (user_id, resource_id).

user_stats table

Aggregate stats per user. Can be computed or cached.

Column	Type	Null?	Notes
user_id	uuid	PK	FK to users.id
xp	integer	no	Default 0. Total experience points
streak	integer	no	Default 0. Current consecutive days
longest_streak	integer	no	Default 0. All-time record
active_days	text[]	no	Default empty. Array of day keys (YYYY-MM-DD)
recent_searches	text[]	no	Default empty. Last 10 search queries
updated_at	timestampz	no	Default now()

Level formula: $\text{level} = \text{floor}(xp / 400) + 1$, progress to next level = $(xp \% 400) / 400$

10. Entity Relationships

All foreign key links between tables. Every user-scoped table has `user_id` FK to `users.id`.

Key relationships:

- `users.current_path_id` → `paths.id` (which path the user is actively on)
- `day_plans.lesson_id` → `lessons.id` (one lesson per day)
- `mission_tasks.resource_id` → `resources.id` (optional linked resource)
- `lessons.resource_ids` → `resources.id` (array of related resources)
- `deals.prospect_id` → `prospects.id` (deal tied to a prospect, nullable for manual deals)
- `user_progress` unique on (`user_id`, `path_id`) — one progress row per path
- Cascade deletes: deleting a prospect should cascade to its notes, contact events, GBP audit, and linked deals

Relationship map (tables grouped by domain):

Parent		Children / FK targets
users	→	onboarding_answers, subscriptions, user_settings, user_progress, user_stats, prospects, deals, notifications, coach_conversations, outreach_templates, weekly_checkins, completed_days, task_completions, user_lessons, user_resources, user_achievements
paths	→	path_weeks, path_tools, day_plans, user_progress
day_plans	→	mission_tasks; lesson_id → lessons
mission_tasks	→	resource_id → resources (optional)
lessons	→	resource_ids → resources
resources	→	resource_sections
prospects	→	prospect_notes, contact_events, gbp_audits, deals
coach_conversations	→	chat_messages
achievements	→	user_achievements

11. Static vs Dynamic Data

Static content — seed once at deploy, read-only API

These tables hold content that is the same for every user. Seed them from the frontend's `src/data/*.ts` files.

Table	Rows	Source file
paths	2	src/data/paths.ts
path_weeks	8	src/data/paths.ts
path_tools	~10	src/data/paths.ts
lessons	74	src/data/lessons/*.ts
resources	23	src/data/resources.ts
resource_sections	~70	src/data/resources.ts
day_plans	60	src/data/missions/*.ts
mission_tasks	~240	src/data/missions/*.ts
achievements	12	src/data/achievements.ts
coach_replies	15	src/data/coach.ts
outreach_templates (built-in)	12	src/data/messages.ts

Dynamic data — full CRUD, user-scoped API

Every query must be scoped to the authenticated `user_id`.

Table	Created by	Notes
users	Signup	One row per user
onboarding_answers	Onboarding flow	One row per user
subscriptions	Payment flow	One row per user
user_settings	Settings screen	One row per user
user_progress	Onboarding complete	One row per path per user
completed_days	Mission complete	Grows as user progresses
task_completions	Checking off tasks	One per task per user
user_lessons	Viewing/saving	One per lesson per user
user_resources	Saving resources	One per resource per user

Table	Created by	Notes
user_stats	Every action	One row, updated frequently
user_achievements	Achievement unlocked	One per achievement per user
prospects	Adding prospects	Core CRM data
prospect_notes	Adding notes	Nested under prospects
contact_events	Logging outreach	Nested under prospects
gbp_audits	Adding GBP prospects	One per GBP prospect
deals	Auto + manual	Revenue pipeline
notifications	System events	Generated server-side
coach_conversations	Starting chats	User chat history
chat_messages	Sending messages	Nested under conversations
outreach_templates (custom)	User-created	is_custom = true
weekly_checkins	Weekly form	One per week per user

Seed data for demo account

The demo user (Alex Carter) is pre-loaded with data so the app looks populated.

Data	Count	Source
Prospects	26 (18 clipping + 8 GBP)	src/data/prospects.ts
Deals	11 (1 collected, 1 booked, 9 potential)	src/data/revenue.ts
Notifications	12	src/data/notifications.ts
Coach conversations	10	src/data/coach.ts
Completed days	6 (days 1–6)	src/store/useApp.ts
Completed lessons	6	src/store/useApp.ts
XP	650 (Level 2)	src/store/useApp.ts
Streak	6 days	src/store/useApp.ts

12. Enums & Allowed Values

Every column that accepts a fixed set of values. Implement as Postgres enums, check constraints, or application-level validation.

Enum name	Allowed values	Used in
PathId	clipping, gbp	users.current_path_id, user_progress, prospects, deals
PathScope	clipping, gbp, all	lessons.path, resources.path, outreach_templates.path
Difficulty	Beginner, Intermediate, Advanced	day_plans.difficulty, paths.difficulty
ProspectStatus	New, Contacted, Replied, Interested, Negotiating, Won, Lost	prospects.status
DealStatus	Potential, Booked, Collected	deals.status
TaskState	done, skipped	task_completions.state
SubscriptionStatus	none, active, expired	subscriptions.status
SubscriptionPlan	monthly, yearly	subscriptions.plan
LessonCategory	Mindset, Getting Started, Finding Clients, Outreach, Sales, Pricing, Delivery, Retention, Clipping, Google Business, Productivity	lessons.category
ResourceType	Template, Tool, Guide, Checklist, Script, Calculator	resources.type
TemplateStage	First touch, Follow-up, Reply, Closing	outreach_templates.stage
ContactEventKind	message, reply, call, status, note, followup	contact_events.kind
ChatSender	user, coach	chat_messages.sender
Theme	dark, light	user_settings.theme
AchievementMetric	missions, lessons, streak, prospects, contacted, replies, clients, revenue, daysCompleted	achievements.metric

Onboarding option values (for validation)

Field	Allowed values
role	Student, Employee, Freelancer, Creator, Entrepreneur, Job seeker, Other
skills	Video editing, Writing, Graphic design, Social media, Sales, Marketing, Customer service, Photography, Research, Web development, None yet, Other

Field	Allowed values
experience	None, Beginner, Some experience, Experienced
time	15 minutes, 30 minutes, 1 hour, 2 hours, 3+ hours
budget	\$0, \$25, \$50, \$100, \$250+
comfort	Very uncomfortable, A little uncomfortable, Neutral, Comfortable, Very comfortable
interest	Creating content, Helping businesses
goal	\$50, \$100, \$250, \$500, \$1,000+
blocker	I don't know what to do, I don't know what to sell, I don't know how to find clients, I'm afraid of rejection, I lack experience, I struggle with consistency, I need a step-by-step plan
learning	Watch videos, Read guides, Do practical tasks, A combination
commitment	Just exploring, I'm interested, I'm committed, I'm ready to start today