1. LUBE OIL RESERVOIR VENT. OIL MIST SEPARATOR INSTALLED OFF-SKID.

2. FLAME ARRESTER INCLUDES FLAME FILTER AND LOCATED AT END OF PIPE.

3. LL SET POINT IS OVERRIDEN AT START-UP.

4. OIL CHANGE BY USING TEMPORARY ARRANGEMENT WITH HOSES.

5. DELETED.

6. DELETED.

7. HIGH POINT VENT AND LOW POINT DRAIN TO BE FINALIZED BY PIPING AS PER PIPING LAYOUT.

8. ATMOSPHERIC VENT.

9. MANUAL DRAIN PRIOR TO EACH START-UP. PUSH BUTTON WITH PERMISSIVE FOR START-UP SEQUENCE.

10. PROVISION FOR FUTURE HOT GAS BYPASS LINE.
11. STRAINER TO BE REMOVED AFTER COMMISSIONING.
12. FROM SEAL GAS SYSTEM RUPTURE DISCS.

13. MAX BACK-PRESSURE 0.005 BARG.

14. UPSTREAM STRAIGHT RUN MIN. 10xD. DOWNSTREAM STRAIGHT RUN MIN. 5xD.

15. BOTTOM ENTRY FOR SUCTION AND DISCHARGE NOZZLES.

16. SAFETY CRITICAL HEAT TRACING - HYDRATE MITIGATION (25 DEGC).

17. THIS P&ID CONTAINS DCN-KP-0273-1/0904-1.

26CB9276

N4207
26CB9142

N4200

PIT 9056 26 SD HH:245 LL:110

PIT 9054 26

FIT 9050 26 SD HH:150 LL:120

26BL9206

N4201

PSE 9058 26 SD HH:235 LL:110

PDIT 9055 26 SD HH:160 LL:110

40BL9281

8"-DC-40-9001-AC21-38

4"-PV-40-9014-AS20S-00

26-KA-902

10"-PL-40-9008-AC21S-08

N4208

4"-AI-26-9010-AS20S-00

N4202

43CH9242

N4206

8"-GI-43-9006-FC11S-08

26BL9098

26CB9048

3"-GI-40-9002-AS20S-08

N4203

N4204

8"-DO-40-9012-AS20-03

2"-VF-40-9004-AC21S-38

8"-PV-43-9009-AC21-00

PDIT 9051 26

TIT 9057 26 SD HH:140 LL:125

10"-GI-40-9007-AS20-00

N4205

TAG NUMBER 26-KA-902

DUTY kW 1835

FLOW RATE kg/h 40210

DISCHARGE / SUCTION DESIGN PRESS. (MAX) Barg FV / 286 / FV / 286

VENDOR MAN ENERGY SOLUTIONS

26BL9169

10"-DC-63-9013-AS20-38

PIT 9052 26

N4209

LIT 9053 26 SD HH:140 LL:120

2"-PL-40-9011-AC21S-38

8"-VA-43-9005-AS20-00

8"-DO-43-9003-AS20S-03

4"-PV-40-9000-GC11S-08

40CB9239

B 2026-06-30 REVISED AS PER DCN
A 2026-01-15 ISSUED FOR DESIGN

2026-01-15

SHEET 1 OF 1

REV B

26-KA-902

3RD STAGE HP GAS LIFT COMPRESSOR

0D204-PID-26-902-001