1. OIL CHANGE BY USING TEMPORARY ARRANGEMENT WITH HOSES.

2. FROM SEAL GAS SYSTEM RUPTURE DISCS.

3. MAX BACK-PRESSURE 1.5 BARG.

4. HIGH POINT VENT AND LOW POINT DRAIN TO BE FINALIZED BY PIPING AS PER PIPING LAYOUT.

5. DELETED.

6. DELETED.

7. MAX BACK-PRESSURE 0.005 BARG.

8. UPSTREAM STRAIGHT RUN MIN. 10xD. DOWNSTREAM STRAIGHT RUN MIN. 5xD.

9. LL SET POINT IS OVERRIDEN AT START-UP.

10. INSULATION THICKNESS TO BE TAKEN INTO CONSIDERATION ON TW SELECTION.

11. DELETED.

12. LUBE OIL RESERVOIR VENT. OIL MIST SEPARATOR INSTALLED OFF-SKID.

13. ATMOSPHERIC VENT.

14. VENT ROUTED TO SAFE LOCATION.

15. BOTTOM ENTRY FOR SUCTION AND DISCHARGE NOZZLES.

16. THIS P&ID CONTAINS DCN-KP-0273-1.

6"-VA-26-9040-FC11S-03

4"-WC-63-9032-EC11S-08

4"-DC-40-9037-AS20-03

FIT 9056 26

26GB9356

LIT 9055 26

10"-VF-40-9041-FC11S-00

26CB9168

N4200

N4202

26BL9029

2"-PL-26-9030-AS20S-38

26GT9284

N4201

TIT 9054 26

8"-WC-40-9035-GD20S-00

PDIT 9060 26 SD HH:135 LL:110

PSE 9062 26

40GB9188

26CB9235

FIT 9058 26 SD HH:135 LL:110

N4203

4"-DO-43-9033-AS20-08

26-KA-901

FIT 9059 26 SD HH:150 LL:110

N4204

40CH9220

PDIT 9057 26

PSE 9061 26

8"-GI-26-9044-AC21S-08

3"-DC-63-9034-GC11S-00

FIT 9052 26

FIT 9050 26

4"-PV-43-9031-AC21-38

FIT 9053 26

LIT 9051 26

TAG NUMBER 26-KA-901

DUTY kW 1835

FLOW RATE kg/h 40210

DISCHARGE / SUCTION DESIGN PRESS. (MAX) Barg FV / 286 / FV / 286

VENDOR MAN ENERGY SOLUTIONS

43CH9191

N4205

43GT9220

26GB9253

8"-PV-43-9042-GD20S-00

2"-PV-63-9045-AS20-03

43BL9155

43CB9361

2"-GI-43-9039-GS20S-00

6"-GI-26-9043-GS20S-38

6"-VA-43-9038-AC21-08

2"-VA-43-9036-AC21-00

A 2026-01-15 ISSUED FOR DESIGN

2026-01-15

SHEET 1 OF 1

REV A

26-KA-901

2ND STAGE MP GAS COMPRESSOR

0D204-PID-26-901-001