1. LUBE OIL RESERVOIR VENT. OIL MIST SEPARATOR INSTALLED OFF-SKID.

2. PRIMARY SEAL GAS IS TAKEN DOWNSTREAM LAST COMPRESSING STAGE. SKID INTERNAL DESIGN.

3. OIL CHANGE BY USING TEMPORARY ARRANGEMENT WITH HOSES.

4. INSULATION THICKNESS TO BE TAKEN INTO CONSIDERATION ON TW SELECTION.

5. MAX BACK-PRESSURE 1.5 BARG.

6. ATMOSPHERIC VENT.

7. LL SET POINT IS OVERRIDEN AT START-UP.

8. FLAME ARRESTER INCLUDES FLAME FILTER AND LOCATED AT END OF PIPE.

9. DELETED.

10. DELETED.

11. HIGH POINT VENT AND LOW POINT DRAIN TO BE FINALIZED BY PIPING AS PER PIPING LAYOUT.

12. CHEMICAL CLEANING (CIP); BLEED/DRAIN CONNECTION.

13. PROVISION FOR FUTURE HOT GAS BYPASS LINE.

14. FROM SEAL GAS SYSTEM RUPTURE DISCS.

15. BOTTOM ENTRY FOR SUCTION AND DISCHARGE NOZZLES.

16. MAX BACK-PRESSURE 0.005 BARG.

17. THIS P&ID CONTAINS DCN-KP-0273-1.

26CH9251

43GB9179

N4206

26GT9050

43CB9339

10"-WC-40-9040-AS20-03

40CB9164

PDIT 9016 26 SD HH:235 LL:120

10"-GI-40-9031-AS20-38

3"-AI-26-9030-AC21S-03

PSE 9013 26 SD HH:245 LL:75

TIT 9012 26

26BL9124

N4204

PSE 9011 26

FIT 9017 26 SD HH:209 LL:50

N4202

TIT 9014 26 SD HH:150 LL:110

26-KA-901

40CH9280

TIT 9018 26 SD HH:150 LL:125

N4201

8"-DO-26-9036-GC11S-38

26GB9111

26GB9369

3"-GI-43-9039-AC21S-03

FIT 9015 26

4"-DC-43-9038-EC11S-08

N4203

6"-DO-26-9035-GS20S-00

TIT 9010 26 SD HH:160 LL:120

10"-PV-40-9033-EC11S-08

43GB9172

TAG NUMBER 26-KA-901

DUTY kW 1835

FLOW RATE kg/h 62809

DISCHARGE / SUCTION DESIGN PRESS. (MAX) Barg FV / 286 / FV / 286

VENDOR MAN ENERGY SOLUTIONS

10"-AI-26-9037-GS20S-38

26CB9106

N4200

N4205

40GT9297

3"-DO-43-9032-AC21-03

3"-GI-43-9034-GD20S-03

A 2026-01-15 ISSUED FOR DESIGN

2026-01-15

SHEET 1 OF 1

REV A

26-KA-901

3RD STAGE HP GAS EXPORT COMPRESSOR

0D204-PID-26-901-001