

Orders of Growth

Recurrence Relation	Time Complexity	Examples
$T(n) = T(n-1) + \Theta(1)$	$\Theta(n)$	linear search
$T(n) = T(n-1) + \Theta(n)$	$\Theta(n^2)$	selection/insertion/bubble sort
$T(n) = T(\frac{n}{2}) + \Theta(1)$	$\Theta(\log n)$	Binary search.
$T(n) = T(\frac{n}{2}) + \Theta(n)$	$\Theta(n)$	Quickselect
$T(n) = 2T(\frac{n}{2}) + \Theta(1)$	$\Theta(n \log n)$	tree traversal
$T(n) = 2T(\frac{n}{2}) + \Theta(n)$	$\Theta(n \log n)$	Merge sort
$T(n) = 2T(n-1) + \Theta(1)$	$\Theta(2^n)$	
$T(n) = T(n-1) + T(n-2) + \Theta(1)$	$\Theta(\phi^n) \approx \Theta(1.62^n)$	Tree recursive fibonacci
$T(n) = T(\sqrt{n}) + \Theta(1)$	$\Theta(\log \log n)$	N.A
$T(n) = \sqrt{n}T(\sqrt{n}) + \Theta(\sqrt{n})$	$\Theta(n \log \log n)$	Let $n = 2^k$ & Master's Theorem

In general, $T(n) = \theta(n^k) + T(n-1) \rightarrow T(n) = \theta(n^{k+1})$

Master Theorem
<p>If $T(n) = aT(\frac{n}{b}) + f(n)$, $f(n) = n^k$, then</p> $T(n) = \begin{cases} n^k, & a < b^k \\ n^k \log_b n, & a = b^k \\ n^{\log_b a}, & a > b^k \end{cases}$


$$\begin{aligned} \text{if } a_n &= a_{n-1} + c \\ \sum_{i=1}^n a_i &= a_1 + a_2 + a_3 + \cdots + a_n \\ &= \frac{n(a_n + a_1)}{2} \\ \sum_{i=1}^n ar^{i-1} &= a + ar + ar^2 + \cdots + ar^{n-1} \\ &= a \cdot \frac{1-r^n}{1-r} \\ \text{if } 0 < r < 1 \\ \sum_{i=1}^{\infty} ar^{i-1} &= \frac{a}{1-r} \end{aligned}$$

Function	Name
5 $O(1)$	Constant
$\log\log(n)$	double log
$\log(n)$	logarithmic
$\log^2(n)$	Polylogarithmic
n	linear
$n\log(n)$	log-linear
n^3	polynomial
$n^3\log(n)$	
n^4	polynomial
2^n	exponential
2^{2^n}	
$n!$	factorial

Sorting


Selection Sort

```
for j in [1:len(A)]:
    k = indexofMin(A[j..len(A)])
    swap(A[j], A[k])
```




Insertion Sort

```
for i in range(1, len(A)):  
    key = A[i]  
    j = i - 1  
    # find correct position for key within  
    # A[:j]  
    while (j >= 0) and (A[j] > key):  
        # move element to the right ('make  
        # space for key')  
        A[j+1] = A[j]  
        j -= 1  
    # insert key here  
    A[j+1] = key
```




Bubble Sort

```
repeat (until no swaps):
    for j in [0 : len(A)-1]:
        if (A[j] > A[j+1]):
            swap(A[j], A[j+1])
```




Merge Sort

```
if (len(A) <= 1):
    return
else:
    mid = len(A) // 2
    left = mergeSort(A[0:mid])
    right = mergeSort(A[mid:len(A)])
    return merge(left, right)
```



QuickSort



Properties

Algorithm	Stability	In-place	Invariant
Selection	✗	✓	At the end of iteration i the i smallest items in the array are sorted.
Insertion	✓	✓	At the end of iteration j the j items in the array are in sorted order.
Bubble	✓	✓	At the end of iteration j the j largest items in the array are sorted.
Merge	✓	✗	N/A
Quick	✗	✓	<ol style="list-style-type: none"> Pivot is in correct position at the end of partitioning For all $1 < i < low$, $A[i] < pivot$ For all $j \gg high$, $A[j] > pivot$

Time Complexity

<i>Algorithm</i>	<i>Unsorted</i>	<i>Sorted</i>	<i>Reverse Sorted</i>	<i>Almost Sorted</i>
Selection	$O(n^2)$	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion	$O(n^2)$	$O(n)$	$O(n^2)$	$O(n)$
Bubble	$O(n^2)$	$O(n)$	$O(n^2)$	$O(n^2)$
Merge	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$
Quick	$O(n \log n)$	$O(n^2)$	$O(n^2)$	$O(n \log n)$

Swaps

<i>Algorithm</i>	<i>Best Case</i>	<i>Worst Case</i>
Selection	0 (Sorted)	$O(n)$
Insertion	0 (Sorted)	$O(n^2)$ (Reverse)
Bubble	0 (Sorted)	$O(n^2)$ (Reverse)
Merge	0	0 (Only Copying)
Quick	$O(n \log n)$	$O(n^2)$ (Reverse)

Comparisons

<i>Algorithm</i>	<i>Best Case</i>	<i>Worst Case</i>
Selection	$O(n^2)$	$O(n^2)$
Insertion	$0(n^2)$ (Sorted)	$O(n^2)$
Bubble	$0(n^2)$ (No Flag)	$O(n^2)$
Merge	$O(n \log n)$	$O(n \log n)$
Quick	$O(n \log n)$	$O(n^2)$

Space Complexity

<i>Algorithm</i>	<i>Extra Memory</i>
Selection	$O(1)$
Insertion	$O(1)$
Bubble	$O(1)$
Merge	$O(n \log n)$
Quick	$O(n)$ (average: $O(\log n)$)

AVL Trees

1. Weight: Number of nodes in the subtree rooted at the node.
 - (a) `weight(null) = 0`
 - (b) `weight(leaf) = 1`
 - (c) `weight(u) = w.left.weight + w.right.weight + 1`
2. Number of edges on the path from the node to the deepest leaf.
 - (a) `height(empty tree) = -1`
 - (b) `height(u) = max(u.left.height, u.right.height) + 1`

- BST is balanced if $h = O(\log n)$, i.e. $c \cdot \log n$, allowing all operations to run in $O(\log n)$ time
- A node u is said to be height-balanced if $|u.\text{left.height} - u.\text{right.height}| \leq 1$.
- BST is height-balanced if every node is height-balanced

Notes

- Height-balanced \Rightarrow Balanced
- Balanced \nRightarrow Height-balanced
- A height-balanced tree has height $O(2\log n) = O(\log n)$
- Define the balance factor of a node `u` as
`balance(u) = u.left.height - u.right.height` When $|\text{balance}(u)| \geq 2$, rebalancing is required. This must be done from the insertion/deletion point **up to the root**

Binary Search

```
def search(A, key, begin, end):
    if (begin > end): return -1
    # avoid integer overflow errors
    mid = begin + (end-begin)/2
    if (key < A[mid]):
        # eliminate right half
        return search(A, key, begin, mid)
    else if (key > A[mid]):
        # eliminate left half
        return search(A, key, mid+1, end)
    else: return mid
```


1. Given a function `complicatedFunction(input)` that is **monotonic increasing**
2. i.e. `complicatedFunction(i) < complicatedFunction(i+1)`
3. Task: Find the minimum value j such that: `complicatedFunction(i) > num`

```
def bisectRight(A, key):
    # returns the index of the first value
    # strictly greater than key
    low = 0, high = len(A) - 1
    if A[high] < key: return -1
    while (low < high)
        mid = (low + high)/2
        if A[mid] <= key: low = mid+1
        else if A[mid] > key: high = mid
    return low
```

Tries

Tries are useful for partial string operations:

- Prefix queries (find all words that start with 'pi')
- Longest prefix (find the longest word that is a prefix to 'pickling')
- Regex (find all words of the form 'pi??le')



Tradeoffs: Tries vs BST

- Time
 - $O(L)$ vs $O(h * L)$
 - Trie operations do not depend on text size or number of words
- Space
 - Tries tend to use more space
 - Both use $O(\text{textsize})$ space, but tries have more nodes and thus more overhead
 - Array implementations waste space in storing children


Interval Trees

- AVL Trees with max value augmentation
- Goal: `searchInterval(x)` finds an interval that contains x in $O(\log n)$ time
- Each node stores an interval
- Sorted by key - left endpoint of the interval
- Nodes augmented by **max right-endpoint**

```
# searches in root to find an interval
containing x
def searchInterval(x, root):
    # base cases
    if (root == null): return null;
    if (u.interval.contains(x)): return u

    if (u.left == null || x > u.left.max):
        return searchInterval(x, root.right)
    else:
        return searchInterval(x, root.left)
```

Searching: `interval-search(22)`



1D Range Searching

Goal: Find keys within <some interval>


- Store data in the **leaves** only (build from bottom-up) - $O(n \log n)$
- Internal nodes store the **max of leaves in left subtree**
- Insert/Delete/Rotate don't require modification

```
# find the highest node between l and h
def findSplitNode(l, h, root):
    if (root.key >= h):
        return findSplitNode(l, h, root.left)
    else if (root.key < l):
        return findSplitNode(l, h, root.right)
    else: return root

def leftTraverse(l, root):
    if (l <= root.key):
        # take everything in the right subtree
        enumerateAll(root.right)
        leftTraverse(l, root.left)
    else:
        leftTraverse(l, root.right)

def query(l, h):
    v = findSplitNode(l, h, root) # O(logn)
    leftTraverse(l, v.left) # O(k)
    rightTraverse(h, v.right) # symmetric
```


Example: query(10, 50)



Successor

```
if (u.right != null):
    return findMin(u.right)
else:
    p = u.parent
    # find an ancestor that is a left child
    while (p is a right child):
        go up the ancestry
    if (p == null): return null
    else: return parent
```

successor(32)



Case 2: node has no right child.

Rank & Select

The rank of an element is its position relative to the sorted order, i.e. the k th smallest item would have a rank of k . Select is the reverse of rank. Given a rank, return the value of the node with that rank.


```
# computes the rank of 'u' within the subtree
rooted at 'root'
getRank(u, root):
    if (u.key < root.key):
        return getRank(u, root.left)
    else if (u.key > root.key):
        return root.left.weight + 1 +
            getRank(u, root.right)
    else:
        return root.left.weight + 1

select(rank, root):
    # this is equivalent to calling
    getRank(root, root)
    rankOfRootInSubTree = root.left.weight + 1
    if (rank < rankOfRootInSubTree):
        return select(rank, root.left)
    else if (rank > rankOfRootInSubTree):
        // eliminate the root and its right
        subtree
        return select(rank -
            rankOfRootInSubTree, root.right)
    else:
        return root
```

Rotations

A node is **left-heavy** if its left subtree is **taller** than the right sub-tree, i.e. `node.left.height > node.right.height`.

- If v is out of balance and left heavy:
 - v .left is **balanced**: `rightRotate(v)`
 - v .left is **left-heavy**: `rightRotate(v)`
 - v .left is **right-heavy**: `leftRotate(v.left)` and `rightRotate(v)`
- If v is out of balance and right heavy: Symmetrical cases, e.g. if v .right is **balanced**: `rightRotate(v)`



Notes

- Right rotations require a left child, left rotations require a right child
- The maximum number of rotations required upon insertion is 2, while for deletion it is $O(\log n)$

Maximum Value

Each node u is augmented with: **value**, that specifies the value associated with that node, and **max**, the maximum **value** of all nodes in the subtree rooted at u

New Operations

`updateValue(key, newValue)`

- Search the tree in the usual way for the specified key
- Assuming a node u was found, update u .value = `newValue`
- Update the tree - for every node v on the path from u to root, update v .max = `max(v.left.max, v.right.max, v.value)`

Maintenance

- When performing a rotation on u , only u and u .parent change. Let $v = u$.parent. After a rotation of u , set u .max = v .max, and update v .max = `v.right.value`
- When a node u is inserted: Set u .value = `<initial>` and u .max = `<initial>`
- When a node u is deleted:
 - if u is a leaf, we can just delete it. For every ancestor v of u , update v .max = `v.points`
 - if u has one child, then delete u , connecting u .parent to u .child. For every node v on the path from u to root, update v .max
 - node u has two children. Let $v = \text{successor}(u)$. Delete v from the tree, and for every node w on the path from v to u , update w .max. Then replace u with v , and continue to update every node w on the path from v to the root.
- Perform rotations to rebalance.

Total Count

Each node u is augmented with: **value**, that specifies the value associated with that node, and **total**, the count of the number of special nodes in the subtree rooted at u

New Operations

`addToValue(key, val)`

- Search the tree in the usual way for the specified key
- Assuming a node u was found, update u .value += `val`
- If `isSpecial(u.value)`, update the tree - for every node v on the path from u to root, update v .total += 1

Symmetrical for `subtractFromValue`

`searchSpecial()`

- Let $v = \text{root}$
- Base Case: if `isSpecial(v.value)`, return v
- If v .total == 0, return null
- Else if v .isLeaf(), return v
- Else if v .left.total > 0, recurse on v .left
- Else recurse on v .right

Note: Avoid `NullPointerException`

Maintenance

Similar to **Max Value** augmentation, except that a node u is updated as follows:

u .total = u .left.total + u .right.total + `isSpecial(u) ? 1 : 0`

Hashing

- Goal: insert and search in $O(1)$ time
- Idea: map $|U|$ possible keys to m buckets via a hash function
 - $h: U \rightarrow \{1 \dots m\}$
 - $\text{time} = \text{cost}(h) + \text{cost}(\text{access})$

Direct Access Tables

- Maps every possible key to a single bucket i.e. $h: U \rightarrow \{1 \dots |U|\}$
- Uses too much space - $O(|U|)$

Chaining

- Maps $|U|$ possible keys to $m < |U|$ buckets
- By PHP, $\exists h(k_1) = h(k_2)$ i.e. **Collision**
- Uses linked lists to store colliding keys
- Insert - $O(1 + \text{cost}(h))$
- Search - $O(n + \text{cost}(h))$ (Depends on distribution of hash function)

