

# StreamStats Version 3.0

## Flow Statistics Ungaged Site Report

Date: Tues Mar 22, 2016 8:43:23 AM GMT-6

Study Area: Utah

NAD 1983 Latitude: 40.7223 (40 43 20)

NAD 1983 Longitude: -111.8475 (-111 50 51)

Drainage Area: 56.9 mi<sup>2</sup>

Peak Flows Basin Characteristics			
100% Region 2 (56.9 mi <sup>2</sup> )			
Parameter	Value	Regression Equation Valid Range	
		Min	Max
Drainage Area (square miles)	56.9	2.14	84.1
Mean Annual Precipitation (inches)	30.5	16.5	53.7

Monthly Exceedance and Annual Mean Flows Basin Characteristics			
100% Mean Flow SIR08 5230 Region 2 (56.9 mi <sup>2</sup> )			
Parameter	Value	Regression Equation Valid Range	
		Min	Max
Drainage Area (square miles)	56.9	2.14	70.1
Mean Basin Elevation (feet)	6740	6440	8550
Mean Annual Precipitation (inches)	30.5	22.3	49.5
Mean August Precipitation (inches)	1.19	0.92	2

Peak Flows Statistics						
Statistic	Value	Unit	Prediction Error (percent)	Equivalent years of record	90-Percent Prediction Interval	
					Min	Max
PK2	158	ft3/s	71	0.9		
PK5	231	ft3/s	58	1.6		
PK10	285	ft3/s	53	2.5		
PK25	332	ft3/s	51	3.7		
PK50	401	ft3/s	50	4.6		
PK100	447	ft3/s	50	5.4		
PK200	492	ft3/s	51	6.1		
PK500	562	ft3/s	52	6.8		

<http://pubs.usgs.gov/sir/2007/5158/> (<http://pubs.usgs.gov/sir/2007/5158/>)

Kenney\_ T.A.\_ Wilkowske\_ C.D.\_ and Wright\_ S.J.\_ 2007\_ Methods for Estimating Magnitude and Frequency of Peak Flows for Natural Streams in Utah: U.S. Geological Survey Scientific Investigations Report 2007-5158\_ 28 p.

Monthly Exceedance and Annual Mean Flows Statistics						
Statistic	Value	Unit	Prediction Error (percent)	Equivalent years of record	90-Percent Prediction Interval	
					Min	Max
QA	26.3	ft3/s	63			
JAND20	8.51	ft3/s	77			

JAND50	4.89	ft3/s	93			
JAND80	3.19	ft3/s	110			
FEBD20	12.5	ft3/s	84			
FEBD50	5.97	ft3/s	90			
FEBD80	3.59	ft3/s	110			
MARD20	27.6	ft3/s	63			
MARD50	16.8	ft3/s	62			
MARD80	11.7	ft3/s	77			
APRD20	58.3	ft3/s	54			
APRD50	32.1	ft3/s	72			
APRD80	16.7	ft3/s	100			
MAYD20	99.9	ft3/s	60			
MAYD50	55.5	ft3/s	72			
MAYD80	29.4	ft3/s	93			
JUND20	59.3	ft3/s	70			
JUND50	36	ft3/s	85			
JUND80	19.8	ft3/s	100			
JULD20	13.3	ft3/s	86			
JULD50	7.68	ft3/s	91			
JULD80	4.04	ft3/s	100			
AUGD20	6.41	ft3/s	130			
AUGD50	3.64	ft3/s	140			
AUGD80	1.98	ft3/s	160			
SEPD20	6.82	ft3/s	88			
SEPD50	4	ft3/s	91			
SEPD80	2.4	ft3/s	110			
OCTD20	8.02	ft3/s	76			
OCTD50	4.96	ft3/s	83			
OCTD80	2.87	ft3/s	110			
NOVD20	9.12	ft3/s	70			
NOVD50	5.56	ft3/s	80			
NOVD80	3.63	ft3/s	96			
DECD20	8.55	ft3/s	73			
DECD50	5.09	ft3/s	89			
DECD80	3.1	ft3/s	110			

<http://pubs.usgs.gov/sir/2008/5230/> (<http://pubs.usgs.gov/sir/2008/5230/>)

Wilkowske\_ C.D.\_ Kenney\_ T.A.\_ and Wright\_ S.J.\_ 2009\_ Methods for Estimating Monthly and Annual Streamflow Statistics at Ungaged Sites in Utah: U.S. Geological Survey Scientific Investigations Report 2008-5230\_ 62 p.

#### Accessibility

#### FOIA

#### Privacy

#### Policies and Notices

U.S. Department of the Interior | U.S. Geological Survey

URL: [http://streamstatsags.cr.usgs.gov/v3\\_beta/FTreport.htm](http://streamstatsags.cr.usgs.gov/v3_beta/FTreport.htm)

Page Contact Information: [StreamStats Help](#)

Page Last Modified: 11/24/2015 12:32:58 (Web1)

[Streamstats Status](#)

[News](#)

