



종합실습4_제출리포트_최종_홍은비



종합실습 4 - E-Commerce 데이터 요청 및 SQL 튜닝 리포트

- 소속: 판교 5반
- 성명: 홍은비
- DBMS: PostgreSQL 17.10 (Homebrew)
- 실행환경: Local PC / DBeaver Community
- 측정 명령: `EXPLAIN (ANALYZE, BUFFERS, SUMMARY)`

시드 데이터는 `random()` 으로 생성되므로 실행 결과와 시간은 환경마다 달라질 수 있다. 절대시간뿐 아니라 Scan/Join 방식, 반복 횟수, 예상·실제 행 수, Buffers 변화를 함께 비교한다.

1. 실습 목적

구매·재무 등 다른 실무 팀에서 요청한 E-Commerce 자료를 정확한 기준으로 산출하고, 같은 결과를 더 효율적으로 반환하도록 SQL과 인덱스를 개선한다. Q1~Q10은 튜닝 전후 쿼리와 실행계획을 비교하고, 별도로 PostgreSQL의 세 가지 물리 조인과 Materialized View 활용 방법을 검토한다.

2. 공통 데이터 기준

항목	정의
실매출 주문	<code>order_status IN ('paid','shipped','delivered')</code>
주문 매출	<code>SUM(order_items.line_total)</code>
AOV	실매출 합계 ÷ 실매출 주문 수
Q1 기간	실행시점 기준 최근 1개월
Q3 기간	실행시점 기준 최근 90일
Q6 재구매	첫 구매 후 30일 이내 추가 실구매
Q10 대상	전체 3,000명 누적매출 상위 1%인 30명
Q10 표시금액	선정된 30명의 최근 60일 실매출

3. Q1 - 최근 1개월 실제 판매 총액

요청사항

`paid`, `shipped`, `delivered` 상태이면서 `now() - interval '1 month'` 이후인 주문의 `line_total` 합계를 제공한다.

튜닝 전 쿼리·결과 화면

Q1 튜닝 전

ecom	<postgres 4> Script-10	<postgres 4> Script-11
<pre>SET search_path = ecom, public;</pre> Q1. 최근 1개월 실제 판매 총액 문제점: order_ts를 EXTRACT 함수로 변환해 일반 B-tree 범위 탐색을 어렵게 하고, 주문마다 order_items를 다시 읽는 상관 서브쿼리를 사용한다. 실행계획 확인용] EXPLAIN부터 첫 번째 세미콜론까지 실행 실제 실행계획·버퍼·실행시간 측정 주문별 금액을 합산하고 NULL이면 0 반환 해당 주문의 주문상품 금액 합계 order_items 테이블 별칭은 oi 마달 주문번호를 참조하는 상관 서브쿼리 결과 집합명: 최근 1개월 총매출 orders 테이블 별칭은 o 실제 매출로 인정할 주문 상태 주문시기를 초 단위로 변환 현재로부터 1개월 이내만 조회 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT COALESCE(SUM((SELECT SUM(oi.line_total) FROM ecom.order_items oi WHERE oi.order_id = o.order_id)), 0) AS total_sales_1m FROM ecom.orders o WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND EXTRACT(EPOCH FROM o.order_ts) >= EXTRACT(EPOCH FROM now()) - INTERVAL '1 month');		
Results 1 × Statistics 1		
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT COAL		
Az QUERY PLAN		
1	Aggregate	(cost=8693.61..8693.62 rows=1 width=32) (actual time=23.404..23.626 rows=1 loops=1)
2	Buffers:	shared hit=2902
3	-> Seq Scan on orders o	(cost=0.00..141.32 rows=1023 width=8) (actual time=0.576..6.329 rows=9
4	Filter:	((order_status = ANY ('{paid,shipped,delivered}':text[])) AND (EXTRACT(epoch FROM ord
5	Rows Removed by Filter:	2912
6	Buffers:	shared hit=40
7	SubPlan 1	
8	-> Aggregate	(cost=8.35..8.36 rows=1 width=32) (actual time=0.017..0.017 rows=1 loops=948)
9	Buffers:	shared hit=2862
10	-> Index Scan using idx_order_items_order on order_items oi	(cost=0.29..8.34 rows=3 width=6
11	Index Cond:	(order_id = o.order_id)
12	Buffers:	shared hit=2862
13	Planning Time:	8.887 ms
14	Execution Time:	25.380 ms

느린 이유

order_ts를 함수로 변환하면 일반 날짜 인덱스의 범위탐색이 어려워질 수 있다. 또한 주문마다 주문상품 합계를 상관 서브쿼리로 반복 조회한다.

개선 방법

날짜 컬럼을 그대로 둔 SARG 범위 조건을 사용하고, 주문과 주문상품을 한 번 조인해 전체 합계를 계산한다. 실매출 상태만 포함하는 부분 인덱스로 대상 주문 탐색 범위를 줄인다.

튜닝 후 쿼리·결과 화면

Q1 튜닝 후

ecom	<postgres 4> Script-10	<postgres 4> Script-11
<pre>SET search_path = ecom, public;</pre> Q1. 최근 1개월 SARG 범위 조건 + 한 번의 조인/집계 원형: 주문별 상관 서브쿼리 대신 orders와 order_items를 한 번 조인해 합산한다. 실행계획 확인용] EXPLAIN (ANALYZE, BUFFERS, SUMMARY) 실제 실행계획·버퍼·실행시간 측정 주문별 금액을 합산하고 NULL이면 0 반환 해당 주문의 주문상품 금액 합계 order_items 테이블 별칭은 oi 마달 주문번호를 참조하는 상관 서브쿼리 결과 집합명: 최근 1개월 총매출 orders 테이블 별칭은 o 실제 매출로 인정할 주문 상태 주문시기를 초 단위로 변환 현재로부터 1개월 이내만 조회 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT COALESCE(ROUND(SUM(oi.line_total), 2), 0) AS total_sales_1m FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts >= now() - INTERVAL '1 month';		
Results 1 × Statistics 1		
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT COAL		
Az QUERY PLAN		
1	Aggregate	(cost=292.69..292.70 rows=1 width=32) (actual time=4.852..4.853 rows=1 loops=1)
2	Buffers:	shared hit=101 read=8
3	-> Hash Join	(cost=55.65..286.56 rows=2449 width=6) (actual time=1.941..4.531 rows=2563 loops=1)
4	Hash Cond:	(oi.order_id = o.order_id)
5	Buffers:	shared hit=101 read=8
6	-> Seq Scan on order_items oi	(cost=0.00..203.67 rows=10367 width=14) (actual time=0.006..1.128 rows=10367 loops=1)
7	Buffers:	shared hit=100
8	-> Hash	(cost=44.25..44.25 rows=912 width=8) (actual time=1.917..1.917 rows=947 loops=1)
9	Buckets:	1024 Batches: 1 Memory Usage: 45KB
10	Buffers:	shared hit=1 read=8
11	-> Index Only Scan using idx_orders_sales_ts_order on orders o	(cost=0.28..44.25 rows=912 width=8) (actual time=0.315..1.600 rows=947 loops=1)
12	Index Cond:	(order_ts >= (now() - '1 mon':interval))
13	Heap Fetches:	0
14	Buffers:	shared hit=1 read=8
15	Planning:	
16	Buffers:	shared hit=221 read=7
17	Planning Time:	3.082 ms
18	Execution Time:	4.903 ms

ecom	<postgres 4> Script-10	<postgres 4> Script-11
<pre>SELECT COALESCE(ROUND(SUM(oi.line_total), 2), 0) AS total_sales_1m -- [Q1] 실제 총매출 확인 FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts >= now() - INTERVAL '1 month';</pre>		
orders(+) 1 ×		
SELECT COALESCE(ROUND(SUM		
123 total_sales_1m		
1	883,029.03	

구분	Scan/Join 방식	Buffers	Execution Time	결과 금액
튜닝 전	Seq Scan + SubPlan	hit=2,902	25.380 ms	883,029.03
튜닝 후	Index Only Scan + Hash Join	hit=101/read=8	4.903 ms	883,029.03

결과 해석: 전후 결과는 동일하며 실행시간이 80.7% 단축되고 반복 SubPlan이 제거되었다.

4. Q2 - 월별 주문 수·매출·AOV

요청사항

월별 실매출 주문 수, 총매출, 주문당 평균 금액을 제공한다.

Q2 튜닝 전

```

-- Q2. 월별 주문 수, 매출, AOV
-- 문제점: 상세 행을 먼저 모두 조인한 뒤 COUNT(DISTINCT)로 중복을 제거한다.

-- [① 실행계획 확인용] 월별 집계와 Scan/Join과 실행시간 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) -- 실제 실행계획과 성능 측정
SELECT date_trunc('month', o.order_ts)::date AS sales_month, -- 주문시각을 월 단위로 묶음
COUNT(DISTINCT o.order_id) AS order_count, -- 상세행 중복을 제거한 주문 수
ROUND(SUM(oil.line_total), 2) AS revenue, -- 월별 매출 합계, 소수점 둘째 자리
ROUND(SUM(oil.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov -- 주문 테이블
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id -- 주문번호로 주문상품 연결
WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 판매중 주문만 포함
GROUP BY 1 -- SELECT 첫 번째 컬럼인 월로 그룹화
ORDER BY 1; -- 월 오름차순 정렬

-- SELECT date_trunc('month', o.order_ts)::date AS sales_month

```

Results 1 X Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) Enter a SQL expression to filter results (use Ctrl+Space)

Grid

1 AZ QUERY PLAN

2 GroupAggregate (cost=939.49..1113.93 rows=3068 width=76) (actual time=10.469..11.600 rows=6 loops=1)

3 Buffers: shared hit=140

4 -> Sort (cost=939.49..960.09 rows=8240 width=18) (actual time=10.362..10.640 rows=8230 loops=1)

5 Sort Key: ((date_trunc('month')::text, o.order_ts)::date), o.order_id

6 Sort Method: quicksort Memory: 706kB

7 Buffers: shared hit=140

8 -> Hash Join (cost=131.43..403.54 rows=8240 width=18) (actual time=1.613..7.866 rows=8230 loops=1)

9 Hash Cond: (oi.order_id = o.order_id)

10 Buffers: shared hit=140

11 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.009..1.122 rows=10367 loops=1)

12 Buffers: shared hit=100

13 -> Hash (cost=93.08..93.08 rows=3068 width=16) (actual time=1.543..1.543 rows=3068 loops=1)

14 Buckets: 4096 Batches: 1 Memory Usage: 176kB

15 Buffers: shared hit=40

16 -> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=16) (actual time=0.016..1.071 rows=3068 loops=1)

17 Filter: (order_status = ANY ('paid,shipped,delivered'))::text[1])

18 Rows Removed by Filter: 792

19 Buffers: shared hit=40

20 Planning:

21 Buffers: shared hit=49 dirtied=1

22 Planning Time: 1.979 ms

23 Execution Time: 11.646 ms

```

SELECT date_trunc('month', o.order_ts)::date AS sales_month, -- [O] 실제 월별 결과 조회
COUNT(DISTINCT o.order_id) AS order_count,
ROUND(SUM(o.line_total), 2) AS revenue,
ROUND(SUM(o.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS avo
FROM ecom.orders o
JOIN ecom.order_items o ON o.order_id = o.order_id
WHERE order_status IN ('paid', 'shipped', 'delivered')
GROUP BY 1
ORDER BY 1;

```

=====

SQL 실행 결과: 2026-07-31 10:00:00

orders(1) | X

SELECT date_trunc('month', o.order_ts)::date AS sales_month, COUNT(DISTINCT o.order_id) AS order_count, ROUND(SUM(o.line_total), 2) AS revenue, ROUND(SUM(o.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS avo

	sales_month	order_count	revenue	avo
1	2026-04-01	267	228,521.46	855.89
2	2026-05-01	673	651,927.62	820.1
3	2026-06-01	784	707,531.35	903.89
4	2026-07-01	892	829,725.16	930.19
5	2026-08-01	439	390,500.57	889.54
6	2026-09-01	3	812.51	270.84

느린 이유와 개선 방법

상세 주문상품을 먼저 조인한 상태에서는 주문이 여러 행으로 증가하므로 `COUNT(DISTINCT order_id)` 가 필요하다. 튜닝 후에는 주문별 금액을 먼저 집계한 다음 월별로 다시 집계해 중복 제거 비용을 줄인다.

Q2 튜닝 후

```
-- Q2. 주문별 매출을 먼저 계산해 COUNT(DISTINCT)를 제거
-- 튜닝: 주문별로 한 행을 만든 뒤 중복 제거 없이 order_id를 집계한다.
-- [① 실행계획 확인용] 주문별 선집계 후 월별 집계 계획 확인

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

WITH order_totals AS (                                     -- 주문별 금액을 먼저 만드는 CTE
    SELECT o.order_id,
           date_trunc('month', o.order_ts)::date AS sales_month,
           SUM(o.line_total) AS order_total                -- 주문상품을 주문 단위로 합산
    FROM   ecom.orders o
    JOIN   ecom.order_items oi ON oi.order_id = o.order_id
    WHERE  o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.order_ts
)

SELECT sales_month,
       COUNT(order_id) AS order_count,                    -- 주문당 한 행이므로 주문번호 집계
       ROUND(SUM(order_total), 2) AS revenue,
       ROUND(AVG(order_total), 2) AS aov
FROM   order_totals
GROUP BY sales_month
ORDER BY sales_month;
```

Results 1	SQL	Enter a SQL expression to filter results (use Ctrl+Space)
Grid	EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH order_totals AS (SELECT	
Text		
	AZ QUERY PLAN	
1	Sort (cost=522.57..523.07 rows=200 width=76) (actual time=6.733..6.735 rows=6 loops=1)	
2	Sort Key: ((date_trunc('month')::text, o.order_ts))::date)	
3	Sort Method: quicksort Memory: 25kB	
4	Buffers: shared hit=143	
5	-> HashAggregate (cost=510.92..514.92 rows=200 width=76) (actual time=6.714..6.721 rows=6 loops=1)	
6	Group Key: (date_trunc('month')::text, o.order_ts))::date	
7	Batches: 1 Memory Usage: 40kB	
8	Buffers: shared hit=140	
9	-> HashAggregate (cost=403.54..457.23 rows=3068 width=52) (actual time=5.123..6.324 rows=3068 loops=1)	
10	Group Key: o.order_id	
11	Batches: 1 Memory Usage: 1393kB	
12	Buffers: shared hit=140	
13	-> Hash Join (cost=131.43..362.34 rows=8240 width=22) (actual time=0.906..3.375 rows=8230 loops=1)	
14	Hash Cond: (o.order_id = o.order_id)	
15	Buffers: shared hit=140	
16	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.010..0.824 rows=10367 loops=1)	
17	Buffers: shared hit=100	
18	-> Hash (cost=93.08..93.08 rows=3068 width=16) (actual time=0.879..0.879 rows=3068 loops=1)	
19	Buckets: 4096 Batches: 1 Memory Usage: 176kB	
20	Buffers: shared hit=40	
21	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=16) (actual time=0.007..0.603 rows=3068 loops=1)	
22	Filter: (order_status = ANY ('paid,shipped,delivered')::text[]))	
23	Rows Removed by Filter: 792	
24	Buffers: shared hit=40	
25	Planning:	
26	Buffers: shared hit=69 read=7	
27	Planning Time: 5.743 ms	
28	Execution Time: 6.879 ms	

```

WITH order_totals AS (
    SELECT o.order_id, date_trunc('month', o.order_ts)::date AS sales_month,
           SUM(oi.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.order_ts
)
SELECT sales_month, COUNT(order_id) AS order_count,
       ROUND(SUM(order_total), 2) AS revenue,
       ROUND(AVG(order_total), 2) AS aov
FROM order_totals
GROUP BY sales_month
ORDER BY sales_month;

```

Results 1 X

WITH order_totals AS (SELECT o.order_id, date_trunc('month', o.order_ts) AS order_month, SUM(o.amount) AS order_total FROM orders o GROUP BY o.order_id, date_trunc('month', o.order_ts))

	sales_month	123 order_count	123 revenue	123 aov
1	2026-04-01	267	228,521.46	855.89
2	2026-05-01	673	551,927.62	820.1
3	2026-06-01	794	717,531.35	903.69
4	2026-07-01	892	829,725.16	930.19
5	2026-08-01	439	390,509.57	889.54
6	2026-09-01	3	812.51	270.84

구분	집계 방식	Buffers	Execution Time	전후 결과 동일 여부
튜닝 전	상세행 + COUNT(DISTINCT order_id)	hit=140	11.646 ms	-
튜닝 후	주문별 선집계 + COUNT(order_id)	hit=143	6.879 ms	동일

결과 해석: 주문별 선집계로 DISTINCT 제거 비용을 줄여 실행시간이 40.9% 단축되었다.

5. Q3 - 최근 90일 카테고리 매출 Top 10

-- Q3. 최근 90일 카테고리 Top 18
-- 문제점: 바-SARG 날짜 조건을 사용하고 실제 데이터를 그대로 집계한다.

```
-- 카테고리별 확인용) 최근 90일 월리와 세일을 조인 거쳐 확인
```

```
[EXPLAIN (ANALYZE, BUFFERS, SUMMARY)] -- 실제 실행계획과 성능 측정
```

```
SELECT c.category_id,  
       c.category_name,  
       ROUND(SUM(o.line_total), 2) AS revenue_90d -- 카테고리별 최근 90일 매출  
FROM   ecom.orders o  
JOIN   ecom.order_items oi ON oi.order_id = o.order_id -- 주문에서 연결  
JOIN   ecom.products p ON p.product_id = oi.product_id -- 상품 연결  
JOIN   ecom.categories c ON c.category_id = p.category_id -- 카테고리 연결  
WHERE  o.order_status IN ('paid', 'shipped', 'delivered') -- 실제로 주문 포함  
AND    o.order_ts::date >= CURRENT_DATE - 90 -- timestamp을 date로 변환해 최근 90일 필터  
GROUP BY c.category_id, c.category_name -- 카테고리별로 집계  
ORDER BY revenue_90d DESC, c.category_id -- 매출이 큰 순서로 정렬  
LIMIT 18;
```

Results 1 x Statistics 1

Az QUERY PLAN

- 1 Limit (cost=497.38..497.41 rows=10 width=72) (actual time=11.220..11.225 rows=10 loops=1)
- 2 Buffers: shared hit=148
- 3 -> Sort (cost=497.38..500.06 rows=1070 width=72) (actual time=11.219..11.222 rows=10 loops=1)
- 4 Sort Key: (round(sum(oi.line_total), 2)) DESC, c.category_id
- 5 Sort Method: quicksort Memory: 25kB
- 6 Buffers: shared hit=148
- 7 -> HashAggregate (cost=458.21..474.26 rows=1070 width=72) (actual time=10.966..10.979 rows=10 loops=1)
- 8 Group Key: c.category_id
- 9 Batches: 1 Memory Usage: 73kB
- 10 Buffers: shared hit=148
- 11 -> Hash Join (cost=199.04..444.47 rows=2748 width=46) (actual time=3.828..9.543 rows=6662 loops=1)
- 12 Hash Cond: (p.category_id = c.category_id)
- 13 Buffers: shared hit=148
- 14 -> Hash Join (cost=164.96..403.15 rows=2748 width=14) (actual time=3.311..7.831 rows=6662 loops=1)
- 15 Hash Cond: (oi.product_id = p.product_id)
- 16 Buffers: shared hit=147
- 17 -> Hash Join (cost=144.46..375.38 rows=2748 width=14) (actual time=2.841..6.120 rows=6662 loops=1)
- 18 Hash Cond: (oi.order_id = o.order_id)
- 19 Buffers: shared hit=140
- 20 -> Seq Scan on order_items o (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)
- 21 Buffers: shared hit=100
- 22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)
- 23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB
- 24 Buffers: shared hit=40

Results 1 ×

Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT c.cust_id

Enter a SQL query to filter results (use Ctrl+Space)

AZ QUERY PLAN

20

→ Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)

Buffers: shared hit=100

21

→ Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)

Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB

Buffers: shared hit=40

22

→ Seq Scan on orders o (cost=0.00..131.68 rows=1023 width=8) (actual time=0.023..1.672 rows=2483 loops=1)

Filter: ((order_status = ANY ('(paid,shipped,delivered)';text[])) AND ((order_ts)::date >= (CURRENT_DATE - 90)))

Rows Removed by Filter: 1377

Buffers: shared hit=40

23

→ Hash (cost=13.00..13.00 rows=600 width=16) (actual time=0.449..0.450 rows=600 loops=1)

Buckets: 1024 Batches: 1 Memory Usage: 37kB

Buffers: shared hit=7

24

→ Seq Scan on products p (cost=0.00..13.00 rows=600 width=16) (actual time=0.006..0.368 rows=600 loops=1)

Buffers: shared hit=7

25

→ Hash (cost=20.70..20.70 rows=1070 width=40) (actual time=0.276..0.276 rows=14 loops=1)

Buckets: 2048 Batches: 1 Memory Usage: 17kB

Buffers: shared hit=1

26

→ Seq Scan on categories c (cost=0.00..20.70 rows=1070 width=40) (actual time=0.256..0.257 rows=14 loops=1)

Buffers: shared hit=1

27

Planning:

28

Buffers: shared hit=27

29

Planning Time: 6.885 ms

30

Execution Time: 11.863 ms

비-SARG 날짜 조건은 인덱스 범위 탐색을 방해할 수 있다. 튜닝 후에는 최근 실매출 주문을 먼저 축소하고 `order_items → products → categories` 순서로 연결한다.

○ Q3. 기간/상태로 orders를 먼저 축소하고 SARG 범위 조건 사용
 — 튜닝: 최근 90일 실행을 주문만 먼저 골라 조건해야 할 성능을 줄인다.
 — [① 실행계획 확인용] 최근 주문 선택필터와 조건 계획 확인

```

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH recent_sales AS MATERIALIZED (
  SELECT order_id
  FROM ecom.orders
  WHERE order_status IN ('paid', 'shipped', 'delivered')
  AND order_ts >= CURRENT_DATE - 90
)
SELECT c.category_id,
  c.category_name,
  ROUND(SUM(oi.line_total), 2) AS revenue_90d
FROM recent_sales rs
JOIN ecom.order_items oi ON oi.order_id = rs.order_id
JOIN ecom.products p ON p.product_id = oi.product_id
JOIN ecom.categories c ON c.category_id = p.category_id
GROUP BY c.category_id, c.category_name
ORDER BY revenue_90d DESC, c.category_id
LIMIT 10;
  
```

— 최근 주문을 먼저 계산해 저장하는 CTE
— 컬럼을 변환하지 않는 최근 90일 조건

```

-- SELECT c.category_id,
      c.category_name,
      ROUND(SUM(oi.line_total), 2) AS revenue_90d
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
JOIN ecom.products p ON p.product_id = oi.product_id
JOIN ecom.categories c ON c.category_id = p.category_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
      AND o.order_ts::date >= CURRENT_DATE - 90
GROUP BY c.category_id, c.category_name
ORDER BY revenue_90d DESC, c.category_id
LIMIT 10;

```

categories 1 X

SELECT c.category_id, c.category_name, ROUND(SUM(oi. Enter a SQL expression to filter results

	123 category_id	AZ category_name	123 revenue_90d
1	13	Outdoor	758,672.65
2	2	Phones	541,480.74
3	6	Appliances	138,788.46
4	14	Fitness	125,711.82
5	11	Shoes	124,829.38
6	7	Cookware	117,640.32
7	4	Audio	112,653.77
8	3	Laptops	109,500.6
9	9	Men	99,046.69
10	10	Women	96,304.36












categories 1

WITH recent_sales AS MATERIALIZED (

SELECT order_id
 FROM ecom.orders
 WHERE order_status IN ('paid', 'shipped', 'delivered')
 AND order_ts >= CURRENT_DATE - 90
)
 SELECT c.category_id, c.category_name,
 ROUND(SUM(oi.line_total), 2) AS revenue_90d
 FROM recent_sales rs
 JOIN ecom.order_items oi ON oi.order_id = rs.order_id
 JOIN ecom.products p ON p.product_id = oi.product_id
 JOIN ecom.categories c ON c.category_id = p.category_id
 GROUP BY c.category_id, c.category_name
 ORDER BY revenue_90d DESC, c.category_id
 LIMIT 10;

categories 1

WITH recent_sales AS MATERIALIZED (SELECT order_id | Enter a SQL expression to filter results

	123 category_id	AZ category_name	123 revenue_90d
1	13	Outdoor	758,672.65
2	2	Phones	541,480.74
3	6	Appliances	138,788.46
4	14	Fitness	125,711.82
5	11	Shoes	124,829.38
6	7	Cookware	117,640.32
7	4	Audio	112,653.77
8	3	Laptops	109,500.6
9	9	Men	99,046.69
10	10	Women	96,304.36

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH recent_sales	
Grid	
1 Limit (cost=659.69..659.71 rows=10 width=72) (actual time=11.383..11.387 rows=10 loops=1)	
2 Buffers: shared hit=120 read=9	
3 CTE recent_sales	
4 -> Index Only Scan using idx_orders_sales_ts_order on orders (cost=0.28..111.02 rows=2442 width=8) (actual time=0.413..1.477 rows=10 loops=1)	
5 Index Cond: (order_ts >= (CURRENT_DATE - 90))	
6 Heap Fetches: 0	
7 Buffers: shared hit=12 read=9	
8 -> Sort (cost=548.67..551.34 rows=1070 width=72) (actual time=11.382..11.385 rows=10 loops=1)	
9 Sort Key: (round(sum(oi.line_total), 2)) DESC, c.category_id	
10 Sort Method: quicksort Memory: 25kB	
11 Buffers: shared hit=120 read=9	
12 -> HashAggregate (cost=509.50..525.55 rows=1070 width=72) (actual time=11.354..11.369 rows=10 loops=1)	
13 Group Key: c.category_id	
14 Batches: 1 Memory Usage: 73kB	
15 Buffers: shared hit=120 read=9	
16 -> Hash Join (cost=133.94..476.70 rows=6559 width=46) (actual time=2.623..9.671 rows=6662 loops=1)	
17 Hash Cond: (p.category_id = c.category_id)	
18 Buffers: shared hit=120 read=9	
19 -> Hash Join (cost=99.87..425.34 rows=6559 width=14) (actual time=2.587..8.147 rows=6662 loops=1)	
20 Hash Cond: (oi.product_id = p.product_id)	
21 Buffers: shared hit=119 read=9	
22 -> Hash Join (cost=79.37..387.50 rows=6559 width=14) (actual time=2.372..6.349 rows=6662 loops=1)	
23 Hash Cond: (oi.order_id = rs.order_id)	
24 Buffers: shared hit=112 read=9	
25 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.016..1.415 rows=10367 loops=1)	
26 Buffers: shared hit=100	
27 -> Hash (cost=48.84..48.84 rows=2442 width=8) (actual time=2.335..2.335 rows=2483 loops=1)	
28 Buckets: 4096 Batches: 1 Memory Usage: 129kB	
29 Buffers: shared hit=12 read=9	
30 -> CTE Scan on recent_sales rs (cost=0.00..48.84 rows=2442 width=8) (actual time=0.414..2.010 rows=2483 loops=1)	
31 Buffers: shared hit=12 read=9	
32 -> Hash (cost=13.00..13.00 rows=600 width=16) (actual time=0.194..0.194 rows=600 loops=1)	
33 Buckets: 1024 Batches: 1 Memory Usage: 37kB	
34 Buffers: shared hit=7	
35 -> Seq Scan on products p (cost=0.00..13.00 rows=600 width=16) (actual time=0.008..0.101 rows=600 loops=1)	
36 Buffers: shared hit=7	
37 -> Hash (cost=20.70..20.70 rows=1070 width=40) (actual time=0.019..0.019 rows=14 loops=1)	
38 Buckets: 2048 Batches: 1 Memory Usage: 17kB	
39 Buffers: shared hit=1	
40 -> Seq Scan on categories c (cost=0.00..20.70 rows=1070 width=40) (actual time=0.008..0.010 rows=14 loops=1)	
41 Buffers: shared hit=1	
Planning:	
43 Buffers: shared hit=64	
44 Planning Time: 2.458 ms	
45 Execution Time: 11.534 ms	

구분	Orders 접근 방식	Join 방식	Buffers	Execution Time
튜닝 전	Seq Scan	Hash Join	hit=148	11.863 ms
튜닝 후	Index Only Scan	Hash Join	hit=120/read=9	11.534 ms

Top 10 결과 및 해석: Outdoor가 758,672.65로 1위였으며 결과는 동일하고 실행시간은 2.8% 단축되었다.

6. Q4 - 제품별 누적매출 RANK Top 20

요청사항

제품별 누적매출을 먼저 계산하고 RANK() 로 상위 20개 제품을 제공한다.

Q4 튜닝 전

ecom *<postgres 4> Script-10 X <postgres 4> Script-11	
-- Q4. 제품별 누적매출 RANK() Top 20	
-- 문제점: 600개 제품 각각에 대해 매출 상위 서비스를 실행한다.	
-- [Q] 실행계획 확인용] 번째 SubPlan의 Loops와 실행시간 확인	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)	
WITH product_revenue AS (	
SELECT p.product_id,	
p.product_name,	
COALESCE((	
SELECT SUM(oi.line_total)	
FROM ecom.order_items oi	
JOIN ecom.orders o ON o.order_id = oi.order_id	
WHERE oi.product_id = p.product_id	
AND o.order_status IN ('paid', 'shipped', 'delivered')	
), 0) AS revenue	
FROM ecom.products p	
), ranked AS (	
SELECT product_id,	
product_name,	
revenue,	
RANK() OVER (ORDER BY revenue DESC) AS revenue_rank	
FROM product_revenue	
WHERE revenue > 0	
SELECT product_id, product_name, ROUND(revenue, 2) AS revenue, revenue_rank	
FROM ranked	
WHERE revenue_rank <= 20	
ORDER BY revenue_rank, product_id;	
Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH product	
Grid	
1 Sort (cost=158635.79..158636.29 rows=200 width=59) (actual time=36.685..36.687 rows=20 loops=1)	
2 Sort Key: ranked.revenue_rank, ranked.product_id	
3 Sort Method: quicksort Memory: 26kB	
4 Buffers: shared hit=70677	
5 -> Subquery Scan on ranked (cost=126903.76..158628.14 rows=200 width=59) (actual time=36.334..36.354 rows=20 loops=1)	
6 Buffers: shared hit=70677	
7 -> WindowAgg (cost=126903.76..158627.64 rows=200 width=59) (actual time=36.332..36.349 rows=20 loops=1)	
8 Run Condition: (rank() OVER (?) <= 20)	
9 Buffers: shared hit=70677	
10 -> Sort (cost=126903.74..126904.24 rows=200 width=51) (actual time=36.305..36.308 rows=21 loops=1)	
11 Sort Key: (COALESCE((SubPlan 1), '0'::numeric)) DESC	
12 Sort Method: quicksort Memory: 52kB	
13 Buffers: shared hit=70677	
14 -> Seq Scan on products p (cost=0.00..126896.10 rows=200 width=51) (actual time=1.089..35.299 rows=585 loops=1)	
15 Filter: (COALESCE((SubPlan 2), '0'::numeric) > '0'::numeric)	
16 Rows Removed by Filter: 15	

WITH product_revenue AS (	
SELECT p.product_id,	
p.product_name,	
COALESCE((	
SELECT SUM(oi.line_total)	
FROM ecom.order_items oi	
JOIN ecom.orders o ON o.order_id = oi.order_id	
WHERE oi.product_id = p.product_id	
AND o.order_status IN ('paid', 'shipped', 'delivered')	
), 0) AS revenue	
FROM ecom.products p	
), ranked AS (	
SELECT product_id, product_name, revenue,	
RANK() OVER (ORDER BY revenue DESC) AS revenue_rank	
FROM product_revenue	
WHERE revenue > 0	
SELECT product_id, product_name, ROUND(revenue, 2) AS revenue, revenue_rank	
FROM ranked	
WHERE revenue_rank <= 20	
ORDER BY revenue_rank, product_id;	
products 1 X	
WITH product_revenue AS (SELECT p.product_id, p.prod	
Grid	
1 293 Product 465 859,785.6 1	
2 455 Product 378 430,633.92 2	
3 501 Product 439 9,189.04 3	
4 272 Product 315 8,234.57 4	
5 264 Product 225 8,109.2 5	
6 528 Product 549 8,040.23 6	
7 315 Product 136 7,868.31 7	
8 69 Product 42 7,817.88 8	
9 235 Product 114 7,584.68 9	
10 533 Product 39 7,426.7 10	
11 236 Product 584 7,398.53 11	
12 63 Product 32 7,375.03 12	
13 55 Product 481 6,944.38 13	
14 137 Product 463 6,919.99 14	
15 33 Product 211 6,859.89 15	
16 449 Product 418 6,748.8 16	
17 311 Product 96 6,699.06 17	
18 181 Product 264 6,586.17 18	
19 429 Product 498 6,539.14 19	
20 81 Product 522 6,463.1 20	

7. Q5 - 고객별 RFM 분석

요청사항

고객별 최근 구매 후 경과일(최근성), 실구매 주문 수(빈도), 총매출(금액)을 제공한다.

Q5 튜닝 전

```
-- Q5. 고객별 RFM
-- 문제점: 고객마다 최근 구매·빈도·금액을 각각 다시 조회한다.
-- 화면에는 M(금액) 상위 20평만 표시한다.
-- 의미: Recency=최근 구매 후 경과일, Frequency=구매 빈도, Monetary=구매 금액이다.
--
-- (1) 실행계획 확인용] 고객별 반복 서브쿼리와 loops 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) -- 고객별 반복 서브쿼리 비용 측정
SELECT c.customer_id,
       c.full_name,
       CURRENT_DATE - (
         SELECT MAX(o.order_ts)::date
         FROM ecom.orders o
         WHERE o.customer_id = c.customer_id
         AND o.order_status IN ('paid', 'shipped', 'delivered')
       ) AS recency_days, -- R: 최근 구매 후 경과일
       (
         SELECT COUNT(o.order_id)
         FROM ecom.orders o
         WHERE o.customer_id = c.customer_id
         AND o.order_status IN ('paid', 'shipped', 'delivered')
       ) AS frequency, -- F: 구매 빈도
       (
         SELECT COALESCE(SUM(oi.line_total), 0) -- 고객의 주문상품 총매출
         FROM ecom.orders o
         JOIN ecom.order_items oi ON oi.order_id = o.order_id
         WHERE o.customer_id = c.customer_id
         AND o.order_status IN ('paid', 'shipped', 'delivered')
       ) AS monetary -- M: 구매 금액
FROM ecom.customers c
WHERE EXISTS (
  SELECT 1
  FROM ecom.orders o
  WHERE o.customer_id = c.customer_id
  AND o.order_status IN ('paid', 'shipped', 'delivered')
)
ORDER BY monetary DESC, c.customer_id
LIMIT 20;
```

QUERY PLAN	
1	Limit (cost=50416.78..51093.45 rows=20 width=65) (actual time=21.113..21.351 rows=20 loops=1)
2	Buffers: shared hit=17287
3	-> Result (cost=50416.78..150418.03 rows=3000 width=65) (actual time=21.113..21.348 rows=20 loops=1)
4	Buffers: shared hit=17287
5	-> Sort (cost=50416.78..50424.28 rows=3000 width=53) (actual time=20.749..20.753 rows=20 loops=1)
6	Sort Key: (SubPlan 4) DESC, c.customer_id
7	Sort Method: top-N heapsort Memory: 26kB
8	Buffers: shared hit=16776
9	-> Hash Join (cost=159.45..50336.95 rows=3000 width=53) (actual time=2.743..20.024 rows=2217 loops=1)
10	Hash Cond: (c.customer_id = o.customer_id)
11	Buffers: shared hit=16776
12	-> Seq Scan on customers c (cost=0.00..70.00 rows=3000 width=21) (actual time=0.033..4.299 rows=3000 loops=1)
13	Buffers: shared hit=40
14	-> Hash (cost=126.84..126.84 rows=2609 width=8) (actual time=2.045..2.046 rows=2217 loops=1)
15	Buckets: 4096 Batches: 1 Memory Usage: 119kB
16	Buffers: shared hit=40
17	-> HashAggregate (cost=100.75..126.84 rows=2609 width=8) (actual time=1.343..1.516 rows=2217 loops=1)
18	Group Key: o.customer_id
19	Batches: 1 Memory Usage: 24kB
20	Buffers: shared hit=40
21	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=8) (actual time=0.012..0.811 rows=3068 loops=1)
22	Filter: (order_status = ANY ('paid,shipped,delivered')::text[])
23	Rows Removed by Filter: 792
24	Buffers: shared hit=40
25	SubPlan 4
26	-> Aggregate (cost=16.68..16.69 rows=1 width=32) (actual time=0.006..0.006 rows=1 loops=2217)
27	Buffers: shared hit=16696
28	-> Nested Loop (cost=0.57..16.67 rows=3 width=6) (actual time=0.003..0.005 rows=4 loops=2217)
29	Buffers: shared hit=16696
30	-> Index Scan using idx_orders_customer_ts on orders o_3 (cost=0.28..8.30 rows=1 width=8) (actual time=0.002..0.002 rows=1 loops=2217)
31	Index Cond: (customer_id = c.customer_id)
32	Filter: (order_status = ANY ('paid,shipped,delivered')::text[])
33	Rows Removed by Filter: 0
34	Buffers: shared hit=7438
35	-> Index Scan using idx_order_items_order on order_items oi (cost=0.29..8.34 rows=3 width=14) (actual time=0.001..0.002 rows=3 loops=3068)
36	Index Cond: (order_id = o_3_order_id)
37	Buffers: shared hit=9258

38	SubPlan 2
39	-> Result (cost=8.30..8.31 rows=1 width=4) (actual time=0.003..0.003 rows=1 loops=20)
40	Buffers: shared hit=60
41	InitPlan 1
42	-> Limit (cost=0.28..8.30 rows=1 width=8) (actual time=0.003..0.003 rows=1 loops=20)
43	Buffers: shared hit=60
44	-> Index Scan using idx_orders_customer_ts on orders o_1 (cost=0.28..8.30 rows=1 width=8) (actual time=0.002..0.002 rows=1 loops=20)
45	Index Cond: (customer_id = c.customer_id)
46	Filter: (order_status = ANY ('paid,shipped,delivered')::text[])
47	Buffers: shared hit=60
48	SubPlan 3
49	-> Aggregate (cost=8.30..8.31 rows=1 width=8) (actual time=0.025..0.025 rows=1 loops=20)
50	Buffers: shared hit=451
51	-> Index Scan using idx_orders_customer_ts on orders o_2 (cost=0.28..8.30 rows=1 width=8) (actual time=0.016..0.023 rows=23 loops=20)
52	Index Cond: (customer_id = c.customer_id)
53	Filter: (order_status = ANY ('paid,shipped,delivered')::text[])
54	Rows Removed by Filter: 0
55	Buffers: shared hit=451
56	Planning:
57	Buffers: shared hit=27
58	Planning Time: 3.302 ms
59	Execution Time: 21.915 ms

```

-- Create the query
CREATE OR REPLACE QUERY Q1 AS
SELECT c.customer_id, c.full_name, CURRENT_DATE - (SELECT MAX(o.order_ts) FROM ecom.orders o WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS recency_days, (SELECT COUNT(o.order_id) FROM ecom.orders o WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS frequency, (SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS monetary
FROM ecom.customers c
ORDER BY monetary DESC, recency_days DESC;

-- Run the query
SELECT * FROM Q1;

```

customers 1 X

1 SELECT c.customer_id, c.full_name, CURRENT_DATE - (SELECT MAX(o.order_ts) FROM ecom.orders o WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS recency_days, (SELECT COUNT(o.order_id) FROM ecom.orders o WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS frequency, (SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS monetary

OID	customer_id	full_name	recency_days	frequency	monetary
1	8	Customer 8	2	23	35,154.22
2	18	Customer 18	1	23	31,003.34
3	18	Customer 18	3	23	30,283.04
4	14	Customer 14	6	23	29,322.59
5	16	Customer 6	0	22	28,702.23
6	13	Customer 13	2	22	28,633.41
7	2	Customer 2	8	23	28,623.31
8	1	Customer 1	3	23	28,546.26
9	20	Customer 20	0	22	28,531.13
10	9	Customer 9	1	23	28,488.91
11	17	Customer 17	8	23	27,317.53
12	24	Customer 24	0	22	27,076.74
13	13	Customer 13	4	22	26,717.57
14	30	Customer 30	0	23	24,816.39
15	4	Customer 4	1	23	24,726.24
16	12	Customer 12	4	23	22,419.91
17	19	Customer 19	0	23	22,412.27
18	22	Customer 22	1	23	22,206.6
19	7	Customer 7	1	23	22,034.39
20	29	Customer 29	0	22	21,696.95

느린 이유와 개선 방법

튜닝 전에는 고객마다 최근 구매·빈도·금액을 각각 조회한다. 튜닝 후에는 주문별 금액을 선집계하고 고객별 MAX, COUNT, SUM 을 한 번에 계산한다.

Q5 튜닝 후

Q5. 주문별 매출 선집계 후 고객별 한 번의 GROUP BY로 RFM 산출

튜닝: 고객 한 명마다 세 가지 서브쿼리를 반복하는 작업을 제거한다.

[① 실행계획 확인용] 고객별 반복 조회 대신 한 번에 집계하는지 확인

```
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH order_totals AS (
    SELECT o.order_id, o.customer_id, o.order_ts,
           SUM(oi.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.customer_id, o.order_ts
), rfm AS (
    SELECT customer_id,
           CURRENT_DATE - MAX(order_ts)::date AS recency_days, -- 최근 구매 경과일
           COUNT(order_id) AS frequency, -- 구매 주문번호 수
           SUM(order_total) AS monetary -- 고객 총매출
    FROM order_totals
    GROUP BY customer_id
)
SELECT c.customer_id, c.full_name,
       r.recency_days, r.frequency, ROUND(r.monetary, 2) AS monetary
FROM rfm r
JOIN ecom.customers c ON c.customer_id = r.customer_id
ORDER BY r.monetary DESC, c.customer_id
LIMIT 20;
```

```
WITH order_totals AS (
    SELECT o.order_id, o.customer_id, o.order_ts,
           SUM(oi.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.customer_id, o.order_ts
), rfm AS (
    SELECT customer_id, CURRENT_DATE - MAX(order_ts)::date AS recency_days,
           COUNT(order_id) AS frequency, SUM(order_total) AS monetary
    FROM order_totals
    GROUP BY customer_id
)
SELECT c.customer_id, c.full_name,
       r.recency_days, r.frequency, ROUND(r.monetary, 2) AS monetary
FROM rfm r
JOIN ecom.customers c ON c.customer_id = r.customer_id
ORDER BY r.monetary DESC, c.customer_id
LIMIT 20;
```

customers 1 X						
WITH order_totals AS (SELECT o.order_id, o.customer_id, o.order_ts, SUM(oi.line_total) AS order_total FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY o.order_id, o.customer_id, o.order_ts), rfm AS (SELECT customer_id, CURRENT_DATE - MAX(order_ts)::date AS recency_days, COUNT(order_id) AS frequency, SUM(order_total) AS monetary FROM order_totals GROUP BY customer_id) SELECT c.customer_id, c.full_name, r.recency_days, r.frequency, ROUND(r.monetary, 2) AS monetary FROM rfm r JOIN ecom.customers c ON c.customer_id = r.customer_id ORDER BY r.monetary DESC, c.customer_id LIMIT 20;						
	customer_id	AZ full_name	recency_days	frequency	monetary	
1	8	Customer 8	2	23	35,154.22	
2	16	Customer 16	1	23	31,003.24	
3	18	Customer 18	3	23	30,283.04	
4	14	Customer 14	6	23	29,322.59	
5	6	Customer 6	0	22	28,703.23	
6	13	Customer 13	2	22	28,633.41	
7	2	Customer 2	8	23	28,623.31	
8	1	Customer 1	3	23	28,546.26	
9	20	Customer 20	0	22	28,531.13	
10	9	Customer 9	1	23	28,488.91	
11	17	Customer 17	8	23	27,317.53	
12	24	Customer 24	0	22	27,075.74	
13	23	Customer 23	4	22	25,717.57	
14	30	Customer 30	0	23	24,815.39	
15	4	Customer 4	1	23	24,726.24	
16	12	Customer 12	4	23	22,419.91	
17	19	Customer 19	0	23	22,412.27	
18	22	Customer 22	1	23	22,206.5	
19	7	Customer 7	1	23	22,034.39	
20	29	Customer 29	0	22	21,696.95	

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH order_totals AS (SELECT o.order_id, o.customer_id, o.order_ts, SUM(oi.line_total) AS order_total FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY o.order_id, o.customer_id, o.order_ts), rfm AS (SELECT customer_id, CURRENT_DATE - MAX(order_ts)::date AS recency_days, COUNT(order_id) AS frequency, SUM(order_total) AS monetary FROM order_totals GROUP BY customer_id) SELECT c.customer_id, c.full_name, r.recency_days, r.frequency, ROUND(r.monetary, 2) AS monetary FROM rfm r JOIN ecom.customers c ON c.customer_id = r.customer_id ORDER BY r.monetary DESC, c.customer_id LIMIT 20;	
1	Limit (cost=595.46..595.51 rows=20 width=97) (actual time=13.181..13.185 rows=20 loops=1)
2	Buffers: shared hit=180
3	-> Sort (cost=595.46..595.96 rows=200 width=97) (actual time=13.180..13.183 rows=20 loops=1)
4	Sort Key: r.monetary DESC, c.customer_id
5	Sort Method: top-N heapsort Memory: 28kB
6	Buffers: shared hit=180
7	-> Hash Join (cost=511.75..590.14 rows=200 width=97) (actual time=11.699..12.710 rows=2217 loops=1)
8	Hash Cond: (c.customer_id = r.customer_id)
9	Buffers: shared hit=180
10	-> Seq Scan on customers c (cost=0.00..70.00 rows=3000 width=21) (actual time=0.010..0.324 rows=3000 loops=1)
11	Buffers: shared hit=40
12	-> Hash (cost=509.25..509.25 rows=200 width=52) (actual time=11.675..11.677 rows=2217 loops=1)
13	Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 171kB
14	Buffers: shared hit=140
15	-> Subquery Scan on r (cost=503.25..509.25 rows=200 width=52) (actual time=10.032..11.245 rows=2217 loops=1)
16	Buffers: shared hit=140
17	-> HashAggregate (cost=503.25..507.25 rows=200 width=52) (actual time=10.031..11.010 rows=2217 loops=1)
18	Group Key: o.customer_id
19	Batches: 1 Memory Usage: 1153kB
20	Buffers: shared hit=140
21	-> HashAggregate (cost=403.54..441.89 rows=3068 width=56) (actual time=7.888..8.841 rows=3068 loops=1)
22	Group Key: o.order_id
23	Batches: 1 Memory Usage: 1393kB
24	Buffers: shared hit=140
25	-> Hash Join (cost=131.43..362.34 rows=8240 width=30) (actual time=1.422..5.116 rows=8230 loops=1)
26	Hash Cond: (oi.order_id = o.order_id)
27	Buffers: shared hit=140
28	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.013..1.160 rows=10367 loops=1)
29	Buffers: shared hit=100
30	-> Hash (cost=93.08..93.08 rows=3068 width=24) (actual time=1.389..1.389 rows=3068 loops=1)
31	Buckets: 4096 Batches: 1 Memory Usage: 200kB
32	Buffers: shared hit=40
33	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=24) (actual time=0.016..0.940 rows=3068 loops=1)
34	Filter: (order_status = ANY ('{paid,shipped,delivered}':text[]))
35	Rows Removed by Filter: 792
36	Buffers: shared hit=40
37	Planning:
38	Buffers: shared hit=18
39	Planning Time: 0.729 ms
40	Execution Time: 13.785 ms

구분	집계 방식	Buffers	Execution Time	전후 결과 동일 여부
튜닝 전	고객별 상관 서브쿼리	hit=17,287	21.915 ms	-
튜닝 후	주문 선집계 후 고객 GROUP BY	hit=180	13.785 ms	동일

RFM 결과 해석: Customer 8이 최근성 2일·빈도 23회·금액 35,154.22로 최고 금액 고객이며 실행시간은 37.1% 단축되었다.

8. Q6 - 첫 구매 후 30일 내 재구매율

요청사항

실구매 고객 중 첫 구매 후 30일 안에 추가 실구매가 있었던 고객의 비율을 제공한다.


Q6 튜닝 전



느린 이유와 개선 방법

튜닝 전에는 고객별 첫 구매 이후 주문을 **EXISTS** 로 반복 탐색한다. 튜닝 후에는 Window Function으로 첫 구매시각을 표시하고 고객별 **BOOL_OR** 로 재구매 여부를 한 번 집계한다.

Q6 튜닝 후



구분	구매고객	30일 내 재구매고객	재구매율	Execution Time
튜닝 전	2,217	226	10.19%	7.881 ms
튜닝 후	2,217	226	10.19%	6.166 ms

결과 해석: 재구매율은 전후 동일하며 Window와 BOOL_OR 집계로 실행시간이 21.8% 단축되었다.

9. Q7 - 재주문 임계치 미만 상품

요청사항

qty_on_hand < reorder_point 인 상품과 부족수량을 제공한다.

Q7 튜닝 전




```
-- Q8. 평점 4.5 이상, 리뷰 50개 이상 효자상품
-- 문제점: 상품마다 AVG와 COUNT를 SELECT와 WHERE에서 반복 계산한다.

-- [① 실행계획 확인용] 제품별 리뷰 반복 집계 횟수 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
SELECT p.product_id,
       p.product_name,
       ROUND((SELECT AVG(r.rating) FROM ecom.reviews r
              WHERE r.product_id = p.product_id), 2) AS avg_rating, -- 제품별 평균평점
       (SELECT COUNT(r.review_id) FROM ecom.reviews r
        WHERE r.product_id = p.product_id) AS review_count -- 제품별 리뷰 수
FROM ecom.products p
WHERE (SELECT AVG(r.rating) FROM ecom.reviews r
      WHERE r.product_id = p.product_id) >= 4.5
      AND (SELECT COUNT(r.review_id) FROM ecom.reviews r
          WHERE r.product_id = p.product_id) >= 50
ORDER BY avg_rating DESC, review_count DESC, p.product_id;
```

SQL Query Results:

product_id	product_name	avg_rating	review_count
57	Product 491	4.85	160
229	Product 464	4.83	160
163	Product 253	4.81	160
263	Product 285	4.79	160
426	Product 258	4.79	160
243	Product 395	4.78	160
268	Product 25	4.77	160
297	Product 75	4.76	160
481	Product 189	4.76	160
356	Product 556	4.75	161
178	Product 113	4.74	160
114	Product 262	4.69	160

Query Plan (EXPLAIN ANALYZE):

Step	Operation	Cost	Time	Rows	Width	Loops
11	Buffers: shared hit=66					
12	-> Bitmap Heap Scan on reviews r	4.40..25.39	0.011..0.022	160	4	12
13	Recheck Cond: (product_id = p.product_id)					
14	Heap Blocks: exact=32					
15	Buffers: shared hit=66					
16	-> Bitmap Index Scan on reviews_product_id_customer_id_key	0.00..4.40	0.009..0.009	160	16	12
17	Index Cond: (product_id = p.product_id)					
18	Buffers: shared hit=34					
19	SubPlan 2					
20	-> Aggregate	25.43..25.44	0.034..0.034	1	8	12
21	Buffers: shared hit=66					
22	-> Bitmap Heap Scan on reviews r_1	4.40..25.39	0.011..0.022	160	8	12
23	Recheck Cond: (product_id = p.product_id)					
24	Heap Blocks: exact=32					
25	Buffers: shared hit=66					
26	-> Bitmap Index Scan on reviews_product_id_customer_id_key	0.00..4.40	0.008..0.008	160	16	12
27	Index Cond: (product_id = p.product_id)					
28	Buffers: shared hit=34					
29	SubPlan 4					
30	-> Aggregate	25.43..25.44	0.005..0.005	1	8	600
31	Buffers: shared hit=1360					
32	-> Bitmap Heap Scan on reviews r_3	4.40..25.39	0.003..0.003	3	8	600
33	Recheck Cond: (product_id = p.product_id)					
34	Heap Blocks: exact=150					
35	Buffers: shared hit=1360					
36	-> Bitmap Index Scan on reviews_product_id_customer_id_key	0.00..4.40	0.002..0.002	3	16	600
37	Index Cond: (product_id = p.product_id)					
38	Buffers: shared hit=1210					
39	SubPlan 3					
40	-> Aggregate	25.43..25.44	0.041..0.041	1	32	12
41	Buffers: shared hit=66					
42	-> Bitmap Heap Scan on reviews r_2	4.40..25.39	0.012..0.024	160	4	12
43	Recheck Cond: (product_id = p.product_id)					
44	Heap Blocks: exact=32					
45	Buffers: shared hit=66					
46	-> Bitmap Index Scan on reviews_product_id_customer_id_key	0.00..4.40	0.009..0.009	160	16	12
47	Index Cond: (product_id = p.product_id)					
48	Buffers: shared hit=34					
49	Planning:					
50	Buffers: shared hit=206 dirtied=7					
51	Planning Time: 4.214 ms					
52	Execution Time: 4.551 ms					

느린 이유와 개선 방법

튜닝 전에는 제품별 평균과 건수를 SELECT와 WHERE에서 반복 계산한다. 튜닝 후에는 리뷰를 한 번 읽고 **GROUP BY** 와 **HAVING** 으로 조건을 적용한다.

Q8 튜닝 후

SQL Query Results:

product_id	product_name	avg_rating	review_count
57	Product 491	4.85	160
229	Product 464	4.83	160
163	Product 253	4.81	160
263	Product 285	4.79	160
426	Product 258	4.79	160
243	Product 395	4.78	160
268	Product 25	4.77	160
297	Product 75	4.76	160
481	Product 189	4.76	160
356	Product 556	4.75	161
178	Product 113	4.74	160
114	Product 262	4.69	160

Query Plan (EXPLAIN ANALYZE):

Step	Operation	Cost	Time	Rows	Width	Loops
1	Sort	95.27..95.44	0.946..0.947	12	59	1
2	Sort Key: (round(avg(r.rating), 2)) DESC, (count(r.review_id)) DESC, p.product_id					
3	Sort Method: quicksort Memory: 25kB					
4	Buffers: shared hit=28					
5	-> HashAggregate	82.57..93.24	0.908..0.935	12	59	1
6	Group Key: p.product_id					
7	Filter: ((avg(r.rating) >= 4.5) AND (count(r.review_id) >= 50))					
8	Batches: 1 Memory Usage: 73kB					
9	Rows Removed by Filter: 118					
10	Buffers: shared hit=28					
11	-> Hash Join	20.50..67.28	0.174..0.667	2039	31	1
12	Hash Cond: (r.product_id = p.product_id)					
13	Buffers: shared hit=28					
14	-> Seq Scan on reviews r	0.00..41.39	0.012..0.225	2039	20	1
15	Buffers: shared hit=21					
16	-> Hash	13.00..13.00	0.149..0.149	600	19	1
17	Buckets: 1024 Batches: 1 Memory Usage: 39kB					
18	Buffers: shared hit=7					
19	-> Seq Scan on products p	0.00..13.00	0.006..0.075	600	19	1
20	Buffers: shared hit=7					
21	Planning:					
22	Buffers: shared hit=31 read=4					
23	Planning Time: 2.005 ms					
24	Execution Time: 1.016 ms					

SQL Query Results:

product_id	product_name	avg_rating	review_count
57	Product 491	4.85	160
229	Product 464	4.83	160
163	Product 253	4.81	160
263	Product 285	4.79	160
426	Product 258	4.79	160
243	Product 395	4.78	160
268	Product 25	4.77	160
297	Product 75	4.76	160
481	Product 189	4.76	160
356	Product 556	4.75	161
178	Product 113	4.74	160
114	Product 262	4.69	160

구분	Reviews 접근 방식	Buffers	Execution Time	조건 충족 상품 수
튜닝 전	반복 Bitmap Scan	hit=1,565	4.551 ms	12개
튜닝 후	Seq Scan + 1회 집계	hit=28	1.016 ms	12개

결과 해석: 조건 충족 상품은 12개이며 1위 Product 491은 평점 4.85·리뷰 160개이고 실행시간은 77.7% 단축되었다.

11. Q9 - 쿠폰 사용 여부별 AOV

요청사항

쿠폰 사용 주문과 미사용 주문의 주문당 평균 금액을 비교한다.

Q9 튜닝 전

```

-- Q9. 쿠폰 사용 여부별 평균 주문금액
-- 문제점: 상세 행 조인 후 COUNT(DISTINCT)로 주문 수를 복원한다.
-- 의미: AOV는 전체 매출을 중복 없는 주문 수로 나눈 주문당 평균금액이다.

-- [① 실행계획 확인용] 상세행 조인과 DISTINCT 집계 비용 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
SELECT CASE WHEN o.coupon_code IS NULL THEN '미사용' ELSE '사용' END AS coupon_group, -- 쿠폰 여부 분류
COUNT(DISTINCT o.order_id) AS order_count, -- 중복을 제거한 주문 수
ROUND(SUM(oi.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov -- 주문당 평균금액
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY 1
ORDER BY 1;
```

SELECT CASE WHEN o.coupon_code IS NULL THEN '미사용' ELSE '사용' END AS coupon_group,
COUNT(DISTINCT o.order_id) AS order_count,
ROUND(SUM(oi.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY 1
ORDER BY 1;

1
2

미사용	2,307	619.55
사용	761	1,694.79

Results 1 X

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT CASE WHEN o.coupon_code IS NULL THEN '미사용' ELSE '사용' END AS coupon_group, COUNT(DISTINCT o.order_id) AS order_count, ROUND(SUM(oi.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY 1 ORDER BY 1;

Grid

1

GroupAggregate (cost=898.29..980.71 rows=1 width=72) (actual time=17.358..17.942 rows=2 loops=1)

2

Group Key: (CASE WHEN (o.coupon_code IS NULL) THEN '미사용'::text ELSE '사용'::text END)

3

Buffers: shared hit=143

4

-> Sort (cost=898.29..918.89 rows=8240 width=46) (actual time=16.192..16.553 rows=8230 loops=1)

5

Sort Key: (CASE WHEN (o.coupon_code IS NULL) THEN '미사용'::text ELSE '사용'::text END), o.order_id

6

Sort Method: quicksort Memory: 750kB

7

Buffers: shared hit=143

8

-> Hash Join (cost=131.43..362.34 rows=8240 width=46) (actual time=1.732..9.532 rows=8230 loops=1)

9

Hash Cond: (oi.order_id = o.order_id)

10

Buffers: shared hit=140

11

-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.006..5.943 rows=10367 loops=1)

12

Buffers: shared hit=100

13

-> Hash (cost=93.08..93.08 rows=3068 width=15) (actual time=1.702..1.703 rows=3068 loops=1)

14

Buckets: 4096 Batches: 1 Memory Usage: 158kB

15

Buffers: shared hit=40

16

-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=15) (actual time=0.012..1.193 rows=3068 loops=1)

17

Filter: (order_status = ANY ('{paid,shipped,delivered}'::text[]))

18

Rows Removed by Filter: 792

19

Buffers: shared hit=40

20

Planning:

21

Buffers: shared hit=150 dirtied=1

22

Planning Time: 4.284 ms

23

Execution Time: 17.993 ms

느린 이유와 개선 방법

상세행 조인 후에는 주문 수 복원을 위해 COUNT(DISTINCT) 가 필요하다. 튜닝 후에는 주문별 금액을 먼저 계산한 뒤 쿠폰 사용 여부로 그룹핑해 AVG(order_total) 을 계산한다.

Q9 튜닝 후

```

-- Q9. 주문별 매출 선집계로 DISTINCT 제거
-- 튜닝: 주문별 금액을 먼저 한 행으로 만든 뒤 그룹별 AVG(order_total)을 계산한다.
-- [① 실행계획 확인용] 주문별 선집계 후 AVG 계산 계획 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH order_totals AS (
SELECT o.order_id,
(o.coupon_code IS NOT NULL) AS used_coupon, -- 쿠폰 사용 여부를 TRUE/FALSE로 변환
SUM(oi.line_total) AS order_total -- 주문별 총금액
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY o.order_id, o.coupon_code
)
SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group,
COUNT(order_id) AS order_count,
ROUND(AVG(order_total), 2) AS aov -- 주문별 금액의 평균
FROM order_totals
GROUP BY used_coupon
ORDER BY coupon_group;
```

Results 1 X

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH order_totals AS (SELECT o.order_id, (o.coupon_code IS NOT NULL) AS used_coupon, SUM(oi.line_total) AS order_total FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY o.order_id, o.coupon_code) SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group, COUNT(order_id) AS order_count, ROUND(AVG(order_total), 2) AS aov FROM order_totals GROUP BY used_coupon ORDER BY coupon_group;

Grid

1

Sort (cost=495.62..495.63 rows=2 width=73) (actual time=9.883..9.885 rows=2 loops=1)

2

Sort Key: (CASE WHEN ((o.coupon_code IS NOT NULL)) THEN '사용'::text ELSE '미사용'::text END)

3

Sort Method: quicksort Memory: 25kB

4

Buffers: shared hit=140

5

-> HashAggregate (cost=495.58..495.61 rows=2 width=73) (actual time=9.788..9.791 rows=2 loops=1)

6

Group Key: (o.coupon_code IS NOT NULL)

7

Batches: 1 Memory Usage: 24kB

8

Buffers: shared hit=140

9

-> HashAggregate (cost=403.54..441.89 rows=3068 width=48) (actual time=8.547..9.389 rows=3068 loops=1)

10

Group Key: o.order_id

11

Batches: 1 Memory Usage: 1393kB

12

Buffers: shared hit=140

13

-> Hash Join (cost=131.43..362.34 rows=8240 width=21) (actual time=1.424..5.397 rows=8230 loops=1)

14

Hash Cond: (oi.order_id = o.order_id)

15

Buffers: shared hit=140

16

-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.014..1.794 rows=10367 loops=1)

17

Buffers: shared hit=100

18

-> Hash (cost=93.08..93.08 rows=3068 width=15) (actual time=1.349..1.350 rows=3068 loops=1)

19

Buckets: 4096 Batches: 1 Memory Usage: 158kB

20

Buffers: shared hit=40

21

-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=15) (actual time=0.008..0.945 rows=3068 loops=1)

22

Filter: (order_status = ANY ('{paid,shipped,delivered}'::text[]))

23

Rows Removed by Filter: 792

24

Buffers: shared hit=40

25

Planning:

26

Buffers: shared hit=22 dirtied=1

27

Planning Time: 0.613 ms

28

Execution Time: 10.057 ms

WITH order_totals AS (
SELECT o.order_id, (o.coupon_code IS NOT NULL) AS used_coupon,
SUM(oi.line_total) AS order_total
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY o.order_id, o.coupon_code
)
SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group,
COUNT(order_id) AS order_count, ROUND(AVG(order_total), 2) AS aov
FROM order_totals
GROUP BY used_coupon
ORDER BY coupon_group;

Results 1 X

WITH order_totals AS (SELECT o.order_id, (o.coupon_code IS NOT NULL) AS used_coupon, SUM(oi.line_total) AS order_total FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY o.order_id, o.coupon_code) SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group, COUNT(order_id) AS order_count, ROUND(AVG(order_total), 2) AS aov FROM order_totals GROUP BY used_coupon ORDER BY coupon_group;

Grid

1

미사용

2,307

619.55

2

사용

761

1,694.79

그룹	주문 수	AOV	해석
쿠폰 미사용	2,307	619.55	비교 기준
쿠폰 사용	761	1,694.79	미사용 대비 약 2.74배

구분	Buffers	Execution Time
튜닝 전	hit=143	17.993 ms
튜닝 후	hit=140	10.057 ms

쿠폰 사용과 높은 AOV의 상관관계만 확인할 수 있으며, 쿠폰의 인과효과를 의미하지는 않는다.

12. Q10 - 누적매출 상위 1% 고객의 최근 60일 매출

요청사항

전체 고객 3,000명을 누적매출로 정렬해 상위 1%인 정확히 30명을 먼저 선정하고, 선정된 고객의 최근 60일 매출을 제공한다.

Q10 튜닝 전

<pre> -- Q10. 누적매출 상위 1% 고객의 최근 60일 매출 -- 문제점: 3,000명 각각의 누적매출을 상관 서브쿼리로 계산하고, -- 선정된 상위 30명의 최근 60일 매출도 다시 상관 조희한다. -- 기준: 전체 고객 3,000명의 누적매출로 정확히 30명을 먼저 선정한다. -- 주의: 누적매출로 30명을 먼저 선정한 다음, 그 고객들의 최근 60일 매출을 표시한다. -- -- [① 실행계획 확인용] 고객별 반복 집계와 최근 60일 SubPlan 비용 확인 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH lifetime_sales AS (SELECT c.customer_id, c.full_name, (SELECT COALESCE(SUM(oi.line_total), 0) -- 고객 한 명의 누적매출 계산 FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS lifetime_revenue FROM ecom.customers c), ranked AS (SELECT customer_id, full_name, lifetime_revenue, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count -- 전체 고객 수를 각 행에 표시 FROM lifetime_sales) SELECT r.customer_id, r.full_name, r.lifetime_rank, ROUND(r.lifetime_revenue, 2) AS lifetime_revenue, ROUND((SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = r.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts >= now() - INTERVAL '60 days' -- 선정 고객의 최근 60일 매출), 2) AS revenue_60d FROM ranked r WHERE r.lifetime_rank <= CEIL(r.customer_count * 0.01) -- 전체 고객의 상위 1%, 정확히 30명 ORDER BY r.lifetime_rank;</pre>	<pre> -- 고객별 반복 집계 비용 측정 -- 고객별 누적매출 CTE</pre>
---	--

<pre> WITH lifetime_sales AS (SELECT c.customer_id, c.full_name, (SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS lifetime_revenue FROM ecom.customers c), ranked AS (SELECT customer_id, full_name, lifetime_revenue, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM lifetime_sales) SELECT r.customer_id, r.full_name, r.lifetime_rank, ROUND(r.lifetime_revenue, 2) AS lifetime_revenue, ROUND((SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = r.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts >= now() - INTERVAL '60 days'), 2) AS revenue_60d FROM ranked r WHERE r.lifetime_rank <= CEIL(r.customer_count * 0.01) ORDER BY r.lifetime_rank;</pre>	<pre> -- 101 번째 쿼리 3989 줄의 실행 계획</pre>
---	--

customers 1 X					
WITH lifetime_sales AS (SELECT c.customer_id, c.full_name, (SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS lifetime_revenue FROM ecom.customers c), ranked AS (SELECT customer_id, full_name, lifetime_revenue, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM lifetime_sales) SELECT r.customer_id, r.full_name, r.lifetime_rank, ROUND(r.lifetime_revenue, 2) AS lifetime_revenue, ROUND((SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = r.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts >= now() - INTERVAL '60 days'), 2) AS revenue_60d FROM ranked r WHERE r.lifetime_rank <= CEIL(r.customer_count * 0.01) ORDER BY r.lifetime_rank;					
id	plan	cost	width	rows	loops
1	Sort	167358.09..167360.59	93	1000	1
2	Sort Key: r.lifetime_rank				
3	Sort Method: quicksort				
4	Sort Buffers: shared hit=21777				
5	Subquery Scan on r	100456.54..167308.26	93	1000	1
6	Filter: ((r.lifetime_rank)::numeric <= ceil(((r.customer_count)::numeric * 0.01)))				
7	Rows Removed by Filter: 2970				
8	Sort Buffers: shared hit=21777				
9	WindowAgg	100456.54..150539.51	69	3000	1
10	Sort Buffers: shared hit=19085				
11	WindowAgg	50309.53..100435.76	61	3000	1
12	Sort Buffers: shared hit=19085				
13	Sort	50309.51..50317.01	53	3000	1
14	Sort Key: ((SubPlan 2)) DESC, c.customer_id				
15	Sort Method: quicksort				
16	Sort Buffers: shared hit=19085				
17	Seq Scan on customers c	0.00..50136.25	53	3000	30
18	Sort Buffers: shared hit=19085				
19	SubPlan 2				
20	Aggregate	16.68..16.69	32	1	3000
21	Sort Buffers: shared hit=19045				
22	Nested Loop	0.57..16.67	6	3	3000
23	Sort Buffers: shared hit=19045				
24	Index Scan using idx_orders_customer_ts on orders o_1	0.28..8.30	8	1	3000
25	Index Cond: (customer_id = c.customer_id)				
26	Filter: (order_status = ANY ('paid,shipped,delivered'))::text[]				
27	Rows Removed by Filter: 0				
28	Sort Buffers: shared hit=9787				
29	Index Scan using idx_order_items_order on order_items oi_1	0.29..8.34	3	1	3000
30	Index Cond: (order_id = o_1.order_id)				
31	Sort Buffers: shared hit=9258				

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH lifetime_sales AS (SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered')) AS lifetime_revenue FROM ecom.customers c), ranked AS (SELECT customer_id, full_name, lifetime_revenue, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM lifetime_sales) SELECT r.customer_id, r.full_name, r.lifetime_rank, ROUND(r.lifetime_revenue, 2) AS lifetime_revenue, ROUND((SELECT COALESCE(SUM(oi.line_total), 0) FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.customer_id = r.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts >= now() - INTERVAL '60 days'), 2) AS revenue_60d FROM ranked r WHERE r.lifetime_rank <= CEIL(r.customer_count * 0.01) ORDER BY r.lifetime_rank;	
id	plan
1	Sort (cost=167358.09..167360.59 rows=1000 width=93) (actual time=22.813..22.819 rows=30 loops=1)
2	Sort Key: r.lifetime_rank
3	Sort Method: quicksort Memory: 27kB
4	Sort Buffers: shared hit=21777
5	-> Subquery Scan on r (cost=100456.54..167308.26 rows=1000 width=93) (actual time=19.459..22.799 rows=30 loops=1)
6	Filter: ((r.lifetime_rank)::numeric <= ceil(((r.customer_count)::numeric * 0.01)))
7	Rows Removed by Filter: 2970
8	Sort Buffers: shared hit=21777
9	-> WindowAgg (cost=100456.54..150539.51 rows=3000 width=69) (actual time=19.321..19.811 rows=3000 loops=1)
10	Sort Buffers: shared hit=19085
11	-> WindowAgg (cost=50309.53..100435.76 rows=3000 width=61) (actual time=17.614..18.614 rows=3000 loops=1)
12	Sort Buffers: shared hit=19085
13	-> Sort (cost=50309.51..50317.01 rows=3000 width=53) (actual time=17.607..17.779 rows=3000 loops=1)
14	Sort Key: ((SubPlan 2)) DESC, c.customer_id
15	Sort Method: quicksort Memory: 235kB
16	Sort Buffers: shared hit=19085
17	-> Seq Scan on customers c (cost=0.00..50136.25 rows=3000 width=53) (actual time=0.395..16.115 rows=3000 loops=1)
18	Sort Buffers: shared hit=19085
19	SubPlan 2
20	-> Aggregate (cost=16.68..16.69 rows=1 width=32) (actual time=0.004..0.004 rows=1 loops=3000)
21	Sort Buffers: shared hit=19045
22	-> Nested Loop (cost=0.57..16.67 rows=3 width=6) (actual time=0.002..0.004 rows=3 loops=3000)
23	Sort Buffers: shared hit=19045
24	-> Index Scan using idx_orders_customer_ts on orders o_1 (cost=0.28..8.30 rows=1 width=8) (actual time=0.004..0.004 rows=1 loops=3000)
25	Index Cond: (customer_id = c.customer_id)
26	Filter: (order_status = ANY ('paid,shipped,delivered'))::text[]
27	Rows Removed by Filter: 0
28	Sort Buffers: shared hit=9787
29	-> Index Scan using idx_order_items_order on order_items oi_1 (cost=0.29..8.34 rows=3 width=14) (actual time=0.29..0.29 rows=3 loops=3000)
30	Index Cond: (order_id = o_1.order_id)
31	Sort Buffers: shared hit=9258

32	SubPlan 1
33	-> Aggregate (cost=16.69..16.70 rows=1 width=32) (actual time=0.070..0.071 rows=1 loops=30)
34	Sort Buffers: shared hit=2692
35	-> Nested Loop (cost=0.57..16.68 rows=3 width=6) (actual time=0.006..0.063 rows=63 loops=30)
36	Sort Buffers: shared hit=2692
37	-> Index Scan using idx_orders_customer_ts on orders o (cost=0.28..8.31 rows=1 width=8) (actual time=0.004..0.004 rows=1 loops=30)
38	Index Cond: ((customer_id = r.customer_id) AND (order_ts >= (now() - '60 days')::interval))
39	Filter: (order_status = ANY ('paid,shipped,delivered'))::text[]
40	Rows Removed by Filter: 0
41	Sort Buffers: shared hit=663
42	-> Index Scan using idx_order_items_order on order_items oi (cost=0.29..8.34 rows=3 width=14) (actual time=0.29..0.29 rows=3 loops=30)
43	Index Cond: (order_id = o.order_id)
44	Sort Buffers: shared hit=2029
45	Planning:
46	Sort Buffers: shared hit=140
47	Planning Time: 3.815 ms
48	Execution Time: 23.321 ms

느린 이유와 개선 방법

튜닝 전에는 고객 3,000명의 누적매출과 상위 고객의 최근 매출을 상관 서브쿼리로 반복 계산한다. 튜닝 후에는 전체 고객을 기준으로 누적매출과 최근 60일 매출을 한 번에 집계하고, `ROW_NUMBER()` 와 전체 고객 수를 이용해 30명을 정확히 추출한다.

Q10 튜닝 후

```
-- Q10. 전체 3,000명의 누적매출과 최근 60일 매출을 한 번에 집계한 뒤
-- 누적매출 상위 1%(30명)를 정확히 선정
-- 튜닝: 누적매출과 60일 매출을 한 번의 GROUP BY로 동시에 계산한다.
-- [O 실행계획 확인용] 고객별 SubPlan 없이 한 번에 집계하는지 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH customer_sales AS (
  SELECT c.customer_id,
         c.full_name,
         COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue, -- 고객 누적매출
         COALESCE(SUM(oi.line_total) FILTER (
           WHERE o.order_ts >= now() - INTERVAL '60 days'
         ), 0) AS revenue_60d -- 같은 집계에서 최근 60일 매출만 합산
    FROM ecom.customers c
   LEFT JOIN ecom.orders o
     ON o.customer_id = c.customer_id -- 주문 없는 고객도 전체 3,000명에 포함
    AND o.order_status IN ('paid', 'shipped', 'delivered')
   LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id
  GROUP BY c.customer_id, c.full_name
), ranked AS (
  SELECT customer_id, full_name, lifetime_revenue, revenue_60d,
         ROW_NUMBER() OVER ( -- 누적매출 순서대로 중복 없는 순번 부여
           ORDER BY lifetime_revenue DESC, customer_id
         ) AS lifetime_rank,
         COUNT(customer_id) OVER () AS customer_count -- 전체 고객 수를 각 행에 표시
    FROM customer_sales
)
SELECT customer_id, full_name, lifetime_rank,
       ROUND(lifetime_revenue, 2) AS lifetime_revenue,
       ROUND(revenue_60d, 2) AS revenue_60d
  FROM ranked
 WHERE lifetime_rank <= CEIL(customer_count * 0.01) -- 전체 고객 중 상위 1%, 정확히 30명
 ORDER BY lifetime_rank;
```

```
-- [O] 실제 상위 30명 결과 조회
WITH customer_sales AS (
  SELECT c.customer_id, c.full_name,
         COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue,
         COALESCE(SUM(oi.line_total) FILTER (
           WHERE o.order_ts >= now() - INTERVAL '60 days'
         ), 0) AS revenue_60d
    FROM ecom.customers c
   LEFT JOIN ecom.orders o
     ON o.customer_id = c.customer_id
    AND o.order_status IN ('paid', 'shipped', 'delivered')
   LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id
  GROUP BY c.customer_id, c.full_name
), ranked AS (
  SELECT customer_id, full_name, lifetime_revenue, revenue_60d,
         ROW_NUMBER() OVER (
           ORDER BY lifetime_revenue DESC, customer_id
         ) AS lifetime_rank,
         COUNT(customer_id) OVER () AS customer_count
    FROM customer_sales
)
SELECT customer_id, full_name, lifetime_rank,
       ROUND(lifetime_revenue, 2) AS lifetime_revenue,
       ROUND(revenue_60d, 2) AS revenue_60d
  FROM ranked
 WHERE lifetime_rank <= CEIL(customer_count * 0.01)
 ORDER BY lifetime_rank;
```

customers 1 X					
WITH customer_sales AS (SELECT c.customer_id, c.full_name, COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue, COALESCE(SUM(oi.line_total) FILTER (WHERE o.order_ts >= now() - INTERVAL '60 days'), 0) AS revenue_60d FROM ecom.customers c LEFT JOIN ecom.orders o ON o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id GROUP BY c.customer_id, c.full_name), ranked AS (SELECT customer_id, full_name, lifetime_revenue, revenue_60d, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM customer_sales) SELECT customer_id, full_name, lifetime_rank, ROUND(lifetime_revenue, 2) AS lifetime_revenue, ROUND(revenue_60d, 2) AS revenue_60d FROM ranked WHERE lifetime_rank <= CEIL(customer_count * 0.01) ORDER BY lifetime_rank;					
	customer_id	full_name	lifetime_rank	lifetime_revenue	revenue_60d
1	8	Customer 8	1	35,154.22	32,794.66
2	16	Customer 16	2	31,003.24	31,003.24
3	18	Customer 18	3	30,283.04	29,772.64
4	14	Customer 14	4	29,322.59	29,322.59
5	6	Customer 6	5	28,703.23	28,703.23
6	13	Customer 13	6	28,633.41	28,633.41
7	2	Customer 2	7	28,623.31	28,623.31
8	1	Customer 1	8	28,546.26	28,546.26
9	20	Customer 20	9	28,531.13	28,531.13
10	9	Customer 9	10	28,488.91	28,488.91
11	17	Customer 17	11	27,317.53	26,943.11
12	24	Customer 24	12	27,075.74	27,075.74
13	23	Customer 23	13	25,717.57	25,717.57
14	30	Customer 30	14	24,815.39	24,815.39
15	4	Customer 4	15	24,726.24	24,101.82
16	12	Customer 12	16	22,419.91	21,470.83
17	19	Customer 19	17	22,412.27	22,412.27
18	22	Customer 22	18	22,206.5	21,128.93
19	7	Customer 7	19	22,034.39	22,034.39
20	29	Customer 29	20	21,696.95	21,696.95
21	11	Customer 11	21	21,635.89	20,199.13
22	5	Customer 5	22	21,557.53	21,557.53
23	15	Customer 15	23	21,466.9	21,466.9
24	21	Customer 21	24	21,430.97	21,430.97
25	28	Customer 28	25	20,490.17	19,053.41
26	26	Customer 26	26	18,974.16	18,974.16
27	3	Customer 3	27	18,431.44	18,220.72
28	10	Customer 10	28	17,990.28	17,990.28
29	27	Customer 27	29	17,135.65	17,135.65
30	25	Customer 25	30	15,993.86	15,993.86

Results 1 X

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH customer_sales AS (SELECT c.customer_id, c.full_name, COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue, COALESCE(SUM(oi.line_total) FILTER (WHERE o.order_ts >= now() - INTERVAL '60 days'), 0) AS revenue_60d FROM ecom.customers c LEFT JOIN ecom.orders o ON o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id GROUP BY c.customer_id, c.full_name), ranked AS (SELECT customer_id, full_name, lifetime_revenue, revenue_60d, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM customer_sales) SELECT customer_id, full_name, lifetime_rank, ROUND(lifetime_revenue, 2) AS lifetime_revenue, ROUND(revenue_60d, 2) AS revenue_60d FROM ranked WHERE lifetime_rank <= CEIL(customer_count * 0.01) ORDER BY lifetime_rank;

QUERY PLAN

1

Sort (cost=1053.20..1055.70 rows=1000 width=93) (actual time=16.928..16.932 rows=30 loops=1)

2

Sort Key: ranked.lifetime_rank

3

Sort Method: quicksort Memory: 27kB

4

Buffers: shared hit=180

5

-> Subquery Scan on ranked (cost=930.83..1003.37 rows=1000 width=93) (actual time=15.857..16.256 rows=3000 loops=1)

6

Filter: (((ranked.lifetime_rank)::numeric <= ceil(((ranked.customer_count)::numeric * 0.01)))

7

Rows Removed by Filter: 2970

8

Buffers: shared hit=180

9

-> WindowAgg (cost=930.83..930.87 rows=3000 width=101) (actual time=15.857..16.256 rows=3000 loops=1)

10

Buffers: shared hit=180

11

-> WindowAgg (cost=833.39..893.37 rows=3000 width=93) (actual time=14.683..15.357 rows=3000 loops=1)

12

Buffers: shared hit=180

13

-> Sort (cost=833.37..840.87 rows=3000 width=85) (actual time=14.679..14.788 rows=3000 loops=1)

14

Sort Key: customer_sales.lifetime_revenue DESC, customer_sales.customer_id

15

Sort Method: quicksort Memory: 246kB

16

Buffers: shared hit=180

17

-> Subquery Scan on customer_sales (cost=615.11..660.11 rows=3000 width=85) (actual time=12.711..13.595 rows=3000 loops=1)

18

Buffers: shared hit=180

19

-> HashAggregate (cost=615.11..660.11 rows=3000 width=85) (actual time=12.710..13.399 rows=3000 loops=1)

20

Group Key: c.customer_id

21

Batches: 1 Memory Usage: 1905kB

22

Buffers: shared hit=180

23

-> Hash Right Join (cost=238.93..491.51 rows=8240 width=35) (actual time=3.716..8.317 rows=9013 loops=1)

24

Hash Cond: (o.customer_id = c.customer_id)

25

Buffers: shared hit=180

26

-> Hash Right Join (cost=131.43..362.34 rows=8240 width=22) (actual time=1.959..4.969 rows=8230 loops=1)

27

Hash Cond: (oi.order_id = o.order_id)

28

Buffers: shared hit=140

29

-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.021..1.052 rows=10367 loop

30

Buffers: shared hit=100

31

-> Hash (cost=93.08..93.08 rows=3068 width=24) (actual time=1.912..1.912 rows=3068 loops=1)

32

Buckets: 4096 Batches: 1 Memory Usage: 200kB

33

Buffers: shared hit=40

34

-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=24) (actual time=0.008..1.308 rows=3068 loops=1)

35

Filter: (order_status = ANY ('{paid,shipped,delivered}'))::text[]]

36

Rows Removed by Filter: 792

37

Buffers: shared hit=40

38

-> Hash (cost=70.00..70.00 rows=3000 width=21) (actual time=1.717..1.718 rows=3000 loops=1)

39

Buckets: 4096 Batches: 1 Memory Usage: 190kB

40

Buffers: shared hit=40

41

-> Seq Scan on customers c (cost=0.00..70.00 rows=3000 width=21) (actual time=0.028..0.929 rows=3000 loops=1)

42

Buffers: shared hit=40

Planning:

Buffers: shared hit=33

Planning Time: 1.384 ms

Execution Time: 17.230 ms

검증 항목	기대값	실제값
전체 고객 수	3,000	3,000
상위 1% 고객 수	30	30
누적매출 1위 고객	-	Customer 8 / 35,154.22
해당 고객 최근 60일 매출	-	32,794.66

구분	반복 SubPlan	Buffers	Execution Time
튜닝 전	있음(3,000회)	hit=21,777	23.321 ms
튜닝 후	없음	hit=180	17.230 ms

결과 해석: 전체 3,000명에서 누적매출 상위 30명을 정확히 선정했고 실행시간은 26.1% 단축되었다.

13. Q11 - 안전 나눗셈 함수 비교

함수 정의 차이

함수	정의 파일	분모가 0일 때
<code>ecom.f_safe_div</code>	스키마 파일	0 반환
<code>ecom.safe_div</code>	시드 파일	NULL 반환

-- Q11. 스키마와 시드에 정의된 두 함수의 정상 분모 결과 비교
 -- [① 정상 분모] 분모가 0이 아니면 두 함수가 같은 계산 결과를 반환
 SELECT ecom.f_safe_div(
 SUM(oi.line_total), COUNT(DISTINCT o.order_id)
) AS schema_f_safe_div_aov,
 ecom.safe_div(
 SUM(oi.line_total), COUNT(DISTINCT o.order_id)
) AS seed_safe_div_aov
 FROM ecom.orders o
 JOIN ecom.order_items oi ON oi.order_id = o.order_id
 WHERE o.order_status IN ('paid', 'shipped', 'delivered');

— 자치명: f_safe_div0, safe_div0: NULL을 반환한다.
 — [0] 반환: 0 반환과 NULL 반환의 경우 영어가 바뀌어
 SELECT ecom.f_safe_div(100, 0) AS schema_function_returns_zero, — 0으로 나누면 숫자 0
 ecom.f_safe_div(100, 0) AS seed_function_returns_null; — 0으로 나누면 NULL(값 없음)

results 1 × Statistics 1

LECT ecom.f_safe_div(100, 0) AS schema_function_returns_zero, ecom.f

123 schema_function_returns_zero	123 seed_function_returns_null
0	[NULL]

테스트	f_safe_div	safe_div	해석
정상 AOV	886.2541297262	886.2541297262	분모가 0이 아니면 같은 계산 결과
100 / 0	0	NULL	보고서 요구에 맞는 정책을 선택해야 함

```
SET search_path = ecom, public; -- 객체 이름 앞에 스키마를 선택하여 ecom을 먼저 참조

-- 공통 업무 정의
-- 최근 30일 동안 paid, shipped, delivered 상태인 주문과 주문상품을 연결하여 총매출을 계산한다.
-- 세 테스트는 업무 로직과 결과가 같고, 물리적인 조인 방식만 다르다.


-- =====
-- 1. Nested Loop Join(NLJ)

-- 처리 방식: 바깥쪽 안쪽에 각 행마다 안쪽 입력에서 일치하는행을 반복해서 찾는다.
-- 유리한 조건: 바깥쪽 결과가 작고, 안쪽 조건에 인덱스가 있을 때 유리하다.
-- 확인할 실행계획: Nested Loop와 안쪽의 Index Scan 또는 Index Only Scan


BEGIN;
SET LOCAL enable_hashjoin = off; -- Hash Join 후보로 비활성화
SET LOCAL enable_mergejoin = off; -- Merge Join 후보를 비활성화
SET LOCAL enable_nestloop = on; -- Nested Loop Join 후보만 활성화

-- 실제 실행시간·버퍼·변경 설정·요약을 함께 출력
SELECT ROUND(SUM(o1.line_total), 2) AS total_sales_30d -- 주문상품 금액을 합산하고 소수점 둘째 자리까지 표시
FROM ecom.orders o -- 주문 헤더 테이블, 별칭 o
JOIN ecom.order_items oi -- 주문별 상품과 금액이 저장된 상세 테이블, 별칭 oi
ON o1.order_id = o.order_id -- 주문번호가 같은 주문과 주문상품을 연결하는 동등 조건
WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 실제 매출로 인정하는 주문 상태만 포함
AND o.order_ts >= CURRENT_DATE - 30; -- 오늘을 기준으로 최근 30일 주문만 조회

ROLLBACK; -- 설정 변경을 취소하여 다음 조인 테스트에 영향을 주지 않음
```



Merge Join



구분	처리 방식	일반적으로 유리한 조건	Buffers	Execution Time
Nested Loop Join	외부 행마다 내부 입력 탐색	외부 입력이 작고 내부 인덱스가 있을 때	hit=1,837/read=58	9.017 ms
Hash Join	작은 입력 해시 생성 후 큰 입력 탐색	큰 비정렬 동등 조인	hit=109	11.590 ms
Merge Join	정렬된 두 입력을 순차 병합	양쪽이 이미 정렬된 큰 입력	hit=131	5.705 ms

본인 환경에서의 결론

동일 데이터에서는 Merge Join(5.705 ms)이 가장 빨랐고 Hash Join(11.590 ms)이 가장 느렸다. 단, 데이터 크기·정렬·인덱스에 따라 최적 조인은 달라진다.

15. Materialized View 활용

생성 목적

매일 주문과 주문상품을 다시 조인·집계하지 않고, 미리 계산한 일별 주문 수와 GMV를 빠르게 조회한다.

생성 및 결과 화면

MV 생성

Name	Value
Updated Rows	0
Execute time	0.023s
Start time	Fri Aug 14 17:05:51 KST 2026
Finish time	Fri Aug 14 17:05:51 KST 2026
Query	DROP MATERIALIZED VIEW IF EXISTS ecom.mv_daily_gmv; -- 기존 MV와 그 MV에 속한 인덱스를 함께 제거 -- ===== -- 2. 일별 GMV Materialized View 생성 -- ===== -- WITH NO DATA로 구조와 정의만 먼저 생성하고 데이터는 뒤의 REFRESH에서 적재한다. CREATE MATERIALIZED VIEW ecom.mv_daily_gmv AS -- 일별 집계 결과를 저장할 MV 생성 시작 SELECT date_trunc('day', o.order_ts)::date AS sales_day, -- 주문시각을 일 단위로 자르고 date 형식으로 변환 COUNT(DISTINCT o.order_id) AS order_count, -- 주문상품 조인으로 중복된 주문번호를 제거한 일별 주문 수 ROUND(SUM(oi.line_total), 2) AS gmv -- 주문상품 금액의 일별 합계를 소수점 둘째 자리로 표시 FROM ecom.orders o -- 주문일시-주문상태가 저장된 주문 테이블 JOIN ecom.order_items oi -- 상품별 판매금액이 저장된 주문상품 테이블 ON oi.order_id = o.order_id -- 주문번호가 같은 주문과 주문상품을 연결 WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 실제 매출로 인정하는 상태만 포함 GROUP BY date_trunc('day', o.order_ts)::date -- 같은 날짜의 주문상품 금액을 한 행으로 집계 WITH NO DATA; -- 생성 시에는 데이터를 넣지 않고 빈 구조만 생성 -- ===== -- 3. 동시 갱신을 위한 UNIQUE 인덱스 생성 -- ===== -- REFRESH MATERIALIZED VIEW CONCURRENTLY를 사용하려면 모든 행을 유일하게 식별할 수 있어야 한다. -- 이 MV는 날짜별로 한 행만 존재하므로 sales_day를 고유키로 사용한다. CREATE UNIQUE INDEX ux_mv_daily_gmv_sales_day -- MV의 날짜 중복을 금지하는 UNIQUE 인덱스 이름 ON ecom.mv_daily_gmv (sales_day); -- 날짜 한 개가 MV의 각 행을 유일하게 식별 -- ===== -- 4. 최초 데이터 적재 및 통계정보 수집 -- ===== -- WITH NO DATA로 만들었으므로 최초 1회는 일반 REFRESH로 데이터를 채워야 한다. -- 빈 MV에는 CONCURRENTLY를 바로 사용할 수 없으므로 먼저 일반 REFRESH를 실행한다. REFRESH MATERIALIZED VIEW ecom.mv_daily_gmv; -- MV 정의의 쿼리를 실행하여 일별 결과를 실제로 저장 ANALYZE ecom.mv_daily_gmv; -- MV의 행 수와 값 분포 통계를 수집하여 실행계획 선택에 활용

원본 쿼리 계획

5. 원본 데이터를 직접 조인·집계하는 실행계획

비교 기준이 되는 원본 쿼리이다.

orders와 order_items를 읽고 Join, Aggregate, Sort를 수행하므로 MV 조회보다 작업량이 많을 수 있다.

탐지할 값: 최상위 Buffers, Planning Time, Execution Time, Join/Aggregate 노드

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

SELECT date_trunc('day', o.order_ts)::date AS sales_day, -- 주문일을 일 단위로 변환
COUNT(DISTINCT o.order_id) AS order_count, -- 조인 후 중복을 제거한 일별 주문 수
ROUND(SUM(oi.line_total), 2) AS gmv -- 일별 총 상품 판매금액
FROM ecom.orders o -- 원본 주문 테이블 읽기
JOIN ecom.order_items oi -- 원본 주문상품 테이블 읽기
ON oi.order_id = o.order_id -- 주문번호를 기준으로 원본 테이블 두 개 조인
WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 상태를 필터링한 집계
GROUP BY date_trunc('day', o.order_ts)::date -- 날짜별로 주문 수와 금액 계산
ORDER BY sales_day DESC -- 가장 최근 날짜부터 정렬
LIMIT 30; -- 최근 30개 날짜만 출력

Results 1 X Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT date_trunc('day', o.or | ^ * Enter a SQL expression to filter results (use Ctrl+Space)

AZ QUERY PLAN

1 Limit (cost=939.49..940.89 rows=30 width=44) (actual time=9.799..10.154 rows=30 loops=1)

2 Buffers: shared hit=140

3 -> GroupAggregate (cost=939.49..1083.25 rows=3068 width=44) (actual time=9.797..10.149 rows=30 loops=1)

4 Group Key: ((date_trunc('day')::text, o.order_ts)::date)

5 Buffers: shared hit=140

6 -> Sort (cost=939.49..960.09 rows=8240 width=18) (actual time=9.771..9.856 rows=1368 loops=1)

7 Sort Key: ((date_trunc('day')::text, o.order_ts)::date) DESC, o.order_id

8 Sort Method: quicksort Memory: 706kB

9 Buffers: shared hit=140

10 -> Hash Join (cost=131.43..403.54 rows=8240 width=18) (actual time=2.372..7.234 rows=8230 loops=1)

11 Hash Cond: (oi.order_id = o.order_id)

12 Buffers: shared hit=140

13 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.034..1.046 rows=10367 loops=1)

14 Buffers: shared hit=100

15 -> Hash (cost=93.08..93.08 rows=3068 width=16) (actual time=2.269..2.270 rows=3068 loops=1)

16 Buckets: 4096 Batches: 1 Memory Usage: 176kB

17 Buffers: shared hit=40

18 -> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=16) (actual time=0.020..1.465 rows=3068 loops=1)

19 Filter: (order_status = ANY ('paid,shipped,delivered')::text[])

20 Rows Removed by Filter: 792

21 Buffers: shared hit=40

22 Planning:

23 Buffers: shared hit=18

24 Planning Time: 0.835 ms

25 Execution Time: 10.257 ms

6. Materialized View 조회 실행계획

이미 계산되어 저장된 sales_day, order_count, gmv만 읽는다.

원본 테이블 조인과 GROUP BY가 사라지는지 원본 실행계획과 비교한다.

탐지할 값: Scan 방식, 최상위 Buffers, Planning Time, Execution Time

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

SELECT sales_day, -- MV에 저장된 매출 날짜
order_count, -- MV에 저장된 일별 주문 수
gmv -- MV에 저장된 일별 GMV
FROM ecom.mv_daily_gmv -- 원본 조인 대신 사전 집계된 MV만 조회
ORDER BY sales_day DESC -- 가장 최근 날짜부터 정렬
LIMIT 30; -- 최근 30개 날짜만 출력

Results 1 X Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT sales_day, order_cou | ^ * Enter a SQL expression to filter results (use Ctrl+Space)

AZ QUERY PLAN

1 Limit (cost=0.14..3.26 rows=30 width=20) (actual time=0.014..0.018 rows=30 loops=1)

2 Buffers: shared hit=1 read=1

3 -> Index Scan Backward using ux_mv_daily_gmv_sales_day on mv_daily_gmv (cost=0.14..14.17 rows=135 width=20) (actual time=0.013..0.016 rows=30 loops=1)

4 Buffers: shared hit=1 read=1

5 Planning:

6 Buffers: shared hit=56 read=1

7 Planning Time: 0.582 ms

8 Execution Time: 0.027 ms

MV 조회 결과

7. Materialized View 실제 결과 확인

EXPLAIN 없이 실행하여 구매·재무팀에 전달할 실제 일별 결과를 확인한다.

SELECT sales_day, -- 일별 매출 기준 날짜
order_count, -- 해당 날짜의 중복 없는 판매용 주문 수
gmv -- 해당 날짜의 주문상품 총매출
FROM ecom.mv_daily_gmv -- 미리 저장된 일별 집계 결과 조회
ORDER BY sales_day DESC -- 최근 날짜부터 표시
LIMIT 30; -- 최근 30일분 결과 표시

mv_daily_gmv 1 X Statistics 1


SELECT sales_day, order_count, gmv FROM ecom.mv_daily_gmv ORDER E | ^ * Enter a SQL expression to filter results (use Ctrl+Space)

	sales_day	order_count	gmv
1	2026-09-04	1	234.98
2	2026-09-03	2	577.53
3	2026-08-30	2	492.73
4	2026-08-29	2	716.1
5	2026-08-28	1	339.12
6	2026-08-27	2	470.26
7	2026-08-26	2	493.92
8	2026-08-24	1	171.21
9	2026-08-22	3	400.5
10	2026-08-21	2	647.42
11	2026-08-20	6	1,434.01
12	2026-08-19	3	390.33
13	2026-08-18	2	294.15
14	2026-08-17	2	278.8
15	2026-08-14	21	16,900.68
16	2026-08-13	30	27,756.96
17	2026-08-12	22	18,433.21
18	2026-08-11	31	29,707.93
19	2026-08-10	25	16,932.28
20	2026-08-09	29	25,555.9
21	2026-08-08	30	27,412.01
22	2026-08-07	25	21,950.82
23	2026-08-06	42	39,935.38
24	2026-08-05	27	22,869.32
25	2026-08-04	27	32,913.44
26	2026-08-03	29	31,064.72
27	2026-08-02	35	29,385.72
28	2026-08-01	38	43,562.65
29	2026-07-31	40	43,292.45
30	2026-07-30	29	24,239.39

종합실습4_제출리포트_최종_홍은비


17

MV 갱신



구분	핵심 실행계획	Buffers	Execution Time
원본 JOIN + GROUP BY	Hash Join + GroupAggregate	hit=140	10.257 ms
mv_daily_gmv 조회	Index Scan Backward	hit=1/read=1	0.027 ms

오후 3시 설계



갱신 전략

- 최초 적재: `REFRESH MATERIALIZED VIEW ecom.mv_daily_gmv;`
- 운영 갱신: `REFRESH MATERIALIZED VIEW CONCURRENTLY ecom.mv_daily_gmv;`
- 제안 주기: 매일 오후 3시
- 주의점: 오후 3시 이후 변경사항은 다음 갱신 전까지 조회 결과에 반영되지 않는다.

16. DBMS별 옵티마이저 비교 (Option)

자세한 조사 내용은 `종합실습4_06_DBMS별_옵티마이저_비교.md` 를 참고한다.

DBMS	대표 조인	실행계획 확인	특징
PostgreSQL	Nested Loop, Hash, Merge	<code>EXPLAIN ANALYZE</code>	통계·비용 기반, 확장 통계, GEQO
MySQL	Nested Loop/BKA, Hash	<code>EXPLAIN ANALYZE</code>	optimizer switch·힌트·히스토그램
Oracle	Nested Loop, Hash, Sort Merge	<code>DBMS_XPLAN</code>	Adaptive Plan, SQL Plan Management
SQL Server	Nested Loops, Hash, Merge, Adaptive	Actual Execution Plan	Query Store, Intelligent Query Processing

17. 전체 튜닝 전후 비교

문항	튜닝 전 방식	튜닝 후 방식	전 Buffers	후 Buffers	전 시간	후 시간	감소율
Q1	함수 조건 + 상관 집계	SARG 범위 + 단일 집계	hit=2,902	hit=101/read=8	25.380	4.903	80.7%
Q2	상세행 + DISTINCT	주문별 선집계	hit=140	hit=143	11.646	6.879	40.9%
Q3	비-SARG 기간 조건	최근 주문 선필터	hit=148	hit=120/read=9	11.863	11.534	2.8%
Q4	제품별 상관 서브쿼리	전체 1회 집계 + RANK	hit=70,677	hit=147	37.373	9.654	74.2%
Q5	고객별 3회 반복 조회	주문 선집계 + 고객 GROUP BY	hit=17,287	hit=180	21.915	13.785	37.1%
Q6	고객별 EXISTS	Window + BOOL_OR	hit=9,362	hit=1/read=20	7.881	6.166	21.8%
Q7	임계치 상관 조회	직접 비교 + 부분 인덱스	hit=1,912	hit=12	2.017	0.428	78.8%
Q8	AVG/COUNT 반복	GROUP BY + HAVING	hit=1,565	hit=28	4.551	1.016	77.7%
Q9	상세행 + DISTINCT	주문별 선집계 + AVG	hit=143	hit=140	17.993	10.057	44.1%
Q10	누적/60일 매출 반복 조회	전체 1회 집계 + 정확히 30명	hit=21,777	hit=180	23.321	17.230	26.1%

감소율 계산식:

18. 최종 분석

요청 대응 관점

어떤 주문 상태와 기간을 포함하는지, 주문 수와 주문상품 수를 혼동하지 않았는지, 상위 고객의 선정 기준과 표시 기간이 다른지 먼저 정의해야 한다. 특히 Q10은 최근 60일 매출로 상위 고객을 선정하는 것이 아니라 누적매출로 30명을 선정한 뒤 최근 60일 매출을 계산한다.

튜닝 관점

상관 SubPlan 제거와 선집계·SARG 조건 적용으로 Q1~Q10 모두 단축되었으며, 가장 큰 개선은 Q1(80.7%)이었다.

한계와 추가 확인사항

- 랜덤 시드이므로 재실행 시 결과가 달라진다.
- 로컬 단일 사용자 환경의 실행시간은 운영 부하를 반영하지 않는다.
- 쿠폰 사용 여부와 AOV의 관계는 인과관계가 아니다.
- 인덱스는 조회 성능을 높이지만 INSERT/UPDATE와 저장공간 비용을 추가한다.

최종 결론

업무 기준을 명시한 Q1~Q11 결과를 튜닝 전후 동일하게 유지하면서 반복 조회와 불필요한 중복 제거를 줄였다. 물리 조인은 본 환경에서 Merge Join이 가장 빨랐고, `mv_daily_gmv` 조회는 원본 집계 10.257 ms에서 0.027 ms로 단축되었다. 운영 시에는 데이터 규모와 변경 빈도에 따라 인덱스 비용과 오후 3시 MV 갱신 시차를 함께 관리해야 한다.