

종합실습 4 - E-Commerce 데이터 요청 및 SQL 튜닝 리포트

소속: 판교 5반
성명: 홍은비
DBMS: PostgreSQL 17.10 (Homebrew)
실행환경: Local PC / DBeaver Community
측정 명령: EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

시드 데이터는 random()으로 생성되므로 실행 결과와 시간은 환경마다 달라질 수 있다. 절대시간뿐 아니라 Scan/Join 방식, 반복 횟수, 예상·실제 행 수와 Buffers를 함께 비교한다.

1. 실습 목적

구매·재무 등 다른 실무 팀에서 요청한 E-Commerce 자료를 정확한 기준으로 산출하고, 같은 결과를 더 효율적으로 반환하도록 SQL과 인덱스를 개선한다. Q1~Q10은 튜닝 전후 쿼리와 실행계획을 비교하고, PostgreSQL의 세 가지 물리 조인과 Materialized View 활용 방법을 검토한다.

2. 공통 데이터 기준

항목	정의
실매출 주문	order_status IN ('paid', 'shipped', 'delivered')
주문 매출	SUM(order_items.line_total)
AOV	실매출 합계 ÷ 실매출 주문 수
Q1 기간	실행시점 기준 최근 1개월
Q3 기간	실행시점 기준 최근 90일
Q6 재구매	첫 구매 후 30일 이내 추가 실구매
Q10 대상	전체 3,000명 누적매출 상위 1%인 30명
Q10 표시금액	선정된 30명의 최근 60일 실매출


3. Q1 - 최근 1개월 실제 판매 총액

요청사항

paid, shipped, delivered 상태이면서 now() - interval '1 month' 이후인 주문의 line_total 합계를 제공한다.

튜닝 전 쿼리·결과 화면

Q1 튜닝 전 - 다음 페이지



느린 이유



`order_ts`를 함수로 변환하면 일반 날짜 인덱스의 범위탐색이 어려워질 수 있다. 또한 주문마다 주문상품 합계를 상관 서브쿼리로 반복 조회한다.

개선 방법

날짜 컬럼을 그대로 둔 SARG 범위 조건을 사용하고, 주문과 주문상품을 한 번 조인해 전체 합계를 계산한다. 실매출 상태만 포함하는 부분 인덱스로 대상 주문 탐색 범위를 줄인다.

튜닝 후 쿼리·결과 화면

Q1 튜닝 후



구분	Scan/Join 방식	Buffers	Execution Time	결과 금액
튜닝 전	Seq Scan + SubPlan	hit=2,902	25.380 ms	883,029.03
튜닝 후	Index Only + Hash	hit= 101/read=8	4.903 ms	883,029.03

결과 해석: 전후 결과는 동일하며 실행시간이 80.7% 단축되고 반복 SubPlan이 제거되었다.

4. Q2 - 월별 주문 수·매출·AOV

요청사항

월별 실매출 주문 수, 총매출, 주문당 평균 금액을 제공한다.

Q2 튜닝 전

```

-- Q2. 월별 주문 수, 매출, AOV
-- 문제점: 상세 행을 먼저 모두 조인한 뒤 COUNT(DISTINCT)로 중복을 제거한다.

-- [① 실행계획 확인용] 월별 집계와 Scan/Join과 실행시간 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) -- 실제 실행계획과 성능 측정
SELECT date_trunc('month', o.order_ts)::date AS sales_month, -- 주문시각을 월 단위로 묶음
COUNT(DISTINCT o.order_id) AS order_count, -- 상세행 중복을 제거한 주문 수
ROUND(SUM(oil.line_total), 2) AS revenue, -- 월별 매출 합계, 소수점 둘째 자리
ROUND(SUM(oil.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov -- 주문 테이블
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id -- 주문번호로 주문상품 연결
WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 판매중 주문만 포함
GROUP BY 1
ORDER BY 1; -- SELECT 첫 번째 컬럼인 월로 그룹화
-- 월 오름차순 정렬

-- SELECT date_trunc('month', o.order_ts)::date AS sales_month

```

Results 1 X Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) Enter a SQL expression to filter results (use Ctrl+Space)

Grid

1 AZ QUERY PLAN

2 GroupAggregate (cost=939.49..1113.93 rows=3068 width=76) (actual time=10.469..11.600 rows=6 loops=1)

3 Buffers: shared hit=140

4 -> Sort (cost=939.49..960.09 rows=8240 width=18) (actual time=10.362..10.640 rows=8230 loops=1)

5 Sort Key: ((date_trunc('month')::text, o.order_ts)::date), o.order_id

6 Sort Method: quicksort Memory: 706kB

7 Buffers: shared hit=140

8 -> Hash Join (cost=131.43..403.54 rows=8240 width=18) (actual time=1.613..7.866 rows=8230 loops=1)

9 Hash Cond: (oi.order_id = o.order_id)

10 Buffers: shared hit=140

11 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.009..1.122 rows=10367 loops=1)

12 Buffers: shared hit=100

13 -> Hash (cost=93.08..93.08 rows=3068 width=16) (actual time=1.543..1.543 rows=3068 loops=1)

14 Buckets: 4096 Batches: 1 Memory Usage: 176kB

15 Buffers: shared hit=40

16 -> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=16) (actual time=0.016..1.071 rows=3068 loops=1)

17 Filter: (order_status = ANY ('(paid,shipped,delivered')::text[]))

18 Rows Removed by Filter: 792

19 Buffers: shared hit=40

20 Planning:

21 Buffers: shared hit=49 dirtied=1

22 Planning Time: 1.979 ms

23 Execution Time: 11.646 ms

The screenshot shows a SQL IDE with a query editor and a results pane. The query in the editor is:

```
SELECT date_trunc('month', o.order_ts)::date AS sales_month, -- [O] 실제 월별 조회 조건
COUNT(DISTINCT o.order_id) AS order_count,
ROUND(SUM(o.line_total), 2) AS revenue,
ROUND(SUM(o.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov
FROM ecom.orders o
JOIN ecom.order_items o_i ON o_i.order_id = o.order_id
WHERE order_status IN ('paid', 'shipped', 'delivered')
GROUP BY 1
ORDER BY 1;
```

The results pane shows the following data:

	sales_month	order_count	revenue	aov
1	2026-04-01	267	228,521.46	855.89
2	2026-05-01	673	551,927.62	820.1
3	2026-06-01	794	757,551.33	953.99
4	2026-07-01	882	829,725.16	930.19
5	2026-08-01	439	390,509.57	889.54
6	2026-09-01	3	812.51	270.84

느린 이유와 개선 방법

상세 주문상품을 먼저 조인한 상태에서는 주문이 여러 행으로 증가하므로 `COUNT(DISTINCT order_id)` 가 필요하다. 튜닝 후에는 주문별 금액을 먼저 집계한 다음 월별로 다시 집계해 중복 제거 비용을 줄인다.

Q2 튜닝 후

```

-- Q2. 주문별 매출을 먼저 계산해 COUNT(DISTINCT)를 제거
-- 튜닝: 주문별로 한 행을 만든 뒤 중복 제거 없이 order_id를 집계한다.
-- [① 실행계획 확인용] 주문별 선집계 후 월별 집계 계획 확인

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

WITH order_totals AS (
    SELECT o.order_id,
           date_trunc('month', o.order_ts)::date AS sales_month,
           SUM(o.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.order_ts
)

SELECT sales_month,
       COUNT(order_id) AS order_count,
       ROUND(SUM(order_total), 2) AS revenue,
       ROUND(AVG(order_total), 2) AS aov
FROM order_totals
GROUP BY sales_month
ORDER BY sales_month;

```

Results 1	SQL	EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH order_totals AS (SELECT	Enter a SQL expression to filter results (use Ctrl+Space)
Grid	Text		
1	AZ QUERY PLAN		
2	Sort (cost=522.57..523.07 rows=200 width=76) (actual time=6.733..6.735 rows=6 loops=1)		
3	Sort Key: ((date_trunc('month')::text, o.order_ts))::date)		
4	Sort Method: quicksort Memory: 25kB		
5	Buffers: shared hit=143		
6	-> HashAggregate (cost=510.92..514.92 rows=200 width=76) (actual time=6.714..6.721 rows=6 loops=1)		
7	Group Key: (date_trunc('month')::text, o.order_ts))::date		
8	Batches: 1 Memory Usage: 40kB		
9	Buffers: shared hit=140		
10	-> HashAggregate (cost=403.54..457.23 rows=3068 width=52) (actual time=5.123..6.324 rows=3068 loops=1)		
11	Group Key: o.order_id		
12	Batches: 1 Memory Usage: 1393kB		
13	Buffers: shared hit=140		
14	-> Hash Join (cost=131.43..362.34 rows=8240 width=22) (actual time=0.906..3.375 rows=8230 loops=1)		
15	Hash Cond: (o.order_id = o.order_id)		
16	Buffers: shared hit=140		
17	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.010..0.824 rows=10367 loops=1)		
18	Buffers: shared hit=100		
19	-> Hash (cost=93.08..93.08 rows=3068 width=16) (actual time=0.879..0.879 rows=3068 loops=1)		
20	Buckets: 4096 Batches: 1 Memory Usage: 176kB		
21	Buffers: shared hit=40		
22	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=16) (actual time=0.007..0.603 rows=3068 loops=1)		
23	Filter: (order_status = ANY ('paid,shipped,delivered')::text[]))		
24	Rows Removed by Filter: 792		
25	Buffers: shared hit=40		
26	Planning:		
27	Buffers: shared hit=69 read=7		
28	Planning Time: 5.743 ms		
29	Execution Time: 6.879 ms		

```

WITH order_totals AS (
    SELECT o.order_id, date_trunc('month', o.order_ts)::date AS sales_month,
           SUM(oi.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.order_ts
)
SELECT sales_month, COUNT(order_id) AS order_count,
       ROUND(SUM(order_total), 2) AS revenue,
       ROUND(AVG(order_total), 2) AS aov
FROM order_totals
GROUP BY sales_month
ORDER BY sales_month;

```

Results 1 X

WITH order_totals AS (SELECT o.order_id, date_trunc('month', o.order_ts) AS order_month, SUM(o.amount) AS order_total FROM orders o GROUP BY o.order_id, date_trunc('month', o.order_ts))

	sales_month	123 order_count	123 revenue	123 aov
1	2026-04-01	267	228,521.46	855.89
2	2026-05-01	673	551,927.62	820.1
3	2026-06-01	794	717,531.35	903.69
4	2026-07-01	892	829,725.16	930.19
5	2026-08-01	439	390,509.57	889.54
6	2026-09-01	3	812.51	270.84

구분	집계 방식	Buffers	Execution Time	전후 결과 동일 여부
튜닝 전	상세행 + COUNT(DISTINCT)	hit=140	11.646 ms	-
튜닝 후	주문별 선집계 + COUNT(order_id)	hit=143	6.879 ms	동일

결과 해석: 주문별 선집계로 DISTINCT 제거 비용을 줄여 실행시간이 40.9% 단축되었다.

5. Q3 - 최근 90일 카테고리 매출 Top 10

요청사항

최근 90일 실매출을 카테고리별로 집계해 상위 10개를 제공한다.

Q3 튜닝 전

Q3. 최근 90일 카테고리의 Top 10 문제점: 비-SARG 날짜 조건을 사용하고 상세 데이터를 그대로 집계한다. [Q1 실행계획 확인용] 최근 90일 필터와 테이블 조건 계획 확인 실행 계획과 성능 측정 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	Results 1 Statistics 1 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
1 Limit (cost=497.38..497.41 rows=10 width=72) (actual time=11.220..11.225 rows=10 loops=1)	1 Limit (cost=497.38..497.41 rows=10 width=72) (actual time=11.220..11.225 rows=10 loops=1)
2 Buffers: shared hit=148	2 Buffers: shared hit=148
3 -> Sort (cost=497.38..500.06 rows=1070 width=72) (actual time=11.219..11.222 rows=10 loops=1)	3 -> Sort (cost=497.38..500.06 rows=1070 width=72) (actual time=11.219..11.222 rows=10 loops=1)
4 Sort Key: (round(sum(oi.line_total), 2)) DESC, c.category_id	4 Sort Key: (round(sum(oi.line_total), 2)) DESC, c.category_id
5 Sort Method: quicksort Memory: 25kB	5 Sort Method: quicksort Memory: 25kB
6 Buffers: shared hit=148	6 Buffers: shared hit=148
7 -> HashAggregate (cost=458.21..474.26 rows=1070 width=72) (actual time=10.966..10.979 rows=10 loops=1)	7 -> HashAggregate (cost=458.21..474.26 rows=1070 width=72) (actual time=10.966..10.979 rows=10 loops=1)
8 Group Key: c.category_id	8 Group Key: c.category_id
9 Batches: 1 Memory Usage: 73kB	9 Batches: 1 Memory Usage: 73kB
10 Buffers: shared hit=148	10 Buffers: shared hit=148
11 -> Hash Join (cost=199.04..444.47 rows=2748 width=46) (actual time=3.828..9.543 rows=6662 loops=1)	11 -> Hash Join (cost=199.04..444.47 rows=2748 width=46) (actual time=3.828..9.543 rows=6662 loops=1)
12 Hash Cond: (p.category_id = c.category_id)	12 Hash Cond: (p.category_id = c.category_id)
13 Buffers: shared hit=148	13 Buffers: shared hit=148
14 -> Hash Join (cost=164.96..403.15 rows=2748 width=14) (actual time=3.311..7.831 rows=6662 loops=1)	14 -> Hash Join (cost=164.96..403.15 rows=2748 width=14) (actual time=3.311..7.831 rows=6662 loops=1)
15 Hash Cond: (oi.product_id = p.product_id)	15 Hash Cond: (oi.product_id = p.product_id)
16 Buffers: shared hit=147	16 Buffers: shared hit=147
17 -> Hash Join (cost=144.46..375.38 rows=2748 width=14) (actual time=2.841..6.120 rows=6662 loops=1)	17 -> Hash Join (cost=144.46..375.38 rows=2748 width=14) (actual time=2.841..6.120 rows=6662 loops=1)
18 Hash Cond: (oi.order_id = o.order_id)	18 Hash Cond: (oi.order_id = o.order_id)
19 Buffers: shared hit=140	19 Buffers: shared hit=140
20 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)	20 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)
21 Buffers: shared hit=100	21 Buffers: shared hit=100
22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)	22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)
23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB	23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB
24 Buffers: shared hit=40	24 Buffers: shared hit=40

Results 1 Statistics 1 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	Results 1 Statistics 1 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
20 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)	20 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)
21 Buffers: shared hit=100	21 Buffers: shared hit=100
22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)	22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)
23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB	23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB
24 Buffers: shared hit=40	24 Buffers: shared hit=40
25 -> Seq Scan on orders o (cost=0.00..131.68 rows=1023 width=8) (actual time=0.023..1.672 rows=2483 loops=1)	25 -> Seq Scan on orders o (cost=0.00..131.68 rows=1023 width=8) (actual time=0.023..1.672 rows=2483 loops=1)
26 Filter: ((order_status = ANY ('paid,shipped,delivered'))::text[]) AND ((order_ts)::date >= (CURRENT_DATE - 90))	26 Filter: ((order_status = ANY ('paid,shipped,delivered'))::text[]) AND ((order_ts)::date >= (CURRENT_DATE - 90))
27 Rows Removed by Filter: 1377	27 Rows Removed by Filter: 1377
28 Buffers: shared hit=40	28 Buffers: shared hit=40
29 -> Hash (cost=13.00..13.00 rows=600 width=16) (actual time=0.449..0.450 rows=600 loops=1)	29 -> Hash (cost=13.00..13.00 rows=600 width=16) (actual time=0.449..0.450 rows=600 loops=1)
30 Buckets: 1024 Batches: 1 Memory Usage: 37kB	30 Buckets: 1024 Batches: 1 Memory Usage: 37kB
31 Buffers: shared hit=7	31 Buffers: shared hit=7
32 -> Seq Scan on products p (cost=0.00..13.00 rows=600 width=16) (actual time=0.006..0.368 rows=600 loops=1)	32 -> Seq Scan on products p (cost=0.00..13.00 rows=600 width=16) (actual time=0.006..0.368 rows=600 loops=1)
33 Buffers: shared hit=7	33 Buffers: shared hit=7
34 -> Hash (cost=20.70..20.70 rows=1070 width=40) (actual time=0.276..0.276 rows=14 loops=1)	34 -> Hash (cost=20.70..20.70 rows=1070 width=40) (actual time=0.276..0.276 rows=14 loops=1)
35 Buckets: 2048 Batches: 1 Memory Usage: 17kB	35 Buckets: 2048 Batches: 1 Memory Usage: 17kB
36 Buffers: shared hit=1	36 Buffers: shared hit=1
37 -> Seq Scan on categories c (cost=0.00..20.70 rows=1070 width=40) (actual time=0.256..0.257 rows=14 loops=1)	37 -> Seq Scan on categories c (cost=0.00..20.70 rows=1070 width=40) (actual time=0.256..0.257 rows=14 loops=1)
38 Buffers: shared hit=1	38 Buffers: shared hit=1
39 Planning:	39 Planning:
40 Buffers: shared hit=27	40 Buffers: shared hit=27
41 Planning Time: 6.885 ms	41 Planning Time: 6.885 ms
42 Execution Time: 11.863 ms	42 Execution Time: 11.863 ms

느린 이유와 개선 방법

비-SARG 날짜 조건은 인덱스 범위 탐색을 방해할 수 있다. 튜닝 후에는 최근 실매출 주문을 먼저 축소하고 `order_items → products → categories` 순서로 연결한다.

Q3 튜닝 후

Q3. 기간/상태로 orders를 먼저 축소하고 SARG 범위 조건 사용 튜닝: 최근 90일 실매출 주문만 먼저 골라 조건해야 할 행 수를 줄인다. [Q1 실행계획 확인용] 최근 주문 선택과 조건 계획 확인 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH recent_sales AS MATERIALIZED (SELECT order_id FROM ecom.orders WHERE order_status IN ('paid', 'shipped', 'delivered') AND order_ts >= CURRENT_DATE - 90) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM recent_sales rs JOIN ecom.order_items oi ON oi.order_id = rs.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	Results 1 Statistics 1 EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH recent_sales AS MATERIALIZED (SELECT order_id FROM ecom.orders WHERE order_status IN ('paid', 'shipped', 'delivered') AND order_ts >= CURRENT_DATE - 90) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM recent_sales rs JOIN ecom.order_items oi ON oi.order_id = rs.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
20 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)	20 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.015..1.308 rows=10367 loops=1)
21 Buffers: shared hit=100	21 Buffers: shared hit=100
22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)	22 -> Hash (cost=131.68..131.68 rows=1023 width=8) (actual time=2.502..2.502 rows=2483 loops=1)
23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB	23 Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 129kB
24 Buffers: shared hit=40	24 Buffers: shared hit=40
25 -> Seq Scan on orders o (cost=0.00..131.68 rows=1023 width=8) (actual time=0.023..1.672 rows=2483 loops=1)	25 -> Seq Scan on orders o (cost=0.00..131.68 rows=1023 width=8) (actual time=0.023..1.672 rows=2483 loops=1)
26 Filter: ((order_status = ANY ('paid,shipped,delivered'))::text[]) AND ((order_ts)::date >= (CURRENT_DATE - 90))	26 Filter: ((order_status = ANY ('paid,shipped,delivered'))::text[]) AND ((order_ts)::date >= (CURRENT_DATE - 90))
27 Rows Removed by Filter: 1377	27 Rows Removed by Filter: 1377
28 Buffers: shared hit=40	28 Buffers: shared hit=40
29 -> Hash (cost=13.00..13.00 rows=600 width=16) (actual time=0.449..0.450 rows=600 loops=1)	29 -> Hash (cost=13.00..13.00 rows=600 width=16) (actual time=0.449..0.450 rows=600 loops=1)
30 Buckets: 1024 Batches: 1 Memory Usage: 37kB	30 Buckets: 1024 Batches: 1 Memory Usage: 37kB
31 Buffers: shared hit=7	31 Buffers: shared hit=7
32 -> Seq Scan on products p (cost=0.00..13.00 rows=600 width=16) (actual time=0.006..0.368 rows=600 loops=1)	32 -> Seq Scan on products p (cost=0.00..13.00 rows=600 width=16) (actual time=0.006..0.368 rows=600 loops=1)
33 Buffers: shared hit=7	33 Buffers: shared hit=7
34 -> Hash (cost=20.70..20.70 rows=1070 width=40) (actual time=0.276..0.276 rows=14 loops=1)	34 -> Hash (cost=20.70..20.70 rows=1070 width=40) (actual time=0.276..0.276 rows=14 loops=1)
35 Buckets: 2048 Batches: 1 Memory Usage: 17kB	35 Buckets: 2048 Batches: 1 Memory Usage: 17kB
36 Buffers: shared hit=1	36 Buffers: shared hit=1
37 -> Seq Scan on categories c (cost=0.00..20.70 rows=1070 width=40) (actual time=0.256..0.257 rows=14 loops=1)	37 -> Seq Scan on categories c (cost=0.00..20.70 rows=1070 width=40) (actual time=0.256..0.257 rows=14 loops=1)
38 Buffers: shared hit=1	38 Buffers: shared hit=1
39 Planning:	39 Planning:
40 Buffers: shared hit=27	40 Buffers: shared hit=27
41 Planning Time: 6.885 ms	41 Planning Time: 6.885 ms
42 Execution Time: 11.863 ms	42 Execution Time: 11.863 ms

SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	Results 1 Statistics 1 SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
categories 1 X SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	categories 1 X SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') AND o.order_ts::date >= CURRENT_DATE - 90 GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
1 13 Outdoor 758,672.65	1 13 Outdoor 758,672.65
2 2 Phones 541,480.74	2 2 Phones 541,480.74
3 6 Appliances 138,788.46	3 6 Appliances 138,788.46
4 14 Fitness 125,711.82	4 14 Fitness 125,711.82
5 11 Shoes 124,829.38	5 11 Shoes 124,829.38
6 7 Cookware 117,640.32	6 7 Cookware 117,640.32
7 4 Audio 112,653.77	7 4 Audio 112,653.77
8 3 Laptops 109,500.6	8 3 Laptops 109,500.6
9 9 Men 99,046.69	9 9 Men 99,046.69
10 10 Women 96,304.36	10 10 Women 96,304.36

WITH recent_sales AS MATERIALIZED (SELECT order_id FROM ecom.orders WHERE order_status IN ('paid', 'shipped', 'delivered') AND order_ts >= CURRENT_DATE - 90) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM recent_sales rs JOIN ecom.order_items oi ON oi.order_id = rs.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	Results 1 Statistics 1 WITH recent_sales AS MATERIALIZED (SELECT order_id FROM ecom.orders WHERE order_status IN ('paid', 'shipped', 'delivered') AND order_ts >= CURRENT_DATE - 90) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM recent_sales rs JOIN ecom.order_items oi ON oi.order_id = rs.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
categories 1 X WITH recent_sales AS MATERIALIZED (SELECT order_id FROM ecom.orders WHERE order_status IN ('paid', 'shipped', 'delivered') AND order_ts >= CURRENT_DATE - 90) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM recent_sales rs JOIN ecom.order_items oi ON oi.order_id = rs.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;	categories 1 X WITH recent_sales AS MATERIALIZED (SELECT order_id FROM ecom.orders WHERE order_status IN ('paid', 'shipped', 'delivered') AND order_ts >= CURRENT_DATE - 90) SELECT c.category_id, c.category_name, ROUND(SUM(oi.line_total), 2) AS revenue_90d FROM recent_sales rs JOIN ecom.order_items oi ON oi.order_id = rs.order_id JOIN ecom.products p ON p.product_id = oi.product_id JOIN ecom.categories c ON c.category_id = p.category_id GROUP BY c.category_id, c.category_name ORDER BY revenue_90d DESC, c.category_id LIMIT 10;
1 13 Outdoor 758,672.65	1 13 Outdoor 758,672.65
2 2 Phones 541,480.74	2 2 Phones 541,480.74
3 6 Appliances 138,788.46	3 6 Appliances 138,788.46
4 14 Fitness 125,711.82	4 14 Fitness 125,711.82
5 11 Shoes 124,829.38	5 11 Shoes 124,829.38
6 7 Cookware 117,640.32	6 7 Cookware 117,640.32
7 4 Audio 112,653.77	7 4 Audio 112,653.77
8 3 Laptops 109,500.6	8 3 Laptops 109,500.6
9 9 Men 99,046.69	9 9 Men 99,046.69
10 10 Women 96,304.36	10 10 Women 96,304.36

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH product Enter a SQL expression to filter results (use Ctrl+Space)	
Grid	A-Z QUERY PLAN
Text	13 Buffers: shared hit=70677
	14 -> Seq Scan on products p (cost=0.00..126896.10 rows=200 width=51) (actual time=1.089..35.299 rows=585 loops=1)
	15 Filter: (COALESCE((SubPlan 2), '0')::numeric) > '0'::numeric)
	16 Rows Removed by Filter: 15
	17 Buffers: shared hit=70677
	18 SubPlan 1
	19 -> Aggregate (cost=158.59..158.60 rows=1 width=32) (actual time=0.025..0.025 rows=1 loops=585)
	20 Buffers: shared hit=35254
	21 -> Nested Loop (cost=4.70..158.55 rows=14 width=6) (actual time=0.006..0.024 rows=14 loops=585)
	22 Buffers: shared hit=35254
	23 -> Bitmap Heap Scan on order_items oi (cost=4.42..49.43 rows=17 width=14) (actual time=0.002..0.005 rows=17 loops=585)
	24 Recheck Cond: (product_id = p.product_id)
	25 Heap Blocks: exact=3099
	26 Buffers: shared hit=4270
	27 -> Bitmap Index Scan on idx_order_items_product (cost=0.00..4.41 rows=17 width=0) (actual time=0.000..0.001 rows=17 loops=585)
	28 Index Cond: (product_id = p.product_id)
	29 Buffers: shared hit=1171
	30 -> Index Scan using orders_pkey on orders o (cost=0.28..6.42 rows=1 width=8) (actual time=0.001..0.001 rows=1 loops=585)
	31 Index Cond: (order_id = oi.order_id)
	32 Filter: (order_status = ANY ('(paid,shipped,delivered)::text[]))
	33 Rows Removed by Filter: 0
	34 Buffers: shared hit=30984
	35 SubPlan 2
	36 -> Aggregate (cost=158.59..158.60 rows=1 width=32) (actual time=0.033..0.033 rows=1 loops=600)
	37 Buffers: shared hit=35416
	38 -> Nested Loop (cost=4.70..158.55 rows=14 width=6) (actual time=0.010..0.031 rows=14 loops=600)
	39 Buffers: shared hit=35416
	40 -> Bitmap Heap Scan on order_items oi_1 (cost=4.42..49.43 rows=17 width=14) (actual time=0.005..0.009 rows=17 loops=600)
	41 Recheck Cond: (product_id = p.product_id)
	42 Heap Blocks: exact=3114
	43 Buffers: shared hit=4315
	44 -> Bitmap Index Scan on idx_order_items_product (cost=0.00..4.41 rows=17 width=0) (actual time=0.000..0.001 rows=17 loops=600)
	45 Index Cond: (product_id = p.product_id)
	46 Buffers: shared hit=1201
	47 -> Index Scan using orders_pkey on orders o_1 (cost=0.28..6.42 rows=1 width=8) (actual time=0.001..0.001 rows=1 loops=600)
	48 Index Cond: (order_id = oi_1.order_id)
	49 Filter: (order_status = ANY ('(paid,shipped,delivered)::text[]))
	50 Rows Removed by Filter: 0
	51 Buffers: shared hit=31101
Record	52 Planning:
	53 Buffers: shared hit=24
	54 Planning Time: 1.451 ms
	55 Execution Time: 37.373 ms

느린 이유와 개선 방법

튜닝 전에는 제품마다 주문상품과 주문을 반복 조회한다. 튜닝 후에는 전체 매출을 제품별로 한 번 집계한 후 Window Function을 적용한다.

Q4 튜닝 후

Q4. 전체 매출을 한 번만 집계한 뒤 RANK 적용	
튜닝: 제품마다 매출을 다시 찾기 않고 전체 데이터를 한 번 읽어 제품별로 묶는다.	
[O 실행계획 확인용] 반복 SubPlan이 제거됐는지 확인	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)	
WITH product_revenue AS (-- 전체 데이터를 제품별로 한 번 집계	
SELECT p.product_id,	
p.product_name,	
SUM(oi.line_total) AS revenue	
FROM ecom.orders o	
JOIN ecom.order_items oi ON oi.order_id = o.order_id	
JOIN ecom.products p ON p.product_id = oi.product_id	
WHERE o.order_status IN ('paid', 'shipped', 'delivered')	
GROUP BY p.product_id, p.product_name	
), ranked AS (-- 집계 결과에 순위를 부여	
SELECT product_id, product_name, revenue,	
RANK() OVER (ORDER BY revenue DESC) AS revenue_rank -- 매출 내림차순 공통 순위	
FROM product_revenue	
SELECT product_id, product_name, ROUND(revenue, 2) AS revenue, revenue_rank	
FROM ranked	
WHERE revenue_rank <= 20	
ORDER BY revenue_rank, product_id;	

WITH product_revenue AS (-- [O] 실제 제품별 순위 조회	
SELECT p.product_id, p.product_name, SUM(oi.line_total) AS revenue	
FROM ecom.orders o	
JOIN ecom.order_items oi ON oi.order_id = o.order_id	
JOIN ecom.products p ON p.product_id = oi.product_id	
WHERE o.order_status IN ('paid', 'shipped', 'delivered')	
GROUP BY p.product_id, p.product_name	
), ranked AS (	
SELECT product_id, product_name, revenue,	
RANK() OVER (ORDER BY revenue DESC) AS revenue_rank	
FROM product_revenue	
SELECT product_id, product_name, ROUND(revenue, 2) AS revenue, revenue_rank	
FROM ranked	
WHERE revenue_rank <= 20	
ORDER BY revenue_rank, product_id;	

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH product Enter a SQL expression to filter results (use Ctrl+Space)	
Grid	A-Z QUERY PLAN
Text	1 Sort (cost=520.70..522.20 rows=600 width=59) (actual time=9.509..9.513 rows=20 loops=1)
	2 Sort Key: ranked.revenue_rank, ranked.product_id
	3 Sort Method: quicksort Memory: 26kB
	4 Buffers: shared hit=147
	5 -> Subquery Scan on ranked (cost=481.03..493.01 rows=600 width=59) (actual time=9.481..9.501 rows=20 loops=1)
	6 Buffers: shared hit=147
	7 -> WindowAgg (cost=481.03..491.51 rows=600 width=59) (actual time=9.479..9.495 rows=20 loops=1)
	8 Run Condition: (rank() OVER (?) <= 20)
	9 Buffers: shared hit=147
	10 -> Sort (cost=481.01..482.51 rows=600 width=51) (actual time=9.473..9.477 rows=21 loops=1)
	11 Sort Key: product_revenue.revenue DESC
	12 Sort Method: quicksort Memory: 52kB
	13 Buffers: shared hit=147
	14 -> Subquery Scan on product_revenue (cost=445.83..453.33 rows=600 width=51) (actual time=9.089..9.292 rows=585 loops=1)
	15 Buffers: shared hit=147
	16 -> HashAggregate (cost=445.83..453.33 rows=600 width=51) (actual time=9.088..9.241 rows=585 loops=1)
	17 Group Key: p.product_id
	18 Batches: 1 Memory Usage: 297kB
	19 Buffers: shared hit=147
	20 -> Hash Join (cost=151.93..404.63 rows=8240 width=25) (actual time=2.183..7.128 rows=8230 loops=1)
	21 Hash Cond: (oi.product_id = p.product_id)
	22 Buffers: shared hit=147
	23 -> Hash Join (cost=131.43..362.34 rows=8240 width=14) (actual time=1.843..5.248 rows=8230 loops=1)
	24 Hash Cond: (oi.order_id = o.order_id)
	25 Buffers: shared hit=140
	26 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=22) (actual time=0.010..1.255 rows=10367 loops=1)
	27 Buffers: shared hit=100
	28 -> Hash (cost=93.08..93.08 rows=3068 width=8) (actual time=1.801..1.802 rows=3068 loops=1)
	29 Buckets: 4096 Batches: 1 Memory Usage: 152kB
	30 Buffers: shared hit=40
	31 -> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=8) (actual time=0.012..1.281 rows=3068 loops=1)
	32 Filter: (order_status = ANY ('(paid,shipped,delivered)::text[]))
	33 Rows Removed by Filter: 792
	34 Buffers: shared hit=40
	35 -> Hash (cost=13.00..13.00 rows=600 width=19) (actual time=0.315..0.316 rows=600 loops=1)
	36 Buckets: 1024 Batches: 1 Memory Usage: 39kB
	37 Buffers: shared hit=7
	38 -> Seq Scan on products p (cost=0.00..13.00 rows=600 width=19) (actual time=0.014..0.147 rows=600 loops=1)
	39 Buffers: shared hit=7
Record	40 Planning:
	41 Buffers: shared hit=114 read=3 dirtied=1
	42 Planning Time: 6.071 ms
	43 Execution Time: 9.654 ms

products 1 X	
WITH product_revenue AS (SELECT p.product_id, p.prod Enter a SQL expression to filter results (use Ctrl+Space)	
Grid	A-Z product_name
Text	123 revenue
	123 revenue_rank
	1 293 Product 465 859,785.6 1
	2 455 Product 378 430,633.92 2
	3 501 Product 439 9,189.04 3
	4 272 Product 315 8,234.57 4
	5 264 Product 225 8,109.2 5
	6 528 Product 549 8,040.23 6
	7 315 Product 136 7,868.31 7
	8 69 Product 42 7,817.88 8
	9 235 Product 114 7,584.68 9
	10 533 Product 39 7,426.7 10
	11 236 Product 584 7,398.53 11
	12 63 Product 32 7,375.03 12
	13 55 Product 481 6,944.38 13
	14 137 Product 463 6,919.99 14
	15 33 Product 211 6,859.89 15
	16 449 Product 418 6,748.8 16
	17 311 Product 96 6,699.06 17
	18 181 Product 264 6,586.17 18
	19 429 Product 498 6,539.14 19
	20 81 Product 522 6,463.1 20

구분	반복 SubPlan	Buffers	Execution Time	1위 제품/매출
튜닝 전	있음(585/600회)	hit=70,677	37.373 ms	Product 465 / 859,785.60
튜닝 후	없음	hit= 147	9.654 ms	Product 465 / 859,785.60

결과 해석: 제품별 반복 SubPlan을 1회 집계로 바꾸어 실행시간이 74.2% 단축되었다.


```
-- Q5. 주문별 매출 선집계 후 고객별 한 번의 GROUP BY로 RFM 산출
-- 튜닝: 고객 한 명마다 세 가지 서브쿼리를 반복하는 작업을 제거한다.
-- [① 실행계획 확인용] 고객별 반복 조회 대신 한 번에 집계하는지 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH order_totals AS (
    SELECT o.order_id, o.customer_id, o.order_ts,
           SUM(oi.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.customer_id, o.order_ts
), rfm AS (
    SELECT customer_id,
           CURRENT_DATE - MAX(order_ts)::date AS recency_days, -- 최근 구매 경과일
           COUNT(order_id) AS frequency, -- 구매 주문번호 수
           SUM(order_total) AS monetary -- 고객 총매출
    FROM order_totals
    GROUP BY customer_id
)
SELECT c.customer_id, c.full_name,
       r.recency_days, r.frequency, ROUND(r.monetary, 2) AS monetary
FROM rfm r
JOIN ecom.customers c ON c.customer_id = r.customer_id
ORDER BY r.monetary DESC, c.customer_id
LIMIT 20;
```

```
-- [②] 실제 고객별 RFM 조회
WITH order_totals AS (
    SELECT o.order_id, o.customer_id, o.order_ts,
           SUM(oi.line_total) AS order_total
    FROM ecom.orders o
    JOIN ecom.order_items oi ON oi.order_id = o.order_id
    WHERE o.order_status IN ('paid', 'shipped', 'delivered')
    GROUP BY o.order_id, o.customer_id, o.order_ts
), rfm AS (
    SELECT customer_id, CURRENT_DATE - MAX(order_ts)::date AS recency_days,
           COUNT(order_id) AS frequency, SUM(order_total) AS monetary
    FROM order_totals
    GROUP BY customer_id
)
SELECT c.customer_id, c.full_name,
       r.recency_days, r.frequency, ROUND(r.monetary, 2) AS monetary
FROM rfm r
JOIN ecom.customers c ON c.customer_id = r.customer_id
ORDER BY r.monetary DESC, c.customer_id
LIMIT 20;
```

	123 customer_id	AZ full_name	123 recency_days	123 frequency	123 monetary
1	8	Customer 8	2	23	35,154.22
2	16	Customer 16	1	23	31,003.24
3	18	Customer 18	3	23	30,283.04
4	14	Customer 14	6	23	29,322.59
5	6	Customer 6	0	22	28,703.23
6	13	Customer 13	2	22	28,633.41
7	2	Customer 2	8	23	28,623.31
8	1	Customer 1	3	23	28,546.26
9	20	Customer 20	0	22	28,531.13
10	9	Customer 9	1	23	28,488.91
11	17	Customer 17	8	23	27,317.53
12	24	Customer 24	0	22	27,075.74
13	23	Customer 23	4	22	25,717.57
14	30	Customer 30	0	23	24,815.39
15	4	Customer 4	1	23	24,726.24
16	12	Customer 12	4	23	22,419.91
17	19	Customer 19	0	23	22,412.27
18	22	Customer 22	1	23	22,206.5
19	7	Customer 7	1	23	22,034.39
20	29	Customer 29	0	22	21,696.95

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH order_totals AS (SELECT

1	Limit (cost=595.46..595.51 rows=20 width=97) (actual time=13.181..13.185 rows=20 loops=1)
2	Buffers: shared hit=180
3	-> Sort (cost=595.46..595.96 rows=200 width=97) (actual time=13.180..13.183 rows=20 loops=1)
4	Sort Key: r.monetary DESC, c.customer_id
5	Sort Method: top-N heapsort Memory: 28kB
6	Buffers: shared hit=180
7	-> Hash Join (cost=511.75..590.14 rows=200 width=97) (actual time=11.699..12.710 rows=2217 loops=1)
8	Hash Cond: (c.customer_id = r.customer_id)
9	Buffers: shared hit=180
10	-> Seq Scan on customers c (cost=0.00..70.00 rows=3000 width=21) (actual time=0.010..0.324 rows=3000 loops=1)
11	Buffers: shared hit=40
12	-> Hash (cost=509.25..509.25 rows=200 width=52) (actual time=11.675..11.677 rows=2217 loops=1)
13	Buckets: 4096 (originally 1024) Batches: 1 (originally 1) Memory Usage: 171kB
14	Buffers: shared hit=140
15	-> Subquery Scan on r (cost=503.25..509.25 rows=200 width=52) (actual time=10.032..11.245 rows=2217 loops=1)
16	Buffers: shared hit=140
17	-> HashAggregate (cost=503.25..507.25 rows=200 width=52) (actual time=10.031..11.010 rows=2217 loops=1)
18	Group Key: o.customer_id
19	Batches: 1 Memory Usage: 1153kB
20	Buffers: shared hit=140
21	-> HashAggregate (cost=403.54..441.89 rows=3068 width=56) (actual time=7.888..8.841 rows=3068 loops=1)
22	Group Key: o.order_id
23	Batches: 1 Memory Usage: 1393kB
24	Buffers: shared hit=140
25	-> Hash Join (cost=131.43..362.34 rows=8240 width=30) (actual time=1.422..5.116 rows=8230 loops=1)
26	Hash Cond: (oi.order_id = o.order_id)
27	Buffers: shared hit=140
28	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.013..1.160 rows=10367 loops=1)
29	Buffers: shared hit=100
30	-> Hash (cost=93.08..93.08 rows=3068 width=24) (actual time=1.389..1.389 rows=3068 loops=1)
31	Buckets: 4096 Batches: 1 Memory Usage: 200kB
32	Buffers: shared hit=40
33	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=24) (actual time=0.016..0.940 rows=3068 loops=1)
34	Filter: (order_status = ANY ('{paid,shipped,delivered}'::text[]))
35	Rows Removed by Filter: 792
36	Buffers: shared hit=40
37	Planning:
38	Buffers: shared hit=18
39	Planning Time: 0.729 ms
40	Execution Time: 13.785 ms

구분	집계 방식	Buffers	Execution Time	전후 결과 동일 여부
튜닝 전	고객별 상관 서브쿼리	hit=17,287	21.915 ms	-
튜닝 후	주문 선집계 후 고객 GROUP BY	hit=180	13.785 ms	동일

RFM 결과 해석: Customer 8이 최근성 2일·빈도 23회·금액 35,154.22로 최고 금액 고객이며 37.1% 단축되었다.

8. Q6 - 첫 구매 후 30일 내 재구매율

요청사항

실구매 고객 중 첫 구매 후 30일 안에 추가 실구매가 있었던 고객의 비율을 제공한다.


Q6 튜닝 전



느린 이유와 개선 방법

튜닝 전에는 고객별 첫 구매 이후 주문을 **EXISTS** 로 반복 탐색한다. 튜닝 후에는 Window Function으로 첫 구매시각을 표시하고 고객별 **BOOL_OR** 로 재구매 여부를 한 번 집계한다.

Q6 튜닝 후



구분	구매고객	30일 내 재구매고객	재구매율	Execution Time
튜닝 전	2,217	226	10.19%	7.881 ms
튜닝 후	2,217	226	10.19%	6.166 ms

결과 해석: 재구매율은 전후 동일하며 Window와 BOOL_OR 집계로 실행시간이 21.8% 단축되었다.

9. Q7 - 재주문 임계치 미만 상품

요청사항

qty_on_hand < reorder_point 인 상품과 부족수량을 제공한다.

Q7 튜닝 전




```
-- Q8. 평점 4.5 이상, 리뷰 50개 이상 효자상품
-- 문제점: 상품마다 AVG와 COUNT를 SELECT와 WHERE에서 반복 계산한다.

-- [① 실행계획 확인용] 제품별 리뷰 반복 집계 횟수 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
SELECT p.product_id,
       p.product_name,
       ROUND((SELECT AVG(r.rating) FROM ecom.reviews r
              WHERE r.product_id = p.product_id), 2) AS avg_rating, -- 제품별 평균평점
       (SELECT COUNT(r.review_id) FROM ecom.reviews r
        WHERE r.product_id = p.product_id) AS review_count -- 제품별 리뷰 수
FROM ecom.products p
WHERE (SELECT AVG(r.rating) FROM ecom.reviews r
      WHERE r.product_id = p.product_id) >= 4.5
      AND (SELECT COUNT(r.review_id) FROM ecom.reviews r
          WHERE r.product_id = p.product_id) >= 50
ORDER BY avg_rating DESC, review_count DESC, p.product_id;
```

SQL Query Results:

id	product_id	product_name	avg_rating	review_count
1	57	Product 491	4.85	160
2	229	Product 464	4.83	160
3	163	Product 253	4.81	160
4	263	Product 285	4.79	160
5	426	Product 258	4.79	160
6	243	Product 395	4.78	160
7	268	Product 25	4.77	160
8	297	Product 75	4.76	160
9	481	Product 189	4.76	160
10	356	Product 556	4.75	161
11	178	Product 113	4.74	160
12	114	Product 262	4.69	160

Query Plan (EXPLAIN ANALYZE):

Step	Operation	Cost	Actual Time	Actual Rows	Width	Loops
11	Buffers: shared hit=66					
12	-> Bitmap Heap Scan on reviews r	(cost=4.40..25.39 rows=16 width=4)	(actual time=0.011..0.022 rows=160 loops=12)			
13	Recheck Cond: (product_id = p.product_id)					
14	Heap Blocks: exact=32					
15	Buffers: shared hit=66					
16	-> Bitmap Index Scan on reviews_product_id_customer_id_key	(cost=0.00..4.40 rows=16 width=0)	(actual time=0.009..0.009 rows=160 loops=12)			
17	Index Cond: (product_id = p.product_id)					
18	Buffers: shared hit=34					
19	SubPlan 2					
20	-> Aggregate	(cost=25.43..25.44 rows=1 width=8)	(actual time=0.034..0.034 rows=1 loops=12)			
21	Buffers: shared hit=66					
22	-> Bitmap Heap Scan on reviews r_1	(cost=4.40..25.39 rows=16 width=8)	(actual time=0.011..0.022 rows=160 loops=12)			
23	Recheck Cond: (product_id = p.product_id)					
24	Heap Blocks: exact=32					
25	Buffers: shared hit=66					
26	-> Bitmap Index Scan on reviews_product_id_customer_id_key	(cost=0.00..4.40 rows=16 width=0)	(actual time=0.008..0.008 rows=160 loops=12)			
27	Index Cond: (product_id = p.product_id)					
28	Buffers: shared hit=34					
29	SubPlan 4					
30	-> Aggregate	(cost=25.43..25.44 rows=1 width=8)	(actual time=0.005..0.005 rows=1 loops=600)			
31	Buffers: shared hit=1360					
32	-> Bitmap Heap Scan on reviews r_3	(cost=4.40..25.39 rows=16 width=8)	(actual time=0.003..0.003 rows=3 loops=600)			
33	Recheck Cond: (product_id = p.product_id)					
34	Heap Blocks: exact=150					
35	Buffers: shared hit=1360					
36	-> Bitmap Index Scan on reviews_product_id_customer_id_key	(cost=0.00..4.40 rows=16 width=0)	(actual time=0.002..0.002 rows=3 loops=600)			
37	Index Cond: (product_id = p.product_id)					
38	Buffers: shared hit=1210					
39	SubPlan 3					
40	-> Aggregate	(cost=25.43..25.44 rows=1 width=32)	(actual time=0.041..0.041 rows=1 loops=12)			
41	Buffers: shared hit=66					
42	-> Bitmap Heap Scan on reviews r_2	(cost=4.40..25.39 rows=16 width=4)	(actual time=0.012..0.024 rows=160 loops=12)			
43	Recheck Cond: (product_id = p.product_id)					
44	Heap Blocks: exact=32					
45	Buffers: shared hit=66					
46	-> Bitmap Index Scan on reviews_product_id_customer_id_key	(cost=0.00..4.40 rows=16 width=0)	(actual time=0.009..0.009 rows=160 loops=12)			
47	Index Cond: (product_id = p.product_id)					
48	Buffers: shared hit=34					
49	Planning:					
50	Buffers: shared hit=206 dirtied=7					
51	Planning Time: 4.214 ms					
52	Execution Time: 4.551 ms					

느린 이유와 개선 방법

튜닝 전에는 제품별 평균과 건수를 SELECT와 WHERE에서 반복 계산한다. 튜닝 후에는 리뷰를 한 번 읽고 **GROUP BY** 와 **HAVING** 으로 조건을 적용한다.

Q8 튜닝 후

SQL Query Results:

id	product_id	product_name	avg_rating	review_count
1	57	Product 491	4.85	160
2	229	Product 464	4.83	160
3	163	Product 253	4.81	160
4	263	Product 285	4.79	160
5	426	Product 258	4.79	160
6	243	Product 395	4.78	160
7	268	Product 25	4.77	160
8	297	Product 75	4.76	160
9	481	Product 189	4.76	160
10	356	Product 556	4.75	161
11	178	Product 113	4.74	160
12	114	Product 262	4.69	160

Query Plan (EXPLAIN ANALYZE):

Step	Operation	Cost	Actual Time	Actual Rows	Width	Loops
1	Sort	(cost=95.27..95.44 rows=67 width=59)	(actual time=0.946..0.947 rows=12 loops=1)			
2	Sort Key: (round(avg(r.rating), 2)) DESC, (count(r.review_id)) DESC, p.product_id					
3	Sort Method: quicksort Memory: 25kB					
4	Buffers: shared hit=28					
5	-> HashAggregate	(cost=82.57..93.24 rows=67 width=59)	(actual time=0.908..0.935 rows=12 loops=1)			
6	Group Key: p.product_id					
7	Filter: ((avg(r.rating) >= 4.5) AND (count(r.review_id) >= 50))					
8	Batches: 1 Memory Usage: 73kB					
9	Rows Removed by Filter: 118					
10	Buffers: shared hit=28					
11	-> Hash Join	(cost=20.50..67.28 rows=2039 width=31)	(actual time=0.174..0.667 rows=2039 loops=1)			
12	Hash Cond: (r.product_id = p.product_id)					
13	Buffers: shared hit=28					
14	-> Seq Scan on reviews r	(cost=0.00..41.39 rows=2039 width=20)	(actual time=0.012..0.225 rows=2039 loops=1)			
15	Buffers: shared hit=21					
16	-> Hash	(cost=13.00..13.00 rows=600 width=19)	(actual time=0.149..0.149 rows=600 loops=1)			
17	Buckets: 1024 Batches: 1 Memory Usage: 39kB					
18	Buffers: shared hit=7					
19	-> Seq Scan on products p	(cost=0.00..13.00 rows=600 width=19)	(actual time=0.006..0.075 rows=600 loops=1)			
20	Buffers: shared hit=7					
21	Planning:					
22	Buffers: shared hit=31 read=4					
23	Planning Time: 2.005 ms					
24	Execution Time: 1.016 ms					

SQL Query Results:

id	product_id	product_name	avg_rating	review_count
1	57	Product 491	4.85	160
2	229	Product 464	4.83	160
3	163	Product 253	4.81	160
4	263	Product 285	4.79	160
5	426	Product 258	4.79	160
6	243	Product 395	4.78	160
7	268	Product 25	4.77	160
8	297	Product 75	4.76	160
9	481	Product 189	4.76	160
10	356	Product 556	4.75	161
11	178	Product 113	4.74	160
12	114	Product 262	4.69	160

구분	Reviews 접근 방식	Buffers	Execution Time	조건 충족 상품 수
튜닝 전	반복 Bitmap Scan	hit=1,565	4.551 ms	12개
튜닝 후	Seq Scan + 1회 집계	hit=28	1.016 ms	12개

결과 해석: 조건 충족 상품은 12개이며 1위 Product 491은 평점 4.85-리뷰 160개이고 77.7% 단축되었다.

11. Q9 - 쿠폰 사용 여부별 AOV

요청사항

쿠폰 사용 주문과 미사용 주문의 주문당 평균 금액을 비교한다.

Q9 튜닝 전

```
-- Q9. 쿠폰 사용 여부별 평균 주문금액
-- 문제점: 상세 행 조인 후 COUNT(DISTINCT)로 주문 수를 복원한다.
-- 의미: AOV는 전체 매출을 중복 없는 주문 수로 나눈 주문당 평균금액이다.

-- [Q1 실행계획 확인용] 상세행 조인과 DISTINCT 집계 비용 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
SELECT CASE WHEN o.coupon_code IS NULL THEN '미사용' ELSE '사용' END AS coupon_group, -- 쿠폰 여부 분류
COUNT(DISTINCT o.order_id) AS order_count, -- 중복을 제거한 주문 수
ROUND(SUM(oi.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov -- 주문당 평균금액
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY 1
ORDER BY 1;
```

coupon_group	order_count	aov
미사용	2,307	619.55
사용	761	1,694.79

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT CASE WHEN o.coupon_code IS NULL THEN '미사용' ELSE '사용' END AS coupon_group, COUNT(DISTINCT o.order_id) AS order_count, ROUND(SUM(oi.line_total) / NULLIF(COUNT(DISTINCT o.order_id), 0), 2) AS aov FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY 1 ORDER BY 1;	
Grid	AZ QUERY PLAN
1	GroupAggregate (cost=898.29..980.71 rows=1 width=72) (actual time=17.358..17.942 rows=2 loops=1)
2	Group Key: (CASE WHEN (o.coupon_code IS NULL) THEN '미사용'::text ELSE '사용'::text END)
3	Buffers: shared hit=143
4	-> Sort (cost=898.29..918.89 rows=8240 width=46) (actual time=16.192..16.553 rows=8230 loops=1)
5	Sort Key: (CASE WHEN (o.coupon_code IS NULL) THEN '미사용'::text ELSE '사용'::text END), o.order_id
6	Sort Method: quicksort Memory: 750kB
7	Buffers: shared hit=143
8	-> Hash Join (cost=131.43..362.34 rows=8240 width=46) (actual time=1.732..9.532 rows=8230 loops=1)
9	Hash Cond: (oi.order_id = o.order_id)
10	Buffers: shared hit=140
11	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.006..5.943 rows=10367 loops=1)
12	Buffers: shared hit=100
13	-> Hash (cost=93.08..93.08 rows=3068 width=15) (actual time=1.702..1.703 rows=3068 loops=1)
14	Buckets: 4096 Batches: 1 Memory Usage: 158kB
15	Buffers: shared hit=40
16	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=15) (actual time=0.012..1.193 rows=3068 loops=1)
17	Filter: (order_status = ANY ('{paid,shipped,delivered}'::text[]))
18	Rows Removed by Filter: 792
19	Buffers: shared hit=40
20	Planning:
21	Buffers: shared hit=150 dirtied=1
22	Planning Time: 4.284 ms
23	Execution Time: 17.993 ms

느린 이유와 개선 방법

상세행 조인 후에는 주문 수 복원을 위해 **COUNT(DISTINCT)** 가 필요하다. 튜닝 후에는 주문별 금액을 먼저 계산한 뒤 쿠폰 사용 여부로 그룹핑해 **AVG(order_total)** 을 계산한다.

Q9 튜닝 후

```
-- Q9. 주문별 매출 선집계로 DISTINCT 제거
-- 튜닝: 주문별 금액을 먼저 한 행으로 만든 뒤 그룹별 AVG(order_total)을 계산한다.
-- [Q1 실행계획 확인용] 주문별 선집계 후 AVG 계산 계획 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH order_totals AS (
SELECT o.order_id,
(o.coupon_code IS NOT NULL) AS used_coupon, -- 쿠폰 사용 여부를 TRUE/FALSE로 변환
SUM(oi.line_total) AS order_total -- 주문별 총금액
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY o.order_id, o.coupon_code
)
SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group,
COUNT(order_id) AS order_count,
ROUND(AVG(order_total), 2) AS aov -- 주문별 금액의 평균
FROM order_totals
GROUP BY used_coupon
ORDER BY coupon_group;
```

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH order_totals AS (SELECT o.order_id, (o.coupon_code IS NOT NULL) AS used_coupon, SUM(oi.line_total) AS order_total FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY o.order_id, o.coupon_code) SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group, COUNT(order_id) AS order_count, ROUND(AVG(order_total), 2) AS aov FROM order_totals GROUP BY used_coupon ORDER BY coupon_group;	
Grid	AZ QUERY PLAN
1	Sort (cost=495.62..495.63 rows=2 width=73) (actual time=9.883..9.885 rows=2 loops=1)
2	Sort Key: (CASE WHEN ((o.coupon_code IS NOT NULL)) THEN '사용'::text ELSE '미사용'::text END)
3	Sort Method: quicksort Memory: 25kB
4	Buffers: shared hit=140
5	-> HashAggregate (cost=495.58..495.61 rows=2 width=73) (actual time=9.788..9.791 rows=2 loops=1)
6	Group Key: (o.coupon_code IS NOT NULL)
7	Batches: 1 Memory Usage: 24kB
8	Buffers: shared hit=140
9	-> HashAggregate (cost=403.54..441.89 rows=3068 width=48) (actual time=8.547..9.389 rows=3068 loops=1)
10	Group Key: o.order_id
11	Batches: 1 Memory Usage: 1393kB
12	Buffers: shared hit=140
13	-> Hash Join (cost=131.43..362.34 rows=8240 width=21) (actual time=1.424..5.397 rows=8230 loops=1)
14	Hash Cond: (oi.order_id = o.order_id)
15	Buffers: shared hit=140
16	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.014..1.794 rows=10367 loops=1)
17	Buffers: shared hit=100
18	-> Hash (cost=93.08..93.08 rows=3068 width=15) (actual time=1.349..1.350 rows=3068 loops=1)
19	Buckets: 4096 Batches: 1 Memory Usage: 158kB
20	Buffers: shared hit=40
21	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=15) (actual time=0.008..0.945 rows=3068 loops=1)
22	Filter: (order_status = ANY ('{paid,shipped,delivered}'::text[]))
23	Rows Removed by Filter: 792
24	Buffers: shared hit=40
25	Planning:
26	Buffers: shared hit=22 dirtied=1
27	Planning Time: 0.613 ms
28	Execution Time: 10.057 ms

```
-- [Q2] 실제 쿠폰 그룹 비교 결과 조회
WITH order_totals AS (
SELECT o.order_id, (o.coupon_code IS NOT NULL) AS used_coupon,
SUM(oi.line_total) AS order_total
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered')
GROUP BY o.order_id, o.coupon_code
)
SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group,
COUNT(order_id) AS order_count, ROUND(AVG(order_total), 2) AS aov
FROM order_totals
GROUP BY used_coupon
ORDER BY coupon_group;
```

Results 1 X

WITH order_totals AS (SELECT o.order_id, (o.coupon_code IS NOT NULL) AS used_coupon, SUM(oi.line_total) AS order_total FROM ecom.orders o JOIN ecom.order_items oi ON oi.order_id = o.order_id WHERE o.order_status IN ('paid', 'shipped', 'delivered') GROUP BY o.order_id, o.coupon_code) SELECT CASE WHEN used_coupon THEN '사용' ELSE '미사용' END AS coupon_group, COUNT(order_id) AS order_count, ROUND(AVG(order_total), 2) AS aov FROM order_totals GROUP BY used_coupon ORDER BY coupon_group;

Grid

123 coupon_group 123 order_count 123 aov

1 미사용 2,307 619.55

2 사용 761 1,694.79

그룹	주문 수	AOV	해석
쿠폰 미사용	2,307	619.55	비교 기준
쿠폰 사용	761	1,694.79	미사용 대비 약 2.74배

느린 이유와 개선 방법

튜닝 전에는 고객 3,000명의 누적매출과 상위 고객의 최근 매출을 상관 서브쿼리로 반복 계산한다. 튜닝 후에는 전체 고객을 기준으로 누적매출과 최근 60일 매출을 한 번에 집계하고, **ROW_NUMBER()** 와 전체 고객 수를 이용해 30명을 정확히 추출한다.

Q10 튜닝 후

```
-- Q10. 전체 3,000명의 누적매출과 최근 60일 매출을 한 번에 집계한 뒤
-- 누적매출 상위 1%(30명)를 정확히 선정
-- 튜닝: 누적매출과 60일 매출을 한 번의 GROUP BY로 동시에 계산한다.
-- [⓪ 실행계획 확인용] 고객별 SubPlan 없이 한 번에 집계하는지 확인
EXPLAIN (ANALYZE, BUFFERS, SUMMARY)
WITH customer_sales AS (
  SELECT c.customer_id,
         c.full_name,
         COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue, -- 고객 누적매출
         COALESCE(SUM(oi.line_total) FILTER (
           WHERE o.order_ts >= now() - INTERVAL '60 days'
         ), 0) AS revenue_60d
        FROM ecom.customers c
        LEFT JOIN ecom.orders o
          ON o.customer_id = c.customer_id
         AND o.order_status IN ('paid', 'shipped', 'delivered')
        LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id
        GROUP BY c.customer_id, c.full_name
      ), ranked AS (
        SELECT customer_id, full_name, lifetime_revenue, revenue_60d,
               ROW_NUMBER() OVER (
                 ORDER BY lifetime_revenue DESC, customer_id
               ) AS lifetime_rank,
               COUNT(customer_id) OVER () AS customer_count -- 전체 고객 수를 각 행에 표시
        FROM customer_sales
      )
  SELECT customer_id, full_name, lifetime_rank,
         ROUND(lifetime_revenue, 2) AS lifetime_revenue,
         ROUND(revenue_60d, 2) AS revenue_60d
  FROM ranked
 WHERE lifetime_rank <= CEIL(customer_count * 0.01) -- 전체 고객 중 상위 1%, 정확히 30명
 ORDER BY lifetime_rank;
```

```
-- [⓪] 실제 상위 30명 결과 조회
WITH customer_sales AS (
  SELECT c.customer_id, c.full_name,
         COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue,
         COALESCE(SUM(oi.line_total) FILTER (
           WHERE o.order_ts >= now() - INTERVAL '60 days'
         ), 0) AS revenue_60d
        FROM ecom.customers c
        LEFT JOIN ecom.orders o
          ON o.customer_id = c.customer_id
         AND o.order_status IN ('paid', 'shipped', 'delivered')
        LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id
        GROUP BY c.customer_id, c.full_name
      ), ranked AS (
        SELECT customer_id, full_name, lifetime_revenue, revenue_60d,
               ROW_NUMBER() OVER (
                 ORDER BY lifetime_revenue DESC, customer_id
               ) AS lifetime_rank,
               COUNT(customer_id) OVER () AS customer_count
        FROM customer_sales
      )
  SELECT customer_id, full_name, lifetime_rank,
         ROUND(lifetime_revenue, 2) AS lifetime_revenue,
         ROUND(revenue_60d, 2) AS revenue_60d
  FROM ranked
 WHERE lifetime_rank <= CEIL(customer_count * 0.01)
 ORDER BY lifetime_rank;
```

customers 1 X					
WITH customer_sales AS (SELECT c.customer_id, c.full_name, COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue, COALESCE(SUM(oi.line_total) FILTER (WHERE o.order_ts >= now() - INTERVAL '60 days'), 0) AS revenue_60d FROM ecom.customers c LEFT JOIN ecom.orders o ON o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id GROUP BY c.customer_id, c.full_name), ranked AS (SELECT customer_id, full_name, lifetime_revenue, revenue_60d, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM customer_sales) SELECT customer_id, full_name, lifetime_rank, ROUND(lifetime_revenue, 2) AS lifetime_revenue, ROUND(revenue_60d, 2) AS revenue_60d FROM ranked WHERE lifetime_rank <= CEIL(customer_count * 0.01) ORDER BY lifetime_rank;					
	customer_id	full_name	lifetime_rank	lifetime_revenue	revenue_60d
1	8	Customer 8	1	35,154.22	32,794.66
2	16	Customer 16	2	31,003.24	31,003.24
3	18	Customer 18	3	30,283.04	29,772.64
4	14	Customer 14	4	29,322.59	29,322.59
5	6	Customer 6	5	28,703.23	28,703.23
6	13	Customer 13	6	28,633.41	28,633.41
7	2	Customer 2	7	28,623.31	28,623.31
8	1	Customer 1	8	28,546.26	28,546.26
9	20	Customer 20	9	28,531.13	28,531.13
10	9	Customer 9	10	28,488.91	28,488.91
11	17	Customer 17	11	27,317.53	26,943.11
12	24	Customer 24	12	27,075.74	27,075.74
13	23	Customer 23	13	25,717.57	25,717.57
14	30	Customer 30	14	24,815.39	24,815.39
15	4	Customer 4	15	24,726.24	24,101.82
16	12	Customer 12	16	22,419.91	21,470.83
17	19	Customer 19	17	22,412.27	22,412.27
18	22	Customer 22	18	22,206.5	21,128.93
19	7	Customer 7	19	22,034.39	22,034.39
20	29	Customer 29	20	21,696.95	21,696.95
21	11	Customer 11	21	21,635.89	20,199.13
22	5	Customer 5	22	21,557.53	21,557.53
23	15	Customer 15	23	21,466.9	21,466.9
24	21	Customer 21	24	21,430.97	21,430.97
25	28	Customer 28	25	20,490.17	19,053.41
26	26	Customer 26	26	18,974.16	18,974.16
27	3	Customer 3	27	18,431.44	18,220.72
28	10	Customer 10	28	17,990.28	17,990.28
29	27	Customer 27	29	17,135.65	17,135.65
30	25	Customer 25	30	15,993.86	15,993.86

Results 1 X	
EXPLAIN (ANALYZE, BUFFERS, SUMMARY) WITH customer_sales AS (SELECT c.customer_id, c.full_name, COALESCE(SUM(oi.line_total), 0) AS lifetime_revenue, COALESCE(SUM(oi.line_total) FILTER (WHERE o.order_ts >= now() - INTERVAL '60 days'), 0) AS revenue_60d FROM ecom.customers c LEFT JOIN ecom.orders o ON o.customer_id = c.customer_id AND o.order_status IN ('paid', 'shipped', 'delivered') LEFT JOIN ecom.order_items oi ON oi.order_id = o.order_id GROUP BY c.customer_id, c.full_name), ranked AS (SELECT customer_id, full_name, lifetime_revenue, revenue_60d, ROW_NUMBER() OVER (ORDER BY lifetime_revenue DESC, customer_id) AS lifetime_rank, COUNT(customer_id) OVER () AS customer_count FROM customer_sales) SELECT customer_id, full_name, lifetime_rank, ROUND(lifetime_revenue, 2) AS lifetime_revenue, ROUND(revenue_60d, 2) AS revenue_60d FROM ranked WHERE lifetime_rank <= CEIL(customer_count * 0.01) ORDER BY lifetime_rank;	
Grid	QUERY PLAN
1	Sort (cost=1053.20..1055.70 rows=1000 width=93) (actual time=16.928..16.932 rows=30 loops=1)
2	Sort Key: ranked.lifetime_rank
3	Sort Method: quicksort Memory: 27kB
4	Buffers: shared hit=180
5	-> Subquery Scan on ranked (cost=930.83..1003.37 rows=1000 width=93) (actual time=15.857..16.256 rows=3000 loops=1)
6	Filter: (((ranked.lifetime_rank)::numeric <= ceil(((ranked.customer_count)::numeric * 0.01)))
7	Rows Removed by Filter: 2970
8	Buffers: shared hit=180
9	-> WindowAgg (cost=930.83..930.87 rows=3000 width=101) (actual time=15.857..16.256 rows=3000 loops=1)
10	Buffers: shared hit=180
11	-> WindowAgg (cost=833.39..893.37 rows=3000 width=93) (actual time=14.683..15.357 rows=3000 loops=1)
12	Buffers: shared hit=180
13	-> Sort (cost=833.37..840.87 rows=3000 width=85) (actual time=14.679..14.788 rows=3000 loops=1)
14	Sort Key: customer_sales.lifetime_revenue DESC, customer_sales.customer_id
15	Sort Method: quicksort Memory: 246kB
16	Buffers: shared hit=180
17	-> Subquery Scan on customer_sales (cost=615.11..660.11 rows=3000 width=85) (actual time=12.711..13.595 rows=3000 loops=1)
18	Buffers: shared hit=180
19	-> HashAggregate (cost=615.11..660.11 rows=3000 width=85) (actual time=12.710..13.399 rows=3000 loops=1)
20	Group Key: c.customer_id
21	Batches: 1 Memory Usage: 1905kB
22	Buffers: shared hit=180
23	-> Hash Right Join (cost=238.93..491.51 rows=8240 width=35) (actual time=3.716..8.317 rows=9013 loops=1)
24	Hash Cond: (o.customer_id = c.customer_id)
25	Buffers: shared hit=180
26	-> Hash Right Join (cost=131.43..362.34 rows=8240 width=22) (actual time=1.959..4.969 rows=8230 loops=1)
27	Hash Cond: (oi.order_id = o.order_id)
28	Buffers: shared hit=140
29	-> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.021..1.052 rows=10367 loops=1)
30	Buffers: shared hit=100
31	-> Hash (cost=93.08..93.08 rows=3068 width=24) (actual time=1.912..1.912 rows=3068 loops=1)
32	Buckets: 4096 Batches: 1 Memory Usage: 200kB
33	Buffers: shared hit=40
34	-> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=24) (actual time=0.008..1.308 rows=3068 loops=1)
35	Filter: (order_status = ANY ('{paid,shipped,delivered}'))::text[]
36	Rows Removed by Filter: 792
37	Buffers: shared hit=40
38	-> Hash (cost=70.00..70.00 rows=3000 width=21) (actual time=1.717..1.718 rows=3000 loops=1)
39	Buckets: 4096 Batches: 1 Memory Usage: 190kB
40	Buffers: shared hit=40
41	-> Seq Scan on customers c (cost=0.00..70.00 rows=3000 width=21) (actual time=0.028..0.929 rows=3000 loops=1)
42	Buffers: shared hit=40

43	Planning:
44	Buffers: shared hit=33
45	Planning Time: 1.384 ms
46	Execution Time: 17.230 ms

검증 항목	기대값	실제값
전체 고객 수	3,000	3,000
상위 1% 고객 수	30	30
누적매출 1위 고객	-	Customer 8 / 35,154.22
해당 고객 최근 60일 매출	-	32,794.66

구분	반복 SubPlan	Buffers	Execution Time
튜닝 전	있음(3,000회)	hit=21,777	23.321 ms
튜닝 후	없음	hit= 180	17.230 ms

결과 해석: 전체 3,000명에서 누적매출 상위 30명을 정확히 선정했고 실행시간은 26.1% 단축되었다.

13. Q11 - 안전 나눗셈 함수 비교

함수 정의 차이

함수	정의 파일	분모가 0일 때
ecom.f_safe_div	스키마 파일	0 반환
ecom.safe_div	시드 파일	NULL 반환

```

-- Q11. 스카마와 시드에 정의된 두 함수의 정상 분모 결과 비교
-- [① 정상 분모] 분모가 0이 아니면 두 함수가 같은 계산 결과를 반환

SELECT ecom.f_safe_div(
    SUM(oi.line_total), COUNT(DISTINCT o.order_id)
) AS schema_f_safe_div_aov,
ecom.safe_div(
    SUM(oi.line_total), COUNT(DISTINCT o.order_id)
) AS seed_safe_div_aov
FROM ecom.orders o
JOIN ecom.order_items oi ON oi.order_id = o.order_id
WHERE o.order_status IN ('paid', 'shipped', 'delivered');

```

orders(+) 1 X

SELECT ecom.f_safe_div(SUM(oi.line_total), COUNT(DISTINCT o.order_id)) AS schema_f_safe_div_aov, ecom.seed_safe_div_aov

	123 schema_f_safe_div_aov	123 seed_safe_div_aov
1	886.2541297262	886.2541297262

- 자이럼: f_safe_div(0, safe_div NULL을 반환한다.
 - [2 0 분조] 0 입력은 NULL 반환의 외부 정책 지역 확인
 - **SELECT ecom.f_safe_div(100, 0) AS schema_returns_zero, ecom.seed_function_returns_zero, -- 0으로 나눈 결과 0
 ecom.f_safe_div(100, 0) AS seed_function_returns_null; -- 0으로 나눈 NULL [값 없음]**

results 1 x Statistics 1
 SELECT ecom.f_safe_div(100, 0) AS schema_returns_zero, ecom. Enter a SQL expression to

123 schema_function_returns_zero	123 seed_function_returns_null
0	[NULL]

테스트	f_safe_div	safe_div	해석
정상 AOV	886.2541297262	886.2541297262	분모가 0이 아니면 같은 계산 결과
100 / 0	0	NULL	보고서 요구에 맞는 정책을 선택해야 함

```

SET search_path = ecom, public; -- 객체 이름 앞에 스키마를 생략하면 ecom을 먼저 탐색

-- 공통 업무 정의
-- 최근 30일 동안 paid, shipped, delivered 상태인 주문과 주문상품을 연결하여 총매출을 계산한다.
-- 세 테스트는 업무 로직과 결과가 같고, 물리적인 JOIN 방식만 다르다.

-- =====
-- 1. Nested Loop Join(NLJ)
-- =====
-- 처리 방식: 바깥쪽 입력이 각 행마다 왼쪽 입력에서 일치하는행을 반복해서 찾는다.
-- 유리한 조건: 바깥쪽 결과가 적고, 왼쪽 조인 키에 인덱스가 있을 때 유리하다.
-- 확인할 실행계획: Nested Loop와 안쪽의 Index Scan 또는 Index Only Scan

BEGIN;
SET LOCAL enable_hashjoin = off; -- SET LOCAL이 현재 테스트에만 적용되도록 트랜잭션 시작
SET LOCAL enable_mergejoin = off; -- Hash Join 후보로 비활성화
SET LOCAL enable_nestloop = on; -- Merge Join 후보를 비활성화
-- Nested Loop Join 후보만 활성화

EXPLAIN (ANALYZE, BUFFERS, SETTINGS, SUMMARY) -- 실제 실행시간·버퍼·변경 설정·요약을 함께 출력
SELECT ROUND(SUM(o.i.line_total), 2) AS total_sales_30d -- 주문상품 금액을 합산하고 소수점 둘째 자리까지 표시
FROM ecom.orders o -- 주문 헤더 테이블, 별칭 ts
JOIN ecom.order_items oi -- 주문별 상품과 금액이 저장된 상세 테이블, 별칭 oi
ON oi.order_id = o.order_id -- 주문번호가 같은 주문과 주문상품을 연결하는 등등 조건
WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 실제 매출로 인정하는 주문 상태만 포함
AND o.order_ts >= CURRENT_DATE - 30; -- 오늘을 기준으로 최근 30일 주문만 조회

ROLLBACK; -- 설정 변경을 취소하여 다음 조인 테스트에 영향을 주지 않음


```

Results 1 x Statistics 1

BEGIN; SET LOCAL enable_hashjoin = off; SET LOCAL enable_mergejoin = 1; Enter a SQL expression to filter results (use Ctrl+Space)

AZ QUERY PLAN

- Aggregate (cost=594.87..594.89 rows=1 width=32) (actual time=8.957..8.963 rows=1 loops=1)
Buffers: shared hit=1837 read=58
-> Nested Loop (cost=0.57..588.86 rows=2404 width=6) (actual time=0.766..8.031 rows=2538 loops=1)
Buffers: shared hit=1837 read=58
-> Index Only Scan using idx_orders_sales_ts_order on orders o (cost=0.28..43.95 rows=895 width=8) (actual time=0.566..1.176 rows=937 loops=1)
Index Cond: (order_ts >= (CURRENT_DATE - 30))
Heap Fetches: 0
Buffers: shared hit=4 read=8
-> Index Only Scan using idx_order_items_order_cover on order_items oi (cost=0.29..0.58 rows=3 width=14) (actual time=0.007..0.007 rows=3 loops=937)
Index Cond: (order_id = o.order_id)
Heap Fetches: 0
Buffers: shared hit=1833 read=50
Settings: search_path = 'ecom, public', enable_hashjoin = 'off', enable_mergejoin = 'off'
Planning:
Buffers: shared hit=427
Planning Time: 2.640 ms
Execution Time: 9.017 ms



동일 데이터에서는 Merge Join(5.705 ms)이 가장 빨랐고 Hash Join(11.590 ms)이 가장 느렸다. 단, 데이터 크기·정렬·인덱스에 따라 최적 조인은 달라진다.

15. Materialized View 활용

매일 주문과 주문상품을 다시 조인·집계하지 않고, 미리 계산한 일별 주문 수와 GMV를 빠르게 조회한다.

생성 및 결과 화면

MV 생성

Name	Value
Updated Rows	0
Execute time	0.023s
Start time	Fri Aug 14 17:05:51 KST 2026
Finish time	Fri Aug 14 17:05:51 KST 2026
Query	DROP MATERIALIZED VIEW IF EXISTS ecom.mv_daily_gmv; -- 기존 MV와 그 MV에 속한 인덱스를 함께 제거 -- ===== -- 2. 일별 GMV Materialized View 생성 -- ===== -- WITH NO DATA로 구조와 정의만 먼저 생성하고 데이터는 뒤의 REFRESH에서 적재한다. CREATE MATERIALIZED VIEW ecom.mv_daily_gmv AS -- 일별 집계 결과를 저장할 MV 생성 시작 SELECT date_trunc('day', o.order_ts)::date AS sales_day, -- 주문시각을 일 단위로 자르고 date 형식으로 변환 COUNT(DISTINCT o.order_id) AS order_count, -- 주문상품 조인으로 중복된 주문번호를 제거한 일별 주문 수 ROUND(SUM(oi.line_total), 2) AS gmv -- 주문상품 금액의 일별 합계를 소수점 둘째 자리로 표시 FROM ecom.orders o -- 주문일시-주문상태가 저장된 주문 테이블 JOIN ecom.order_items oi -- 상품별 판매금액이 저장된 주문상품 테이블 ON oi.order_id = o.order_id -- 주문번호가 같은 주문과 주문상품을 연결 WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 실제 매출로 인정하는 상태만 포함 GROUP BY date_trunc('day', o.order_ts)::date -- 같은 날짜의 주문상품 금액을 한 행으로 집계 WITH NO DATA; -- 생성 시에는 데이터를 넣지 않고 빈 구조만 생성 -- ===== -- 3. 동시 갱신을 위한 UNIQUE 인덱스 생성 -- ===== -- REFRESH MATERIALIZED VIEW CONCURRENTLY를 사용하려면 모든 행을 유일하게 식별할 수 있어야 한다. -- 이 MV는 날짜별로 한 행만 존재하므로 sales_day를 고유키로 사용한다. CREATE UNIQUE INDEX ux_mv_daily_gmv_sales_day -- MV의 날짜 중복을 금지하는 UNIQUE 인덱스 이름 ON ecom.mv_daily_gmv (sales_day); -- 날짜 한 개가 MV의 각 행을 유일하게 식별 -- ===== -- 4. 최초 데이터 적재 및 통계정보 수집 -- ===== -- WITH NO DATA로 만들었으므로 최초 1회는 일반 REFRESH로 데이터를 채워야 한다. -- 빈 MV에는 CONCURRENTLY를 바로 사용할 수 없으므로 먼저 일반 REFRESH를 실행한다. REFRESH MATERIALIZED VIEW ecom.mv_daily_gmv; -- MV 정의의 쿼리를 실행하여 일별 결과를 실제로 저장 ANALYZE ecom.mv_daily_gmv; -- MV의 행 수와 값 분포 통계를 수집하여 실행계획 선택에 활용

원본 쿼리 계획

5. 원본 데이터를 직접 조인·집계하는 실행계획

비교 기준이 되는 원본 쿼리이다.

orders와 order_items를 읽고 Join, Aggregate, Sort를 수행하므로 MV 조회보다 작업량이 많을 수 있다.

탐지할 값: 최상위 Buffers, Planning Time, Execution Time, Join/Aggregate 노드

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

SELECT date_trunc('day', o.order_ts)::date AS sales_day, -- 주문일을 일 단위로 변환
COUNT(DISTINCT o.order_id) AS order_count, -- 조인 후 중복을 제거한 일별 주문 수
ROUND(SUM(oi.line_total), 2) AS gmv -- 일별 총 상품 판매금액
FROM ecom.orders o -- 원본 주문 테이블 읽기
JOIN ecom.order_items oi -- 원본 주문상품 테이블 읽기
ON oi.order_id = o.order_id -- 주문번호를 기준으로 원본 테이블 두 개 조인
WHERE o.order_status IN ('paid', 'shipped', 'delivered') -- 상태를 필터링한 집계
GROUP BY date_trunc('day', o.order_ts)::date -- 날짜별로 주문 수와 금액 계산
ORDER BY sales_day DESC -- 가장 최근 날짜부터 정렬
LIMIT 30; -- 최근 30개 날짜만 출력

Results 1 X Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT date_trunc('day', o.or

AZ QUERY PLAN

1 Limit (cost=939.49..940.89 rows=30 width=44) (actual time=9.799..10.154 rows=30 loops=1)

2 Buffers: shared hit=140

3 -> GroupAggregate (cost=939.49..1083.25 rows=3068 width=44) (actual time=9.797..10.149 rows=30 loops=1)

4 Group Key: ((date_trunc('day')::text, o.order_ts)::date)

5 Buffers: shared hit=140

6 -> Sort (cost=939.49..960.09 rows=8240 width=18) (actual time=9.771..9.856 rows=1368 loops=1)

7 Sort Key: ((date_trunc('day')::text, o.order_ts)::date) DESC, o.order_id

8 Sort Method: quicksort Memory: 706kB

9 Buffers: shared hit=140

10 -> Hash Join (cost=131.43..403.54 rows=8240 width=18) (actual time=2.372..7.234 rows=8230 loops=1)

11 Hash Cond: (oi.order_id = o.order_id)

12 Buffers: shared hit=140

13 -> Seq Scan on order_items oi (cost=0.00..203.67 rows=10367 width=14) (actual time=0.034..1.046 rows=10367 loops=1)

14 Buffers: shared hit=100

15 -> Hash (cost=93.08..93.08 rows=3068 width=16) (actual time=2.269..2.270 rows=3068 loops=1)

16 Buckets: 4096 Batches: 1 Memory Usage: 176kB

17 Buffers: shared hit=40

18 -> Seq Scan on orders o (cost=0.00..93.08 rows=3068 width=16) (actual time=0.020..1.465 rows=3068 loops=1)

19 Filter: (order_status = ANY ('paid,shipped,delivered')::text[])

20 Rows Removed by Filter: 792

21 Buffers: shared hit=40

22 Planning:

23 Buffers: shared hit=18

24 Planning Time: 0.835 ms

25 Execution Time: 10.257 ms

6. Materialized View 조회 실행계획

이미 계산되어 저장된 sales_day, order_count, gmv만 읽는다.

원본 테이블 조인과 GROUP BY가 사라지는지 원본 실행계획과 비교한다.

탐지할 값: Scan 방식, 최상위 Buffers, Planning Time, Execution Time

EXPLAIN (ANALYZE, BUFFERS, SUMMARY)

SELECT sales_day, -- MV에 저장된 매출 날짜
order_count, -- MV에 저장된 일별 주문 수
gmv -- MV에 저장된 일별 GMV
FROM ecom.mv_daily_gmv -- 원본 조인 대신 사전 집계된 MV만 조회
ORDER BY sales_day DESC -- 가장 최근 날짜부터 정렬
LIMIT 30; -- 최근 30개 날짜만 출력

Results 1 X Statistics 1

EXPLAIN (ANALYZE, BUFFERS, SUMMARY) SELECT sales_day, order_cou

AZ QUERY PLAN

1 Limit (cost=0.14..3.26 rows=30 width=20) (actual time=0.014..0.018 rows=30 loops=1)

2 Buffers: shared hit=1 read=1

3 -> Index Scan Backward using ux_mv_daily_gmv_sales_day on mv_daily_gmv (cost=0.14..14.17 rows=135 width=20) (actual time=0.013..0.016 rows=30 loops=1)

4 Buffers: shared hit=1 read=1

5 Planning:

6 Buffers: shared hit=56 read=1

7 Planning Time: 0.582 ms

8 Execution Time: 0.027 ms

MV 조회 결과

7. Materialized View 실제 결과 확인

EXPLAIN 없이 실행하여 구매·재무팀에 전달할 실제 일별 결과를 확인한다.

SELECT sales_day, -- 일별 매출 기준 날짜
order_count, -- 해당 날짜의 중복 없는 판매용 주문 수
gmv -- 해당 날짜의 주문상품 총매출
FROM ecom.mv_daily_gmv -- 미리 저장된 일별 집계 결과 조회
ORDER BY sales_day DESC -- 최근 날짜부터 표시
LIMIT 30; -- 최근 30일분 결과 표시

mv_daily_gmv 1 X Statistics 1

SELECT sales_day, order_count, gmv FROM ecom.mv_daily_gmv ORDER E

Grid

sales_day

order_count

gmv

1

2026-09-04

1

234.98

2

2026-09-03

2

577.53

3

2026-08-30

2

492.73

4

2026-08-29

2

716.1

5

2026-08-28

1

339.12

6

2026-08-27

2

470.26

7

2026-08-26

2

493.92

8

2026-08-24

1

171.21

9

2026-08-22

3

400.5

10

2026-08-21

2

647.42

11

2026-08-20

6

1,434.01

12

2026-08-19

3

390.33

13

2026-08-18

2

294.15

14

2026-08-17

2

278.8

15

2026-08-14

21

16,900.68

16

2026-08-13

30

27,756.96

17

2026-08-12

22

18,433.21

18

2026-08-11

31

29,707.93

19

2026-08-10

25

16,932.28

20

2026-08-09

29

25,555.9

21

2026-08-08

30

27,412.01

22

2026-08-07

25

21,950.82

23

2026-08-06

42

39,935.38

24

2026-08-05

27

22,869.32

25

2026-08-04

27

32,913.44

26

2026-08-03

29

31,064.72

27

2026-08-02

35

29,385.72

28

2026-08-01

38

43,562.65

29

2026-07-31

40

43,292.45


30

2026-07-30

29


24,239.39

MV 갱신



구분	핵심 실행계획	Buffers	Execution Time
원본 JOIN + GROUP BY	Hash Join + GroupAgg	hit=140	10.257 ms
mv_daily_gmv 조회	Index Scan Backward	hit=1/read=1	0.027 ms

오후 3시 설계



- 최초 적재: REFRESH MATERIALIZED VIEW ecom.mv_daily_gmv;
- 운영 갱신: REFRESH MATERIALIZED VIEW CONCURRENTLY ecom.mv_daily_gmv;
- 제안 주기: 매일 오후 3시
- 주의점: 오후 3시 이후 변경사항은 다음 갱신 전까지 조회 결과에 반영되지 않는다.

16. DBMS별 옵티마이저 비교 (Option)

자세한 조사 내용은 종합실습4_06_DBMS별_옵티마이저_비교.md 를 참고한다.

DBMS	대표 조인	실행계획 확인	특징
PostgreSQL	Nested Loop, Hash, Merge	EXPLAIN ANALYZE	통계·비용 기반, 확장 통계, GEQO
MySQL	Nested Loop/BKA, Hash	EXPLAIN ANALYZE	optimizer switch·힌트·히스토그램
Oracle	Nested Loop, Hash, Sort Merge	DBMS_XPLAN	Adaptive Plan, SQL Plan Management
SQL Server	Nested Loops, Hash, Merge, Adaptive	Actual Execution Plan	Query Store, Intelligent Query Processing

17. 전체 튜닝 전후 비교

문항	튜닝 전 방식	튜닝 후 방식	전 Buffers	후 Buffers	전 시간	후 시간	감소율
Q1	함수 조건 + 상관 집계	SARG 범위 + 단일 집계	hit=2,902	hit=101/read=8	25.380	4.903	80.7%
Q2	상세행 + DISTINCT	주문별 선집계	hit=140	hit=143	11.646	6.879	40.9%
Q3	비-SARG 기간 조건	최근 주문 선필터	hit=148	hit=120/read=9	11.863	11.534	2.8%
Q4	제품별 상관 서브쿼리	전체 1회 집계 + RANK	hit=70,677	hit=147	37.373	9.654	74.2%
Q5	고객별 3회 반복 조회	주문 선집계 + 고객 GROUP BY	hit=17,287	hit=180	21.915	13.785	37.1%
Q6	고객별 EXISTS	Window + BOOL_OR	hit=9,362	hit=1/read=20	7.881	6.166	21.8%
Q7	임계치 상관 조회	직접 비교 + 부분 인덱스	hit=1,912	hit=12	2.017	0.428	78.8%
Q8	AVG/COUNT 반복	GROUP BY + HAVING	hit=1,565	hit=28	4.551	1.016	77.7%
Q9	상세행 + DISTINCT	주문별 선집계 + AVG	hit=143	hit=140	17.993	10.057	44.1%
Q10	누적/60일 매출 반복	전체 1회 집계 + 정확히	hit=21,777	hit=180	23.321	17.230	26.1%

(튜닝 전 시간 - 튜닝 후 시간) / 튜닝 전 시간 × 100

18. 최종 분석

요청 대응 관점

어떤 주문 상태와 기간을 포함하는지, 주문 수와 주문상품 수를 혼동하지 않았는지, 상위 고객의 선정 기준과 표시 기간이 다른지 먼저 정의해야 한다. 특히 Q10은 최근 60일 매출로 상위 고객을 선정하는 것이 아니라 누적매출로 30명을 선정한 뒤 최근 60일 매출을 계산한다.

튜닝 관점

상관 SubPlan 제거와 선집계·SARG 조건 적용으로 Q1~Q10 모두 단축되었으며, 가장 큰 개선은 Q1(80.7%)이었다.

한계와 추가 확인사항

- 랜덤 시드이므로 재실행 시 결과가 달라진다.
- 로컬 단일 사용자 환경의 실행시간은 운영 부하를 반영하지 않는다.
- 쿠폰 사용 여부와 AOV의 관계는 인과관계가 아니다.
- 인덱스는 조회 성능을 높이지만 INSERT/UPDATE와 저장공간 비용을 추가한다.

최종 결론

업무 기준을 명시한 Q1~Q11 결과를 튜닝 전후 동일하게 유지하면서 반복 조회와 불필요한 중복 제거를 줄였다. 물리 조인은 본 환경에서 Merge Join이 가장 빨랐고, mv_daily_gmv 조회는 원본 집계 10.257 ms에서 0.027 ms로 단축되었다. 운영 시에는 데이터 규모와 변경 빈도에 따라 인덱스 비용과 오후 3시 MV 갱신 시차를 함께 관리해야 한다.