

Test report 1 - 50

<p><em style="color: rgb(127, 132, 142);"> Notice the use of <strong style="color: rgb(127, 132, 142);">PUBLIC_URL<em style="color: rgb(127, 132, 142);"> in the tags above.</p><p><em style="color: rgb(127, 132, 142);"> It will be replaced with the URL of the `public` folder during the build.</p><p><em style="color: rgb(127, 132, 142);"> Only files inside the `public` folder can be referenced from the HTML.</p><p>
</p><p><em style="color: rgb(127, 132, 142);"> Unlike "/favicon.ico" or "favicon.ico", "%PUBLIC_URL%/favicon.ico" will</p><p><em style="color: rgb(127, 132, 142);"> work correctly both with client-side routing and a non-root public URL.</p><p><em style="color: rgb(127, 132, 142);"> Learn how to configure a non-root public URL by running `npm run build`.</p>

Report 2 for 1 - 50

<p><em style="color: rgb(127, 132, 142);"> Notice the use of <strong style="color: rgb(127, 132, 142);">PUBLIC_URL<em style="color: rgb(127, 132, 142);"> in the tags above.</p><p><em style="color: rgb(127, 132, 142);"> It will be replaced with the URL of the `public` folder during the build.</p><p><em style="color: rgb(127, 132, 142);"> Only files inside the `public` folder can be referenced from the HTML.</p><p>
</p><p><em style="color: rgb(127, 132, 142);"> Unlike "/favicon.ico" or "favicon.ico", "%PUBLIC_URL%/favicon.ico" will</p><p><em style="color: rgb(127, 132, 142);"> work correctly both with client-side routing and a non-root public URL.</p><p><em style="color: rgb(127, 132, 142);"> Learn how to configure a non-root public URL by running `npm run build`.</p>