

Motion Planning

Stephen J. Guy

March 2, 2020

Many images from *Lavalle, Planning Algorithms* and *Peter Abbeel*

1

Recap

- Why use spatial-data structures
 - Exploit locality in the environment
- BSP-tree vs KD-tree
 - BSP allows arbitrary cuts
- Efficient nearest neighbor search?
 - Store all agents in kd-tree
 - Intersect kd-tree with circle centered on agent in question

2

2

HW3 – Motion Planning

- Posted already?
- Check-in: March 16
- Due: March 30
- Should be able to finish check-in from today's lecture
- Very different than HW2!
 - For good or ill ...

3

3

Burn-out?

- I know HW2 was difficult
 - Material is straightforward, but
 - Different from other type of course work
 - Lots of parameter tuning & tweaking
 - Small errors cause big issues
- HW3
 - You have a long time to complete
 - Still parameter tuning, but less difficult
 - Not as much ~~difficult~~ fun new math
 - A lot of fun new algorithms ☺

4

4

Motion in Games/Movies

- Natural Phenomena (Passive)
 - Water, Ocean
 - Fire, Smoke
 - Snow
 - Cloth
- Planned Phenomena (Active)
 - Walking, Running
 - Animal locomotion
 - Herding, flocking
 - Planning in complex environments
 - Intent

Physically Based Animation

Motion Planning

5

5

Motion Planning

- Problem
 - Given start state X_s and goal state X_G
 - Find a path leading from start to goal
- Difficulties
 - Need to avoid obstacles
 - Systems may be “underarticulated”
 - Can not move along any coordinate at will
 - Cars, Tanks, Airplanes
 - Humans, Animals, Robots (e.g. joint limits)

6


6

Motion Planning in Robotics

- Piano movers problem



- Cart-pole problem




7

7

Examples


- Alpha puzzle



8

8

Examples - Robots



9

Outline



- Configuration Space
- Probabilistic Roadmaps
 - Sampling
 - Collision Checking
- Rapidly-exploring Random Trees (RRTs)
- Smoothing

10

10

Representing Paths

- Issues with raw position
 - Doesn't account for an agent's extent
 - Doesn't account for orientation
 - Doesn't allow arbitrary changes in configuration
- What is "correct" path around obstacle
 - Depends on whose taking the path



1

11


Configuration Space (C-Space)

- $= \{x \mid x \text{ is pose of agent}\}$
- Key idea: Replace obstacles with configuration space obstacles!

Workspace

Configuration Space

(2 DOF: translation only, no rotation)




1:

12

C-Space Example


- Works on arbitrarily complex agents!



13

Planning a Path

- How to get from one configuration to another
- Must find path in free space of c-space
 - Path in c-space that doesn't intersect any c-obstacles



14


14

Minkowski Sums

- Geometric concept which can help compute C-space
- **Minkowski sum** is set of sum of every point in two sets

$$A + B = \{a + b \mid a \in A, b \in B\}$$

- Can be computed by a convolution




15

15

Minkowski Sum for C-Space

- Obstacle is A
- Robot is B
 - B' is B reflected around reference point
- If only translation is allowed C-space is $A \oplus B'$



16

16


Roadmaps

- Given a start and goal position
- And a representation of Configuration space
- How can we plan a collision free path from start to goal?

17

17

Roadmaps




18

18

Probabilistic Roadmap

- Sampling random configurations
 - Choose each coordinate at random




19

19

Probabilistic Roadmap (PRM)

- Randomly sample configurations




20

20

Probabilistic Roadmap (PRM)

- Test configurations for collisions




21

21

Probabilistic Roadmap (PRM)

- Collision-free states are saved as milestones




22

22

Probabilistic Roadmap (PRM)

- Each milestone is linked to its nearest neighbors by a straight line




23

23

Probabilistic Roadmap (PRM)

- Straight lines connect neighboring milestones




24

24

Probabilistic Roadmap (PRM)

- Collision-free links of local paths from PRM




25

25

Probabilistic Roadmap (PRM)

- Start and goal retained as milestones




26

26

Probabilistic Roadmap (PRM)

- PRM searched for path from s to g




27

27

Finding Path in PRM

- Graph search algorithms
 - Dijkstra's / Uniform Cost Search
 - A*



28

28

PRM – Overview


- Initialize sets of points with X_S and X_G
- Randomly sample points in configuration space
- Connect nearby points if they can be reached from each other
- Find path from X_S to X_G
 - Alternatively, track connected components. Stop when X_S and X_G are connected

29

29

PRM - Examples

- Bruno Adorno - Automation and Robotics Laboratory (LARA) - University of Brasilia



30

30

PRM Difficulties

- Connecting neighboring points:
 - Only easy for holonomic systems
 - Systems where you can move in any direction from any state
 - General solution requires a Boundary Value Problem
 - E.g., Car, Tank, Bicycle

$$\begin{array}{ll}
 \min_{u,x} & \|u\| \\
 \text{s.t.} & x_{t+1} = f(x_t, u_t) \quad \forall t \\
 & u_t \in \mathcal{U}_t \\
 & x_t \in \mathcal{X}_t \\
 & x_0 = x_S \\
 & x_T = x_G
 \end{array}$$

Typically solved without collision checking; later verified if valid by collision checking

31

31

PRM Challenges (cont.)

- Collision Checking
 - Determining if local path intersects c-space
 - Often the bottleneck in planning (see Lavalle book)
- Sampling
 - Sample uniformly at random
 - Same strategies as in stochastic animation
 - Bias sampling based on prior knowledge
 - E.g., more samples near narrow passages

32

32

PRM Analysis

- Advantages:
 - Probabilistically complete
 - Probability of finding a solution approaches one over time (if solution exists)
- Issues:
 - Required to solve 2-point boundary value problem
 - Graph is built over all state-space without focus on generating a path

33

33

Next Several Lectures

- Search & Maps
- Multi-agent planning
 - Centralizing
 - Distributed

34

34