

CSC 337 — Midterm 1 Study Guide

Start Here

Guide updated: 2026-09-24 afternoon (America/Phoenix) -- Start Here rewrite. Reviewed 2026-09-24 evening by Claude Opus 5.5 (see §8c).

If you only read one thing: A4 is due Tue Sep 29 at 3:30 PM, but Tuesday is a class day (9:30-10:45, then 12:30-3:15 back to back). So the **real A4 deadline is Mon Sep 28 night**; 10:45-12:30 Tue is the only backup. Midterm study really starts Wed Sep 30 and peaks with the Sun Oct 4 paper mock.

Next scheduled assessment

Field	Value	Label
Assessment	CSC 337 Midterm 1	confirmed item
Date	Tue Oct 6, 2026	confirmed (D2L syllabus / Midterms calendar)
When	75 minutes; class period 3:30-4:45 PM if held in class	date confirmed; 75 min per inventory (= the class period); in-class clock from the calendar description
Delivery / materials	Closed-book not in inventory	verify
Coverage	Syllabus weeks 1-7: intro, HTML/CSS, forms, Get & Post, JS, DOM, client/server	PROVISIONAL -- schedule-based review
Do not invent	Node, Express, MongoDB, D3	those are weeks 8+

Do **not** schedule study during class blocks (Tue/Thu through Dec 9, Arizona time): CSC 252 9:30-10:45 AM; CSC 335 12:30-1:45 PM; CSC 345 2:00-3:15 PM; CSC 337 3:30-4:45 PM; CSC 380 5:00-6:15 PM. All times below are **Arizona (MST, UTC-7)**. Combined daily order: `weekly/2026-09-24-weekly-study-order.md`.

Nearby deadline (outranks midterm study until it is in): CSC 337 **Assignment 4** due **Tue Sep 29 3:30 PM** (Gradescope / tracker). A4 topics: HTML/CSS/JS form validation, sorting, word-frequency, number-guessing. This guide does **not** contain A4 solutions. DOM (week 6, Sep 28-Oct 1) and client/server (week 7, Oct 5-8 -- midterm week) may **not** be lectured yet.

Topics to study first (order + WHY)

1. **Finish A4 first (until Tue Sep 29 3:30 PM)** -- WHY: hard deadline before any midterm deep-dive; skills overlap (forms, JS, sort, counts) but A4 is individual submitted work.
2. **337-M1-http + 337-M1-getpost** -- WHY: week 1 + week 4; GET vs POST is easy points; slides `02-Browsers-URL-HTTP` and `06-HTML-Forms`.

3. **337-M1-html + 337-M1-css + 337-M1-layout** -- WHY: week 2 content; box model and specificity are high-miss; slides 03-05.
4. **337-M1-forms + 337-M1-js** -- WHY: weeks 3 and 5; already lectured; A4 overlap without copying A4.
5. **337-M1-dom then 337-M1-client-server** -- WHY: weeks 6-7; study **only after lecture**. Client/server is conceptual only.
6. **337-M1-integrate** -- last, after the mock.

Confirmed vs schedule-based: Date confirmed; 75-min length per inventory (matches the class period). Scope is **not published**. Slides 02-08 are harvested lecture content. DOM / client-server remain schedule-based until taught.

Day-by-day tasks (minutes; no class-block study)

When	Window	Task	Guide / slides / problems	Min
Thu Sep 24	After 6:15 PM only (do not study 3:30-4:45)	A4 work, not midterm. Optional 10-min GET vs POST if A4 is already in.	A4 files; 337-M1-getpost table	10 midterm / rest A4
Fri Sep 25	Anytime	A4 primary. If stuck, 20-min CSS specificity tuples.	Slides 04; P4; GS-337-R1	20 + A4
Sat Sep 26	Anytime	A4 primary.	--	A4
Sun Sep 27	Anytime	A4 primary; 25-min JS traps if A4 is nearly done.	337-M1-js; T1, T3; P8	25 + A4
Mon Sep 28	Anytime	A4 polish and submit tonight (target). Open the Gradescope page and confirm every file is there (GS-337-E2). After A4: HTTP + Get/Post.	337-M1-http, getpost; P2, P7, R3, R4	40 after A4
Tue Sep 29	A4 due 3:30 PM. Class stack 9:30-10:45 and 12:30-3:15. Backup window 10:45-12:30 only	If A4 is not in yet, finish and submit in 10:45-12:30. Do not plan on the 3:15-3:30 gap. After 6:15: LIGHT HTTP flash only.	R3, R4	15
Wed Sep 30	No class	HTTP, URLs, Get & Post.	Slides 02 + 06; ICA-M1; P7	50
Thu Oct 1	10:45-12:30 gap after 252 Test 2	Start HTML/CSS review.	html, css, layout; excerpt layout p.3; P3-P5; ICA-M5	50
Fri Oct 2	Anytime	Deep HTML + CSS + layout.	Slides 03-05; R1; ICA-M2, M4	80
Sat Oct 3	Anytime	Forms, JS, and DOM if week-6 lecture happened.	forms, js, dom; W1; ICA-M6, M8	80

When	Window	Task	Guide / slides / problems	Min
Sun Oct 4	Anytime	50-minute paper mock (R1-R4, T1-T4, W1-W2, plus P5 and ICA-M5 for CSS), then review.	Sec 4b	75
Mon Oct 5	Anytime; stop by evening	Even rotation; client/server concepts only. Redo every mock miss blind.	All 337-M1-*; P9, E1	70
Tue Oct 6	Class day. Calm-buffer windows: before 9:30 or 10:45-12:30 only (252 / 335 / 345 meet 9:30-10:45 and 12:30-3:15). Midterm 3:30-4:45 if in class	No new topics.	--	10

Is this enough time? Almost 7 hours (about 405 minutes) of focused midterm study (Wed Sep 30 - Mon Oct 5), plus A4, which exercises forms and JS. That is adequate for a 75-minute exam over 7 weeks. The thinnest spot is **JavaScript/DOM**, which gets one deep block (Sat Oct 3). If the Sun mock shows JS misses, give Mon Oct 5 to T1-T5 and W1-W2 instead of an even rotation.

Final self-check

- [] A4 submitted (Sep 29 3:30 PM) -- process, not content
- [] Blind pass over all 11 section IDs
- [] 50-minute paper mock done, and every miss redone blind on Mon Oct 5
- [] Can predict the output of GS-337-T1 and T3 **without running code**, and say why
- [] Specificity tuples and content-box vs border-box from memory
- [] GET vs POST differences without notes
- [] DOM / client-server studied only as lectured
- [] No Node/Mongo invented
- [] Light Monday night -- no cram

Slide excerpts (personal study channel only)

Excerpt -- margin vs padding (CSC 337, CSS Layout, page 3)

Slide image (CSC 337 CSS Layout p.3 margin and padding) is not mirrored in this repo. It lives on the Munch box at /home/box/shared/munch/study-guides/csc337/assessments/excerpts/csc337-css-layout-p3-box.png. The own-words caption below and the original deck page are enough to study from.

In my own words: `width` in the default content-box model is the content only. This rule sets content 70px, padding 50px on every side, and margin 10px on every side, plus a 2px border. Total rendered width = $70 + 250 + 22 = 174\text{px}$, then the 10px margins sit outside that. Under `box-sizing: border-box`, the 70px would have to include padding and border. Here padding +

border alone is 104px, which is more than 70px, so the content area collapses to 0 and the box renders **104px** wide, not 70px. Border-box only "shrinks the content" when width is larger than padding + border (see P5: 100px leaves 78px of content).

Original deck: `/home/box/shared/munch/study-guides/_meta/d2l-harvest/csc337/content-05-CSS-Layout.pdf` (D2L slide 05-CSS-Layout), page 3. Personal study channel only.

Also review (no extra image -- point to exact decks): - `content-02-Browsers-URL-HTTP.pdf` -- URL parts + status codes - `content-04-CSS.pdf` -- class vs id (ICA-M4 grain) - `content-06-HTML-Forms.pdf` -- GET vs POST + label/for pairing - `content-07-Javascript.pdf` -- events, `===`, default sort - `content-08-html-css-js-site.pdf` -- integration

Banner — scope PROVISIONAL. Midterm 1 scope is **not published**. Practice covers the lectures so far, following the syllabus weeks 1–7: Introduction, HTML & CSS, HTML forms, Get & Post, JavaScript, DOM, and the client/server model. The **date is confirmed**: Tue Oct 6, 2026, 75 minutes, in the class period. Do **not** invent Node, Express, MongoDB, or D3 detail; those are weeks 8+.

Canonical maps: `csc337-topic-map.md` · `announced-assessments-inventory-2026-09-24.md`

1. Header

Field	Value	Status
Course	CSC 337 Web Programming (FA26), TuTh 3:30–4:45 PM, The Commons 305	Confirmed
Assessment	Midterm 1	Confirmed
Date	Tue Oct 6, 2026	Confirmed (D2L syllabus / tracker)
Length	75 minutes, class period	Confirmed (inventory)
Delivery / materials	Closed-book and the delivery method are not in the inventory or topic map	Verify in class or on D2L
Coverage	Syllabus weeks 1–7 (client side, plus the client/server model)	PROVISIONAL
Timing caveat	The DOM (week 6) and client/server (week 7) lectures have not happened yet . Client/server is scheduled for the midterm week itself , so it may or may not be lectured before Oct 6.	Watch lecture
Guide updated	2026-09-24 (America/Phoenix) — Opus + Content-fold	

All times are **Arizona time (MST)**.

Sources

Source	Role
<code>csc337-topic-map.md</code> + inventory	Week topics, date, provisional label

Source	Role
Content slides 02-Browsers-URL-HTTP ... 08-html-css-js-site (+ Web Programming)	Topic checklist and explanations (Content-pass 2026-09-24)
Content ICA1.pdf - ICA10.pdf	ICA-style micro practice grain (Practice recommendation ; not copied wholesale)
Content Assignments 1-3 (+ existing A4)	Practice context / topic overlap only. No assignment solutions in this guide. A4 remains open/individual.
Csc337-fall26-Syllabus.pdf (on box)	Midterm date and length
Gradescope format notes csc337-2026-09-24.md	ICA and assignment formats (not a midterm format)

2. Topic checklist (learning order)

Order	Section ID	Topic (syllabus week)	Blind [x]	Check [x]	Retake [x]
1	337-M1-overview	Web overview (wk 1)			
2	337-M1-http	Browsers, URLs, HTTP basics (wk 1)			
3	337-M1-html	HTML structure and elements (wk 2)			
4	337-M1-css	CSS selectors, cascade, specificity, box model (wk 2)			
5	337-M1-layout	CSS layout (wk 2)			
6	337-M1-forms	HTML forms (wk 3)			
7	337-M1-getpost	Get & Post (wk 4) — <i>new in this review</i>			
8	337-M1-js	JavaScript core and events (wk 5)			
9	337-M1-dom	DOM (wk 6 — not yet lectured)			
10	337-M1-client-server	Client/server model (wk 7) — conceptual only			
11	337-M1-integrate	Integrated HTML/CSS/JS			

Content slide map (02-08). 02 browsers/URL/HTTP -> 337-M1-http; 03 HTML -> 337-M1-html; 04 CSS -> 337-M1-css; 05 CSS Layout -> 337-M1-layout; 06 HTML Forms (+ GET/POST in slides) -> 337-M1-forms / 337-M1-getpost; 07 Javascript -> 337-M1-js; 08 html-css-js site -> 337-M1-integrate. DOM and client/server remain syllabus weeks 6-7 (provisional; may not be lectured yet).

3. Plain explanations + worked examples

Overview + HTTP (337-M1-overview, 337-M1-http)

- **Three client-side layers:** HTML is structure and content, CSS is presentation, and JavaScript is behavior.
- **URL parts:** in `https://example.com:443/shop/items?id=7#reviews`, the scheme is `https`, the host is `example.com`, the port is `443`, the path is `/shop/items`, the query is `id=7`, and the fragment is `reviews`. The browser keeps the fragment; it is never sent to the server.
- **HTTP exchange:** the client sends a request (method, path, headers, optional body). The server replies with a response (status code, headers, optional body). HTTPS is HTTP over TLS encryption.
- **Status code families:** 2xx success (200 OK), 3xx redirect (301, 302), 4xx client error (404 Not Found, 403 Forbidden), and 5xx server error (500).

HTML (337-M1-html)

- A document has `<!DOCTYPE html>`, then `<html lang="en">` containing `<head>` (`<meta charset>`, `<title>`, CSS `<link>`) and `<body>`.
- Semantic elements (`header`, `nav`, `main`, `section`, `article`, `footer`) describe meaning. `div` and `span` are generic containers; `div` is block-level and `span` is inline.
- Attributes: `id` must be unique on the page, while a `class` can be reused. `<img>` needs `alt` text. `<a href>` makes links.

CSS (337-M1-css , 337-M1-layout)

Specificity is compared as a tuple (ids, classes/attributes/pseudo-classes, elements), from left to right:

Selector	Tuple
<code>p</code>	(0,0,1)
<code>.note</code>	(0,1,0)
<code>div.note</code>	(0,1,1)
<code>#main</code>	(1,0,0)
<code>ul li.active a</code>	(0,1,3)
<code>nav > a:hover</code>	(0,1,2)

Inline `style=""` beats all of these, and `!important` overrides normal rules; avoid relying on it. When specificity ties, the rule that appears **later** wins.

Box model: content, then padding, then border, then margin. - With `box-sizing: content-box` (the default), `width` sets the content only, so total width = width + left/right padding + left/right border. - With `border-box`, `width` already includes padding and border.

Layout: normal flow (block elements stack; inline elements flow in a line), then flexbox (`display:flex`, `justify-content`, `align-items`), grid, and positioning (`relative`, `absolute`, `fixed`), as taught.

Forms (337-M1-forms)

- `<form action="/search" method="get">` holds the controls. Each control's `name` attribute becomes the parameter key.
- Pair each control with a label: `<label for="email">` matches `<input id="email">`.
- Common input types: `text`, `email`, `number`, `password`, `checkbox`, `radio` (same name makes a group), `submit`, plus `<select>` and `<textarea>`.
- Built-in validation attributes include `required`, `min`, `max`, and `pattern`. JavaScript validation can check anything and show a message in the page.

Get & Post (337-M1-getpost) — added in this review (syllabus week 4)

	GET	POST
Where the data goes	In the URL query string (? q=cats&page=2)	In the request body
Visible and bookmarkable?	Yes, and it is cached and kept in history	No
Typical use	Retrieving, search, filters	Creating or changing data, logins, larger payloads
Size	Limited by URL length	Much larger

POST is **not** encryption. Only HTTPS protects the data in transit.

JavaScript (337-M1-js)

- **Declarations:** `let` and `const` are block-scoped; `var` is function-scoped. `const` stops reassignment but not mutation of an object's contents.
- **Equality:** `===` is strict (no type conversion). `==` converts types first, so `0 == ""` is `true`. Use `===`.
- **Types:** `+` with any string concatenates (`1 + "2"` gives `"12"`). Other arithmetic converts to numbers (`"3" * 2` gives `6`).
- **Sorting:** `arr.sort()` compares values **as strings** by default, so `[10, 9, 1].sort()` gives `[1, 10, 9]`. For numbers use `arr.sort((a, b) => a - b)`.
- **Parsing input:** `Number("")` is `0`, not `NaN`. Check for empty input separately. `Number("12px")` is `NaN`, while `parseInt("12px")` is `12`.
- **Events:** `el.addEventListener("click", handler)` passes the function itself. Writing `handler()` there calls it immediately, which is a bug.

DOM (337-M1-dom) — week 6, not yet lectured

- Select elements with `document.getElementById("x")` or `document.querySelector(".card")`.
- Change content with `el.textContent = "..."`, which is safe plain text. `el.innerHTML = "..."` parses HTML, so avoid it with user input.
- Build elements with `document.createElement("li")`, then `parent.appendChild(li)`.
- Change styles and classes with `el.classList.add("hidden")`, or directly with `el.style.color = "red"`.

Client/server (337-M1-client-server) — conceptual only

- The client (browser) sends requests; the server holds data and logic and returns responses.
 - A **static** page is the same file for everyone. A **dynamic** response is generated per request.
 - Client-side JavaScript runs in the browser, so users can see and change it. Validation there improves the user experience but **must be repeated on the server** for security.
 - **Stop here.** Server frameworks (Node, Express) and databases are weeks 8+.
-

4. Practice questions (core)

P1 (recall). Name the three client-side layers and give one responsibility of each.

P2 (explain). What does an HTTP response contain besides the body?

P3 (code). Write a minimal valid HTML page with an external stylesheet `site.css` and a script `main.js` that runs after the page's elements exist.

P4 (CSS). Which is more specific, `div.note` or `#main`? Give both tuples.

P5 (box). An element has `width: 100px`, `padding: 10px`, and `border: 1px solid`, with content-box sizing. What is its total rendered width? What is it under border-box?

P6 (forms). Write a form with a labelled email input (required) and a submit button that sends a GET request to `/subscribe`.

P7 (Get & Post). A search form uses GET with fields `q=red shoes` and `size=9`. Write the URL the browser requests from `/search`. What changes if the form uses POST instead?

P8 (JS). A user types `"12, 3, 100"`. Outline the steps to show the numbers sorted ascending, and name the trap in the default `sort()`.

P9 (explain). Why must input validated in client-side JavaScript be checked again on the server?

P10 (recall). When is Midterm 1, and how long is it?

P11 (explain). Why does this guide avoid inventing Node or MongoDB content for the "client/server" topic?

4b. Gradescope-format and midterm-style practice — Practice recommendation

Where this format comes from. The Gradescope format notes show short ICA checks (10 points each) and multi-page assignments graded per page (Assignment 3: four rubric questions x 25 points, shown as Page 1–4). They do **not** show a midterm format, which is unpublished. The mix below (recall, trace, write code, short explain) is a generic 75-minute written-exam shape. Treat it as a recommendation, not a claimed format.

Timed mock (Sun Oct 4): do R1-R4, T1-T4, W1-W2, plus core P5 (box model) and ICA-M5 (write a CSS rule) in **50 minutes**, on paper, closed-book. The two CSS items make sure the mock covers HTML/CSS as well as JS.

Short recall (ICA grain)

GS-337-R1. Order by specificity, lowest to highest: `.card`, `div`, `#app`, `div.card`, `#app .card`.

GS-337-R2. What does `el.textContent = "<b>Hi</b>"` display, compared with `el.innerHTML = "<b>Hi</b>"`? Which is safer with user input, and why?

GS-337-R3. Match each status code to its meaning: 200, 301, 404, 500.

GS-337-R4. Give two differences between GET and POST.

Output tracing

GS-337-T1. What does this log?

```
console.log(1 + "2", "3" * 2, 0 == "", 0 === "");
```

GS-337-T2. What does this log?

```
let s = 0;
for (let i = 1; i <= 5; i++) {
  if (i % 2 === 0) continue;
  s += i;
}
console.log(s);
```

GS-337-T3. What does this log, and how do you get numeric order?

```
const a = [10, 9, 1, 100];
a.sort();
console.log(a);
```

GS-337-T4. After one full outer pass (`i = 0`) of this bubble sort, what is `a`?

```
const a = [5, 2, 4, 1];
for (let i = 0; i < a.length; i++)
  for (let j = 0; j < a.length - 1 - i; j++)
    if (a[j] > a[j + 1]) { const t = a[j]; a[j] = a[j + 1]; a[j + 1] = t; }
```

GS-337-T5. Count letters case-insensitively in `"Mississippi"`. What are the counts?

Write code (DOM + events)

GS-337-W1. Given `<input id="n"> <button id="go">Double</button> <p id="out"></p>`, write JavaScript so that clicking the button shows twice the number, or `Not a number` for empty or invalid input.

GS-337-W2. Write `validZip(s)`, which returns `true` only for exactly 5 digits. This is a practice spec, deliberately different from any assignment.

Short explain

GS-337-E1. A number-guessing page picks a secret from 1 to 100. With the best strategy (always guess the middle), what is the maximum number of guesses needed? Why?

GS-337-E2. You submit a multi-file web assignment on Gradescope. What two checks prevent a zero for "missing file"? This is process, not content.

ICA habit (process)

The format notes show every submitted ICA earned full credit, but two ICAs had **no submission**, an upload miss rather than a content gap. The habit to build: upload each ICA before 11:00 PM on lecture day. No extra ICA content drilling is needed.

4c. ICA-style micro practice — Practice recommendation

Where this comes from. Content ICA1-ICA10 (D2L Content-pass). These are **new** short items in the same grain (URL parts, HTML/CSS write, box model, forms, JS/DOM). They are not copies of ICA PDFs. Midterm format remains unpublished.

ICA-M1 (URL; ICA2 grain). For `https://docs.arizona.edu/csc337/fa26/schedule/?week=5#forms`, name scheme, domain, path, query, fragment. Which part is not sent to the server?

ICA-M2 (HTML+CSS; ICA3 grain). Write a minimal page with an unordered list of three animals and yellow body background (inline style or `<style>`).

ICA-M3 (forms; ICA3 grain). Gender (one choice) vs hobbies (many choices): radio or checkbox for each?

ICA-M4 (CSS selectors; ICA5 grain). The page has:

```
<p id="taylor" class="guitar">Taylor</p>
<p id="martin" class="guitar">Martin</p>
<p id="pearl" class="drums">Pearl</p>
<p id="gretsch" class="drums">Gretsch</p>
```

Which rule set colors **all four** paragraphs? Explain why each of the others fails.

- (a) `.guitar { color: green; } #drums { color: blue; }`
- (b) `.guitar { color: green; } .drums { color: blue; }`
- (c) `#taylor, .drums { color: red; }`
- (d) `p.guitar, #pearl { color: red; }`

ICA-M5 (box model; ICA6 grain). Write a rule for `div.box` with margin 10px top/bottom and 15px left/right; border 2px solid black; padding 5px top/bottom and 10px left/right.

ICA-M6 (show/hide; ICA7 grain). (a) JS to show `#my_div` currently `display:none`. (b) CSS to hide `#my_p` with `visibility`. (c) One difference between `display:none` and `visibility:hidden`.

ICA-M7 (JS; ICA8-9 grain). (a) Min of a number list without `Math.min`. (b) Round a float to two decimals with `Math.round`. (c) Word-count object for a sentence split on spaces.

ICA-M8 (events+DOM; ICA10 grain). Textbox `#t` and div `#count`: on each input, show the current character length in `#count` using `textContent`.

4d. Assignments 1-3 as practice context (no solutions)

Content Assignments 1-3 are completed topics for self-review. Use them as a **topic checklist**, not as something to re-solve here:

Assignment	Practice-context themes (study the skills, do not paste solutions)
A1	Multi-page HTML site; nav links; images+alt; tables; inline styles
A2	Theme / style toggles; contrast text; localStorage vs non-persistent state
A3	Inline vs block; id/class styling; positioning/float; margin vs padding; visibility vs display; simple onload/onclick JS

A4 remains open and individual — topic overlap only; no A4 solutions in this guide.

5. ANSWER KEY

Core keys

A1. HTML gives structure and content, CSS gives presentation and layout, and JavaScript gives behavior and interactivity.

A2. A status line (code and reason, such as 200 OK) and headers (such as Content-Type, Set-Cookie, and caching). The body is the payload.

A3.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="utf-8">
  <title>Demo</title>
  <link rel="stylesheet" href="site.css">
  <script src="main.js" defer></script>
</head>
<body>
  <h1>Hi</h1>
</body>
</html>
```

defer in <head> works, and so does placing the <script> as the last element inside <body>.

A4. #main is (1,0,0) and div.note is (0,1,1). Ids beat any number of classes, so #main is more specific.

A5. Content-box: $100 + 2 \cdot 10 + 2 \cdot 1 = 122\text{px}$. Border-box: **100px**, with content shrunk to $100 - 20 - 2 = 78\text{px}$.

A6.

```
<form action="/subscribe" method="get">
  <label for="em">Email</label>
  <input type="email" id="em" name="email" required>
  <button type="submit">Subscribe</button>
</form>
```

A7. `/search?q=red+shoes&size=9`. The space is encoded as `+` or `%20`. With POST, the URL is just `/search`, and `q=red+shoes&size=9` travels in the request body, so it is not visible in the URL or history.

A8. Steps: 1. Split on `,`. 2. Trim each piece and convert it with `Number`. 3. Reject `NaN` values. 4. Sort with `(a, b) => a - b`. 5. Display the result with `textContent` or a `textarea` value.

The trap: the default `sort()` compares strings, so it gives `[100, 12, 3]`.

A9. Client code runs on the user's machine and can be bypassed, for example by disabling JavaScript or sending a request directly. Only server checks are trustworthy. Client checks exist for fast feedback.

A10. Tue Oct 6, 2026, in the 75-minute class period (3:30–4:45 PM Arizona).

A11. The scope is provisional, and the only published topic label is "client/server model" (week 7). Node, Express, and MongoDB are scheduled for weeks 8+ and have not been taught, so inventing detail would mean studying the wrong material.

ICA-micro keys (ICA-M1 to ICA-M8)

ICA-M1. scheme `https`; domain `docs.arizona.edu`; path `/csc337/fa26/schedule/`; query `week=5`; fragment `forms`. Fragment is not sent to the server.

ICA-M2. Example shape: `<!DOCTYPE html><html><head><title>...</title>`
`<style>body{background:yellow;}</style></head><body><ul><li>cats</li><li>dogs</li>`
`<li>birds</li></ul></body></html>.`

ICA-M3. (a) radio (one of a group). (b) checkbox (multi-select).

ICA-M4. (b) colors all four. The others fail: - (a) `#drums` looks for an element whose **id** is `drums`. There is none, because `drums` is a **class**. Pearl and Gretsch stay uncolored. - (c) It misses Martin, since only `#taylor` is picked from the guitars. - (d) It misses Gretsch.

ICA-M5.

```
div.box {
  margin: 10px 15px;
  border: 2px solid black;
  padding: 5px 10px;
}
```

ICA-M6. (a) `document.getElementById("my_div").style.display = "block";` (or `""`). (b) `#my_p { visibility: hidden; }`. (c) `display:none` removes layout space; `visibility:hidden` hides but

keeps the space.

ICA-M7. (a) Loop comparing, track min. (b) `Math.round(x * 100) / 100`. (c) Split on " ", count into an object {}.

ICA-M8.

```
document.getElementById("t").addEventListener("input", () => {
  document.getElementById("count").textContent =
    String(document.getElementById("t").value.length);
});
```

Gradescope-format keys

GS-337-R1. `div (0,0,1) < .card (0,1,0) < div.card (0,1,1) < #app (1,0,0) < #app .card (1,1,0)`.

GS-337-R2. `textContent` shows the literal text `<b>Hi</b>`. `innerHTML` renders a bold **Hi**. `textContent` is safer, because `innerHTML` with user input can inject markup or scripts (XSS).

GS-337-R3. 200 = OK. 301 = moved permanently (redirect). 404 = not found. 500 = internal server error.

GS-337-R4. Any two of: - GET puts data in the URL; POST puts it in the body. - GET is visible, bookmarkable, and cached; POST is not. - GET is for retrieval; POST is for creating or changing data. - GET is limited by URL length.

GS-337-T1. `12 6 true false`

GS-337-T2. `9 (1 + 3 + 5)`.

GS-337-T3. `[1, 10, 100, 9]`, because the values are compared as strings. Fix: `a.sort((x, y) => x - y)` gives `[1, 9, 10, 100]`.

GS-337-T4. `[5,2,4,1] -> [2,5,4,1] -> [2,4,5,1] -> [2,4,1,5]`. After the pass, `a` is `[2, 4, 1, 5]`, and the largest value has bubbled to the end.

GS-337-T5. m: 1, i: 4, s: 4, p: 2 (11 letters total).

GS-337-W1.

```
document.getElementById("go").addEventListener("click", () => {
  const raw = document.getElementById("n").value.trim();
  const out = document.getElementById("out");
  const v = Number(raw);
  out.textContent = (raw === "" || Number.isNaN(v)) ? "Not a number" : String(v * 2);
});
```

The key points are passing the handler without `()`, trimming the input, catching the empty-string trap, and using `textContent`.

GS-337-W2.

```
function validZip(s) {  
  return /^d{5}$/.test(s);  
}
```

A loop that checks `s.length === 5` and that every character is between `'0'` and `'9'` is also fine.

GS-337-E1. 7 guesses. Each guess splits the remaining range around the middle. With k guesses you can distinguish at most $2^k - 1$ numbers. $2^6 - 1 = 63 < 100$, so 6 guesses are not enough, while $2^7 - 1 = 127 \geq 100$, so 7 always are.

GS-337-E2. (1) Upload **every** required file, with filenames exactly as the assignment PDF lists them. (2) Open the submission page afterwards to confirm all files are there. Also check the deadline: assignments are due at **3:30 PM**, not 11:59 PM.

6. Common mistakes + readiness

- Invalid nesting, or a `label` whose `for` doesn't match the input's `id`.
- Fighting specificity with `!important` instead of writing a clearer selector.
- Assuming border-box sizing when the default is content-box.
- Thinking POST is "secure." Only HTTPS encrypts.
- Using `==` instead of `===`, or forgetting that `Number("")` is `0`.
- Sorting numbers with the default `sort()`.
- `addEventListener("click", f())`, which calls `f` immediately.
- Using `innerHTML` with user text.

Readiness: a blind pass over all **11** section IDs, the 50-minute paper mock (§4b), and a light review on Monday night — no cram.

Start Here (top of this guide) is the canonical day-by-day. The later prep table is kept as a short copy.

7. Day-by-day prep (Tue/Thu light; no day-before cram)

Day	Focus	IDs	Notes
Mon Sep 28	—	—	Submit A4 tonight (target). This guide does not cover A4.
Tue Sep 29	—	—	A4 due 3:30 PM; backup window 10:45-12:30 only.
Wed Sep 30	HTTP, URLs, Get & Post	http, getpost	Short

Day	Focus	IDs	Notes
Fri Oct 2	HTML and CSS review	html, css, layout	Deep day
Sat Oct 3	Forms, JS, and DOM (after the week-6 lecture)	forms, js, dom	Deep day
Sun Oct 4	50-minute paper mock (§4b), then review	integrate	Blind, then check
Mon Oct 5	Even rotation over all IDs; client/server concepts	all 337-M1-*	Deep day, but stop by evening
Tue Oct 6	Calm buffer only (before 9:30 or 10:45-12:30)	—	Midterm in class at 3:30 PM (if held in class)

8. Changes in this review (2026-09-24)

- Added **Get & Post** (syllabus week 4), which was missing from the checklist. It now has an explanation, practice items, and keys.
- **Removed Assignment 4-specific solution material:** the working email validator for A4's exact rule, A4's exact validation list, and A4's filenames. A4 is open and individual-only. The drills are re-specified: ZIP validator, letter counts, a DOM "double" button, and guess-count reasoning.
- Added a timing caveat: DOM and client/server have not been lectured yet, and client/server falls in the midterm week itself.
- Marked "closed-book" as **verify**, because the inventory and topic map don't state it.
- Rebuilt the specificity explanation with tuples, and added JavaScript traps (`==`, `Number("")`, default `sort`, event handler), DOM safety, and status codes.
- Fixed the readiness line: it said "all eight IDs" when there were ten; there are now eleven.
- Changed times to Arizona time.

8b. Content-fold (2026-09-24, America/Phoenix)

- Mapped Content slides 02-08 onto the existing topic IDs; kept honesty banners (scope PROVISIONAL; date confirmed Oct 6).
- Added ICA-style micro practice ICA-M1..M8 (**Practice recommendation**) from Content ICA grain without copying ICA PDFs.
- Added A1-A3 practice-context table (skills only); A4 still open/individual, no solutions.

8c. Opus 5.5 review (2026-09-24 evening, America/Phoenix)

- Re-checked every key. JS outputs (T1-T5, W2, the `Number/parseInt` claims) were run in Node and match. **No wrong answers found.**
- **ICA-M4 was underspecified.** Its key depended on which ids had which class, and the question never said. It is now a concrete four-option question with an unambiguous answer.

- **Fixed the border-box claim** in the excerpt caption. With 70px width and 104px of padding + border, border-box collapses the content to 0 and renders 104px; it does not simply "shrink".
- Tightened the GS-337-E1 justification ($2^k - 1$ numbers with k guesses).
- **Class-block fixes:** the A4 hand-in was planned "before class" on Tue Sep 29, but 9:30-3:15 is almost all class. It is now a Mon Sep 28 night target with a 10:45-12:30 backup. The Tue Oct 6 buffer now names the only free windows (before 9:30 or 10:45-12:30).
- The mock grew from 45 to 50 minutes and added P5 + ICA-M5, so HTML/CSS is tested too, not only JS.
- The 75-minute length is now labeled "per inventory". The verified facts sheet only states the 3:30-4:45 class period.

9. Disclaimer

The Gradescope format notes describe ICA and assignment formats only. The midterm format and blueprint are **not published**, so the §4b shape is a recommendation.

Study aid only — not for submitted work (assignments or exams). Follow CSC 337 and UA AI and academic-integrity policies.