

CHAPTER 2

INTELLIGENT AGENTS

```
function TABLE-DRIVEN-AGENT(percept) returns an action
  persistent: percepts, a sequence, initially empty
               table, a table of actions, indexed by percept sequences, initially fully specified

  append percept to the end of percepts
  action  $\leftarrow$  LOOKUP(percepts, table)
  return action
```

Figure 2.7 The TABLE-DRIVEN-AGENT program is invoked for each new percept and returns an action each time. It retains the complete percept sequence in memory.

```
function REFLEX-VACUUM-AGENT([location,status]) returns an action
  if status = Dirty then return Suck
  else if location = A then return Right
  else if location = B then return Left
```

Figure 2.8 The agent program for a simple reflex agent in the two-location vacuum environment. This program implements the agent function tabulated in Figure ??.

```
function SIMPLE-REFLEX-AGENT(percept) returns an action
  persistent: rules, a set of condition–action rules

  state  $\leftarrow$  INTERPRET-INPUT(percept)
  rule  $\leftarrow$  RULE-MATCH(state, rules)
  action  $\leftarrow$  rule.ACTION
  return action
```

Figure 2.10 A simple reflex agent. It acts according to a rule whose condition matches the current state, as defined by the percept.

function MODEL-BASED-REFLEX-AGENT(*percept*) **returns** an action
persistent: *state*, the agent's current conception of the world state
 transition_model, a description of how the next state depends on
 the current state and action
 sensor_model, a description of how the current world state is reflected
 in the agent's percepts
 rules, a set of condition–action rules
 action, the most recent action, initially none

state \leftarrow UPDATE-STATE(*state*, *action*, *percept*, *transition_model*, *sensor_model*)
rule \leftarrow RULE-MATCH(*state*, *rules*)
action \leftarrow *rule*.ACTION
return *action*

Figure 2.12 A model-based reflex agent. It keeps track of the current state of the world, using an internal model. It then chooses an action in the same way as the reflex agent.
