Power

Maximum input voltage: 26V



Battery Input and
Current Sense Resistor

(Vin+ − Vin−)max = 320mV



I2C address: 0x40

Voltage/Current/Power Sense IC

C1, C8 are Al Electrolytics
C2, C9 are 1210 ceramics
C1, C2 rated at >= 35V



Keep SGND and PGND separate − connect only at one location!



3.3V 2A Regulator (MCUs and Sensors)

Aikyam Innovators

Sheet: /

File: Agri_Drone.kicad_sch

Title: Power

Size: A4	Date: 2024−09−28	Rev:
KiCad E.D.A. 8.0.5		Id: 1/6

Flight Control Computer (FCC)

STM32H7: see AN4938

Not using LSE as do not need RTC

C13, C14: ESR < 100mOhm



AN2606 (Bootloaders): USART1 Bootloader (PB14/PB15)

UART2, I2C1, and GPIO_A to GPIO_H -> NAVC
UART1 -> Debug (via USB)
TIM4 -> PWM/PPM input

C15, C27, C29 Tantalum



Decoupling Capactors



Test Points (I2C2)



I2C Pull-Up Resistors



VDDA Filter



Indicator LEDs



VREF+ Filter

STM32H7 has internal NRST pull-up resistor (40k)



Reset Switch

ABM8G-25.000MHZ-4Y-T3



High Speed External Crystal

C32 = C33 = 2 * (CL - Cstray) Rext = 1/(2*pi*f*CL2)
Cstray = {2pF, 5pf}

TDD01H0SB1R = SPDT



Bootmode Switch

Aikyam Innovator

Sheet: /Flight controller Computer/
File: FCC.kicad_sch

Title: Flight Controller Computer

Size: A4	Date: 2024-09-28	Rev:
KiCad E.D.A. 8.0.5		Id: 2/6

FCC Peripherals



PWM Driver



Servo Connector
(3 Rows, 8 Cols, 2.54mm Pitch)



Board To Wire Connectors
(Molex PicoBlade)



EEPROM



FLASH Memory

Aikyam Innovators

Sheet: /FCC Peripheral/
File: FCCPeripherals.kicad_sch

Title: FCC Peripheral

Size: A4	Date: 2024-09-28	**Rev:**
KiCad E.D.A. 8.0.5		Id: 3/6

Navigation Computer (NAVC)



UART2, I2C2, and GPIO_A to GPIO_H -> FCC
UART3 -> Debug (via USB)

AN2606 (Bootloaders): USART3 Bootloader PC10/PC11



Bootmode Switches



Decoupling Capacitors

STM32F4 has internal
NRST pull-up resistor (40k)



Reset Switch



Test Points (I2C1)



VDDA Filter



I2C Pull-Up Resistors

I2C2_NAVC already pulled up by I2C1_FCC resistors!

ABM8G-25.000MHZ-4Y-T3



High Speed External Crystal

C52 = C53 = 2 * (CL - Cstray)
Cstray = {2pF, 5pf}

Rext = 1/(2*pi*f*CL2)



Indicator LEDs

Aikyam Innovators

Sheet: /NAVC/
File: NAVC.kicad_sch

Title: NAVC

Size: A4	Date: 2024-09-28	**Rev:**
KiCad E.D.A. 8.0.5		Id: 4/6

NAVC Peripherals



Inertial Measurement Unit (Accelerometer + Gyroscope)



Temperature Sensor



Absolute Pressure Sensor

C59 ESR < 200mOhm



Magnetometer



EEPROM



GPS Receiver and SMA Antenna Connector



Board To Wire Connectors
(Molex PicoBlade)

Aikyam Innovators

Sheet: /NAVC Perripheral/
File: NAVCPeripherals.kicad_sch

Title: NAVC Peripheral

Size: A4	Date: 2024-09-28	**Rev:**
KiCad E.D.A. 8.0.5		Id: 5/6

Connections (FCC <-> NAVC)







Connectors (Programming & Debug)







GPS Backup Battery



Aikyam Innovators		
Sheet: /Connections/		
File: Connections.kicad_sch		
Title: Connections		
Size: A4	Date: 2024-09-28	**Rev:**
KiCad E.D.A. 8.0.5		Id: 6/6