

Name: Shrikant Pawar

Roll No.: 57

Assignment No.: 06

Title: Implement a client and a server on different computers using python. Perform the authentication of sender between these two entities by using RSA digital signature cryptosystem

Server Code:

```
import random
import hashlib

def gcd(a,b):
    if b==0:
        return a
    else:
        return gcd(b,a%b)

def isPrime(n) :
    # Corner cases
    if (n <= 1) :
        return False
    if (n <= 3) :
        return True

    # This is checked so that we can skip
    # middle five numbers in below loop
    if (n % 2 == 0 or n % 3 == 0) :
        return False

    i = 5
    while(i * i <= n) :
        if (n % i == 0 or n % (i + 2) == 0) :
            return False
        i = i + 6

    return True

# Get a prime number
def generatePrime(num = 100):
    L1 = []
    for i in range(60, num + 1):
        if isPrime(i):
            L1.append(i)

    p = random.choice(L1)
```

```
L1.pop(L1.index(p))
q = random.choice(L1)
```

```
t = (p-1)*(q-1)
n = p*q
```

```
for e in range(2,t):
    if gcd(e,t) == 1:
        break
```

```
for i in range(1,10):
    x = 1 + i*t
    if x % e == 0:
        d = int(x/e)
        break
```

```
return e,d,n
```

```
Alphabet_List = {'A': '01', 'B': '02', 'C': '03', 'D': '04', 'E': '05', 'F': '06', 'G': '07', 'H': '08', 'I': '09', 'J': '10',
                 'K': '11', 'L': '12', 'M': '13', 'N': '14', 'O': '15', 'P': '16', 'Q': '17', 'R': '18', 'S': '19', 'T': '20',
                 'U': '21', 'V': '22', 'W': '23', 'X': '24', 'Y': '25', 'Z': '26', ' ': '27', '1': '28', '2': '29', '3': '30',
                 '4': '31', '5': '32', '6': '33', '7': '34', '8': '35', '9': '36', '0': '37'}
```

```
key_list = list(Alphabet_List.keys())
val_list = list(Alphabet_List.values())
```

```
def convertText(msg,Ekey, N):
    li = list(msg)
    lii = [Alphabet_List[i] for i in li]
    if(len(lii)%2 != 0):
        lii.append('27')
    #print(lii)
    l1 = [int(lii[i]+lii[i+1]) for i in range(0,len(lii),2)]
    #print(l1)
    ctt = [str(pow(no,Ekey)%N).zfill(4) for no in l1]
    ct = ".join(ctt)
    return ct
```

```
def decrypt(cipherText, Dkey, N):
    text = [str(pow(int(cipherText[i:i+4]),Dkey)%N).zfill(4) for i in range(0, len(cipherText), 4)]
    #print(text)
```

```
L1 = []
for i in text:
    L1.append(i[0:2])
```

```

        L1.append(i[2:4])

    L2 = []
    for i in L1:
        L2.append(key_list[val_list.index(i)])

    msg = ".join(L2)
    return msg
import socket,threading

e,d,n = generatePrime()

localIP    = "192.168.43.125"
localPort  = 20003
bufferSize = 1024
msgFromServer = "Hello UDP Client "+str(e)+" "+str(n)
flag=1
bytesToSend = str.encode(msgFromServer)

# Create a datagram socket
UDPServerSocket = socket.socket(family=socket.AF_INET, type=socket.SOCK_DGRAM)

# Bind to address and ip
UDPServerSocket.bind((localIP, localPort))
print("UDP server up and listening")

def recv():
    global flag
    while True:
        recieve= UDPServerSocket.recvfrom(bufferSize)
        msg = recieve[0].decode('utf-8')
        plainText = decrypt(msg, d, n)
        if recieve[0].decode('utf-8')== 'bye':
            flag=0
            break
        print (plainText)

def Send(a):
    global flag
    while True:
        if flag==0:
            print("Connection closed")
            break
        message=input("Enter your reply ").upper()
        L1 = list(message.split())
        cipherText = convertText(L1[0], int(L1[1]), int(L1[2]))

```

```

UDPServerSocket.sendto(cipherText.encode('utf-8'),a)

# Listen for incoming datagrams
while(True):
    flag=1
    bytesAddressPair = UDPServerSocket.recvfrom(bufferSize)

    message = bytesAddressPair[0]
    address = bytesAddressPair[1]

    clientMsg = "Message from Client:{ }".format(message)
    clientIP = "Client IP Address:{ }".format(address)

    print(clientMsg)
    print(clientIP)

    UDPServerSocket.sendto(bytesToSend, address)
    threading.Thread(target=recv).start()
    threading.Thread(target=Send(address)).start()

```

OUTPUT:

```

UDP server up and listening
Message from Client:b'Hello UDP Server!. My public Key is: 5 6499'
Client IP Address:('192.168.43.125', 63145)
Enter your reply HelloClient 5 6499
HIISERVER
Enter your reply ByeBye 5 6499
OKBYE

```