

# Inheritance

## OOP Principles, Inheritance



**SoftUni Team**

**Technical Trainers**



**SoftUni**



**Software University**

<https://softuni.bg>

1. Inheritance
2. Class Hierarchies
3. Inheritance in C++
4. Accessing Members of the Base Class
5. Types of Class Reuse
  - Extension, Composition, Delegation
6. When to Use Inheritance





sli.do

#cpp-oop



**OOP**

## **OOP Principles**

Encapsulation, Inheritance, Polymorphism,  
Abstraction

- Classes have internal state (**vector**'s capacity)
  - **private/protected** – state inaccessible to outside code
  - **public** members interact with outside code, keep state correct

```
class IntArray {  
private:  
    int* data; int size;  
public:  
    IntArray(int size) : data(new int[size]), size(size) {}  
    ~IntArray() { delete[] this->data; }  
    ...  
};
```

Can't be modified from the outside, so the class can:

- assume **data** needs a **delete[]** in destructor
- assume last index in data is **size-1**
- rename **size** to **length** without checking for outside usages

- **Derived** classes **inherit** a **base** class to reuse its members

```
class Vehicle { private: double speed;  
public: Vehicle(double speed) : speed(speed) {}  
        void setSpeed(double speed) { this->speed = speed; }  
};
```

```
class Car : public Vehicle {  
private: bool parkingBrakeOn;  
public:  
Car(double spd, bool park) : Vehicle(spd), parkingBrakeOn(park) {}  
};
```

```
class Airplane : public Vehicle {  
private: double altitude;  
public:  
Airplane(double spd, double alt) : Vehicle(spd), altitude(alt) {}  
};
```

- Base class can have **virtual** members
  - Derived classes **override** them to have different behavior

```
class Vehicle { ...  
    virtual void stop() { this->speed = 0; }  
};
```

```
class Car : public Vehicle {  
    ...  
    virtual void stop() override {  
        Vehicle::stop();  
        this->parkingBrakeOn = true;  
    }  
};
```

```
class Airplane : public Vehicle {  
    ...  
    virtual void stop() override {  
        Vehicle::stop();  
        this->altitude = 0;  
    }  
};
```


- Base class pointers/references can point to any derived class
  - Normal members access **base** class member
  - **virtual** members access **override** member in **derived**

```
std::vector<Vehicle*> vehicles{
    new Car(90, false),
    new Airplane(700, 10000, 242),
    new Car(0, true)
};
vehicles[0]->stop(); // calls Car::stop()
vehicles[1]->stop(); // calls Airplane::stop()
vehicles[2]->stop(); // calls Car::stop()
```




- Abstraction – using base virtual members
  - So allowing any class with **overrides** for them
- **ostream& operator<<(ostream& out, const Person& p)**
  - Allows any **ostream** – **ostringstream**, **ofstream**, **cout**

```
void stopIfOverLimit(Vehicle* v, double limit) {  
    if (v->getSpeed() > limit) {  
        v->stop();  
    }  
}
```




# **Class Hierarchies**

- **Inheritance** leads to **hierarchies** of classes and/or interfaces in an application:



# Class Hierarchies – C++ Stream Library




- C++ supports inheritance through **access modifier**


```
class Person { ... }
```

```
class Student : public Person { ... }
```

```
class Employee : public Person { ... }
```

Student **inherit**  
Person





# Inheritance

Syntax, Protected Members, Accessing Base

- Code reuse patterns:
  - Repeated code -> extract function
  - Functions using similar parameters/globals -> extract **class**
  - Repeated members in multiple classes -> extract **base class**
- Inheritance – sharing member definitions
  - A class declares/defines members
  - Other classes inherit it – get all members of inherited class

- **class Derived : access-modifier Base { ... }**
  - **access-modifier** – one of **public/protected/private**
- Members of **Base** class added to **Derived** class
  - Access limited to inheritance access-modifier
  - **public**: doesn't change **Base** modifiers
  - **protected**: **public** from **Base** -> **protected** in **Derived**
  - **private**: any from **Base** -> **private** in **Derived**



# Inheritance – Extracting Base Class


- Extract common members into a base class

```
class Vehicle {  
public: double speed;  
};
```

Can't use initializer-list  
for base class field

```
class Car : public Vehicle {  
    bool parkingBrakeOn;  
  
public:  
    Car(double speed, bool parked)  
        : parkingBrakeOn(parked) {  
        this->speed = speed;  
    }  
};
```

```
class Airplane : public Vehicle {  
    double altitude;  
    double heading;  
  
public:  
    Airplane(double spd, double alt, double hdg)  
        : altitude(alt), heading(hdg) {  
        this->speed = spd;  
    }  
};
```




# Inheritance

LIVE DEMO

# Share Access with Derived – protected

- **public speed** – breaking encapsulation
  - Can't use **private**, because we lose access to **speed**
- **protected** members – accessible to inheriting class



```
class Vehicle {  
protected:  
    double speed;  
};
```

```
class Car : public Vehicle { ...  
public:  
    Car(...) { this->speed = speed; }  
};
```

```
Car car(90, false);  
cout << car.speed << std::endl;  
// compilation error
```



# Protected Members

LIVE DEMO

# Using Base Constructors

- Inheriting class can call **base** constructor
  - In initializer list, like field, BUT with base class name
- **Syntax:**

```
Derived(...) : Base(...), ... { ... }
```



# Using Base Constructors - Example

```
class Vehicle { protected:  
    double speed;  
    Vehicle(double speed) : speed(speed) {}
```

```
class Car : public Vehicle {  
    ...  
    Car(double speed, bool park)  
        : Vehicle(speed), parkingBrakeOn(park) {}
```

```
class Airplane : public Vehicle {  
    ...  
    Airplane(double s, double a, double h)  
        : Vehicle(s), altitude(a), heading(h) {}
```

- Methods are inherited just like any member
- Hiding – using same signature in **derived** as in **base**
  - E.g. **base** has **void f()**, **derived** hides with **int f()**
    - calling **f()** in **derived** calls **derived** version (same for objects)
- Explicit access to base member (field/method/...)
  - Prefix member with **base** class name and **operator::**
  - E.g. **Base::f()** calls **f()** of inherited class **Base**


# Example: Hiding & Calling Base Methods

- Example: Let's make a **toString()** for **Vehicle**
  - Reuse it in **Car's toString()**

```
class Vehicle {  
  
    ...  
    string toString() const {  
        ostreamstream stream;  
        stream << "speed: "  
            << this->speed;  
        return stream.str();  
    }  
}
```

```
class Car {  
    ...  
    string toString() const {  
        ostreamstream stream;  
        stream << Vehicle::toString()  
            << " parking brake: "  
            << this->parkingBrakeOn;  
        return stream.str();  
    }  
}
```





# Calling Base Constructors and Methods

LIVE DEMO



# Practice

Live Exercise in Class


# Problem 1 - ArrayTrouble

- Study and implement the missing functionality described in the "ArrayTrouble description and skeleton code"

# C++ Object Slicing

- Base objects can be assigned with derived objects
  - Implicit cast, called **upcasting**
  - Fields from derived object are "sliced off"
  - *Should generally be avoided*
- **Base x = Derived();**
  - **x** can only access **Base** fields





# Object Slicing

LIVE DEMO

## ■ What will this code do?

```
Vehicle v =  
    Airplane(250, 10000);  
  
cout << v.speed << endl;
```

a) Print **250**

**b)** Print **0**

c) Compilation error

d) Behavior is undefined

```
struct Vehicle {  
public:  
    double speed;  
    Vehicle() : speed(0) {}  
};  
  
class Airplane : public Vehicle {  
public:  
    double speed; double altitude;  
  
    Airplane(double speed, double altitude)  
        : speed(speed), altitude(altitude) {}  
};
```

## C++ PITFALL: SLICING A HIDDEN FIELD

Fields can be hidden just like methods can.

The derived class in the example initializes its own field, not the base field. That field gets sliced-off.

The base class has a default constructor – it gets called on derived initialization, hence `0`




- If a **base** has no default constructor
  - **Derived** must define constructor calling the **base** constructor
- Assignment operator is always hidden in a **derived** class
  - Signature not the same, but implicitly the same as base (**upcast**)
- Constructors aren't inherited – can't be used externally
  - Only used internally in initializer list
  - This also applies to copy/move constructors



- **Base** pointers/references can point to **derived** objects
  - **upcast**, NO slicing – not fitting larger into smaller object
  - **Derived d; Base\* p = &d;**
  - **Base\* p = new Derived(); ...**
- Accesses base members, regardless of hiding

```
Airplane plane(510, 2400, 90);  
Vehicle* v = &plane;  
cout << v->toString() << endl; // calls Vehicle::toString()
```

- Unless members are **virtual overrides**  
(will be covered in the next lecture - Polymorphism)




# Base Pointer to Derived Class

LIVE DEMO

# Inheritance – Derived Class

- Class **taking all members** from another class




# Using Inherited Members

```
class Person { public void sleep() { ... } }  
class Student :public Person { ... }  
class Employee :public Person { ... }
```


```
Student student;  
student.sleep();  
Employee* employee = new Employee();  
employee->sleep();
```

- A derived class instance **contains** an instance of its base class



- Inheritance has a **transitive relation**


```
class Person { ... }  
class Student :public Person { ... }  
class CollegeStudent :public Student { ... }
```



- Inheriting from a final classes is forbidden

```
class Animal final {  
    ...  
}
```


```
public class Dog :public Animal { } // Error...
```



**Reusing Classes**



- **Duplicate code** is error prone
- **Reuse classes** through an **extension**
- Sometimes the only way




- Using classes to **define classes**

```
class Laptop {  
    Monitor monitor;  
    Touchpad touchpad;  
    Keyboard keyboard;  
    ...  
}
```

Reusing classes



```
class Laptop {  
    Monitor monitor;  
    void incrBrightness() {  
        monitor.brighten();  
    }  
  
    void decrBrightness() {  
        monitor.dim();  
    }  
}
```







# Practice

Live Exercise in Class

# Problem 2 - Hardware Store

- Study and implement the missing functionality described in the "Hardware Store description and skeleton code"

- Classes share **IS-A** relationship  Too simplistic
  - A car "is a" vehicle, a person "is a" mammal
- Derived class **IS-A-SUBSTITUTE** for the base class
- Share the **same role**
- Derived class is the **same as the base class** but adds a **little bit more functionality**
- Composition **HAS-A** relationship
  - A car "has an" engine, a person "has a" name



# Signaling from Composition Classes to Owner Class


LIVE DEMO

- Inheritance is a powerful tool for **code reuse**
- **Subclass inherits** members from **Superclass**
- Subclass can **override** methods
- Look for classes with the **same role**
- Look for **IS-A** and **IS-A-SUBSTITUTE** for relationship
- Consider **Composition** and **Delegation** instead
- Extract multiple-usage code into a base class





# Questions?



# SoftUni Diamond Partners




**SCHWARZ**



**SUPER  
HOSTING  
.BG**





**VIRTUAL RACING SCHOOL**



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg/>
- © Software University – <https://softuni.bg>



- Software University – High-Quality Education, Profession and Job for Software Developers

- [softuni.bg](http://softuni.bg), [about.softuni.bg](http://about.softuni.bg)

- Software University Foundation

- [softuni.foundation](http://softuni.foundation)

- Software University @ Facebook

- [facebook.com/SoftwareUniversity](https://facebook.com/SoftwareUniversity)

- Software University Forums

- [forum.softuni.bg](http://forum.softuni.bg)

