

Lab: Stacks and Queues

This document defines the exercises for ["Java Advanced" course @ Software University](#). Please submit your solutions (source code) of all below described problems in [Judge](#).

I. Working with Stacks

1. Browser History

Write a program which takes 2 types of browser instructions:

- Normal navigation: a URL is set, given by a string
- The string **"back"** that sets the current URL to the last set URL

After each instruction the program should print the current URL. If the **back** instruction can't be executed, print **"no previous URLs"**. The input ends with **"Home"** command, then simply you have to stop the program.

Examples

| Input | Output |
|--|---|
| https://softuni.bg/ back https://softuni.bg/trainings/courses back https://softuni.bg/trainings/2056 back https://softuni.bg/trainings/live https://softuni.bg/trainings/live/details Home | https://softuni.bg/ no previous URLs https://softuni.bg/trainings/courses https://softuni.bg/ https://softuni.bg/trainings/2056 https://softuni.bg/ https://softuni.bg/trainings/live https://softuni.bg/trainings/live/details https://softuni.bg/trainings/live/details |

Hints

- Use `ArrayDeque<>`
- Use `String` to keep current page
- Use `push()`, when moving to next page
- Use `pop()`, when going back

2. Simple Calculator

Create a simple calculator that can evaluate simple expressions that will not hold any operator different from addition and subtraction. There will not be parentheses or operator precedence.

Solve the problem using a Stack.

Examples

| Input | Output |
|--------------------|--------|
| 2 + 5 + 10 - 2 - 1 | 14 |
| 2 - 2 + 5 | 5 |

Hints

- Use an **ArrayDeque<>**
- Consider using the **add()** method
- You can either
 - add the elements and then pop them out
 - or push them and reverse the stack

3. Decimal to Binary Converter

Create a simple program that **can convert a decimal number to its binary representation**. Implement an elegant solution **using a Stack**.

Print the binary representation back at the terminal.

Examples

| Input | Output |
|-------|-------------|
| 10 | 1010 |
| 1024 | 10000000000 |

Hints

- If the given number is 0, just print 0
- Else, while the number is greater than zero, divide it by 2 and push the remainder into the stack

```
while (decimal != 0) {  
    stack.push(decimal % 2);  
    decimal /= 2;  
}
```

- When you are done dividing, pop all reminders from the stack, that is the binary representation

4. Matching Brackets

We are given an arithmetical expression with brackets. Scan through the string and extract each sub-expression.

Print the result back at the terminal.

Examples

| Input | Output |
|-------------------------------------|---|
| 1 + (2 - (2 + 3) * 4 / (3 + 1)) * 5 | (2 + 3) (3 + 1) (2 - (2 + 3) * 4 / (3 + 1)) |
| (2 + 3) - (2 + 3) | (2 + 3) (2 + 3) |

Hints

- Use a stack, namely an **ArrayDeque()**
- Scan through the expression searching for brackets
 - If you find an opening bracket, push the index into the stack

- If you find a closing bracket pop the topmost element from the stack. This is the index of the opening bracket.
- Use the current and the popped index to extract the sub-expression

```
if (ch == '(') {
    stack.push(index);
}
else if (ch == ')') {
    int startIndex = stack.pop();
    String contents = expression.substring(startIndex, index + 1);
    System.out.println(contents);
}
```

II. Working with Queues

5. Printer Queue

The printer queue is a simple way to control the order of files sent to a printer device. We know that a single printer can be shared between multiple devices. So to preserve the order of the files sent, we can use queue. Write down a program which takes filenames until **"print"** command is received. Then as output print the filenames in the order of printing. Some of the tasks may be **canceled** if you receive **"cancel"** you have to remove the first file to be printed. If there is no current file to be printed print **"Printer is on standby"**.

Examples

| Input | Output |
|--|--|
| Lab.docx cancel cancel Presentation.pptx NoteNothing.txt SomeCode.java cancel print | Canceled Lab.docx Printer is on standby Canceled Presentation.pptx NoteNothing.txt SomeCode.java |
| Presentation.pptx cancel Text.txt cancel cancel cancel print | Canceled Presentation.pptx Canceled Text.txt Printer is on standby Printer is on standby |

Hints

- Use an **ArrayDeque<>**
- Use **offer()**, when adding file
- Use **pollFirst()**, when printing file

6. Hot Potato

Hot potato is a game in which **children form a circle and start passing a hot potato**. The counting starts with the first kid. **Every n^{th} toss the child left with the potato leaves the game**. When a kid leaves the game, it passes the potato forward. This continues repeating **until there is only one kid left**.

Create a program that simulates the game of Hot Potato. **Print every kid that is removed from the circle**. In the end, **print the kid that is left last**.

Examples

| Input | Output |
|-------------------------------------|--|
| Sam John Sara 2 | Removed John Removed Sam Last is Sara |
| George Peter Sam John Zak 10 | Removed Zak Removed Peter Removed Sam Removed George Last is John |
| George Peter Misha Sara Kendal 1 | Removed George Removed Peter Removed Misha Removed Sara Last is Kendal |

7. Math Potato

Rework the previous problem so that a **child is removed only on a composite (not prime) cycle** (cycles start from 1)

If a **cycle is prime**, just **print the child's name**.

As before, print the name of the child that is left last.

Examples

| Input | Output |
|--------------------------------------|---|
| Maria Peter George 2 | Removed Peter Prime Maria Prime George Removed Maria Last is George |
| George Peter Misha Sara Kendal 10 | Removed Kendal Prime Peter Prime Misha Removed Sara Prime George Removed George Prime Misha Removed Peter Last is Misha |

8. Browser History Upgrade

Extend "Browser History" with a "**forward**" instruction which visits URLs that were navigated away from by "**back**"

Each forward instruction visits the next most-recent such URL. If a normal navigation happens, all potential forward URLs are removed until a new back instruction is given. If the forward instruction can't be executed, print "**no next URLs**".

Examples

| Input | Output |
|--|--|
| forward https://softuni.bg/ https://softuni.bg/trainings/courses back forward https://softuni.bg/trainings/2056 back forward forward https://softuni.bg/trainings/courses Home | no next URLs https://softuni.bg/ https://softuni.bg/trainings/courses https://softuni.bg/ https://softuni.bg/trainings/courses https://softuni.bg/trainings/2056 https://softuni.bg/trainings/courses https://softuni.bg/trainings/2056 no next URLs https://softuni.bg/trainings/courses |

Hints

- Use the solution from Browser History
- Use **ArrayDeque<>** as queue to keep the forward pages
- Use **clear()** method to reset the forward pages
- Use **addFirst()** when adding page to the forward pages