

# Aspect Oriented Programming AOP

SoftUni Team  
Technical Trainers



**SoftUni**



Software University

<https://softuni.bg>

1. What is AOP
2. Why do we use AOP?
3. AOP Concepts and Terminologies
4. Spring AOP AspectJ Annotations
5. Examples



# Have a Question?

sli.do

**#java-web**



**What is AOP**

- **AOP** breaks the program logic into distinct parts (called **concerns**)
- **Cross-cutting concern**
  - Concern that can affect the whole application and **should be centralized in one location**, such as transaction management, authentication, logging, security etc.



# Why We Use AOP

# Why Use AOP

- To **dynamically add the additional concern** before, after or around the actual logic
- Suppose that we have to maintain methods and needs to do actions before or after they are called
- We can solve the problem **with** or **without AOP**



# Why Using AOP – Problem Example

- **Student class** with some methods whose activity we want to track

```
public class Student{  
    public void actionOne(){...};  
    public void actionTwo(){...};  
    public void actionThree(){...};  
    public void actionFour(){...};  
    public void actionFive(){...};  
}
```



# Why Using AOP – Problem Solution

## ■ Solution **without AOP**

- If we need to log all activity of student, we need to write additional code in all tracked methods
- It leads to the maintenance problem.

## ■ Solution **with AOP**

- We can define the additional concern like maintaining log, sending notification, etc. in the method of a class
- Maintenance is easy in AOP





# AOP Concepts and Terminology

# Terminologies

- The AOP **concepts** and **terminologies** are
  - Join point
  - Advice
  - Pointcut
  - Introduction
  - Target Object
  - Aspect
  - Interceptor
  - AOP Proxy
  - Weaving



# Join Point

- **Join point**

- A Join point is **any point in your program** such as method execution, exception handling, field access etc.
- We can have many Join points
- Spring supports **only the method** execution join point



# Advices and Types

- Represents an action taken by an aspect at a join point
  - **Before Advice**: it executes before a join point
  - **After Returning Advice**: it executes after a joint point completes normally
  - **After Throwing Advice**: it executes if method exits by throwing an exception
  - **After Advice**: it executes after a join point regardless of join point exit whether normally or exceptional return
  - **Around Advice**: It executes before and after a join point



- **Pointcut**

- It is an expression language of AOP that matches join points

- **Introduction**

- Introduction of additional method and fields for a type

- **Target Object**

- The object i.e. being advised by one or more aspects
- Also known as **Proxied Object**

- **Aspect**
  - A class that contains advices
- **Interceptor**
  - An aspect that contains only one advice
- **AOP Proxy**
  - Used to implement aspect contracts, created by AOP framework
- **Weaving**
  - The process of linking aspect with other application types or objects to create an advised object.



# Spring AOP AspectJ Annotations



# Spring AOP AspectJ (1)

- The 3 ways to use spring AOP are
  - By Spring 1.2 old style
  - By AspectJ annotation-style
    - The widely used approach is Spring AspectJ Annotation Style
  - By Spring XML configuration-style(schema based)



- There are two ways to use Spring AOP AspectJ implementation
  - By annotation
  - By XML Configuration

```
@Aspect
public class LoggingAspect {
    @Before("execution(* Student.*(..))")
    public void logBefore(JoinPoint joinPoint) {
        ...
    }
}
```

```
<!-- Aspect -->
<bean id="logAspect" class="" />
<aop:config>
    <aop:aspect id="aspectLogging" ref="logAspect" >
        <!-- @Before -->
        <aop:pointcut id="pointCutBefore"
            expression="execution(* Student.*(..))" />
        <aop:before method="logBefore" pointcut-ref="pointCutBefore" />
    </aop:aspect>
</aop:config>
```

# AspectJ Annotations in Spring (1)

- **@Aspect**
  - Declares the class as aspect
- **@Pointcut**
  - Declares the pointcut expression
- **@Before**
  - Declares the before advice
  - Applied before calling the actual method



# AspectJ Annotations in Spring (2)

- **@After**
  - Declares the after advice
  - Applied after calling the actual method and before returning result
- **@AfterReturning**
  - Declares the after returning advice
  - Applied after calling the actual method and before returning result, can get the result value in the advice



# AspectJ Annotations in Spring (3)

- **@Around**

- Declares the around advice
- Applied before and after calling the actual method

- **@AfterThrowing**

- Declares the throws advice
- Applied if actual method throws exception



# Pointcut

- Pointcut is an **expression language** of Spring AOP
- **@Pointcut** annotation is used to define the pointcut
- We can also **refer the pointcut expression by name**



```
@Pointcut("execution(public * *(..))")  
private void trackStudentActions() {}
```

- Applied on all the public methods

```
@Pointcut("execution(public * *(..))")
```

- Applied on all methods of Student class

```
@Pointcut("execution(* Student.*(..))")
```

- Applied on all setter methods of Student class

```
@Pointcut("execution(* Student.set*(..))")
```

- Applied on all methods of class that returns an int value

```
@Pointcut("execution(int Student.*(..))")
```



# Examples

Live Demonstration



- You remember from previous slides our Student class

```
public class Student {  
    public void actionOne(){...};  
    public void actionTwo(){...};  
    public void actionThree(){...};  
    public void actionFour(){...};  
    public void actionFive(){...};  
}
```

- We need to create a class with **@Aspect**, that contains all advices

```
@Aspect
@Configuration
public class TrackStudent{
    @Pointcut("execution(* Student.*(..))")
    public track(){

        //Can have more than one pointcuts
        //Here place all advices

    }
```

- Add **before advice** to our TrackStudent class

```
@Aspect
@Configuration
public class TrackStudent {
    @Pointcut("execution(* Student.*(..))")
    public track(){}
    @Before("track()") // Execute before track pointcut
    public void beforeAdvice(JoinPoint joinPoint){
        System.out.println("Before advice executed");
    }
}
```

- Add after advice to our TrackStudent class

```
@Aspect
@Configuration
public class TrackStudent {
    @Pointcut("execution(* Student.*(..))")
    public track(){}
    @After("track()") // Execute after track pointcut
    public void afterAdvice(JoinPoint joinPoint){
        System.out.println("After advice executed");
    }
}
```

# @AfterReturning Example

- Add after returning advice to our TrackStudent class

```
...  
@AfterReturning  
(pointcut="execution(* Student.action())",returning="result")  
public void afterReturning(JoinPoint joinPoint,  
                           Object result){  
    System.out.println("AfterReturning advice executed");  
    //In AfterReturning we can get the result of pointcut  
}  
...
```

- Add **around advice** to our TrackStudent class

```
@Around("track()")
public Object aroundAdvices(ProceedingJoinPoint pjp)
                                throws Throwable {

    System.out.println("Before calling");
    Object obj = pjp.proceed();
    //We need to pass the pjp references in the advice
    method, so that we can proceed
    the request by calling the proceed method
    System.out.println("After calling");

}
...
```

# @AfterThrowing Example

- Add after throwing advice to our TrackStudent class

```
...  
@AfterThrowing  
(pointcut="execution(* Student.action())",throwing="error")  
Public void afterReturning(JoinPoint joinPoint,  
                           Throwable error){  
    System.out.println("AfterReturning advice executed");  
    System.out.println("Exception is: " + error);  
    //In AfterThrowing we can get the exception  
}  
...
```

# Specifying Aspects Ordering

- There are two ways:

- By annotation

```
@Aspect  
@Order(0)  
public class TrackStudent{//...}
```

- By implementing interface


```
@Aspect  
public class TrackStudent implements Ordered {  
    //Override this method  
    public int getOrder(){ return 0; }  
}
```



- **AOP – Aspect Oriented Programming**
  - Breaks the program logic into distinct parts (called **concerns**)
  - Maintenance is **easy** in **AOP**
- **Spring AOP AspectJ Annotation**
  - The widely used approach is Spring AspectJ Annotation Style



# Questions?



# SoftUni Diamond Partners




**SCHWARZ**



**SUPER  
HOSTING  
.BG**





**VIRTUAL RACING SCHOOL**



- Software University – High-Quality Education, Profession and Job for Software Developers
  - [softuni.bg](http://softuni.bg), [about.softuni.bg](http://about.softuni.bg)
- Software University Foundation
  - [softuni.foundation](http://softuni.foundation)
- Software University @ Facebook
  - [facebook.com/SoftwareUniversity](https://facebook.com/SoftwareUniversity)
- Software University Forums
  - [forum.softuni.bg](http://forum.softuni.bg)



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is copyrighted content
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg/>
- © Software University – <https://softuni.bg>

