

Visualizing-Graphs-with-NetworkX

July 2, 2020

1 Visualizing Networks

```
[1]: %matplotlib notebook

import networkx as nx
import matplotlib.pyplot as plt

# read in the graph
G = nx.read_gpickle('major_us_cities')

[2]: # draw the graph using the default spring layout
plt.figure(figsize=(10,9))
nx.draw_networkx(G)
```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```
[3]: # See what layouts are available in networkX
[x for x in nx.__dir__() if x.endswith('_layout')]
```

```
[3]: ['circular_layout',
      'random_layout',
      'shell_layout',
      'spring_layout',
      'spectral_layout',
      'fruchterman_reingold_layout']
```

```
[4]: # Draw the graph using the random layout
plt.figure(figsize=(10,9))
pos = nx.random_layout(G)
nx.draw_networkx(G, pos)
```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```
[5]: # Draw the graph using the circular layout
plt.figure(figsize=(10,9))
pos = nx.circular_layout(G)
nx.draw_networkx(G, pos)
```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```
[6]: # Draw the graph using custom node positions
plt.figure(figsize=(10,7))

pos = nx.get_node_attributes(G, 'location')
nx.draw_networkx(G, pos)
```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```
[7]: # Draw the graph adding alpha, removing labels, and softening edge color
plt.figure(figsize=(10,7))

nx.draw_networkx(G, pos, alpha=0.7, with_labels=False, edge_color='.4')

plt.axis('off')
plt.tight_layout();
```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```
[8]: # Draw graph with varying node color, node size, and edge width
plt.figure(figsize=(10,7))

node_color = [G.degree(v) for v in G]
node_size = [0.0005*nx.get_node_attributes(G, 'population')[v] for v in G]
edge_width = [0.0015*G[u][v]['weight'] for u,v in G.edges()]

nx.draw_networkx(G, pos, node_size=node_size,
```

```

        node_color=node_color, alpha=0.7, with_labels=False,
        width=edge_width, edge_color='.4', cmap=plt.cm.Blues)

plt.axis('off')
plt.tight_layout();

```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>

```

[9]: # Draw specific edges and add labels to specific nodes
plt.figure(figsize=(10,7))

node_color = [G.degree(v) for v in G]
node_size = [0.0005*nx.get_node_attributes(G, 'population')[v] for v in G]
edge_width = [0.0015*G[u][v]['weight'] for u,v in G.edges()]

nx.draw_networkx(G, pos, node_size=node_size,
                 node_color=node_color, alpha=0.7, with_labels=False,
                 width=edge_width, edge_color='.4', cmap=plt.cm.Blues)

greater_than_770 = [x for x in G.edges(data=True) if x[2]['weight']>770]
nx.draw_networkx_edges(G, pos, edgelist=greater_than_770, edge_color='r',
    →alpha=0.4, width=6)

nx.draw_networkx_labels(G, pos, labels={'Los Angeles, CA': 'LA', 'New York, NY':
    → 'NYC'}, font_size=18, font_color='w')

plt.axis('off')
plt.tight_layout();

```

<IPython.core.display.Javascript object>

<IPython.core.display.HTML object>