

Programming-Assignment-2

July 2, 2020

You are currently looking at **version 1.2** of this notebook. To download notebooks and datafiles, as well as get help on Jupyter notebooks in the Coursera platform, visit the [Jupyter Notebook FAQ](#) course resource.

1 Assignment 2 - Network Connectivity

In this assignment you will go through the process of importing and analyzing an internal email communication network between employees of a mid-sized manufacturing company. Each node represents an employee and each directed edge between two nodes represents an individual email. The left node represents the sender and the right node represents the recipient.

```
[1]: import networkx as nx

# This line must be commented out when submitting to the autograder
# !head email_network.txt
```

#Sender	Recipient	time
1	2	1262454010
1	3	1262454010
1	4	1262454010
1	5	1262454010
1	6	1262454010
1	7	1262454010
1	8	1262454010
1	9	1262454010
1	10	1262454010

1.0.1 Question 1

Using networkx, load up the directed multigraph from `email_network.txt`. Make sure the node names are strings.

This function should return a directed multigraph networkx graph.

```
[2]: def answer_one():
```

```

    G = nx.read_edgelist('email_network.txt', delimiter = '\t', data=[('time',
→int)], create_using = nx.MultiDiGraph())

    return G

answer_one()

```

[2]: <networkx.classes.multidigraph.MultiDiGraph at 0x7ff600ea9320>

1.0.2 Question 2

How many employees and emails are represented in the graph from Question 1?

This function should return a tuple (#employees, #emails).

```

[3]: def answer_two():

    g_node = answer_one()
    employees = len(g_node.nodes())
    emails = len(g_node.edges())

    return (employees, emails)

answer_two()

```

[3]: (167, 82927)

1.0.3 Question 3

- Part 1. Assume that information in this company can only be exchanged through email. When an employee sends an email to another employee, a communication channel has been created, allowing the sender to provide information to the receiver, but not vice versa. Based on the emails sent in the data, is it possible for information to go from every employee to every other employee?
- Part 2. Now assume that a communication channel established by an email allows information to be exchanged both ways. Based on the emails sent in the data, is it possible for information to go from every employee to every other employee?

This function should return a tuple of bools (part1, part2).

```

[4]: def answer_three():

    g_node = answer_one()
    strongly_conn = nx.is_strongly_connected(g_node)
    conn = nx.is_connected(g_node.to_undirected())

    return (strongly_conn, conn)

```

```
answer_three()
```

[4]: (False, True)

1.0.4 Question 4

How many nodes are in the largest (in terms of nodes) weakly connected component?

This function should return an int.

```
[5]: def answer_four():  
  
    g_node = answer_one()  
    wccs = nx.weakly_connected_components(g_node)  
    largest = len(max(wccs, key = len))  
  
    return largest  
  
answer_four()
```

[5]: 167

1.0.5 Question 5

How many nodes are in the largest (in terms of nodes) strongly connected component?

This function should return an int

```
[6]: def answer_five():  
  
    g_node = answer_one()  
    sccs = nx.strongly_connected_components(g_node)  
    largest = len(max(sccs, key = len))  
  
    return largest  
  
answer_five()
```

[6]: 126

1.0.6 Question 6

Using the NetworkX function `strongly_connected_component_subgraphs`, find the subgraph of nodes in a largest strongly connected component. Call this graph `G_sc`.

This function should return a networkx MultiDiGraph named `G_sc`.

```
[7]: def answer_six():  
  
    g_node = answer_one()  
    sccs_subgraph = nx.strongly_connected_component_subgraphs(g_node)  
    G_sc = max(sccs_subgraph, key = len)
```

```
    return G_sc

answer_six()
```

[7]: <networkx.classes.multidigraph.MultiDiGraph at 0x7ff697b3e710>

1.0.7 Question 7

What is the average distance between nodes in G_sc?

This function should return a float.

```
[8]: def answer_seven():

    G_sc = answer_six()
    adbn = nx.average_shortest_path_length(G_sc)

    return adbn

answer_seven()
```

[8]: 1.6461587301587302

1.0.8 Question 8

What is the largest possible distance between two employees in G_sc?

This function should return an int.

```
[9]: def answer_eight():

    G_sc = answer_six()
    largest = nx.diameter(G_sc)

    return largest

answer_eight()
```

[9]: 3

1.0.9 Question 9

What is the set of nodes in G_sc with eccentricity equal to the diameter?

This function should return a set of the node(s).

```
[10]: def answer_nine():

    G_sc = answer_six()
    per = set(nx.periphery(G_sc))

    return per
```

```
answer_nine()
```

```
[10]: {'129', '134', '97'}
```

1.0.10 Question 10

What is the set of node(s) in G_{sc} with eccentricity equal to the radius?

This function should return a set of the node(s).

```
[11]: def answer_ten():  
  
    G_sc = answer_six()  
    ecc_to_radius = set(nx.center(G_sc))  
  
    return ecc_to_radius  
  
answer_ten()
```

```
[11]: {'38'}
```

1.0.11 Question 11

Which node in G_{sc} is connected to the most other nodes by a shortest path of length equal to the diameter of G_{sc} ?

How many nodes are connected to this node?

This function should return a tuple (name of node, number of satisfied connected nodes).

```
[13]: def answer_eleven():  
  
    G_sc = answer_six()  
    d = nx.diameter(G_sc)  
    per = nx.periphery(G_sc)  
    result = None  
    max_count = float('-inf')  
    for node in per:  
        shortest_path = nx.shortest_path_length(G_sc, node)  
        count = list(shortest_path.values()).count(d)  
        if count > max_count:  
            result = node  
            max_count = count  
  
    return (result, max_count)  
  
answer_eleven()
```

```
[13]: ('97', 63)
```

1.0.12 Question 12

Suppose you want to prevent communication from flowing to the node that you found in the previous question from any node in the center of G_{sc} , what is the smallest number of nodes you would need to remove from the graph (you're not allowed to remove the node from the previous question or the center nodes)?

This function should return an integer.

```
[14]: def answer_twelve():  
  
    G_sc = answer_six()  
    center = nx.center(G_sc)[0]  
    chosen_node = answer_eleven()[0]  
    min_node_cut = len(nx.minimum_node_cut(G_sc, center, chosen_node))  
  
    return min_node_cut  
  
answer_twelve()
```

[14]: 5

1.0.13 Question 13

Construct an undirected graph G_{un} using G_{sc} (you can ignore the attributes).

This function should return a networkx Graph.

```
[15]: def answer_thirteen():  
  
    G_sc = answer_six()  
    undirected_sgraph = G_sc.to_undirected()  
    G_graph = nx.Graph(undirected_sgraph)  
  
    return G_graph  
  
answer_thirteen()
```

[15]: <networkx.classes.graph.Graph at 0x7ff69f66e160>

1.0.14 Question 14

What is the transitivity and average clustering coefficient of graph G_{un} ?

This function should return a tuple (transitivity, avg clustering).

```
[16]: def answer_fourteen():  
  
    G_sc = answer_thirteen()  
    transitivity = nx.transitivity(G_sc)  
    avg_clustering_coeff = nx.average_clustering(G_sc)  
  
    return (transitivity, avg_clustering_coeff)
```

```
answer_fourteen()
```

[16]: (0.570111160700385, 0.6975272437231419)