



Comment	Description	Designator	Footprint	LibRef	Quantity
	LEDSMD1206 High				
(1000) PFP	Quality Forward	0.01/0.1550	DE200045; == +:	I 570 4000	
(1206) RED	Voltage: 3.2 V	3.3VP, LED2	RESC3015X65-01	LED1206	2
	Brightness: 700 mcd				
	LEDSMD1206 High				
	Quality Forward				
(1206) Blue	Voltage: 3.2 V	5VP, RX	RESC3015X65-01	LED1206	2
	Brightness: 700 mcd				
	LEDSMD1206 High				
(1206) white	Quality Forward				
	Voltage: 3.2 V	9VP	RESC3015X65-01	LED1206	1
	Brightness: 700 mcd				
	Digitiloss. 700 mod		QFP50P1600X1600X1		
		Atmega1	20-100N	ATMEGA2560-16AU	1
	Conn Unshrouded		25 10011		
4 Position PinHeader	Header HDR4 POS			4 Position PinHeader	
1Row	2.54mm Solder STThru-	BURN	TE_3-644456-4	1Row	1
	Hole Bag/Box				
	UMF316B7103KFHT/1	+			
(1206) 22pF	206 Capacitor	C1, C10, C11	CAPC3216X125N0	Capacitor 1206	3
	UMK212SD103KD-	1			
(000E) 100pE	T/CAP CER 10000PF	C2, C3, C4, C5, C7,	CAPC2012X95N-0	Canacitor 0905	8
(0805) 100nF	50V0805	C8, C9, C12	UMFUZU1ZA90N+U	Capacitor 0805	8
	***************************************				
(0805) 10nF	UMK212SD103KD-	· ·	CADOGGAOVOCKI O	Conneitor COOF	
	T/CAP CER10000PF	O6	CAPC2012X95N-0	Capacitor 0805	1
	50V0805				
2 Position PinHeader	Cabezal del conector				
	Agujero pasante 2	Gyro PW	TE 2-103327-2	2 Position PinHeader	1
	posiciones 0,100 (2,54	1			
	mm)				
	LEDSMD1206 High				
(1206) GREEN	Quality Forward	GYRO, LED3, TX	RESC3015X65-01	LED1206	3
(1-1-1)	Voltage: 3.2 V	01110, 2220, 171	120001070001	1200	
	Brightness: 700 mcd				
20 Position Bevated	20 Position Bevated			20 Position Bevated	
Socket Connector	Socket Connector	J1, J2	ESQ-110-XX-X-D	Socket Connector	2
	Through Hole				
(1206) Yellow MPU-9250	LEDSMD1206 High				
	Quality Forward	LED1	RESC3015X65-01	LED1206	1
	Voltage: 3.2 V		120001070001	1200	· i
	Brightness: 700 mcd				
	MPU-9250 series				
	Accelerometer,				
	Gyroscope, Humidity,		QFN40P300X300X105-		
	Magnetometer,	MPU9250	25N	MPU-9250	1
	Pressure,		2011		
	Temperature Sensor				
	Evaluation Board				
	Connector Header				
6 Position PinHeader	Through Hole 6	POWER	TE 6-146285-6	6 Position PinHeader	1
1Row	position 0.100	I-OVILIA	11_0*140203*0	1Row	'
	(2.54mm)				
(1206) 65		R1, R15	CAPC3216X125N0	Resistor 1206	2
(1206) 10k		R2, R10, R11	CAPC3216X125N0	Resistor 1206	3
(1206) 150		R3, R17, R18, R20	CAPC3216X125N0	Resistor 1206	4
(0805) 1K		R4, R6	CAPC2012X95N-0	Resistor 0805	2
(1206) 85		R5, R12	CAPC3216X125N0	Resistor 1206	2
(1206) 510K		R7, R8	CAPC3216X125N0	Resistor 1206	2
(1206) 300		R9	CAPC3216X125N0	Resistor 1206	1
(1206) 120		R14	CAPC3216X125N0	Resistor 1206	1
	Conn Unshrouded				
3 Position PinHeader 1Row	Header HDR3 POS	DECET Cor :-	TE 0 400007.0	3 Position PinHeader	_
	2.54mm Solder STThru-	RESET, Servo	TE_3-103327-3	1Row	2
	Hole Carton				
MANAGOFOA.	1/1 Transceiver Full	I_m	SOIC127P600X175-	MANAGOEO:	
MAX488ESA+ Crystal-16MHZ	RS422, RS485 8-SOIC	RS	8N0	MAX488ESA+	1
		1.0	XTAL1140X490X430N-	0	
		Y1	0	Crystal-16MHZ	1
l .			l"	1	1