



Comment	Description	Designator	Footprint	LibRef	Quantity
	LED SMD 1206 High				
BLUE-LED	Quality Forward		DE00004EV0E 04	LED 4000	
	Voltage: 3.2 V	?	RESC3015X65-01	LED1206	1
	Brightness: 700 mcd				
		Atmega?	QFP50P1600X1600X1	ATMEGA2560-16AU	1
		Aimega:	20-100N	ATIVILOAZ300°T0A0	'
	LEDSMD1206 High				
(1206) GREEN	Quality Forward	Bluetooth LED?	RESC3015X65-01	LED1206	1
	Voltage: 3.2 V				'
	Brightness: 700 mcd				
2 Position PinHeader	Cabezal del conector	Bluetooth POWER?, NRE POWER?	TE_2-103327-2	2 Position PinHeader	
	Agujero pasante 2				2
	posiciones 0,100 (2,54				
	mm)				
(0805) 100nF	UMK212SD103KD-		CADCO040\/05\10	Connector COOF	
	T/CAP CER 10000PF	C?	CAPC2012X95N-0	Capacitor 0805	6
	50V 0805 UMF316B7103KFHT/1				
(1206) 22pF		C?	CAPC3216X125N0	Capacitor 1206	3
	206 Capacitor Connector Header				
6 Position PinHeader	Through Hole 6			6 Position PinHeader	
1Row	position 0.100	HC-?	TE_6-146285-6	1Row	1
	(2.54mm)				
	20 Position Bevated				+
20 Position Bevated	Socket Connector	J1, J2	ESQ-110-XX-X-D	20 Position Elevated	2
Socket Connector	Through Hole	01,02	200 11070000	Socket Connector	
	LEDSMD1206 High				
(1206) Yellow	Quality Forward	LED?, NRF LED?	RESC3015X65-01	LED1206	2
	Voltage: 3.2 V				
	Brightness: 700 mcd				
8 Position PinHeader	08 MODII HDR DRST	NDE DI IO	TT 0.4400F0.0	8 Position PinHeader	,
2Row	B/A.100CLLF	NRFPH?	TE_8-146256-8	2Row	1
(1206)		R?	CAPC3216X125N0	Resistor 1206	2
(1206) 10K		R?	CAPC3216X125N0	Resistor 1206	1
(1206) 65		R?	CAPC3216X125N0	Resistor 1206	1
(1206) 120		R?	CAPC3216X125N0	Resistor 1206	1
(1206) 150		R?	CAPC3216X125N0	Resistor 1206	3
(1206) 510K		R?	CAPC3216X125N0	Resistor 1206	2
3 Position PinHeader 1Row	Conn Unshrouded	RESETPH?	TE_3-103327-3	3 Position PinHeader 1Row	
	Header HDR3 POS				1
	2.54mm Solder STThru-				
	Hole Carton				
MAX488ESA+	1/1 Transceiver Full	RS?	SOIC127P600X175-	MAX488ESA+	1
	RS422, RS485 8-SOIC		8N0		
16MHZ		Y?	XTAL1140X490X430N-	Crystal 16MHZ	1
=			0	, <u>-</u>	,