



Comment	Description	Designator	Footprint	LibRef	Quantity
74LVC125APW_118_ic		2	OODCCDC40V440.44NI	74LVC125APW_118_ic	,
in microSD module		(	SOP65P640X110-14N	in microSD module	1
BLUE-LED	LED SMD 1206 High				
	Quality Forward	2	RESC3015X65-01	LED 1206	1
	Voltage: 3.2 V	i	10-0000 10/100-01	1200	1
	Brightness: 700 mcd				
		Atmega?	QFP50P1600X1600X1	ATMEGA2560-16AU	1
		7 amoga.	20-100N	7 (IIVILO) 2000 TO 10	'
(0805) 100nF	UMK212SD103KD-	C?	CAPC2012X95N-0	Capacitor 0805	8
	T/CAP CER 10000PF				
	50V 0805				
(1206) 22pF	UMF316B7103KFHT/1	C?	CAPC3216X125N0	Capacitor 1206	3
	206 Capacitor				
20 Position Elevated Socket Connector	20 Position Bevated	J1, J2	ESQ-110-XX-X-D	20 Position Bevated Socket Connector	2
	Socket Connector				
	Through Hole				
(1206) Yellow	LED SMD 1206 High	LED?	RESC3015X65-01	LED1206	
	Quality Forward				1
	Voltage: 3.2 V				
Micro-SD-Card-	Brightness: 700 mcd			Micro-SD-Card-	
Module		Micro SDCard Slot?	SD-Card-Module	Module	1
(1206) 3.3K		R?	CAPC3216X125N0	Resistor 1206	4
(1206) 10K		R?	CAPC3216X125N0	Resistor 1206	3
(1206) 85		R?	CAPC3216X125N0	Resistor 1206	1
(1206) 120		R?	CAPC3216X125N0	Resistor 1206	3
(1206) 150		R?	CAPC3216X125N0	Resistor 1206	1
(1206) 510K		R?	CAPC3216X125N0	Resistor 1206	2
( 22/2 2	Conn Unshrouded				
3 Position PinHeader	Header HDR3 POS	D-0		3 Position PinHeader	
1Row	2.54mm Solder STThru-	RESETPH?	TE_3-103327-3	1Row	1
	Hole Carton				
	1/1 Transceiver Full	RS?	SOIC127P600X175-	MAX488ESA+	
	RS422, RS485 8-SOIC		8N0		3
16MHZ		Y?	XTAL1140X490X430N-	Chystol 16MU7	4
		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	0	Crystal 16MHZ	1