

Sighting Service

Endpoints — Sighting Service

Reportes

Se definen dos variantes del objeto reporte según el contexto de uso:

reportList — usado en respuestas de colección (GET /reports, GET /reports/my-reports)
Versión liviana para renderizar tarjetas. No incluye descripción ni datos del reportante.

```
{
  "id": "uuid",
  "status": "pendiente | enviado | procesando | resuelto | falso",
  "animalCount": "int",
  "reportPhotoUrl": "string | null",
  "latitude": "float",
  "longitude": "float",
  "createdAt": "datetime",
  "incidentType": {
    "id": "int",
    "name": "string",
    "category": "avistamiento | emergencia | amenaza"
  },
  "species": {
    "id": "int",
    "commonName": "string",
    "animalGroup": "mamífero | ave | reptil | otro"
  }
}
```

species es **null** si el usuario no identificó la especie al reportar.

reportDetail — usado en respuestas de objeto único (GET /:id, POST, PATCH /status)
Versión completa para la vista de detalle. Incluye todos los sub-objetos relevantes.

```
{
  "id": "uuid",
  "status": "pendiente | enviado | procesando | resuelto | falso",
  "animalCount": "int",
  "description": "string",
  "reportPhotoUrl": "string | null",
  "latitude": "float",
  "longitude": "float",
  "createdAt": "datetime",
  "reporter": {
```

```

    "id": "uuid",
    "name": "string",
    "cellphoneNumber": "string",
    "trustPoints": "int"
  },
  "incidentType": {
    "id": "int",
    "name": "string",
    "category": "avistamiento | emergencia | amenaza"
  },
  "species": {
    "id": "int",
    "commonName": "string",
    "scientificName": "string",
    "animalGroup": "mamífero | ave | reptil | otro",
    "photoUrl": "string | null"
  },
  "assignedInstitution": {
    "id": "int",
    "name": "string",
    "emergencyPhone": "string"
  },
  "recomendatedAction": {
    "id": "int",
    "title": "string",
    "type": "reporte | catalogo"
  }
}

```

`species`, `assignedInstitution` y `recomendatedAction` son `null` si aún no han sido asignados.

POST /reports

Crea un nuevo reporte y retorna el objeto creado. El `reporterId` se extrae automáticamente del token de autenticación. El `status` inicial siempre es `enviado`.

URL Params:

None

Headers:

Authorization: Bearer `<Auth Token>`

Role: usuario_base

Content-Type: application/json

Data Params:

```

{
  "incidentTypeId": "int",
  "speciesId": "int | null",
  "animalCount": "int",
  "description": "string",
  "reportPhotoUrl": "string | null",
  "latitude": "float",

```

```
"longitude": "float"
}
```

Success Response:

Code: 201

Content: { <reportDetail> }

Error Response:

Code: 400

Content: { "error": "Missing required fields" }

OR

Code: 401

Content: { "error": "You are unauthorized to make this request." }

OR

Code: 500

Content: { "error": "Internal server error" }

GET /reports

Obtiene todos los reportes. Admite filtros opcionales por query params.

URL Params:

Optional: status=[pendiente | enviado | procesando | resuelto | falso]

Optional: categoryId=[int]

Optional: incidentTypeId=[int]

Optional: assignedInstitutionId=[int]

Optional: from=[datetime]

Optional: to=[datetime]

Data Params:

None

Headers:

Authorization: Bearer <Auth Token>

Role: admin, institucion.

Content-Type: application/json

Success Response:

Code: 200

Content:

```
{
  "reports": [
    {
      "id": "uuid",
      "status": "enviado",
      "animalCount": 2,
```

```
    "reportPhotoUrl": "https://...",
    "latitude": -38.7359,
    "longitude": -72.5904,
    "createdAt": "2026-06-08T10:00:00Z",
    "incidentType": {
      "id": 2,
      "name": "Atropello",
      "category": "emergencia"
    },
    "species": {
      "id": 3,
      "commonName": "Puma",
      "animalGroup": "mamífero"
    }
  },
  "..."]
}
```

Error Response:

Code: 401

Content: { "error": "You are unauthorized to make this request." }

OR

Code: 500

Content: { "error": "Internal server error" }

GET /reports/my-reports

Obtiene todos los reportes enviados por el usuario autenticado, extraído desde el token.

URL Params:

None

Data Params:

None

Headers:

Authorization: Bearer <Auth Token>

Role: usuario_base

Content-Type: application/json

Success Response:

Code: 200

Content:

```
{
  "reports": [
    {
      "id": "uuid",
      "status": "procesando",

```

```
    "animalCount": 1,  
    "reportPhotoUrl": null,  
    "latitude": -38.7359,  
    "longitude": -72.5904,  
    "createdAt": "2026-06-08T10:00:00Z",  
    "incidentType": {  
      "id": 4,  
      "name": "Especie invasora",  
      "category": "amenaza"  
    },  
    "species": null  
  },  
  "..."  
]  
}
```

Error Response:

Code: 401

Content: { "error": "You are unauthorized to make this request." }

OR

Code: 500

Content: { "error": "Internal server error" }

GET /reports/:id

Obtiene un reporte específico por su ID con todos los sub-objetos expandidos.

URL Params:

Required: id=[uuid]

Data Params:

None

Headers:

Authorization: Bearer <Auth Token>

Role: usuario_base, institucion, admin.

Content-Type: application/json

Success Response:

Code: 200

Content:

```
{  
  "id": "3f7a1c2d-...",  
  "status": "procesando",  
  "animalCount": 1,  
  "description": "Encontré un puma herido al costado de la ruta 5.",  
  "reportPhotoUrl": "https://...",  
  "latitude": -38.7359,  
  "longitude": -72.5904,
```

```
"createdAt": "2026-06-08T10:00:00Z",
"reporter": {
  "id": "a1b2c3d4-...",
  "name": "Juan Pérez",
  "cellphoneNumber": "+56912345678",
  "trustPoints": 42
},
"incidentType": {
  "id": 2,
  "name": "Atropello",
  "category": "emergencia"
},
"species": {
  "id": 3,
  "commonName": "Puma",
  "scientificName": "Puma concolor",
  "animalGroup": "mamífero",
  "photoUrl": "https://..."
},
"assignedInstitution": {
  "id": 1,
  "name": "CONAF Araucanía",
  "emergency_phone": "+5645123456"
},
"recomendatedAction": {
  "id": 5,
  "title": "Protocolo fauna atropellada",
  "type": "reporte"
}
}
```

Error Response:

Code: 404

Content: { "error": "Report doesn't exist" }

OR

Code: 401

Content: { "error": "You are unauthorized to make this request." }

PATCH /reports/:id/status

Actualiza el estado de un reporte y opcionalmente le asigna una institución o acción recomendada. Retorna el objeto completo actualizado.

URL Params:

Required: id=[uuid]

Data Params:

```
{
  "status": "procesando | resuelto | falso",
  "assignedInstitutionId": "int | null",
```

```
"recommendedActionId": "int | null"  
}
```

Headers:

Authorization: Bearer `<Auth Token>`

Role: admin, institucion.

Content-Type: application/json

Success Response:

Code: 200

Content: `{ <report_detail> }`

Error Response:

Code: 400

Content: `{ "error": "Invalid status value" }`

OR

Code: 403

Content: `{ "error": "You are unauthorized to make this request." }`

OR

Code: 404

Content: `{ "error": "Report doesn't exist" }`

DELETE /reports/:id

Realiza un soft delete del reporte especificado.

URL Params:

Required: `id=[uuid]`

Data Params:

None

Headers:

Authorization: Bearer `<Auth Token>`

Role: admin.

Content-Type: application/json

Success Response:

Code: 204

Error Response:

Code: 403

Content: `{ "error": "You are unauthorized to make this request." }`

OR

Code: 404

Content: { "error": "Report doesn't exist" }

Validaciones de Reporte

Objeto validación:

```
{
  "reportId": "uuid",
  "user": {
    "id": "uuid",
    "name": "string",
    "trustPoints": "int"
  },
  "isValid": "boolean",
  "createdAt": "datetime"
}
```

Se expande `user` con nombre y puntos de confianza para dar contexto sobre quién validó y cuánto peso tiene su validación.

POST /reports/:id/validations

Agrega una validación de un usuario sobre un reporte existente. Un usuario no puede validar su propio reporte ni validar el mismo reporte dos veces.

URL Params:

Required: `id=[uuid]`

Data Params:

```
{
  "isValid": "boolean"
}
```

Headers:

Authorization: Bearer `<Auth Token>`

Role: usuario_base, institucion, admin.

Content-Type: application/json

Success Response:

Code: 201

Content:

```
{
  "reportId": "3f7a1c2d-...",
  "user": {
    "id": "a1b2c3d4-...",
    "name": "María González",
    "trustPoints": 78
  }
}
```



```
{,
  "isValid": true,
  "createdAt": "2026-06-08T11:30:00Z"
}
```

Error Response:

Code: 400

Content: { "error": "Missing required fields" }

OR

Code: 403

Content: { "error": "You cannot validate your own report" }

OR

Code: 409

Content: { "error": "You have already validated this report" }

OR

Code: 404

Content: { "error": "Report doesn't exist" }

OR

Code: 401

Content: { "error": "You are unauthorized to make this request." }

GET /reports/:id/validations

Obtiene todas las validaciones asociadas a un reporte específico con el resumen de conteos.

URL Params:

Required: id=[uuid]

Data Params:

None

Headers:

Authorization: Bearer <Auth Token>

Role: usuario_base, institucion, admin.

Content-Type: application/json

Success Response:

Code: 200

Content:

```
{
  "total": 5,
  "valid": 4,
  "notValid": 1,
  "validation": [
    {
      "reportId": "3f7a1c2d-...",
      "user": {
```

```
    "id": "a1b2c3d4-...",  
    "name": "María González",  
    "trustPoints": 78  
  },  
  "isValid": true,  
  "createdAt": "2026-06-08T11:30:00Z"  
},  
"..."  
]  
}
```

Error Response:

Code: 404

Content: { "error": "Report doesn't exist" }

OR

Code: 401

Content: { "error": "You are unauthorized to make this request." }
