# SeqTrimNext Statistics of pre-processing

# Plataforma Andaluza de Bioinformática

Universidad de Málaga

April 23, 2020





# 1 Output Files

SeqTrimNext provides several files, the most interesting ones are in the following directories:

#### output\_files

- output.less, containing an extensive information about the trimming of each sequence. It can be visualised on terminal using the command less -R.
- used\_params.txt, containing the complete set of parameters used for execution of SeqTrimNext with your data
- rejected.txt, containing a list of rejected sequences together with the reason for their removal.
- initial\_stats.json, containing statistics for raw sequences.
- stats.json, containing the statistics of the cleaning process.
- There is a collection of folders that gather sequences with the same MID; each folder contains a sequences file (in FASTQ format) with useful reads. There may also exists a file with reads containing low complexity regions. If you want to reconstruct a SFF with the useful segment of each pre-processed read, use sff\_info file in combination with the original SFF file for the sfffile tool.

#### • graphs

- size\_stats.png, a graph with the distribution of read lengths in raw data (see Fig. ??).
- qualities.png, a graph to inspect read qualities in raw data (see Fig. ??).
- PluginExtractInserts\_insert\_size.png, a graph with the distribution of read lengths after SeqTrimNext pre-processing (see Fig. 1).
- There are other graphs (mostly bar plots) that illustrate the quality of pre-processed reads. All are in PNG format.

#### • latex

 It is provided as a compressed file latex.zip containing all ".tex" files required to compile this document. Graphs are taken from the graph folder

# 2 Relevant parameters

In this section, the relevant parameters used in your experiment are shown. Full information about the parameters can be obtained from file used\_params.txt





#### 2.1 General

Plugins applied to every sequence, separated by commas. Order is important

- 1. PluginIndeterminations
- 2. PluginFindPolyAt
- 3. PluginAbAdapters
- 4. PluginUserContaminants
- 5. PluginContaminants
- 6. PluginVectors
- 7. PluginLowQuality
- 8. PluginLowComplexity
- $9. \ \ Plugin Extract Inserts$

Remove duplicated (clonal) sequences (using CD-HIT 454)

remove\_clonality: false

Minimum insert size for every trimmed sequence

min\_insert\_size\_trimmed: 30

Minimum insert size for each end of paired-end reads; true paired-ends have both single-ends longer than this value

min\_insert\_size\_paired: 40

Seqtrim version

seqtrim\_version: 2.0.67

min\_sequence\_size\_raw:

#### 2.2 Quality

Minimum quality value for every nucleotide

min\_quality: 20

window\_width:

#### 2.3 Contaminants

Blast E-value used as cut-off when searching for contaminations

blast\_evalue\_contaminants: 1.0e-10

Minimum required identity (%) for a reliable contamination

blast\_percent\_contaminants: 85

Minimum hit size (nt) for considering a true contamination

min\_contam\_seq\_presence: 40

Genus of input data: contaminations belonging to this genus will be ignored genus:





Is a contamination considered a source of sequence rejection? (setting to false will only trim contaminated sequences instead of rejecting the complete read)

contaminants\_reject: true
Path for contaminants database
 contaminants.fasta
 cont\_ribosome.fasta

# 3 Pre-processing statistics

Next figure is equivalent to Figure ?? but using output reads (useful sequences). The mode is expected to decrease but the shape of the plot should be similar.




Figure 1: Size distribution of the output sequences. Short sequences (< min\_insert\_size\_trimmed) were removed. [PluginExtractInsert\_size.png]

Summary statistics of the SeqTrimNext analysis. Be careful and read all warnings that are indicating concerns about your data. In the files initial\_stats.json and stats.json can be found a full statistics of your data and SeqTrimNext pre-processing





Smallest read (bp) Largest read (bp) Mode (bp) Mean (bp)  total Rejected	101 101 0 0.0 5947174
Mode (bp) Mean (bp) total	0 0.0 5947174
Mean (bp) total	5947174
total	5947174
*****	00-1-1-
*****	00-1-1-
Painated	
Rejected	17367359
ow complexity reads	114331
Mode (bp)	91
Mean (bp)	89.9
Output paired reads	97399744
Total output reads	103346918
	Mode (bp) Mean (bp) Output paired reads

Table 1: List of the most frequent Vectors found among your reads  $\,$ 

Vectors	sequences
Cloning vector pAAV-MCS, complete sequence.	750088
Cloning vector pKOHPRT complete sequence.	735192
Enterobacteria phage lambda	165016
Cloning vector Mini-Tn4001PStetM, complete sequence	60265
Cloning vector pVLH/hsp	56858

Table 2: List of the most frequent Adapters found among your reads

Adapters	sequences
TruSeq_Universal_Adapter	619426
ABI_Solid3_Adapter_A	336060
Illumina_Single_End_Adapter_1	273949
Illumina_Multiplexing_Read2_Sequencing_Primer	263547
ABI_Solid3_GAPDH_Reverse_Primer	257042





Table 3: List of the most frequent Contaminants found among your reads

Contaminants	sequences
rRNA_small_subunit_Metazoa_Myotis	108216
rRNA_long_subunit_Metazoa_Dasypus	104384
Saccharomyces cerevisiae S288c chromosome XII, complete se-	92902
quence	
Podospora anserina S mat+ unordered scaffolds, whole genome	70546
shotgun sequence	
Schizosaccharomyces pombe 972h- chromosome III, complete se-	65032
quence	

Table 4: Summary of nucleotides removed in every plugin.

Plugin	Nucleotides	Percent	Warnings
Low Quality	2112867664	Inf %	OK
Low Complexity	92427562	Inf $\%$	OK
Poly T	43663975	Inf $\%$	OK
Poly A	45699017	Inf $\%$	OK
Contaminants	71428055	Inf $\%$	OK
Adapters	120560055	Inf $\%$	OK
Vectors	76927249	Inf $\%$	OK
Indeterminations	1270558	Inf $\%$	OK
Inserts	9298313592	Inf %	iW1

iW1 Warning!, only Inf% of nucleotides are useful

# 4 Rejected reads

Input sequences	120828608
Output sequences	5947174
Rejected sequences	17367359
Output paired sequences	97399744
Total output sequences	103346918
Low complexity sequences	114331





Table 5: Summary of reads removed in every plugin.

Case	Number of sequences	Percent	Warnings
	17367359	14.374 %	OK
Short inserts	11343737	9.388~%	rdW2
Empty Inserts	5216184	4.317~%	rdW3
Contaminants	769051	0.636~%	OK
No Valid Inserts	26128	0.022~%	OK
Low Complexity	10864	0.009~%	OK
Indeterminations	1238	0.001~%	OK
Unexpected Vector	157	0.000~%	OK
Total rejected	17367359	14.374 %	OK

rdW2 Warning!, a 9.388 % of your sequences are too short

rdW3 Warning!, a 4.317 % of your sequences are empty (without an insert)

### References

- [1] Falgueras et al. SeqTrim: a high-throughput pipeline for preprocessing any type of sequence reads.  $BMC\ Bioinformatics\ 11:38\ (2010)$
- [2] Weizhong Li & Adam Godzik. Cd-hit: a fast program for clustering and comparing large sets of protein or nucleotide sequences. *Bioinformatics* (2006) 22:1658-9

Thanks you for use SeqTrimNext! Send us any comment to scbi support



