belinus®

ARCHIVE DATASHEET
DISCONTINUED PRODUCT
SOLD 2023

NOX 60 IBC

SOLAR PANEL

Interdigitated back-contact panel: no silver lines on the front, full black.

SOLD	2023
CELL TECHNOLOGY	back contact (IBC)
POWER	390 – 400 Wp
EFFICIENCY	21.7 – 22.3 %
DIMENSIONS	1727 × 1039 × 30 mm
WEIGHT	23.5 kg
CELLS	120 half-cut, 166 mm
BIFACIALITY	80 %
GLASS	glass-glass, 2.0 + 2.0 mm
FIRE CLASS	A (UL 790)
SNOW / WIND LOAD	5400 / 2400 Pa
OPEN-CIRCUIT VOLTAGE	41.9 – 42.1 V
SHORT-CIRCUIT CURRENT	11.8 – 12.0 A
TEMP. COEFFICIENT PMAX	−0.28 %/°C
MODEL REFERENCE	M8-IBC-GG-xxx

Warranty and service. Product warranty 35 years · performance warranty 35 years · service warranty 35 years, as stated in the sales documents. This product is no longer sold; warranty and service continue under the terms that came with your installation. Request service at belinus.com or service@belinus.com. The original datasheet is available on request.