belinus®

ETAPPro · EV Charger
v01 · 2026-01
MODEL · belinus ETAPPro

RESIDENTIAL EV CHARGER · FIXED OR MOBILE · UP TO 22 KW

ETAPPro

Unlock the power of nature.

#ResidentialEVcharger #Click&Go #Plug&Play #MultiCPO #MadeInBelgium

01 **Integrated belinus EMS.** Communicates with energy management systems over ModBus or API.

02 **Load balancing & sharing.** Adjusts current to household consumption; distributes power across chargers.

03 **Multi-CPO connectivity.** Use charging cards from different providers without making the point public.

04 **Dynamic tariff optimisation.** Charges when tariffs are low; peak shaving and negative-pricing protection.

05 **Solar charging.** 100 % of generated solar energy used instead of exporting to the grid.

06 **24h replacement service.** First-line support with next-day replacement.







10 yr
PRODUCT WARRANTY

10 yr
PERFORMANCE WARRANTY

10 yr
SERVICE WARRANTY

Copyright © 2026 Belinus Holding B.V.

www.belinus.com · info@belinus.com

belinus®

TECHNICAL SPECIFICATIONS

ETAPPro · Smart EV Charger

POWER	CURRENT	PROTECTION	CONNECTOR
22 kW	32 A	IP67	Type 2

ELECTRICAL

Charging capacity	Single 7.4 kW · 1/3-phase 11 / 22 kW
Output	230 – 400 V, 32 A
Charge mode	Mode 2 & 3 (IEC 61851)
Rated current	up to 32 A / phase
Current range	6 – 32 A
Connector	IEC 62196 Type 2 (Tesla opt.)
Safety class	Class I
Self-consumption	3.5 W

GENERAL

Control	ETAP App / Web portal
Operating temperature	−25 °C to +40 °C
Storage temperature	−40 °C to +60 °C
Altitude	0 – 2000 m
Humidity	95 %, non-condensing
Positioning	GPS / Wi-Fi

ENCLOSURE

Material	Polycarbonate
Protection	IP67
Impact	IK08
Cable	5 m / 7.5 m (custom)
Weight	2.8 kg (5 m) · 3.4 kg (7.5 m)
Dimensions (H × W × D)	244 × 134 × 55 mm
Energy meter	Calibrated, MID planned

CONNECTIVITY

Links	Bluetooth · Wi-Fi · Powerline AV2 · SIM 4G
Protocols	OCPP 1.6 · ModBus TCP/IP · API
Session	Plug & Charge · App · RFID · schedules
Firmware	OTA updates
Status	RGB LED · App

CERTIFICATION

Product	CE
Standards	IEC 61851-1 mode 2/3 · 61851-22
Earth leakage	AC 30 mA · DC 6 mA
Origin	Made in Belgium
Warranty	10 yr · product / performance / service

Notice: specifications are subject to change without notice.